

1 FORMULA
ONE EQUATION. 817 DRIVERS. ONE ANSWER.
JEAN-M

1 Formula

A Mathematical Analysis to Identify the Top Formula 1 Driver in History

Jean-Marie Roy

2026-11-14

DRAFT



Contents

1. Introduction **5**

2. Dataset **6**

2.1 Source . . . 6

2.2 Pipeline . . . 6

2.3 Tables . . . 8

2.3.0 Overview . . . 8

2.3.1 Core Season & Race Structure . . . 8

2.3.2 Session-Level Detail . . . 8

2.3.3 Driver & Constructor Records . . . 9

2.3.4 Championship Standings . . . 9

2.3.5 Scoring Systems . . . 9

2.3.6 Performance Metrics . . . 10

2.3.7 Staging Tables (Not Used in Analysis) . . . 10

2.4 Quick Analysis . . . 11

2.4.1 A First Look at the Raw Tables . . . 11

2.4.2 The `api_id` Column . . . 11

2.4.3 Winner Uniqueness . . . 12

2.4.4 Shared Drives in the Early Years . . . 12

2.4.5 Fractional Point Values . . . 13

2.4.6 Finer Fractions from Shared Awards . . . 14

2.4.7 The Absent Fastest Lap . . . 14

2.4.8 Ineligible Drivers Who Scored Points . . . 15

2.4.9 Unclassified Drivers Who Scored Points . . . 16

2.4.10 Country or Nationality . . . 16

3. Transformation **18**

3.1 Principles . . . 18

3.2 The dbt Layer . . . 19

3.3 Removing the `api_id` Columns . . . 20

3.4 Season-Scoped Nationalities . . . 21

3.5 Restoring Fastest-Lap Coverage, 1950–1957 . . . 22

3.6 A Convenience View: `f1summary` . . . 23

3.7 The Resulting Schema . . . 24

3.8 What Is Deliberately Not Changed . . . 25

DRAFT

4. Exploratory Data Analysis **26**
4.1 Drivers . . . 26
4.1.1 Grand Prix . . . 26
4.1.2 Winning Probability . . . 28
4.1.3 Top Drivers . . . 28
4.1.4 Timeline . . . 30
4.1.5 Comparison . . . 32
4.1.6 Summary . . . 34
4.2 Constructors . . . 35
4.3 Championship Framework . . . 38
4.3.1 Races . . . 38
4.3.2 Points and Rules . . . 41
4.3.3 Comparing Across Eras . . . 46

9. References **47**

DRAFT

1. Introduction

When posed the question, "Who is or was the best Formula 1 driver of all time?" an AI agent will likely first mention **Lewis Hamilton**, followed by **Michael Schumacher**, based primarily on their respective world championship titles. If asked for a list of top drivers, it might also include **Juan Manuel Fangio**, **Alain Prost**, **Max Verstappen**, and **Sebastian Vettel**, arranged alphabetically. **Fangio** stands out with five championships, while the others each have four.

Interestingly, many fans regard **Ayrton Senna**, with his three titles, as a superior driver compared to **Alain Prost**, despite the latter's four championships. This raises the question: how significant are titles in evaluating a driver's greatness? Should we consider alternative criteria for determining who truly excels?

If we delve deeper, **Juan Manuel Fangio** won five titles in the 1950s, during the formative years of the Formula 1 World Championship. His legacy is so profound that his name has become synonymous with exceptional driving. In French-speaking regions, the phrase "driving like Fangio" denotes flawless driving. A notable reference appears in *The Adventures of Tintin: The Calculus Affair* [1], where a character remarks, "This must be Fangio at the wheel" as a car skillfully avoids a net, reflecting Fangio's prowess during the height of his career. (In the English edition, it is translated as *"They must have a Jack Brabham at the wheel!"*)




Figure 1: *"This must be Fangio at the wheel!"*

Complicating matters further, the rules of Formula 1 have evolved significantly over the years. The number of races has increased (from seven during Fangio's era to 22 today), and the points system has undergone various changes. For instance, the winner received 8 points until **1960**, then 9 points until **1990**, followed by 10 points until **2009**, and has been set at 25 points since **2010**. Additionally, until **1990**, only the best results counted towards the championship, which allowed Senna to secure the title in **1990** against Prost, despite the latter having more points overall; under modern rules, Prost would have been awarded the title instead.

Ultimately, it is evident that even the most skilled drivers depend significantly on their cars' performance. Both Alain Prost in **1991** and Lewis Hamilton in **2025** encountered substantial difficulties while driving for Ferrari, so much so that Prost was dismissed from his team after comparing his car to a "truck." This raises an important question: to what extent is a world title attributable to the car, and how much is a reflection of the driver's ability?

2. Dataset

2.1 Source

The data used throughout this study comes from **Jolpica F1** [2], an open-source (Apache 2.0) Formula 1 API maintained by a group of volunteers. Jolpica was created as the successor to the widely used Ergast API, which was deprecated at the end of the 2024 season, and provides the same type of historical data (drivers, teams, sessions, results, standings, lap times and pit stops) through a redesigned database schema. According to its maintainers, this new schema is intended to better accommodate changing rule sets, reduce duplicated information and allow the storage of additional F1-related data.

As Jolpica is an independent open-source project, its internals — scraping process, data validation and correction policies — are the responsibility of its maintainers and are outside the scope of this work. We therefore treat Jolpica as the *system of record* for historical Formula 1 data and restrict ourselves to documenting how the data is ingested, transformed and audited on our side. A full description of the tables can be found in the project's database documentation [3].

It should be noted that Jolpica publishes its database dump with a delay of approximately two weeks: more recent data is only available through a paid tier. Since this study analyses historical data up to the end of the previous season — deliberately excluding the ongoing season — the free release is entirely sufficient, and the delayed publication has no impact on the completeness of the dataset used here.

2.2 Pipeline

The ingestion, transformation and publication of the data is fully automated in an ELT pipeline published on GitHub [4], orchestrated with **GitHub Actions** and scheduled to run **weekly** (with manual triggering also possible). The pipeline extracts the raw data from Jolpica and produces two outputs: a normalised SQLite database used for validation and transformation, and a mirror of the raw tables in Databricks used for interactive analysis.

The pipeline performs the following steps:

1. **Extract** — the full Jolpica database dump (18 CSV files, one per table, ~40 MB compressed) is downloaded from the Jolpica data endpoint. A freshness check skips the download if the data is less than 7 days old, and the original Ergast/Jolpica table schemas are preserved.
2. **Load** — the raw CSVs are normalised into a **star schema SQLite** database (`jolpica.db`), with foreign key validation guaranteeing referential integrity. This database (~900K rows covering every F1 race since 1950) acts as a portable, version-controlled snapshot of the raw data, fully independent from any cloud service.
3. **Transform** — running in parallel with the publication step, the transformation job reshapes the raw schema into an analytics schema (`formula1.db`), adds derived fields (driver age, cumulative points, country flags), and applies **dbt** models and tests on top.
4. **Publish to Databricks** — each raw SQLite table is exported to Parquet, staged in a Unity Catalog volume, and loaded into **Delta tables** in Databricks via `COPY INTO`, with automatic type widening and row-count verification against the source. This gives a queryable copy of the raw dataset for exploratory analysis without needing to download the SQLite file.

DRAFT

The two branches of the pipeline are intentionally decoupled: a Databricks outage cannot block the local SQLite build and release.




Figure 2: Pipeline architecture: Jolpica → SQLite → dbt / Databricks

Two design decisions are worth highlighting, as they affect the reproducibility of the analysis:

- **Full reload instead of incremental processing.** With roughly 900K rows, reloading the entire dataset at each run is cheap, and — more importantly — safe: F1 stewards occasionally issue disqualifications or points adjustments *after* races, so append-only logic would silently miss retroactive corrections. This is particularly relevant for the historical quirks discussed in Section 2.4.
- **Release strategy.** The database is distributed via GitHub Releases under a mutable `data-latest` tag, overwritten at each run. Versioned immutable releases (`data-YYYYMMDD`) are a planned improvement; for this study, the dataset snapshot used for the analysis is documented together with the results to ensure reproducibility.

The pipeline consumes a single input: the Jolpica database dump, delivered as a ZIP archive of 18 CSV files, one per table. The table below lists these input files as recorded in the database inventory; each file corresponds one-to-one with a table described in Section 2.3.

Files		
base_team.csv	lap.csv	season.csv
championship_adjustment.csv	penalty.csv	session.csv
championship_system.csv	pit_stop.csv	session_entry.csv
circuit.csv	points_system.csv	team.csv
driver.csv	round.csv	team_championship.csv
driver_championship.csv	roundentry.csv	team_driver.csv

DRAFT

2.3 Tables

2.3.0 Overview

The Jolpica export consists of **18 tables** covering seasons, rounds, circuits, sessions, results, teams, championships, scoring systems, lap times, pit stops and staging tables. Note that the schema intentionally differs from Ergast's: Jolpica splits the old monolithic races/results concepts into fine-grained round, session and session_entry tables, which allows a modern race weekend (practice, qualifying, sprint, race) to be modelled explicitly.

2.3.1 Core Season & Race Structure

The three tables below form the backbone of the temporal dimension: they identify each season, each Grand Prix, and each physical circuit.

Table	Rows	Purpose
`season`	77	Master record of every F1 season (1950-present). Contains year, championship system reference, and Wikipedia link. Primary time dimension for all temporal queries.
`round`	1,173	Individual Grands Prix within seasons. Links to season and circuit, includes race number, official name, date, and Wikipedia reference. Represents the traditional race event concept.
`circuit`	78	Physical racetracks. Stores track metadata including location data and Wikipedia URL. Rarely changes over time - a dimensional lookup table.

2.3.2 Session-Level Detail

Modern Formula 1 weekends comprise multiple timed sessions (practice, qualifying, sprint, race). Jolpica models this explicitly with two tables:

Table	Rows	Purpose
`session`	5,130	Granular timing sessions (Race, Qualifying, Sprint, Practice). Modern F1 structure where a round may have multiple sessions. Includes scheduled laps, timezone, and cancellation flags.
`session_entry`	51,983	Driver results per session. Contains grid position, finishing position, points scored, laps completed, time/difference, status codes, and classification eligibility. Most frequently queried results table.

DRAFT

2.3.3 Driver & Constructor Records

Drivers and constructors are tracked both as profiles and as historical pairings, alongside the legacy entry mechanism used before session-level granularity:

Table	Rows	Purpose
`driver`	884	Driver profiles: names, nationality, date of birth and country. Core dimension for any driver-level aggregation; driver age at race date is derived from it during transformation.
`team`	214	All constructor entries in history. Note: constructors evolve or rebrand - this tracks distinct legal entities, not just Ferrari/Mercedes/Red Bull brand names.
`team_driver`	3,633	Historical pairings of which driver drove for which team. Junction table linking drivers and teams, with validity periods implied by related records.
`roundentry`	27,740	Which team-driver combination entered which round (before session granularity). Contains car number assignment. Legacy linkage from older schema design.

2.3.4 Championship Standings

Both championships are tracked cumulatively after every round, enabling trajectory analysis over the course of a season:

Table	Rows	Purpose
`driver_championship`	36,869	Cumulative driver standings across the season. Tracks points accumulation after each round - enabling analysis of championship trajectories, comebacks, and mathematical elimination dates.
`team_championship`	14,579	Equivalent constructor standings. Mirrors the driver championship table structure but for teams. Critical for analysing constructor battles and historic dominance patterns.

2.3.5 Scoring Systems

Point allocation has changed repeatedly across F1 history. Three tables document the rules governing how results translate into points:

Table	Rows	Purpose
`points_system`	24	Historical point-allocation rules. Each row defines a unique scoring scheme used during a period, explaining why different eras award points differently.
`championship_system`	11	Broader championship format definitions. May encompass tiebreaker rules, sprint weekend variants, or multi-season aggregations.
`championship_adjustment`	3	Special corrections to historical standings. Likely captures retroactive disqualifications, title rescissions, or corrections to original records.

DRAFT

2.3.6 Performance Metrics

Two high-cardinality tables capture on-track performance:

Table	Rows	Purpose
`lap`	740,109	Per-lap timing data. The highest-cardinality table, containing individual lap times for every driver in every race session. Essential for pace analysis, fastest-lap identification, and tyre-strategy modelling.
`pit_stop`	13,087	Pit-stop events, including duration and timing within a race, and potentially crew performance data. Critical for race-strategy analysis and comparing pit-crew performance.

2.3.7 Staging Tables (Not Used in Analysis)

Two tables exist as empty staging structures with no analytical value:

Table	Rows	Purpose
`base_team`	0	Empty staging table - likely intended for ETL operations or future use. Currently contains no data.
`penalty`	0	Intended for driver or constructor penalties but currently empty. It may be populated by future pipeline updates or used only when infractions occur.

DRAFT

2.4 Quick Analysis

2.4.1 A First Look at the Raw Tables

Before describing the issues hidden in the data, it is worth looking at the tables themselves. The extracts below show the first rows of two tables — `season`, one of the smallest tables in the schema, and `pit_stop`, a fact table — chosen so that all their columns fit on the page.

First, the `season` table — with only a handful of rows and columns, it defines the championship calendar:

id	year	api_id	championship_system_id	wikipedia
1	1950	season_oPqQEC4b	1	https://en.wikipedia.org/wiki/1950_Formula_One_season
2	1951	season_nH07GTj5	1	https://en.wikipedia.org/wiki/1951_Formula_One_season
3	1952	season_AkHDeRX4	1	https://en.wikipedia.org/wiki/1952_Formula_One_season
4	1953	season_E63rvZZO	1	https://en.wikipedia.org/wiki/1953_Formula_One_season
5	1954	season_B36NWfA1	2	https://en.wikipedia.org/wiki/1954_Formula_One_season

The extract below shows the first rows of the `pit_stop` table:

id	session_entry_id	lap_id	number	duration	local_timestamp	api_id
1	27696	275638	2	00:00:24.036	17:59:17	pitstop_IYavKg2C
2	27696	275672	1	00:00:22.603	17:25:17	pitstop_XDzyA9tn
3	27700	275742	1	00:00:23.227	17:28:24	pitstop_c0OV7PJY
4	27700	275746	2	00:00:23.199	17:59:29	pitstop_SFBiesKg
5	27704	275769	1	00:00:24.535	17:28:39	pitstop_ZS3hcaW8

2.4.2 The `api_id` Column

The two extracts above reveal a common pattern: every table begins with an `api_id` column. This identifier is present in **all 18 tables** of the export — inspecting the remaining tables (not reproduced here) shows exactly the same structure. It mirrors the primary key exposed by the Jolpica API and is therefore *application specific*: it identifies records within Jolpica's own infrastructure (and its Ergast-compatible endpoints) rather than describing anything about the racing data itself.

Since it carries no analytical meaning, duplicates the information already present in the pipeline's own keys, and wastes width in every table, **these columns will be dropped from all tables during the dbt transformation step**; the details are covered in Chapter 3.

Dropping the columns from the analytical tables does not mean discarding the information permanently. Should the values ever prove useful again — for example, for tracing records back to Jolpica's endpoints or for debugging the extraction process — they could be preserved in dedicated, application-level lookup tables, kept strictly separate from the F1 data tables described above.

DRAFT

2.4.3 Winner Uniqueness

The most basic integrity expectation for a results table is that each race has exactly one winner. This expectation is, however, merely an assumption made by the analyst — the raw export is never accompanied by a formal definition of what constitutes a unique race winner — and is therefore worth verifying explicitly.

Working directly from the Jolpica `results` table, a simple count of drivers classified in first position per race confirms two things. First, no race in the dataset lacks a winner altogether; second, several races list **more than one** driver in first position:

id	n_winners
31	2
145	2
181	2

To identify the affected races, the races listing more than one winner are then joined with the `races` and `drivers` tables — the joins serve purely to attach human-readable context, not to derive the counts:

year	circuit	n_winners
1951	French Grand Prix	2
1956	Argentine Grand Prix	2
1957	British Grand Prix	2

At first glance this looks like a data-quality defect, but it turns out to be a historically faithful representation of the sport's earliest era, as the next section explains.

2.4.4 Shared Drives in the Early Years

The multiple-winner phenomenon observed above is not an error in the export but a consequence of a practice that was accepted in Formula One's formative years: **car sharing**. In the early seasons, teams frequently entered smaller fields than the grid size, and a single car could be driven by several drivers over the course of one race — one driver starting the race and another taking over later, in the manner of an endurance relay.

Under the regulations of the time, all drivers who took the wheel were credited with the race result achieved by that car. Consequently, when a shared car finished first, the results table records several drivers sharing the win — exactly the pattern surfaced by the aggregation in Section 2.4.3. The same convention extends beyond victories: position assignments, classifications, and championship points accrued by such cars were likewise divided among the participating drivers.

From a data-modelling perspective, this means the natural key of the results table is not (race, position) alone, since a single finishing position can legitimately be occupied by multiple driver rows. Any transformation or analysis step must therefore account for this historical peculiarity rather than treating duplicate positions as anomalies to be corrected.

DRAFT

2.4.5 Fractional Point Values

The shared-drive practice of Section 2.4.4 leaves an arithmetic fingerprint in the `points` column — but it is not the only source of non-integer point values. Up to this point the integrity checks have concerned the *structural* attributes of the export — keys, positions, flags; the `points` column itself has not been inspected yet, even though it encodes the accumulated effect of every historical scoring quirk. Championship points are expected to be whole numbers — or, at worst, halves — so a natural first check is to ask which values violate this expectation. The query below surveys every non-integer value appearing anywhere in the results and counts how many rows carry each fractional part:

fractional_part	n_rows
0.50	35
0.14	7
0.33	3

The distribution is remarkably clean: the overwhelming majority of fractional rows carry an exact half, while only two much finer fractions appear at all. Several distinct, well-documented mechanisms can produce exact halves, and they are worth enumerating before attempting to attribute individual rows:

- **Abandoned races.** When a Grand Prix was halted before the full distance had been covered — typically by torrential rain or a serious accident, with the race unable to resume — drivers received **half** of the points attached to their finishing position. A driver classified fourth in such a race, a placement worth 3 points under the scoring systems that governed the sport for its first four decades, was consequently credited with 1.5 points. Rain-shortened editions appear irregularly across the entire history of the championship.
- **Shared drives.** Whenever *two* drivers shared one car that finished in a points-paying position, the points attached to that place were divided equally between them (Section 2.4.4), and a division of an integer by two again yields exactly one half.
- **Shared fastest-lap points.** Under the early scoring systems, the bonus point attached to the fastest lap could be **split** when two drivers recorded an identical fastest time — each taking half of the single point. A driver who finished in a points-paying position and co-held the fastest lap thus carries a half appended to an otherwise integral total: second place under the 1950–1959 system (6 points) plus half the bonus yields 6.5. This is the two-driver case of the seven-way split examined in Section 2.4.6.

Attributing each individual half to its mechanism is more delicate than it may seem, and naive heuristics fail quickly: a points value is the *sum* of position points and a possible bonus share, so either component may be the halved one, and the mechanisms are not mutually exclusive — a shared car in a rain-shortened race is divided twice over, yielding quarters. Rather than attempting a per-row classification, the survey above is treated as evidence that all fractional values fall within a known, historically grounded set of mechanisms. What *cannot* be explained by any of them are the values that are neither integers nor exact halves, visible at the tail of the extract; isolating them pins down only two affected races, which the next section inspects individually.

DRAFT

2.4.6 Finer Fractions from Shared Awards

Values that are neither integers nor exact halves resist the explanation of Section 2.4.5 and require a closer look. Isolating them from the unique point values of the `session_entry` table yields only two contaminated races:

year	circuit	driver	team	position	points
1954	British Grand Prix	José Froilán González	Ferrari	1	8.14
1954	British Grand Prix	Mike Hawthorn	Ferrari	2	6.14
1954	British Grand Prix	Onofre Marimón	Maserati	3	4.14
1954	British Grand Prix	Juan Fangio	Mercedes	4	3.14
1954	British Grand Prix	Stirling Moss	Maserati	16	0.14
1954	British Grand Prix	Jean Behra	Gordini	18	0.14
1954	British Grand Prix	Alberto Ascari	Maserati	24	0.14
1955	Argentine Grand Prix	Umberto Maglioli	Ferrari	3	1.33
1955	Argentine Grand Prix	Nino Farina	Ferrari	3	1.33
1955	Argentine Grand Prix	Maurice Trintignant	Ferrari	3	1.33

Both races illustrate points being **divided rather than awarded**, each in its own way. At the 1954 British Grand Prix, every affected driver carries an identical increment of 1/7 point on top of the points earned by finishing position — the fastest-lap bonus point of the era's scoring system, awarded jointly to seven drivers who set an identical fastest lap and thus shared its single point seven ways. At the 1955 Argentine Grand Prix, three drivers sharing one car finished jointly in third position; the four points attached to that place were divided equally, each driver recording 4/3 points. Both mechanisms are consequences of the shared-car and shared-award practices of the period described in Section 2.4.4, confined to the 1950s — confirming that these fractions are faithful historical records rather than pipeline errors.

2.4.7 The Absent Fastest Lap

Among the shared awards of Section 2.4.6, one subset deserves a final inspection: the drivers who received 1/7 of the fastest-lap point at the 1954 British Grand Prix. Their fractional increment of ~0.14 makes them easy to isolate, and their rows are informative — although a fastest-lap award is recorded in the `points` column, the dedicated `fastest_lap_rank` column remains empty for every one of them:

year	circuit	driver	team	position	points	fastest_lap_rank
1954	British Grand Prix	José Froilán González	Ferrari	1	8.14	NA
1954	British Grand Prix	Mike Hawthorn	Ferrari	2	6.14	NA
1954	British Grand Prix	Onofre Marimón	Maserati	3	4.14	NA
1954	British Grand Prix	Juan Fangio	Mercedes	4	3.14	NA
1954	British Grand Prix	Stirling Moss	Maserati	16	0.14	NA
1954	British Grand Prix	Jean Behra	Gordini	18	0.14	NA
1954	British Grand Prix	Alberto Ascari	Maserati	24	0.14	NA

The seven `NA` values in the extract are not an accidental omission of these particular rows, but a coverage boundary of the source: the dataset contains fastest-lap records only starting from the 1958 season, earlier editions of the championship having no officially tracked fastest lap. The boundary can be located precisely in the data:

first_season_with_fastest_lap
1958

The situation is therefore somewhat ironic: the very drivers who *jointly* set the fastest lap in 1954 cannot be recognised as such from the `fastest_lap_rank` column. Closing this gap is a candidate for the transformation work described in Chapter 3: fastest-lap data for the earlier seasons could be integrated from an

DRAFT

external source as part of the planned modifications, restoring complete coverage of this statistic across the championship's history.

2.4.8 Ineligible Drivers Who Scored Points

The last integrity check concerns the consistency between the eligibility flag and the `points` column. Every row of the results carries an `is_eligible_for_points` indicator, and the naive expectation is a strict correspondence: drivers flagged as ineligible should record zero points. The export violates this expectation exactly once:

year	circuit	driver	team	position	points	detail	laps_completed
1956	Monaco Grand Prix	Juan Fangio	Ferrari	4	1.5	+1 Lap	99

Consulting the historical record resolves the apparent contradiction, and it involves the shared-drive practice of Section 2.4.4 twice over. At the 1956 Monaco Grand Prix, Juan Manuel Fangio drove two cars: he shared the car number 26, which finished second, with Peter Collins, and the car number 20, which finished fourth, with Eugenio Castellotti. Under the regulations of the time, the points of a shared car were divided among its drivers — but a driver who had already received points from one car was **not entitled to collect points from a second one**. Fangio therefore took his half of the second-place points (three of six, shared with Collins), while his would-be share of the fourth place — three points divided by two, the 1.5 recorded in the extract — went uncollected.

The extract below places this single violating row in its full context by listing every Ferrari entry of that race:

driver	position	points	eligible	detail	laps_completed
Juan Fangio	2	4.0	t	Finished	100
Peter Collins	2	3.0	t	Finished	100
Eugenio Castellotti	4	1.5	t	+1 Lap	99
Juan Fangio	4	1.5	f	+1 Lap	99
Eugenio Castellotti	11	0.0	t	Clutch	14
Luigi Musso	14	0.0	t	Accident	2

The table rewards a careful reading. The second row pair shows the shared second place: Collins and Fangio both completed 100 laps in car number 26, yet Fangio records one point more than his co-driver — the fastest-lap bonus of the era's scoring system (Section 2.4.6), set by Fangio that afternoon, appended to his half of the position points. The fourth row pair shows the shared fourth place at one lap behind (`+1 Lap`, 99 laps completed): Castellotti's 1.5 was awarded, while the identical figure next to Fangio's name — flagged ineligible, and singled out by the check at the top of this section — records the *notional* share that the regulations denied him. The two remaining rows complete the picture of the team's afternoon: Castellotti's own car, sidelined by clutch failure after 14 laps but still classified eleventh, and Musso's, eliminated in an accident after two laps and classified fourteenth — a reminder that retirement and classification are independent attributes in this export, exactly as the classifications of Section 2.4.9 presuppose.

The row is thus internally coherent once both columns are read together: the `points` column preserves the notional share attached to the fourth-place finish, exactly as the sharing arithmetic would assign it, while the `is_eligible_for_points` flag correctly records that this share was not awarded. Far from being a data defect, the combination demonstrates that the export encodes a subtle piece of period regulation — and, since it is unique across the entire dataset, any transformation step can handle it as an explicitly documented single case rather than a systematic issue.

DRAFT

2.4.9 Unclassified Drivers Who Scored Points

The mirror image of the eligibility check of Section 2.4.8 concerns the classification flag. The naive expectation is again a strict correspondence: a driver flagged as unclassified — one who did not complete a sufficient portion of the race distance — should record zero points. The export contains a sizeable group of violations of exactly this shape:

year	circuit	driver	team	position	points	detail	fastest_lap_rank
1950	Italian Grand Prix	Juan Fangio	Alfa Romeo	15	1.00	Gearbox	NA
1951	British Grand Prix	Nino Farina	Alfa Romeo	14	1.00	Clutch	NA
1953	Belgian Grand Prix	José Froilán González	Maserati	16	1.00	Throttle	NA
1953	Dutch Grand Prix	Luigi Villoresi	Ferrari	10	1.00	Throttle	NA
1953	German Grand Prix	Alberto Ascari	Ferrari	17	1.00	Engine	NA
1954	British Grand Prix	Stirling Moss	Maserati	16	0.14	Axle	NA
1954	British Grand Prix	Jean Behra	Gordini	18	0.14	Suspension	NA
1954	British Grand Prix	Alberto Ascari	Maserati	24	0.14	Engine	NA
1954	French Grand Prix	Hans Herrmann	Mercedes	14	1.00	Engine	NA
1954	Spanish Grand Prix	Alberto Ascari	Lancia	19	1.00	Clutch	NA
1955	Indianapolis 500	Bill Vukovich	Kurtis Kraft	25	1.00	Accident	NA
1955	Italian Grand Prix	Stirling Moss	Mercedes	14	1.00	Engine	NA
1955	Monaco Grand Prix	Juan Fangio	Mercedes	15	1.00	Transmission	NA
1956	British Grand Prix	Stirling Moss	Maserati	12	1.00	Axle	NA
1956	Indianapolis 500	Paul Russo	Kurtis Kraft	33	1.00	Accident	NA
1958	German Grand Prix	Stirling Moss	Vanwall	21	1.00	Magneto	1
1958	Monaco Grand Prix	Mike Hawthorn	Ferrari	11	1.00	Fuel pump	1
1959	Dutch Grand Prix	Stirling Moss	Cooper-Climax	11	1.00	Gearbox	1
1959	French Grand Prix	Stirling Moss	BRM	12	1.00	Disqualified	1

The pattern in the extract admits a single coherent explanation: the **fastest-lap bonus point**. Every row in the table records exactly one point — the value traditionally attached to the fastest lap — and every `detail` describes a retirement: a mechanical failure, an accident, or, in one case, a disqualification. A driver who sets the fastest lap and then abandons the race cannot be classified, yet the bonus point earned before the retirement remains attached to his name. The rows from 1958 onwards make the mechanism directly visible, since they carry `fastest_lap_rank = 1` in the column whose coverage gap was analysed in Section 2.4.7; the earlier rows show the same one-point signature, but the rank column — not populated before 1958 — cannot corroborate them.

The extract also contains a historical curiosity: at the 1959 French Grand Prix, Stirling Moss was disqualified after setting the fastest lap of the race. Stripped of his classification but not of his bonus point, he appears in this table as the only disqualified driver of the period to score a championship point — a memorable edge case that the export preserves faithfully through the combination of `is_classified = f`, a positive point value, and the `Disqualified` detail.

2.4.10 Country or Nationality

The `team` table attaches a single `nationality` attribute to every constructor. A first extract suffices to raise a question about how that attribute is assigned:

name	nationality
Alfa Romeo	Swiss
Maserati	Italian
Alta	British
ERA	British
Talbot-Lago	French
Ferrari	Italian

Alfa Romeo — one of the most famous Italian carmakers, and almost certainly an Italian team in the championship's early years — appears here as Swiss. The situation is in fact stricter than a mere ambiguity:

DRAFT

Alfa Romeo is recorded as Swiss **for all of its races**, including the very first seasons of the championship, when the team was run as an Italian works outfit. The dataset therefore does not merely store a single nationality per team — it *retrojects the most recent one onto the entire history.* The schema cannot express that the nationality attached to an entity changed over the decades the data spans: whatever value the source associates with Alfa Romeo today (likely reflecting later changes of ownership) silently overwrites the Italian identity the team carried in 1950.

The same limitation, in an even more striking form, affects drivers. A driver may hold and compete under different nationalities during his career, but the export allows only one value per person. Bertrand Gachot is a confirmed case: he entered Grands Prix under a Belgian flag as well as a French flag, yet the `driver` table can record only one of them. The Renault team may present a similar ambiguity, having arguably raced under both French and British identities depending on the period considered.

For the analytical purposes of this work the impact is limited — nationality is used mainly for descriptive statistics rather than as a join key — but the limitation is now confirmed rather than suspected: any temporal analysis of team or driver nationality built on this dataset would wrongly describe the 1950 Alfa Romeo entries as Swiss achievements. This gap is addressed in Chapter 3, where a transformation introduces **season-scoped nationality tables** for teams and drivers, restoring the ability to represent a nationality as it was at the time of each season rather than in its most recent state.

DRAFT

3. Transformation

3.1 Principles

The quality review of Chapter 2 leads to a conclusion that shapes every decision described in this chapter: the Jolpica export is not a dirty dataset in need of cleaning, but a faithful historical record whose apparent anomalies — shared drives, divided points, unclassified but scored drivers — reflect the regulations of the periods they describe. Editing such values would not improve the data; it would destroy it. The transformation work presented here is therefore governed by a deliberately restrictive principle:

> **Jolpica data is preserved as-is. Structural changes (renaming, reshaping, removing redundant columns) are permitted freely; editorial changes to the values themselves are permitted only where the source is demonstrably wrong, and are always documented as explicit corrections.**

Three modifications satisfy this criterion and constitute the analytical schema (`formula1.db`) built with **dbt** on top of the raw `jolpica.db`:

1. the removal of the application-specific `api_id` column from all tables (Section 3.3);
2. the introduction of **season-scoped nationality tables** for drivers and teams, correcting the retrojection problem identified in Section 2.4.10 (Section 3.4);
3. the restoration of fastest-lap coverage for the seasons 1950–1957 from an external source, closing the gap documented in Section 2.4.7 (Section 3.5).

Everything else passes through unchanged. The historical quirks analysed in Sections 2.4.3–2.4.9 are carried into the analytical schema deliberately, and Section 3.6 records this decision explicitly so that future readers do not mistake preserved history for uncorrected defects.

DRAFT

3.2 The dbt Layer

The transformation is implemented with **dbt** and executed on the local SQLite database (`jolpica.db`) produced by the pipeline's load step. Each raw table is declared as a dbt source, and models are organised in the customary staging → mart progression. The lineage of the current implementation is shown below.




Figure 3: Transformation lineage: Jolpica source tables (left) mapped through dbt to the analytical tables (right). This figure is a snapshot; the full, interactive and always up-to-date diagram is available in the project's online dbt documentation.

Two observations about the shape of this graph summarise the philosophy of Section 3.1. First, the large majority of source tables map one-to-one to their analytical counterparts with no intermediate logic: they are renamed, stripped of `api_id`, and passed through. Second, the deviations from this pattern are few and concentrated — the nationality corrections feed two dedicated tables, the external fastest-lap source feeds the enriched results model, and a single derived view exists at present. The transformation layer is intentionally thin, and it is expected to grow slowly: as new analytical views are added, the online documentation will diverge from the snapshot reproduced here, which is precisely why the authoritative version is published alongside the dbt-generated documentation rather than frozen in this document.

DRAFT

3.3 Removing the `api_id` Columns

As established in Section 2.4.2, every table of the export begins with an `api_id` column that identifies records within Jolpica's own infrastructure but carries no analytical meaning. All such columns are dropped during the staging step. The removal is purely structural — it affects no values, no joins and no row counts — and is verified by the row-count checks described in Section 2.2.

It should be stressed that this is a **deferral, not a rejection**, of the underlying information. Should a need ever arise to trace analytical records back to Jolpica's API endpoints — for example, for debugging the extraction process or reconciling against future revisions of the dump — the original identifiers can be recovered from the raw SQLite snapshot, which is itself version-controlled and distributed with the pipeline. Introducing dedicated application-level lookup tables now would add joins and maintenance surface for a use case that does not currently exist; the decision is therefore recorded here and revisited only if that use case materialises.

DRAFT

3.4 Season-Scoped Nationalities

Section 2.4.10 documented the central limitation of the raw schema regarding nationality: a single, current-day value is retrojected onto the entire history of each driver and team, so that the 1950 Alfa Romeo works outfit — unambiguously Italian at the time — is recorded as Swiss, and drivers who competed under more than one nationality, such as Bertrand Gachot, can exhibit only one of them.

Fixing this properly would mean recording the nationality of every entity in every season. For roughly 800 drivers and several hundred constructor entities spanning three quarters of a century, such a complete mapping cannot be reliably constructed from public records, and fabricating coverage would violate the principle of Section 3.1. The transformation therefore takes a narrower and more honest form:

- the original `country_code` attributes on `driver` and `team` are retained unchanged and continue to serve as the **default** nationality;
- two dedicated correction tables, `driver_nationality_corrections` and `team_nationality_corrections`, associate a country with an entity **over an explicit season interval** (`season_id_start` to `season_id_end`), overlaying the default wherever a correction exists.

The resulting model restores temporal resolution exactly where it is needed: a query about a driver's or team's nationality in a given season resolves against the correction table first, and falls back to the source value otherwise. Corrections are applied only to the cases documented in Section 2.4.10 — Alfa Romeo's Italian identity prior to its post-war reorganisation, Renault's dual French/British identity, and drivers with confirmed multi-nationality careers such as Gachot — each entry traceable to the historical evidence discussed in Chapter 2.

driver_id	season_id_start	season_id_end	country_code
684	40	41	FRA

team_id	season_id_start	season_id_end	country_code	name
152	62	62	GBR	Lotus Renault GP
1	1	2	ITA	NA
1	30	36	ITA	NA

The distinction from the raw schema is worth making explicit: where Jolpica can only state what an entity's nationality *is*, the analytical schema can state what it *was at the time of a given season*. Temporal analyses of nationality built on `formula1.db` now describe the 1950 Alfa Romeo entries as Italian, at the cost of a single join and a documented, extendable correction mechanism.

DRAFT

3.5 Restoring Fastest-Lap Coverage, 1950–1957

Section 2.4.7 located a precise coverage boundary in the source: the `fastest_lap_rank` column is empty for every session before the 1958 season, because officially tracked fastest laps were not part of the championship's recordkeeping before then. The irony highlighted there — that the seven drivers who jointly set the fastest lap at the 1954 British Grand Prix carry their 1/7-point award in `points` but cannot be recognised by the dedicated column — is preserved verbatim by the pass-through philosophy of this chapter.

However, unlike the other quirks of Chapter 2, this gap is a genuine *absence* of data rather than a period-accurate encoding, and the missing information is recoverable: an external dataset records the fastest-lap achievers for the seasons 1950–1957. As part of the imminent modifications to the pipeline, this external table will be joined onto the results model, populating `fastest_lap_rank` (and the related fastest-lap attributes) for the affected seasons. The enrichment is applied exclusively where the source is empty, so the original values from 1958 onwards remain untouched and traceable to Jolpica; provenance of the enriched values is recorded separately, in keeping with the audit practices of the pipeline.

For the shared-award cases of Section 2.4.6, the enrichment deliberately records the joint achievement as it stands in the historical record rather than electing a single fastest driver — consistent with the treatment of multi-winner races in Section 2.4.4.

With this change, fastest-lap coverage becomes complete across the entire championship history, and the "absent fastest lap" ceases to be a limitation of the analytical dataset — while remaining faithfully absent from the raw snapshot, which is never modified.

DRAFT

3.6 A Convenience View: `f1summary`

The analytical schema is normalised: answering even a simple question — *who finished where, in which car, scoring how many points?* — requires joining `session_entry`, `round`, `season`, `circuit`, `driver`, `team` and the nationality resolution logic of Section 3.4. Writing these joins anew for every query or visualisation is error-prone and obscures the analysis itself. To make day-to-day access to the dataset frictionless, the transformation therefore includes **convenience views**: flat, de-normalised tables that pre-resolve the most common joins and expose the data ready for display.

The principal view is `f1summary`, one row per race result, whose columns are listed below.

Column	Description
resultId	Unique identifier for each result
grid	The driver's starting grid position
positionOrder	The driver's finishing position in order
points	Points scored by the driver in the race
laps	Number of laps completed by the driver
rank	The rank of the driver's fastest lap
statusId	Foreign key to status.csv
year	The year of the race
round	The round number of the race in the season
circuit	The official name of the circuit
driverNationality	The driver's nationality
constructorName	The full name of the constructor
constructorNationality	The nationality of the constructor
status	A description of the finishing status
driverAge	The driver's age at the time of the race
driverName	The driver's full name

An extract of the view illustrates the outcome: each row combines result, context and human-readable attributes into a single, display-ready record.

resultId	positionOrder	points	year	circuit	driverName	driverAge	constructorName
1	1	9	1950	British Grand Prix	Nino Farina	44	Alfa Romeo
2	2	6	1950	British Grand Prix	Luigi Fagioli	52	Alfa Romeo
3	3	4	1950	British Grand Prix	Reg Parnell	39	Alfa Romeo
4	4	3	1950	British Grand Prix	Yves Cabantous	46	Talbot-Lago
5	5	2	1950	British Grand Prix	Louis Rosier	45	Talbot-Lago
6	6	0	1950	British Grand Prix	Bob Gerard	36	ERA

Two details of the view deserve emphasis. First, the nationality columns (`driverNationality`, `constructorNationality`) are **not** a verbatim copy of the source attributes: they are resolved through the season-scoped correction mechanism of Section 3.4, so the 1950 entries display Alfa Romeo as Italian rather than Swiss. This is precisely the kind of logic that belongs inside a view rather than being reimplemented (or forgotten) in every downstream query. Second, derived attributes computed during transformation — `driverAge` among them — appear alongside the raw passthrough columns, giving the view everything needed for descriptive analysis without touching the normalised tables.

The view is intentionally materialised as a thin projection over the analytical tables rather than a replacement for them: any measure beyond its fixed column set (per-lap timings, pit stops, championship trajectories) still queries the underlying schema directly. As the transformation layer grows, additional views following the same pattern will be added; the online dbt documentation referenced in Section 3.2 remains the authoritative record of what currently exists.

DRAFT

3.7 The Resulting Schema

The outcome of the transformation is the analytical database `formula1.db`, whose structure is shown below. The raw tables appear in the schema largely unchanged, grouped by domain; the additions of Section 3.4 are visible as the two `*_nationality_corrections` tables together with the `countries` lookup, and the season-scoped `season_driver` and `season_team` associations.




Figure 4: Entity-relationship diagram of the analytical database ‘formula1.db‘ after transformation.

3.8 What Is Deliberately Not Changed

Completeness requires stating the inverse of the preceding sections: the anomalies of Chapter 2 that survive the transformation **on purpose**.

The multiple-winner races arising from shared drives (Section 2.4.3) and the fractional points they produce (Section 2.4.6) are preserved as-is; any "deduplication" would erase the only record that several drivers jointly achieved a result. The driver whose eligibility flag contradicts a positive point total (Section 2.4.8) is likewise preserved — the combination of `is_eligible_for_points` and the notional point share encodes a genuine period regulation, and separating the two columns would lose it. Unclassified drivers carrying a fastest-lap point (Section 2.4.9) are retained, including the singular case of Stirling Moss at the 1959 French Grand Prix. Finally, the legacy `roundentry` linkage and the empty staging tables (`base_team`, `penalty`) are carried through unchanged: they cost nothing, document the source's own evolution, and removing them would couple the analytical schema to assumptions about Jolpica's future development.

Further integrity inconsistencies identified in Chapter 2 that do not admit a verified correction at present are explicitly deferred: as with the application-level identifier lookup tables of Section 3.3, the guiding rule is that a documented limitation is preferable to a silent or speculative "fix". The corrections mechanism of Section 3.4 and the enrichment of Section 3.5 establish the pattern by which such fixes will be introduced as evidence becomes available — narrowly scoped, individually documented, and never at the expense of the raw snapshot.

DRAFT

4. Exploratory Data Analysis

This chapter explores the dataset along three levels, each one stepping back from the raw record book. We first examine the drivers and the achievements they accumulated — titles, wins, careers. We then turn to the constructors, whose cars set the ceiling under which those achievements were earned. Finally, we examine the championship framework itself — the calendar and the scoring rules — and show that any comparison of drivers across eras must first neutralize how much the framework has changed.

4.1 Drivers

4.1.1 Grand Prix

The formula 1 world championship started in 1950, and has been held since then with no interruption. As of 2026, 76 seasons has been held, with 1,149 races where 817 drivers were involved. Only 115 won a race, and 35 won the world champion title :

Number of Seasons	Number of Races	Number of Drivers	Number of Winners	Number of Champions
76	1,149	817	115	35

Out of the 35 world champions, 17 of them won the title several times. The plots below show the number of drivers per title or win category :




Figure 5: Number of Titles or Wins per Driver

If we remove the drivers who didn't win any title or Grand Prix, we can see the distinction in the plots below :




Figure 6: Number of Titles or Wins per Driver (who won at least one race or title)

The plots above show that most drivers didn't win any title. For those who won at least one, half won only one title while the other won 2 or more titles.

Very few drivers were able to become world champion while winning less than 11 Grand prix in their whole career, and with no surprise they were all competing in the early years, the most recent title being won by Keke Rosberg in 1982, Rosberg who won 5 Grand Prix in his whole career :

driverName	titles	wins	year
Nino Farina	1	5	1950
Mike Hawthorn	1	3	1958
Phil Hill	1	3	1961
John Surtees	1	6	1964
Denny Hulme	1	8	1967
Jochen Rindt	1	6	1970
James Hunt	1	10	1976
Jody Scheckter	1	10	1979
Keke Rosberg	1	5	1982

On the other side, we also have drivers who, while winning many races (more than 10), didn't win any title. The list below shows that, unlike for the low-wins world champions, some of them were competing in the early years of the F1. Notably, Carlos Reutemann and above all, Stirling Moss won 16 Grand Prix over a career of 11 years starting in 1951 and ending in 1961. As a comparison the champion Fangio won 24 races and 5 titles at the same period (1950-1958) :

driverName	wins	careerstart	careerend	careerlength
Stirling Moss	16	1951	1961	11
Carlos Reutemann	12	1972	1982	11
Rubens Barrichello	11	1993	2011	19
David Coulthard	13	1994	2008	15
Felipe Massa	11	2002	2017	15

DRAFT

4.1.2 Winning Probability




Figure 7: Probability of Winning

The ploys above show that the probability of winning is very low for drivers who didn't win a title, and stays about 50% for the other ones. So each time a driver wins a title, he has 50% of chances to win another one. The 100% probability at 6 titles is not very accurate given the low number of drivers who won more than 5 titles (only 3 including Fangio).

4.1.3 Top Drivers

If we define the leading drivers as those with the highest number of titles, and among those who are world champions with an equal number of titles, we can use the number of wins to differentiate them. This results in the following table displaying the 17 drivers who won at least 2 titles (as of 2025) :

driverName	titles	wins	races	seasons	points	titlespc	winspc
Lewis Hamilton	7	105	380	19	4,955.50	0.368	0.276
Michael Schumacher	7	91	308	19	1,566.00	0.368	0.295
Juan Fangio	5	24	58	8	279.14	0.625	0.414
Max Verstappen	4	71	233	11	3,301.50	0.364	0.305
Sebastian Vettel	4	53	300	16	3,098.00	0.250	0.177
Alain Prost	4	51	202	13	798.50	0.308	0.252
Ayrton Senna	3	41	161	11	614.00	0.273	0.255
Jackie Stewart	3	27	100	9	360.00	0.333	0.270
Niki Lauda	3	25	173	13	420.50	0.231	0.145
Nelson Piquet	3	23	205	14	485.50	0.214	0.112
Jack Brabham	3	14	129	16	261.00	0.188	0.109
Fernando Alonso	2	32	428	22	2,380.00	0.091	0.075
Jim Clark	2	25	73	9	274.00	0.222	0.342
Mika Häkkinen	2	20	163	11	420.00	0.182	0.123
Emerson Fittipaldi	2	14	146	11	281.00	0.182	0.096
Graham Hill	2	14	177	18	289.00	0.111	0.079
Alberto Ascari	2	13	36	6	140.14	0.333	0.361

DRAFT

For each driver, we observe the number of titles, total races won, total races competed, the number of seasons or years they participated, the total points earned (only those that count toward the championship), the ratio of titles to seasons, and the ratio of wins to races.

Although the number of titles and races won clearly shows that Michael Schumacher and Lewis Hamilton outshine other drivers, the same is not necessarily the case for points. When we rank drivers by points, both Verstappen and Vettel surpass Schumacher. Even Alonso who won 2 titles, compared with the 7 by Schumacher, has more points than the latter.

To add another layer of complexity, if we look at the ratio of titles to seasons or the ratio of wins to races, Juan Manuel Fangio emerges as the top performer. Even Ascari, who appears at the bottom of the list, has the second best ratio win to races.

Now if we look at the first 9 pilots, only 2 of them (Fangio and Stewart) were racing at the earliest days of Formula 1. On the opposite, if we look at the last 8 drivers, 4 of them were driving at the earliest days : Brabham, Clark, Hill and Ascari. We can also notice that most of these early drivers had a career under 10 years, when modern days drivers have a career that last more than 10 years if not 20. Only notable exception is Graham Hill who had a long career of 18 years from 1958 to 1975.

We will now see the careers and titles of these 17 drivers across the years.

DRAFT

4.1.4 Timeline

The plot below illustrates the duration and timeline of careers without indicating any breaks; for instance, Alain Prost did not compete in 1992, and Schumacher was absent from the tracks from 2007 to 2009.




Figure 8: Careers

Some drivers enjoyed longer careers than others. For instance, Alonso, Schumacher, and Hamilton had the longest career spans, while Ascari, Clark, and Stewart had the shortest. The problem with this graph is that it does not effectively depict the dominance of any particular driver. For instance, Alonso secured his two titles in 2005 and 2006, and has continued racing since without winning any additional titles.

Now, if we replace the career duration with titles, where each segment represents the years between a driver's first and last title, we obtain the following graph :




Figure 9: Titles

We divided this timeline into three phases: the first phase, the early stage, extends from the beginning until the late 1960s. The second phase begins with Jackie Stewart's first title in 1969 and continues until Michael Schumacher's first title in 1994. The final phase, or modern era, starts in 1994 and continues to the present.

In the plot above, each phase is marked with a vertical dashed grey line.

Now, when we display the career lengths based on the year of the first title, we can observe a gradual increase over the years :




Figure 10: Career Start vs Career Length

A clear upward trend emerges, suggesting that drivers who started their careers in more recent decades tend to have longer careers. This may be attributed to various factors, including advancements in safety, improvements in car technology, and changes in race formats that allow for prolonged competition. Notable drivers in the modern era, such as Hamilton, benefit from these advancements, resulting in extended careers compared to drivers from earlier periods.

We can notice that while Juan Manuel Fangio was able to secure 5 titles within 8 years in the 1950s, Michael Schumacher and Lewis Hamilton achieved their 7 titles in 19 and 20 years respectively, with Hamilton still actively competing. This illustrates how the demands and dynamics of racing have shifted over time. The differentiation of data points by title count adds another layer of insight. Drivers with more titles, represented by larger and darker-colored points, typically have career lengths that align with the observed trend. The correlation suggests that those who excel and secure multiple championships also tend to enjoy longer careers, potentially due to their consistent performance, adaptability, and resilience in the competitive environment.

Conversely, while some historical drivers achieved significant success in fewer years, many of them faced different challenges, such as fewer races per season and a more hazardous racing environment. This context helps explain why earlier drivers, despite their talent, often have shorter career lengths represented in the plot.

The dashed line in the graph indicates the overall trend, reinforcing the notion that career length has increased over time for Formula 1 drivers. This trend not only reflects the effects of improved safety and technology but may also point to changes in how drivers manage their careers, including fitness and approach to racing.

4.1.5 Comparison

Now, let's compare the top drivers based on their wins and the number of races they have participated in :




Figure 11: Wins vs Races

There is a noticeable upward trend in the plot, suggesting that drivers who participate in more races tend to achieve a higher number of wins. This correlation implies that experience and track time significantly contribute to success in the sport. Drivers from the 1994 to 2023 era, such as Hamilton and Vettel, are positioned in the top right quadrant, indicating both a high number of races and wins. The representation of this era in a distinct color underscores the advantages of modern technology and greater competitiveness, reflecting a notable shift in performance standards.

The varying colors used to group drivers by era emphasize the differences in victory rates and opportunities for success across time. Historical drivers may have achieved fewer wins but did so in a context with fewer races and different competitive landscapes. For instance, earlier eras, represented in warmer colors, often had fewer wins despite high title counts, pointing to the unique challenges faced by those drivers. Additionally, Fernando Alonso stands out for having a considerable number of races with only two titles, highlighting that a lengthy career does not guarantee championship success. This suggests that various external factors, such as team dynamics and competitive context, play significant roles in determining outcomes.

Overall, the plot illustrates that while participation in a greater number of races can lead to more wins, it does not exclusively dictate a driver's success. Factors like team performance, car technology, and the competitiveness of each era are crucial. The shifts in driver success across different decades indicate an evolution in Formula 1, influenced by changes in race formats and team strategies, as well as an expanding global audience. The color-coded groupings serve to highlight how drivers' experiences and achievements are shaped by the specific challenges and opportunities of their respective eras. This analysis provides a thorough understanding of the factors influencing driver success in Formula 1, as visualized through the plot, while also acknowledging the historical context that contributes to these differences.

And now the number of titles and seasons per driver :




Figure 12: Titles vs Seasons

While the plot displays a trend where drivers with more seasons tend to win multiple titles, this is true for those who have achieved two or more titles. Notably, modern drivers such as Hamilton and Vettel, positioned in the top right quadrant, exemplify this trend, showcasing the advantage of extended careers combined with high performance. Their achievements in more recent years highlight the advancements in technology and team strategies that have influenced competitive outcomes.

The color coding of the data points emphasizes differences in performance across historical eras. For instance, drivers from the 1950 to 1988 timeframe, such as Fangio and Clark, achieved multiple titles within fewer seasons, reflecting the unique challenges of their competitive environments, which often had fewer races and different dynamics compared to today. This juxtaposition illustrates how the number of titles can vary significantly based on the era in which the drivers competed.

Additionally, the representation of drivers like Alonso showcases the relationship between seasons and titles, as he has spent a considerable number of seasons in the sport but has only two titles. This highlights that having a long career does not always correlate with championship victories, suggesting the impact of factors like team performance, adaptability, and the competitive landscape at any given time.

Overall, the plot underscores that while participation in more seasons can lead to multiple titles, it does not guarantee success. Various factors, including team dynamics, technological advancements, and the competitive environment in different eras, play crucial roles in determining a driver's achievements. The shifts in performance across different decades indicate an evolution within Formula 1, influenced by changing race formats and an increasingly global audience. This analysis provides a comprehensive understanding of how the number of seasons impacts title success while also recognizing the historical context that shapes these outcomes.

4.1.6 Summary

[We saw that recent drivers achieved better results with time, we also saw that some drivers were able to achieve better or same results in a shorter timeframe.

But this is not enough to determine if these drivers were really better than others. Would Fangio have achieved 10 titles have he run 16 seasons? What about the variation of number of races, points and rules over the seasons? And what about the car itself?]

We observed that recent drivers have generally achieved better results over time, indicating a trend of improved performance in modern Formula 1. This improvement can be attributed to a variety of factors, including advancements in technology, enhanced training practices, and improved team dynamics. However, it is equally noteworthy that some drivers from earlier eras managed to achieve comparable results within a significantly shorter timeframe. This raises an important question regarding the true measure of a driver's ability and whether career longevity directly equates to skill or success on the race track.

To determine if these recent drivers are genuinely better than their predecessors, we must consider multiple dimensions of comparison. For instance, would Juan Manuel Fangio have achieved 10 titles if he had raced for 16 seasons, similar to modern drivers? Fangio, who secured his five titles in just eight years during the 1950s, faced vastly different competitive landscapes and challenges than those in contemporary racing. His remarkable success in such a brief period prompts an investigation into context: how much of his success was due to his skill versus the circumstances and limitations of his era?

Additionally, the evolution of the sport itself complicates these comparisons. Over the years, Formula 1 has undergone significant changes in terms of race formats, scoring systems, and regulations. The number of races in a season has fluctuated, impacting a driver's opportunity to accumulate wins and points. In some seasons, drivers competed in fewer races, which naturally limits their chances for high totals, making it essential to contextualize statistics within the framework of their respective eras.

Points systems have also varied dramatically, altering how achievements are measured. Modern scoring rewards consistency and resilience across more races, which can skew comparisons against drivers from the past, who may have excelled under a different set of rules. For instance, Fangio's era awarded fewer points for victories, but achieving those wins was often subject to harsher competition and racing conditions.

Moreover, the cars themselves represent a crucial aspect of this discussion. The technology and engineering behind F1 cars have advanced exponentially over the decades, with modern vehicles benefiting from aerodynamics, data analysis, and materials that were not available in the past. This raises another question: how much of a driver's success is attributable to their talent and how much is due to the superior performance of the car?

The answer, of course, is that no such verdict can be reached from raw tallies alone. Would Juan Manuel Fangio have accumulated 10 titles had he contested 16 seasons like a modern driver, instead of the 8 years over which he collected his 5? The question sounds speculative, but its premise is measurable: the number of races contested per season, the points awarded for each result, and the number of seasons over which a career could unfold all differ systematically between Fangio's era and Hamilton's. A title count, a win count, or a points total is therefore not a pure measure of ability — it is a count of *opportunities converted*, and the number of opportunities on offer varied enormously across the championship's history.

Before these quantities can be compared, one further confounder must be acknowledged: none of the results catalogued above were achieved alone. Every win and every title was earned in a car built by a constructor, and the spread between the dominant machines and the rest has been wider in some eras than in others. The next section therefore turns to the constructors, whose fortunes bound those of the drivers they employ.

4.2 Constructors

The table below shows the number of constructors involved in the championship over the years ;

Number of Constructors	Points	Wins	Titles
203	106	47	18

As of 2025, 203 constructors participated in the world championships. 106 of them won at least one point, 47 won a race and 18 won a title.

And this is a list of the constructors who won the championship at least once :

constructorName	titles	wins	points	start	end	seasons
Ferrari	22	249	11,451.27	1950	2025	76
McLaren	11	199	7,797.50	1968	2025	56
Mercedes	9	131	8,154.64	1954	2025	18
Williams	9	114	3,765.00	1975	2025	50
Red Bull	6	130	8,083.00	2005	2025	21
BRM	3	17	537.50	1951	1977	23
Renault	2	35	1,777.00	1977	2020	24
Tyrrell	2	23	711.00	1970	1998	29
Cooper-Climax	2	12	336.50	1959	1968	9
Brabham-Repco	2	8	175.00	1966	1969	4
Team Lotus	1	45	995.00	1958	1994	29
Benetton	1	27	861.50	1986	2001	16
Lotus-Climax	1	22	281.00	1961	1967	7
Alfa Romeo	1	11	361.00	1950	2023	16
Lotus-Ford	1	11	209.00	1963	1971	5
Maserati	1	9	313.42	1950	1960	11
Matra-Ford	1	9	130.00	1968	1969	2
Brawn	1	8	172.00	2009	2009	1

Ferrari stands out prominently with 22 titles and 249 wins, indicating a dominant presence in the sport since 1950. McLaren and Mercedes follow, with 11 and 9 titles respectively. Constructors like Williams and Red Bull have also made significant contributions, evidenced by their multiple wins and points. However, it's important to note that constructors such as Mercedes and Alfa Romeo did not participate consistently throughout the years. For instance, Mercedes withdrew from racing after the 24h of Le Mans disaster in 1954 and returned to the tracks only in 2010. Similarly, Alfa Romeo has had gaps in its participation, despite its historical significance, which reflects the varying levels of engagement among different teams over the decades.

DRAFT

Now the constructors results over time. Comparison between constructors who won most points from first to second :




Figure 13: Constructor Results

And the driver results as a comparison :




Figure 14: Driver Results

These trajectories make clear that a driver's record is partly a record of the car beneath him. Fangio's 5 titles were won with four different manufacturers — a feat reflecting an era in which the field was comparatively level — while several modern champions collected titles in long stretches of team dominance that no rival could match. Participating in the right era of the right constructor can thus inflate or deflate a driver's tally as surely as any change of rules. Yet even controlling for the car does not level the playing field, because the two frameworks in which every constructor and driver operated — the length of the calendar and the scoring system — shifted repeatedly across the decades. It is to these framework effects that the final section of this

chapter turns.

DRAFT

4.3 Championship Framework

4.3.1 Races

The plot below illustrates the trend in the number of Formula 1 races held each year from 1950 to 2023. The x-axis represents the year, while the y-axis indicates the number of races. Each point reflects the actual number of races for that specific year, depicted in gray, and the variation among these points indicates fluctuations in race counts over the years, reflecting changes in the racing calendar and external factors affecting the sport.




Figure 15: Races per Year

A clear upward trend is evident, starting from just 7 races in 1950 and gradually increasing, with several plateaus extending into the late 20th century. A more pronounced rise occurs in the 21st century, culminating in approximately 23 races by 2023, suggesting the growing popularity and expansion of Formula 1.

The loess smoothing curve, shown in royal blue, overlays the data points to provide a clearer representation of the overall trend in race numbers. This curve highlights the acceleration in race counts, particularly after 2000, indicating that Formula 1 has adapted to demand and increased the frequency of races. The shaded area around the smoothing line captures the confidence interval of the smoothed trend in a light blue hue, suggesting the level of uncertainty about the estimated values and demonstrating the variability in the data points over the years.

The plot conveys the evolution of Formula 1 through the number of races conducted annually. The sharp increase in races in later years reflects various factors, such as enhanced global interest in motorsports, changes in regulations, and the expansion of the racing calendar. The data's variability, particularly in the earlier decades, can be attributed to the formative years of the sport, which experienced significant changes in organization and promotion.

The plot below shows for every world champion, the percentage of wins over the season :




Figure 16: Percentage Wins

We can see that from 1965 and Jim Clark's title, until 2004 and Michael Schumacher third or fourth title, that is a period of 40 years, no pilot achieved a win to race ratio over 65%. And if we filter out the earlier championships with less than 12 races (where a high percentage is easier to achieve than when there are more races), the only high percentage championships are the recent ones, that is after 2000.

The two highest percentages are when Max Verstappen won the title in 2023 with 19 races won over 22, and Alberto Ascari with 6 wins over 7 races. Both achieved more than 85% win success.

year	driverName	nbraces	wins	winspc
2023	Max Verstappen	22	19	86.4
1952	Alberto Ascari	7	6	85.7
1954	Juan Fangio	8	6	75.0
2004	Michael Schumacher	18	13	72.2
1963	Jim Clark	10	7	70.0
2020	Lewis Hamilton	16	11	68.8
2013	Sebastian Vettel	19	13	68.4
2022	Max Verstappen	22	15	68.2
1955	Juan Fangio	6	4	66.7
1965	Jim Clark	9	6	66.7

Draft

On the other side, it is possible to win the championship by winning less races. The table below shows the drivers who won the championship with the lowest win to race ratio :

year	driverName	nbraces	wins	winspc
1964	John Surtees	10	2	20.0
1974	Emerson Fittipaldi	15	3	20.0
1977	Niki Lauda	15	3	20.0
1979	Jody Scheckter	15	3	20.0
1981	Nelson Piquet	15	3	20.0
1983	Nelson Piquet	15	3	20.0
1987	Nelson Piquet	16	3	18.8
1967	Denny Hulme	11	2	18.2
1958	Mike Hawthorn	10	1	10.0
1982	Keke Rosberg	15	1	6.7

We can se that from 1974 until 1987, it was very common to win the world title with less than 20% races won. Notably, the Brasilian driver Nelson Piquet won his 3 world titles by winning less than 20% of the races each time.

The record being held by Keke Rosberg who won the 1982 championship by winning only 1 race out of 15.

Note tat in 2025 the win to races ratio was one of the lowest in the recent years : with only 29% wins, Lando Norris was able to win the title, even with less victories (7) than Verstappen (8). His teammate Piastri was able to win the same number of races.

DRAFT

4.3.2 Points and Rules

The evolution of points systems and rules in Formula 1 has undergone significant changes over the years, reflecting the sport's adaptability to enhance competition and viewer engagement. Understanding these modifications is crucial for properly interpreting statistics and achievements across different eras of racing.

One of the most notable changes in the points system involves the method of calculating scores based on race results. In earlier years, drivers earned points for finishing in the top positions, but not all results were counted towards the championship. For instance, the introduction of the "**8 best results**" system allowed drivers to select their top performances to be counted toward their final tally. This change meant that a driver could have an off day in a few races but still remain competitive based on their standout performances. The revised approach promotes consistency and allows for some leeway, encouraging drivers to focus on achieving high results in selected races rather than simply accumulating points in every competition.

In recent years, the integration of new formats such as **sprint races** has further influenced the dynamics of scoring. Sprint events, which typically take place on weekends with traditional Grand Prix races, offer additional points opportunities. This development adds an exciting layer to the race weekend, allowing drivers to earn points not just through their main races but also by performing well in shorter sprints. The introduction of these sprints has reshaped strategies, pushing teams to adapt their approaches to maximize potential points across various race formats.

Another element that has gained attention is the inclusion of points awarded for the **fastest lap** during a race, further enriching the competitive landscape. By recognizing drivers who secure the fastest lap, this rule incentivizes aggressive racing strategies, compelling drivers to push their limits even when their overall position may not warrant it. This addition exemplifies how changes in rules can elevate the excitement and intensity of each race.

As we compare drivers and their results over time, it is important to note that we will not consider sprint races or fastest laps in our study. Our analysis will focus solely on race results, and we will take into account all points awarded across each driver's career. This approach allows us to maintain a more consistent basis for comparison, ensuring that our findings reflect the fundamental aspects of performance in Formula 1.

The implications of these transformed points systems extend beyond mere statistics. They affect team and driver strategies, influencing how races are approached. Teams may prioritize specific races or adopt riskier tactics, knowing that achieving the fastest lap or excelling in a sprint can contribute critically to their overall standings. This fosters a more vibrant competitive environment where drivers constantly seek opportunities to maximize their returns, complicating the notion of what it means to be successful in Formula 1.

Moreover, when comparing drivers across different eras, it becomes essential to contextualize their accomplishments within the frameworks established by the rules at the time. Historical figures like Juan Manuel Fangio, for example, achieved remarkable titles under a vastly different scoring system, contrasting sharply with the multifaceted approach seen today. Understanding these differences in rules and points systems allows fans and analysts to appreciate the evolution of the sport while acknowledging the unique challenges faced by drivers across generations.

DRAFT

The plot below shows the number of points given according to the race final position :




Figure 17: Points per Year

Until 1959, the scoring system for races awarded the winner 8 points, with an additional point granted for the fastest lap achieved during the race. However, in 1960, the point for the fastest lap was eliminated, and instead, the driver finishing in 6th position would receive one point. The following year, in 1961, the points awarded to the winner increased to 9, further evolving the scoring structure. By 1991, winners would receive 10 points, while other position points remained unchanged. The scoring system underwent a significant revision in 2003, when drivers other than the winner began to receive an additional 2 points. Additionally, drivers finishing in 7th and 8th positions would earn 2 points and 1 point, respectively. By 2010, the rules changed again, increasing the winner's points to 25 and extending points to the top 10 finishers.

Although not depicted in this analysis, it's worth noting that in 2019, a point for the fastest lap was reintroduced. Furthermore, between 1950 and 1990, only certain race results contributed towards the championship standings, indicating fluctuations in how scoring impacted overall competitive success during that period.

DRAFT

The plot below shows the percentage difference :




Figure 18: Percentage Difference

From 1950 until 1959, the winner received 33% more points than the second-place driver, who was awarded 50% more points than the driver finishing in third, while the third place earned 33% more points than the fourth. However, in 1960, the rules shifted so that the winner received 50% more points than the second-place driver, and this percentage increased to 66% in 1991. Starting in 2003, this difference in points began to decrease significantly, with a slight increase in 2010, resulting in the winner obtaining approximately 40% more points than the second-place finisher, who in turn received 20% more than the third, while the third place earned 25% more than the fourth.

This plot illustrates how the importance of finishing position has diminished since 2003, suggesting that the risks associated with overtaking another driver may no longer justify the potential rewards. As drivers weigh the dangers of overtaking, the incentive structure of points allocation reflects a changing competitive landscape, where maintaining position may become a more strategic choice.

DRAFT

The table below displays championships in which the driver who earned the highest total points did not win the title. This occurred because only a portion of these points were counted, allowing the second-place driver to secure the championship with a greater proportion of their retained points :

year	driverNameChampion	pointsChampion	driverNameBest	pointsBest
1964	John Surtees	40(40)	Graham Hill	41(39)
1988	Ayrton Senna	94(90)	Alain Prost	105(87)

In the world of Formula 1 racing, championship titles are not solely determined by the total points a driver accumulates over the season. This nuance became particularly evident in dramatic cases such as those of John Surtees in 1964 and Ayrton Senna in 1988.

In 1964, John Surtees clinched the World Championship with a total of 40 points, and importantly, all of these points were eligible for inclusion in the championship standings. Surtees faced stiff competition from his rival, Graham Hill, who ended the season with 41 points—just a single point ahead. However, not all of Hill's points were counted towards the championship, as only 39 points were eligible, thus causing him to lose the title to Surtees. This incident serves as a poignant reminder of the impact of point retention rules in determining the final standings, which can overshadow pure performance metrics.

Fast forward to 1988, when the same theme of point retention played out yet again in a fierce rivalry between Ayrton Senna and Alain Prost. Senna finished the season with an impressive 94 points, out of which 90 points were counted towards his championship total. Conversely, Alain Prost amassed a remarkable 105 points but faced a significant setback as only 87 of these points were deemed eligible for the championship classification. This discrepancy ultimately placed Prost in second position, despite his overall higher point total.

DRAFT

The plot below shows the total number of points given per year :




Figure 19: Total Points per Year

In conclusion, the changes in points and rules over time significantly impact how success and performance are measured in Formula 1. The transition from early systems to contemporary practices reflects the sport's commitment to enhancing competitiveness and excitement. Analyzing these developments provides crucial context for assessing driver achievements and understanding the strategic decisions made by teams and drivers alike. The interplay between points systems, race formats, and performance metrics illustrates the complexity of the sport and highlights how Formula 1 continually evolves to captivate its audience.

DRAFT

4.3.3 Comparing Across Eras

The previous two sections of this chapter have each peeled back one layer between a driver's statistics and his ability: the car he drove, and now the framework in which he raced. Putting the framework's dimensions together, the drift across the championship's history is stark. In 1950 a title was decided over 7 races; by the 2020s, a season comprises roughly four times as many, multiplying the occasions on which a strong driver can win and score. The points attached to a victory have grown from 8 to 25, and the widening of the points-paying positions — from the top five to the top ten — further rewards consistency over the long calendars of the modern era. And careers themselves have stretched: where drivers of the 1950s typically raced fewer than ten seasons, the front-runners of today contest twenty or more, giving each generation more seasons in which to stack titles.

None of this is evidence that modern drivers are superior; it is evidence that the units in which their records are denominated have inflated. A win in 1953 was scarcer by a factor of three than a win in 2023, a title cost fewer conversions, and a season offered fewer opportunities to convert them at all. Raw tallies — the 105 titles, wins and points enumerated at the opening of this chapter — therefore measure opportunities converted, not skill displayed.

The conclusion for the remainder of this study follows directly. To compare drivers of different eras fairly, the framework must be held constant along all three dimensions:

- **Scoring** — each result should be awarded the same points regardless of the season in which it was achieved, normalizing away the evolution from the 8-point systems of the 1950s to the 25-point system in force today;
- **Calendar** — each season should be reduced to a common number of races, so that a champion of a 7-round calendar is not penalized relative to a champion of a 24-round one;
- **Longevity** — each career should be measured over the same number of seasons, since the inflation of career length across the decades mechanically favours recent drivers in any cumulative statistic.

Only under these three normalizations do titles, wins and points become comparable quantities — and only then can the question left open in Section 4.1.6, whether Fangio would have matched today's champions on equal terms, be answered with data rather than opinion. Chapter 5 implements exactly these transformations.

DRAFT

9. References

[1] Hergé. 1956. “The Calculus Affair” https://www.tintin.com/en/albums/the-calculus-affair

[1] Jean-Luc. 2019. “Tintin – The Calculus Affair – The liberties of English translation” https://tintinomania.com/tintin-affaire-tournesol-anglais-brabham

[2] Kaggle “Formula 1 World Championship (1950 - 2024)” https://www.kaggle.com/datasets/rohanrao/formula-1-world-championship-1950-2020

[3] Tracing Insights “Race Data” https://github.com/TracingInsights/RaceData

[4] Dataset copied to GitHub. Available at: https://github.com/jmr-lab/Formula-1 (Accessed: 2026).

[5] Flags from icons8 : https://icons8.com/icons/set/flags--style-color

[3] Rafael Irizarry. “Introduction to Data Science.” https://rafalab.dfci.harvard.edu/dsbook/

[8] Cover image from SVG SILH https://svgsilh.com/c3c3c3/image/309862.html

[9] Icons from Font Awesome https://fontawesome.com/

[10] The text of this report was reviewed by DuckAI, an AI language model that also assisted in reviewing and correcting some of my code : https://duck.ai/

DRAFT