


Programme loudness compliance

EBU R 128 programme loudness. Rating per EBU R 128 / ITU-R BS.1770-5 (K-weighting, gated).

Client:	Example broadcaster	Programme:	Reference tone sequence (-20.4 / -30.4 dBFS steps)
Manufacturer:	Example post-production	Test room:	Reference monitoring room (example)
Date of test:	2026-07-20		

Compliance summary

Metric	Measured	Target / Limit	Result
Integrated (Programme) Loudness	-23.0 LUFS	-23.0 LUFS ±0.2 LU (Δ +0.0 LU)	PASS
Maximum True Peak	-20.4 dBTP	≤ -1.0 dBTP	PASS
Loudness Range (LRA)	10.0 LU	informational	—
Max Momentary	-20.4 LUFS	informational	—
Max Short-term	-20.4 LUFS	informational	—



I = -23.0 LUFS (LRA = 10.0 LU, max TP = -20.4 dBTP)

Result vs requirement: Compliant when I is within -23.0 LUFS ±0.2 LU (EBU R 128 item i) and true peak ≤ -1.0 dBTP → **PASS**

Loudness tolerance ±0.2 LU for measurement errors in loudness workflows, e.g. Quality Control (EBU R 128 item i).

Gating -70 LUFS absolute / -10 LU relative (ITU-R BS.1770); 1 LU = 1 dB; true peak per EBU Tech 3341; LRA per EBU Tech 3342 (not recommended for programmes under 60 s).

Laboratory: Phonometry reference example

Report no.: EXAMPLE-R128

Date: 2026-07-20

Operator: phonometry **Signature:** _____

■ The results relate only to the tested specimen.

Generated by phonometry.