

docker-compose.yml services: `stirling-pdf`: image: `stirlingtools/stirling-pdf:latest` container_name: `stirling-pdf` ports: - `'8080:8080'` volumes: - `./stirling-data/tessdata:/usr/share/tessdata` # OCR language files - `./stirling-data/configs:/configs` # Settings & database - `./stirling-data/logs:/logs` # Application logs - `./stirling-data/pipeline:/pipeline` # Automation configs environment: - `SECURITY_ENABLELOGIN=false` # Set true to enable user authentication - `LANGS=pt_BR` # Interface language - `SYSTEM_MAXFILESIZE=2000` # MB - `SPRING_SERVLET_MULTIPART_MAX_FILE_SIZE=2000MB` - `SPRING_SERVLET_MULTIPART_MAX_REQUEST_SIZE=2000MB` - `JAVA_TOOL_OPTIONS="-Xms512m -Xmx4g"` # Min 512MB, Max 4GB RAM

```
restart: unless-stopped
```

baixar pacotes de idiomas para OCR <https://github.com/tesseract-ocr/tessdata>

cat: `/etc/nginx/conf.d/pdf.jmsalles.homelab.br`: No such file or directory server { listen 80; server_name `pdf.jmsalles.homelab.br`;

```
access_log /var/log/nginx/pdf.jmsalles.homelab.access.log;
error_log /var/log/nginx/pdf.jmsalles.homelab.error.log;

location / {
    proxy_pass http://127.0.0.1:8080;

    proxy_http_version 1.1;

    proxy_set_header Host $host;
    proxy_set_header X-Real-IP $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    proxy_set_header X-Forwarded-Proto $scheme;

    proxy_connect_timeout 60s;
    proxy_send_timeout 60s;
    proxy_read_timeout 60s;
}
```

```
}
```