Everything but the Software:

Feature-Driven Decay in an Agentic Coding Loop. An Exploratory Case Study and an Experiment Protocol

Juan Manuel Servera Bondroit*

Senior Partner Solution Architect, Microsoft Schweiz, Zurich

Draft of 25 October 2026

Abstract

When does apparent agentic delivery progress cease to represent software progress? I examine a traceable exploratory case in which artefact-level completion diverged from usable behaviour, then present a prospective consolidation experiment. Over six weeks I used agents, centred on Microsoft's HyperVelocity Engineering (HVE Core) framework, to research a fictional housing retrofit programme, write requirements and deploy an MVP. A coordinator then ran parallel research–plan–implement–review loops over a backlog that grew to 192 issues. In ten days it merged 183 pull requests and the log grew by about 37,000 words, yet I could not sign in to the replacement system; an automated rubric rated implementation completeness five out of five. Five candidate mechanisms organise the evidence: specification inflation, proxy capture, learning evaporation, process-gate inflation and feedback starvation. The confounded participant-observer case establishes neither accelerated code decay nor the effectiveness of a remedy. It motivates a test of scheduled, behaviour-preserving consolidation after each feature. The unregistered, exploratory first-pass protocol compares feature-only, consolidation and review-only arms on retained behaviour, an unforeseen change request, internal quality, intervention demand and cost. Its contrasts estimate a consolidation package, including extra resources and different notes, not refactoring alone. No study results are reported. The contribution is the chain from observed divergence, through candidate explanations, to a falsifiable test of retained behaviour and future changeability, not evidence that more agents restore either.

Keywords: agentic software engineering; coding agents; spec-driven development; software evolution; technical debt; refactoring; feedback loops; human–AI interaction; exploratory case study; experiment protocol.

1 Introduction

On 15 October 2026 I started an agent coordinator against a backlog of more than 180 GitHub issues and let it run. Each issue went into its own git worktree, where an agent session ran a full research, plan, implement and review loop, passed a local validation gate and published a pull request. The coordinator assessed each candidate, merged it when every gate was green, rebased the remaining branches and started the next wave of work. Ten days later, 183 pull requests had been merged. I could not sign in to a running version of the system I was building.

That gap, between an extraordinary volume of activity and the absence of anything I could touch, try and learn from, is the subject of this report. It is the wall that several of the most experienced practitioners in our field have been describing. Kent Beck compares coding agents to

*The views expressed are the author's own and do not necessarily reflect those of Microsoft. The case organisation, Zava North Homes, is fictional.

genies that grant wishes literally, warns that plausible code is not working code, and has written about the existential crisis that follows when the visible part of a craft can be produced by a machine [11, 15, 16, 79]. Robert C. Martin argues that agents will out-code us, so our discipline must move into constraints that machines enforce [69, 70]. Andrew Murphy reminds engineering leaders that the speed of writing code was never the bottleneck [74]. I knew these warnings and followed many of them. I hit the wall anyway, and the way I hit it is instructive.

The hypothesis did not originate with this repository alone. In an earlier attempt, Aithena, I used Squad and found the resulting system too complex to maintain comfortably; that is my retrospective judgement, not a measured complexity result. I expected HVE Core's research, plan critique and post-implementation review to improve on less structured agent workflows. That expectation was not a controlled framework comparison. AMA is the focal, traceable case; selected public repository observations, especially PhotoCraft's attempt at Photoshop parity, provide additional motivation (Section 2.8).

The central question is how feature-centric agentic delivery can produce strong completion signals while failing to preserve a usable and adaptable system. The argument follows one chain: observed divergence, candidate mechanisms, a consolidation hypothesis and a prospective controlled test. The case documents loss of access to a usable replacement; it does not measure a rate of structural code decay or identify an agent-caused acceleration.

My working theory draws on software evolution: feature accumulation can increase complexity and the cost of later changes unless counter-work is done [27, 34, 62, 83]. Two possible amplifiers are compounding errors and output exceeding review capacity. Earlier misreadings can become the context for later steps, as in Beck's literal-minded genie [79]; high volume can obscure the gap between recorded completion and observed behaviour. These are propositions, not effects estimated by this case. Scheduled review and consolidation are a plausible intervention [12, 14, 16], not an established remedy.

The prospective question is whether an additional agent can preserve working behaviour and options for later change through that bounded intervention. I use reflection to mean checking assumptions and a working model against observed behaviour, not generating another approval record. The experiment tests a scheduled consolidation package, not autonomous product steering or the replacement of human judgement.

The case is unusually well documented. The repository is public, every change went through a pull request, an append-only log recorded what the agents did and why, and the coordinator's own instructions are versioned with the code [92]. I approach the central question through three more specific questions:

- **RQ1.** What did a long-running, autonomous, spec-driven delivery loop produce, and what did it fail to produce?
- **RQ2.** Which candidate mechanisms are consistent with the gap, and what counter-evidence and rival explanations limit each interpretation?
- **RQ3.** Can an additional agent preserve correctness and future changeability through a consolidation step after every feature, and at what cost? The experiment tests this bounded form of correction, not general autonomous steering.

The report makes three linked contributions:

1. A documented case of one architect working with agents for six weeks, from desk research to a deployed MVP and then a ten-day autonomous delivery loop, with descriptive measures, bounded within-case contrasts and an observation–interpretation–proposition audit trail (Sections 3 and 4).
2. An integrated model of five candidate mechanisms, with operational boundaries, case indicators, counter-evidence and rival explanations. The individual phenomena are not claimed as new (Section 5).

3. A consolidation harness and a prospective controlled protocol to test an intervention whose effect between feature steps is not isolated in the related work reviewed here [3, 77, 84]. The protocol follows the registered-report example of Lulla et al. [66] and HVE Core's Minimum Viable Experiment method. It retains the tagged design and makes its identification and precision limits explicit; prospective documentation and fresh exploratory runs remain pending (Sections 7 and 8).

Practice implications are proposals, not a separately validated operating model (Section 6). The broader question of reflective delegation and human accountability is discussed, not answered, in Section 9.

This is not an evaluation of the tools I used. The framework at the centre of the case keeps a human between its phases by default; the failures described here occurred in a configuration I designed that delegated delivery and merge decisions (Section 2.7). I still handled approvals and technical blockers, but no longer learned from using the replacement product. I cannot isolate that change from the others.

2 Background

2.1 Software that only grows

That software decays when it only accumulates features is one of the oldest observations in our field. Lehman's laws of software evolution hold that a program in real-world use must keep changing, and that its complexity grows as it evolves unless work is done to maintain or reduce it [62]; a later formulation adds that its quality will appear to decline unless it is rigorously maintained and adapted [63]. Parnas called the result software aging, and blamed in part the changes made by people who do not understand the original design [83]. Eick and colleagues found mixed but, on the whole, persuasive evidence of code decay in fifteen years of change data from a large telephone-switching system [34]. Cunningham's technical-debt metaphor framed the cost of not consolidating as interest paid on every later change [27], and Fowler's design stamina hypothesis holds that without attention to design, adding features eventually becomes slower than it would have been with it [36]. Studies have since put numbers on the interest: across 39 proprietary code bases, low-quality code had fifteen times more defects and took 124% longer to develop than high-quality code [100], and developers in a longitudinal study lost about 23% of their working time to technical debt [18].

The evidence has limits. Lehman's laws are conditional: they predict decay only when no counter-work is done. Increasing complexity and declining quality are among the least empirically supported of the laws, and some open-source systems, Linux among them, have grown without the predicted decay [47]. Several of the studies above are correlational. The common lesson is narrower and sturdier: quality is not preserved by default. It is the product of work that feature delivery tends to crowd out.

2.2 Why agents might accelerate the decay

Two properties of current agents could speed that decay up. The first is compounding error. When language models execute long tasks they condition on their own earlier mistakes, so errors become more likely as tasks lengthen [95]; in multi-turn, underspecified conversations their performance drops by 39% on average, largely because they commit to early, wrong assumptions and then build on them [57]. Coding benchmarks show the same pattern at the scale of a code base. In SlopCodeBench, where agents repeatedly extend their own solutions, structural erosion rises in 77% of trajectories, agent code is 2.3 times more verbose and twice as eroded as comparable open-source code, and explicit quality instructions improve the starting point without changing the rate of degradation [78]. In SWE-CI, which replays months of real repository

history, regressions increased with iterations for most of the models tested [24]. All 20 models scored below human oracle code on the Maintainability Index, although 15 of 20 scored better on Pylint; most had a zero-regression rate below 0.25. Code could look clean on the surface while scoring worse on structure. Heander et al. found a related caution in agentic review: better CodeHealth was associated with lower token cost, but batch fixing left median CodeHealth unchanged [46]. Given only a requirements document and an empty repository, agents lose global coherence [30], and some "pass" tests by modifying them [107]. Field data point the same way. Open-source projects that adopted an AI coding tool saw a short-lived jump in velocity but persistent increases of about 30% in static-analysis warnings and 41% in code complexity, which in turn slowed later development [45]; repository-scale analyses report copy-pasted code rising and moved, that is refactored, code falling as AI assistance spread [41]; and DORA associated a 25% increase in AI adoption with better documentation and code quality but lower delivery stability (-7.2%) in 2024, with stability still lower in its 2025 report, which describes AI as an amplifier of existing strengths and dysfunctions and recommends working in small batches and a user-centric focus [31–33, 44].

The evidence is not one-sided. A preregistered randomised trial found no significant difference in how easily developers evolved code that others had written with or without AI assistance [21]. A study of chained maintenance tasks found that the downstream cost of agent edits comes mainly from inherited test failures and disappears when the earlier tests pass, which points to regressions rather than complexity as the channel of compounding [82]. And the best-known controlled productivity result, experienced developers 19% slower with early-2025 tools while believing they had been 20% faster [17], has since been qualified by its authors, who think developers are probably faster now [71]. Its durable lesson is the gap between perceived and measured progress.

The second property is volume. Human review works best on small changes in short sessions: industrial guidance is to review no more than a few hundred lines at a time [26], the median change at Google is about two dozen lines [89], and understanding the change, more than finding defects, is the main challenge of modern code review [4]. Agents break those conditions. Among repeat reviewers of agent-authored pull requests, approval rates rose while inline comments fell, a pattern its authors call habituation [106]. Multi-agent systems add failure modes of their own, in system design, inter-agent misalignment and verification [23]; agent builders advise sharing full context rather than splitting it across agents that each see a fragment [104]; and models use long contexts unevenly and less reliably as they grow [48, 65]. By contrast, tests that clarify intent help both the model and the person judging its output [35].

2.3 Refactoring, review and evaluation boundaries

Agentic refactoring, review and human correction are already studied. RefactorBench evaluates 100 handcrafted multi-file refactoring tasks across nine Python repositories, not scheduled consolidation between feature additions [40]. Kumar et al.'s ASE 2025 study observed developers collaborating with agents on existing issues: incremental, active collaboration was associated with greater success, not randomly assigned to establish an optimal intervention rate [56]. SWE-Sharp-Bench supplies a reproducible C# issue-resolution benchmark and curation pipeline [72]; reproducible repository-scale evaluation itself is not a contribution claimed here.

Two recent preprints sharpen the evaluation problem. CRBugBench evaluates review agents on 1,000 open-source and 800 proprietary tasks from one company, reporting weaker detection on complex, non-local and proprietary-context changes [105]. It is a 9 October 2026 preprint, not an independently replicated result establishing that review cannot work. *Building to the Test* reports near-perfect behavioural scores for demos while the requested reusable library was unused or absent. Its unchanged, source-hidden oracle did not check that delivery contract [67]. This is distinct from altering tests, as examined in ImpossibleBench [107]: test integrity and adequate outcome coverage are separate safeguards.

These studies narrow the proposed novelty to the case trace and the specific prospective package comparison, including an unforeseen change request. They also caution against assuming that another reviewer, a stricter check or a high hidden-test score necessarily certifies the intended deliverable. The literature discussion is focused, not systematic. Preprints, observational studies, practitioner accounts and first-party industrial reports have different evidential roles; none substitutes for the planned controlled comparison.

2.4 Optimisation with behavioural feedback

Pavlenko et al.'s *Towards an AI Software Factory for Data Systems* offers a complementary case [84]. They describe an Amdahl's-law limit: faster coding alone yields limited improvement across the development lifecycle. Their response deliberately narrows the problem to *Evolutionary Coding Tasks*: existing, human-architected systems with stable semantics and automatically measurable objectives, such as latency. Hotspan uses telemetry, code analysis and past reviews to select optimisation targets and package evaluations. Darwin combines local code–test–debug–reflect cycles with agents that generate, refine and select hypotheses across candidate solutions. This is agent-led steering within an explicit objective, not merely faster execution of a fixed backlog.

The authors report improvements across 45 open-source systems, with a mean performance gain of 13.8% for the best-performing twenty, not the full set. For a Microsoft performance team, they report 0.35 pull requests per engineer-hour of application work, estimated at three times the rate with agentic coding tools. That calculation excludes the 57% of team time spent building infrastructure and onboarding repositories; the output enters engineering review queues. These are reported optimisation results and an application-work productivity estimate, not a controlled estimate of end-to-end delivery, maintainability or future changeability. General semantic equivalence, automated reviewing and privacy-preserving shadow execution remain open challenges in their account [84].

The contrast matters for this paper. It is evidence against treating high agent throughput as inherently unproductive: an explicit objective and behavioural feedback can support useful improvement. It does not isolate the effect of consolidation between feature additions or establish that autonomous optimisation can choose the right product. The proposed experiment addresses that narrower consolidation question, not the invention of agent-led reflection or continuous optimisation.

2.5 The practitioner conversation

The closest practitioner argument is Waseem et al.'s account of internally developed MVPs and industry reports [101]. They describe the same trade-off: rapid generation can accumulate debt through architectural inconsistency, security vulnerabilities and maintenance overhead. Their account includes descriptive security-scan counts but does not estimate a controlled effect of consolidation. I do not claim that argument as new. I add a public case trace, candidate mechanisms and a prospective test.

Practitioner accounts motivate, rather than establish, the intervention. For Kent Beck, augmented coding differs from accepting generated output because the programmer still cares about the code, its complexity, tests and coverage; his B+ tree experiment uses strict test-driven development [13]. In his Prodacity talk, he argues for maximising learning, with software as a side effect, and for alternating features with consolidation to restore the future options that feature additions consume [14, 16]. This supplies a conceptual bridge from the case to the experiment. The concern is not only blocked sign-in, but delivery continuing without product-use feedback that could challenge assumptions and deepen understanding; the narrower hypothesis is that scheduled consolidation can preserve working behaviour and later changeability. His distinction between visible output and the less visible work of understanding, simplifying and

building abstractions also grounds the question of which reflective responsibilities an agent might perform [15]. These arguments motivate the test; they establish neither the harness's effectiveness nor a permanent boundary between human and agent capabilities.

Robert C. Martin stresses executable engineering constraints [69]; Andrew Murphy stresses bottlenecks other than coding [74]. Lanzetta's sprint retrospectives and Lamanna's emphasis on quality rather than additional features are reported practices, not controlled estimates of this harness [58, 60]. Appendix A retains the extended accounts and their source boundaries.

Spec-driven development (SDD) is the most direct attempt to tame agents with structure. GitHub's Spec Kit proposes a specify, plan, tasks and implement flow in which the developer's role is to verify, not merely to steer [28]. Birgitta Böckeler's review of SDD tools distinguishes spec-first, spec-anchored and spec-as-source approaches, reports one tool turning a small bug into four user stories with sixteen acceptance criteria, observes that agents both ignored and over-followed instructions, and concludes: "I'd rather review code than all these markdown files" [20]. A study of SDD in practice reports more reliable agent behaviour but higher planning and review costs, and specifications that decay [1]. Other voices frame the same tension: *vibe coding* for throwaway projects [52]; *vibe engineering*, in which experienced engineers stay accountable [102]; the observation that AI gets a project most of the way while the rest needs engineering judgement [80]; software engineering joining the non-deterministic engineering disciplines [37]; and the advice to hold back on complacency with AI-generated code [99].

2.6 Older theory

None of this is new in kind. Peter Naur argued that programming is primarily the building of a theory, held by the programmers, of how the program solves its problem, and that documentation cannot fully carry that theory. In his example, a second team equipped with full documentation still made changes that destroyed the power and simplicity of the original design [76]. Brooks located the essential difficulty of software in specifying, designing and testing the conceptual construct rather than in representing it [22]. Royce, often cited as the origin of the waterfall model, called the purely sequential approach risky because testing at the end is the first time behaviour is experienced rather than analysed [87]. Gall observed that complex systems that work evolve from simple systems that worked [38]. Extreme Programming built its practices around short feedback loops and small releases [8, 9]; Cockburn's walking skeleton and Hunt and Thomas's tracer bullets both start with a thin end-to-end implementation [25, 50]; and the Agile Manifesto values "working software over comprehensive documentation" [2]. Beck's *Tidy First?* treats design as small, reversible structural changes made before behaviour changes [12].

From human factors, Bainbridge's ironies of automation explain why automating the routine parts of a task leaves operators with the hardest parts, monitoring and intervention, while eroding the skills those parts need [5]. Recent work applies this to generative AI: users shift from producing to evaluating, workflows are restructured unhelpfully, and automation makes easy tasks easier and hard tasks harder [94]. Working with generative AI makes metacognitive demands similar to delegating to a team [98]; higher confidence in AI is associated with less critical thinking [61]; and AI that challenges rather than obeys has been proposed as a counterweight [90]. Finally, Goodhart's law, in Strathern's formulation, warns that a measure used as a target "ceases to be a good measure" [43, 97].

2.7 HyperVelocity Engineering (HVE Core)

HVE Core is an open-source framework from Microsoft that describes itself as an opinionated agentic software development lifecycle built on GitHub Copilot, guided by the principle "AI carries the rules, humans keep the judgment" [51]. Its central workflow is Research, Plan, Implement and Review (RPI): research when evidence is missing, a plan with a default critique, implementation, review and follow-up. Each phase writes dated artefacts under a `.copilot-tracking` folder,

so that context travels through files rather than chat history, and the framework treats these artefacts as git-ignored working memory by default. Its RPI agent runs in a manual mode by default; a fully automatic mode must be confirmed explicitly and still stops for blockers, required human review, and destructive or externally visible actions. The framework describes itself as a lifecycle wrapper rather than a dispatcher of autonomous worker agents. Around RPI it offers product-side agents: a Design Thinking coach, builders for business and product requirements documents (BRD and PRD), a Socratic assistant for architecture decision records (ADRs) and a backlog manager for GitHub, Azure DevOps and Jira. The project warns that it evolves quickly and is best treated as a source of patterns [51]. Its experimental collection includes an Experiment Designer agent that coaches a team through a Minimum Viable Experiment: falsifiable hypotheses with success thresholds set before any run, vetting against red flags, a minimal design, and an evaluation of the outcome against the precommitted criteria [51]. Section 8 uses it. I used the HVE Core plugin snapshot `plugins-v3.3.106` throughout the case. Its snapshot commit is `2df5013e29ebfd2ce61bcd0cf021d8c8186482eb`, generated from source commit `e9af018fe5ffbfbc72321a8bca21fb987359af08`. Historical use is my account; the snapshot identifiers do not establish an installation date.

2.8 Motivating experience and external repository observations

Aithena and Squad. Aithena is my book-search project, with PDF ingestion, full-text and embedding-based search, and a browser interface. At the inspected `dev` revision `f27aa2e`, its Squad records describe specialist agents, shared decisions, a work monitor, pre-task design review and post-failure retrospectives [91]. Squad's current documentation describes persistent learning through repository files, but explicitly calls the framework human-led and retains human accountability for priorities, review and decisions [96]. These are designed feedback mechanisms, not evidence that every session used them effectively or that self-improvement was demonstrated.

There are concrete reasons to inspect the integration boundary rather than rely on my complexity judgement. Aithena issue #1828 reports misleading end-to-end coverage from skipped Phase 3 scenarios. The pinned test file contains active preflight assertions as well as unconditional `pytest.skip` calls in fixture-dependent scenarios: neither "all tests are skipped" nor "all intended behaviour is tested" follows. Issue #1804 reports ingestion acknowledgement after processing failures; the pinned callback places `basic_ack` in its `finally` block. This static observation supports examining the failure contract, not a claim that a particular document was lost in a reproduced run. The repository also records quality gates, releases and substantive search functionality. Of its 35 open PRs at retrieval, 34 carried a dependency label; that queue cannot reasonably be treated as 35 unfinished product features or a measure of architectural decay [91].

PhotoCraft: a known target is not a complete oracle. PhotoCraft describes itself as an early-alpha, clean-room Rust reimplementation of Adobe Photoshop, not the whole Adobe suite [86]. Its controls include dependency-layer checks, regression tests, real-file corpora, visual inspection instructions and a common command interface for the UI, CLI and MCP. Its committed scorecard reports 631 of 631 menu items live. The inspected `parity.rs` counts catalogue entries for which `is_live` recognises a command, tool or UI handler; it does not execute each Photoshop workflow or compare its result. The project's README explicitly warns that menu wiring is not behaviour.

The distinction is visible in the project's own records. Its dated 10 October parity assessment estimated about 76% feature breadth but about 45% readiness for real work; these are project-defined, partly subjective estimates, not independently validated measurements or a fresh assessment of the inspected revision. Its gap register separately records PSD exchange and interactive-performance limitations. It states that its exports are not opened in a third-party editor by an automated test. This is narrower and more informative than treating a large implementation surface as established Photoshop equivalence [86].

At the 25 October 2026, 22:52 UTC tracker snapshot, PhotoCraft had 2,060 open issues, including 212 carrying the `bug` label, and 1,091 open PRs; the paginated PR list contained 49

drafts. It also had 2,604 closed issues and 3,189 merged PRs. Those counts describe tracker state, not unique confirmed defects, failed implementations or a defect rate. Selected open reports describe Windows printing attempting to call CUPS (#5328), repeated save/conflict prompts on a network share despite the file being saved (#9440), and a crash opening a large PSD (#9448). These reports were not reproduced here. The sample also contains duplicate labels, while PR #9552 proposes sharing duplicated helpers across crates: evidence of reported problems and corrective work, not an absence of consolidation. An open queue can reflect active contribution, review capacity, overlapping proposals or ordinary alpha-stage development [86].

Knowing Photoshop's visible features makes reference-based testing conceivable, not automatic. File interchange, platform behaviour, large documents, responsiveness and interacting tools need explicit inputs, oracles and acceptance tolerances. Computer use could help exercise those comparisons; access to the original application alone does not establish that they occurred. These selected examples motivate a candidate distinction between *issue-level correction* and *cumulative system steering*. They do not establish that HVE Core or Squad is inferior to simpler agents, that every large agent-built project deteriorates, or that steering must permanently remain human.

3 Case and method

3.1 Setting

The case is my capstone for Microsoft's *Azure Master Architect* (AMA) programme. Its name is public in the Microsoft Employee Learning badge listing.[1] That public listing does not authorise publication of internal assessment material or this paper. The brief, Case Study 48, describes Zava North Homes, a fictional not-for-profit housing association that manages about 60,000 homes in the North of England. It must improve the energy efficiency of its stock while meeting statutory response times for hazards such as damp and mould, and it coordinates retrofit assessment, grants, procurement, resident consent and quality assurance in spreadsheets. The brief asks for a research-backed proposal, business requirements, an agent architecture, a delivery plan, a working demonstrator and an executive presentation. The programme's rubric has twenty criteria; the top descriptor for implementation completeness is "all required capabilities working end to end".

I worked alone, as architect and product owner, from 11 September to 24 October 2026. Agents did almost all of the research synthesis, writing and coding. The repository also contains an automated scorer: a GitHub agentic workflow that asks a language model to score each pull request against the rubric and records the result [92].

3.2 Workflow and tools

For interactive development I used GitHub Copilot in VS Code, mainly Opus 5.5 during the first two weeks and then GPT-6.1 Sol through the case cut-off. These are the model labels I recall using, not verified provider build identifiers or an exact switch date.

- **Research.** Sixteen official legislation, regulator, policy, standards and funding documents were downloaded, converted to Markdown and organised, with agent-written sector and company research, into a knowledge base: an index, immutable sources, maintained syntheses, an owner-curated memory file and an append-only log of every change.
- **Challenge.** Eight agents role-playing the case organisation's stakeholders (asset management, programme delivery, finance, procurement, data, building safety, neighbourhood housing and resident engagement) and HVE Core's Design Thinking coach challenged each idea. Their first verdict was that none of the five end-to-end agents requested in the brief should be built as such.

[1] https://www.credly.com/org/microsoft-employee-learning/badge/azure-master-architect

- **Requirements and decisions.** HVE Core's BRD and PRD builders, a BRD quality reviewer and the ADR assistant produced and revised the requirements and six architecture decision records.
- **Prototypes and MVP.** Several prototypes were built, reviewed by the role agents and kept as evidence. An MVP followed and was deployed to Azure.
- **Backlog.** HVE Core's backlog manager turned the requirements and decisions into GitHub issues with epics, features, acceptance criteria and dependencies, labelled by how much of each item already existed in the MVP.
- **Coordinator.** On 15 October I added a coordinator agent of my own design to deliver the backlog (Section 3.3).

3.3 The coordinator

The coordinator ran through Copilot CLI on a VM. It selected waves of issues whose dependencies were merged and launched parallel worker CLI sessions through `tmux`, each in an isolated git worktree with HVE Core's RPI agent and one issue as its brief. I used Sonnet 5.5 for the workers, including before the explicit pin. At the pinned repository commit the worker selector is `claude-sonnet-5.5`; PR #420 introduced that requirement on 21 October. The earlier use is my recollection; the committed selector independently records the later configuration. The coordinator used Auto selection with the Intelligence setting. I observed it tending to select GPT-6.1 Sol, but this was not a guaranteed model pin or proof of every session's actual model or provider build. Within its first day I added four rules, each in response to an observed problem. First, it could merge its own pull requests through a gate it verified itself, because repository auto-merge was unavailable. Second, the full research, plan, implement and review loop became mandatory for every issue, and the presence of the loop's `.copilot-tracking` artefacts in the pull request became a merge condition, because the first waves of sessions had implemented directly without them. Third, it updated the project board and ticked only the acceptance criteria that reviewed evidence proved. Fourth, it monitored sessions on a schedule instead of blocking. Later rules required a complete local validation gate before every push, including documentation-only changes, covering five source projects, infrastructure templates, a disposable SQL Server, browser accessibility checks, migrations, four container images, vulnerability scans and a software bill of materials, to be rerun after every correction or rebase. An issue stopped only on a *human blocker*: an owner decision, a named approval, a missing credential, or a review finding still open after two correction cycles. On the same day an accepted ADR made migrating the working MVP into a new source layout the first priority and barred new feature code from the MVP.

3.4 Data and analysis

I use an exploratory single-case design, with myself as participant-observer. The case is the delivery of this repository from 11 September to 24 October 2026. The unit of analysis is the autonomous loop of 15–24 October. The MVP period of 8–14 October, when I used the system intermittently to refine ideas and the user experience, provides a within-case contrast, not a control group. I chose the case because it is revelatory: a public, contemporaneous trace of an autonomous agent loop.

I analysed the public repository at commit `29c6b51` (24 October 2026, 16:19 UTC) [92] with issue and pull-request metadata retrieved from the GitHub API on the same day. The main sources are the append-only knowledge-base log (368 dated entries and about 57,000 words from 11 September to 22 October; entries before 25 September were reconstructed from history), the knowledge-base index, the BRD (version 0.19), the PRD (version 0.18), the coordinator's definition, issue bodies and the rubric scorer's latest result. I used descriptive counts; a hedging

lexicon applied to each log entry (Appendix D); reference tracing, in which I followed the identifiers of recorded learnings through the log by date; and AI-assisted interpretation of my observations. I described the candidate mechanisms, possible amplifiers and consolidation hypothesis. GitHub Copilot in VS Code organised those explanations, named the five patterns and drafted the account, using Opus 5.5 and then GPT Sol 6 and 6.1 as reported interface labels. Microsoft 365 Copilot helped summarise material and find relevant reference documents; it did not perform the log analysis or develop the mechanisms. This was not a systematic entry-by-entry qualitative coding study. I reviewed important specification sections selectively, especially the addendum, rather than auditing the full BRD and PRD. Their identifiers and cross-references made the overall design difficult to follow. I have checked the repository figures and Azure expenditure reported here. Independent author checks of numerical findings from cited studies and of the log-growth figure remain pending. The central discrepancy needs a compact, release-linked evidence package: the dated score and its assessed capability scope, the deployment revision and configuration, and dated evidence of the failed sign-in journey. The retained account does not yet establish that the scorer assessed the same release and capability claim as the usability observation. Until those links are checked, I report their coexistence in the case chronology, not a verified same-release contradiction. The report is informed by established guidance for case study research in software engineering [88] and the ACM SIGSOFT Empirical Standards [93]. As the sole developer and author I am a participant-observer; Section 10 discusses what that implies.

The contextual observations in Section 2.8 were added on 25 October after the case analysis. They use purposively selected public repositories, pinned source files, GitHub tracker counts, and ten newest plus five oldest open `bug`-labelled PhotoCraft reports. They are not a systematically sampled multi-case study and are not pooled with AMA's measurements. The ancillary repository-observation record states the retrieval boundary, locators and exclusions. No external application, original Photoshop installation or reference-parity suite was executed.

3.5 Constructs and evidential boundaries

Working behaviour means completing an intended task through the running system, including the identity, data and service dependencies needed for that task. A healthy endpoint or a passing repository test alone does not establish it. *Decay* denotes loss of previously working behaviour or increasing difficulty of understanding and changing a system. The case documents a usability discontinuity during replacement, not a measured decline in intrinsic code quality; deployment drift could produce the same observation. *Adaptability* is operationalised prospectively as success and cost on the fixed-budget, unforeseen change request, not as a universal measure of maintainability. *Consolidation* means scheduled structural work intended to preserve observable behaviour, with tests checking that intention; passing finite tests cannot prove semantic equivalence.

I keep five measurement categories separate. PRs, lines and words describe *production volume*; checks, reviews and receipts describe *validation activity*; observed user tasks describe *system behaviour*; code metrics and the change request probe *internal quality and changeability*; and corrective help requested or supplied describes *intervention*. Only the first three have case observations. The case has no longitudinal complexity measure, controlled changeability task or systematically coded intervention dataset. Neither volume nor validation activity is used as a direct estimate of decay.

3.6 Chain of evidence and reflexivity

Table 1 separates observations, interpretations and propositions. It indexes evidence already described here, not a newly coded dataset. Repository sources refer to the pinned commit unless identified as author reports. Log entries before 25 September are retrospective reconstructions; later dated entries are the project's contemporaneous record, not independent corroboration of every statement they contain. The 22 and 24 October instructions, historical model use and

intermittent product use remain author reports where original records have not been recovered.

Table 1: Observation–interpretation–proposition audit trail. Interpretations are contestable; the proposed tests have not been performed.

ID	Observation and provenance	Interpretation	Proposition or discriminating evidence
O1	Log, 8–14 Oct, plus author report: an MVP with sign-in and realistic synthetic data was used; 16 Oct record: replacement has one case, no staff and no model.	Recorded engineering completion did not preserve the owner's usable workflow.	Independently execute the same journey before and after migration; separate configuration failure from code regression.
O2	GitHub metadata: 183 PRs merged, 15–24 Oct; scorer records 5/5 completeness; author could not sign in. Dated API/scorer captures still need to be retained.	Completion proxies and task-level success diverged.	A behavioural evaluator should expose disagreement with an artefact-based score.
O3	BRD/PRD versions and log: growth before and during the loop; PR #445: two changed lines and a 78-line evidence record.	Requirements and process records may consume attention without delivering equivalent feedback.	Compare review effort and validated behaviour, not word counts alone.
O4	Log reference tracing: last simplicity citation on 13 Oct; missing registration/staff bindings in the replacement.	Some lessons may have fallen off the effective read path. Absence of a citation is not proof of absence of knowledge.	Inspect actual session inputs and test whether the prior lesson was available, understood and executable.
O5	Coordinator definition and ADR 0006: committed RPI records, full gates, delegated merging and migration priority; author still resolved blockers.	Reduced product-use feedback coexisted with substantial oversight.	Distinguish outcome-level feedback from approval activity; test the consolidation package separately from the migration.

I selected the episodes, designed the coordinator and wanted the capstone to succeed. Those roles make a coherent retrospective explanation attractive. Developers' experience-based beliefs need not correspond with project evidence [29]; that methodological caution applies to my own account, not only to agent-generated claims. AI-written project records are data about recorded activity, not independent judges of success; AI-assisted synthesis is analysis assistance, not another observer. No independent second coding or empirical peer-debrief pass has been completed. The supplied editorial critique prompted stronger boundaries and explicit rival explanations, but does not fill that gap. An independent check of O1–O5 against retained source and execution records remains necessary before presenting the interpretations as independently corroborated.

4 What happened

Table 2 summarises the case and Table 3 compares the periods before and during the delivery loop.

Table 2: Timeline of the case (all dates 2026).

Dates	Phase	What happened
11 Sep – 7 Oct	Research and requirements	Sixteen regulatory sources converted; role agents reject five end-to-end agents (26 Sep); BRD and PRD drafted and repeatedly revised; prototypes reviewed; my usability feedback recorded (7 Oct).
8 – 14 Oct	A usable MVP	MVP built and reshaped through several feedback passes in one day (8 Oct); running on Azure with SQL, blob storage and two replicas over 980 synthetic cases (9 Oct); rebuilt with Entra ID sign-in, which I used (12–13 Oct); five assistant paths exercised against a real model (14 Oct).
14 – 15 Oct	Backlog and coordinator	Backlog generated as GitHub issues; coordinator created and hardened within a day; an ADR makes migrating the MVP to a new source layout the first priority.
15 – 22 Oct	The loop at scale	Pull requests merged at about eighteen a day; the log grows by about 37,000 words; the migrated deployment holds one fictional case, no staff and no model deployment (16 Oct); browser sign-in blocked; validation moved off hosted CI to save budget (18 Oct); cloud cost ceiling raised (22 Oct); new cross-cutting requirements appended to open issues (22 Oct).
22 – 24 Oct	Asking for something that runs	Ten issues labelled *feedback-first*; instruction to make employee and resident sites available as soon as possible with at most eight parallel items; checkpoint and refactoring instruction (24 Oct).

Table 3: Before and during the delivery loop. Counts from the repository at commit `29c6b51` and the GitHub API on 24 October 2026; hedging phrases as defined in Appendix D.

Measure	Before the loop	During the loop
Pull requests merged	52 (26 Sep – 14 Oct; 2.7 a day)	183 (15 – 24 Oct; 18.3 a day)
Knowledge-base log entries	126 (to 14 Oct)	242 (15 – 22 Oct)
Words appended to the log	19,967 to 14 Oct (about 1,000 a day from 25 Sep)	36,755 (15 – 22 Oct; about 4,600 a day)
Hedging phrases per 1,000 log words	1.2	3.8
Log entries citing my simplicity requirements	4 (last on 13 Oct)	0
Deployment I could use	Entra sign-in, 980 synthetic cases, live model calls (12 – 14 Oct)	One fictional case, no staff, no model deployment (16 Oct); sign-in blocked

4.1 Research, requirements and a usable MVP

Table 4 adds code-level activity from the pinned history. The script classifies paths and compares each selected first-parent commit with its first parent, detecting renames. The integration view includes multi-parent merges and PR-numbered squash commits: 31 before the loop and 177 during it. These are not the API pull-request counts in Table 3; the literal-merge subset, seven in each period, is also reported in `anc/repo_history_metrics.out.txt`. Classification rules and commands are printed there. The additions and removals show work volume, not net code size, maintainability or delivered value. No complexity comparison was made because `lizard` was not installed.

Table 4: Text lines added and removed in first-parent integrations, including PR-numbered squash commits, through `29c6b51`. Detected pure renames add no lines; binary deltas are excluded.

Path class	8–14 Oct		15–24 Oct	
	Added	Removed	Added	Removed
Product source	8,136	421	23,408	2,184
Tests	6,871	537	73,478	1,416
Documentation	12,065	1,297	25,210	2,455
Tracking artefacts	238,185	2,642	240,369	1
Infrastructure	2,708	73	6,162	485
CI and workflows	240	64	897	246
Other	25,320	1,099	72,711	1,776

The September work was research and requirements preparation, not application building or a project-free baseline. The agents assembled a regulatory corpus, sector baselines and a modelled customer profile, and the role agents produced a genuinely useful early verdict: each requested *end-to-end* agent bundled deterministic controls, accountable human decisions and a smaller set of tasks suited to bounded AI, so none should be built as such. Requirements were written, reviewed by an automated quality reviewer and revised many times. Application prototypes followed in October.

On 7 October I used the latest prototype myself and recorded what was wrong with it. The next day the agents combined my notes with critiques of three prototypes by the UX, Design Thinking and role agents into ten simplicity requirements (SA-001 to SA-010): a default view listing only my cases, each with one plain status and one next action; a case that opens full screen; blockers explained in plain words with an owner; no role simulator in user views; optional AI that never blocks manual work; and so on. On 8 October they built an MVP that followed those requirements and then reshaped it through several rounds of my feedback the same day: filters, an overview map, visits, handover suggestions and document uploads. On 9 October it ran on Azure with Azure SQL, blob storage and two replicas over 980 synthetic cases. On 12 October the stack was rebuilt from an empty resource group with Entra ID sign-in; I signed in and used it, and the problems I reported, a missing logo and an account switch that only signed me out, were fixed within a day. On 14 October five assistant paths produced cited proposals through a real model deployment, using 6,884 tokens across five calls. I tested the initial proof of concept for a couple of days, discarded it, then used the MVP for a few days to refine ideas and the user experience. This was intermittent use, not daily use throughout the week. I then carried those ideas into requirements, ADRs and the hierarchical backlog.

I treat 8–14 October as a within-case contrast with 15–24 October: intermittent use of a usable MVP versus no realistic end-to-end task completed in the replacement during the autonomous loop. I remained involved, mainly answering approval requests and resolving technical blockers to keep the loop running. The contrast concerns product-use feedback, not the complete removal of human oversight. It is consistent with the importance of feedback, but cannot establish that

removing product-use feedback caused the outcome: the migration, workload, gate rules, models and deployment conditions also changed, and the periods were not assigned at random.

4.2 Bounded within-case contrasts

Table 5 compares episodes and negative cases already in the chronology. It is an analytical contrast, not a new PR-cohort study or an exhaustive search for disconfirming cases. In particular, documentation expansion preceded autonomy and the tracking/source churn ratio fell during the loop. Both limit a story in which autonomous coordination alone created the problem. The successful health and restart checks are also real successes; they did not exercise the same outcome as the blocked sign-in journey.

Table 5: Within-case contrasts and their limits, using the existing chronology and measurements.

Contrast	Recorded difference or negative case	What it can and cannot discriminate
Product use, 8–14 versus 15–24 Oct	Intermittent MVP use and same-day feedback versus no completed realistic replacement journey.	Consistent with feedback starvation; migration, environment, workload and models changed at the same time.
Requirements before versus during the loop	Growth and review overhead already existed before autonomous coordination.	Weakens an autonomy-onset explanation; there is no matched small-specification comparison.
Integration artefacts, 8–14 versus 15–24 Oct	Tracking/product-source additions fell from 29.28 to 10.27 while absolute output remained high.	Volume is not a monotonic decay measure; churn does not assess understanding or usability.
Replacement engineering checks versus user task	Health, restart and unauthenticated-request rejection passed; real-user sign-in remained blocked.	Shows the boundary of those checks, not that passing checks were fabricated or that intrinsic code quality declined.
Domain challenge versus backlog execution	Early role agents rejected the five-agent proposal; later sessions delivered the specified issues.	Negative case against inevitable agent compliance; role, task and human interaction differ, so this is not a treatment comparison.

4.3 The backlog and the coordinator

Late on 14 October the backlog manager generated the backlog from the BRD, PRD and ADRs. Many issues carried a label stating that part of the work already existed in the MVP. On 15 October I created the coordinator and, as Section 3.3 describes, hardened it within the day. The log recorded 91 entries that day, against at most 19 on any earlier day. The accepted source-layout ADR made the migration of the MVP's code the first priority; the MVP itself was to be retired.

4.4 The loop at scale

From 15 to 24 October, 183 pull requests were merged, compared with 52 in the nineteen days before. The knowledge-base log grew by 36,755 words between 15 and 22 October, 31,005 of them in the first three days (Figure 1). The share of hedged statements, such as "remains unmet", "not inferred" or "not accepted", rose from 1.2 to 3.8 per thousand words.

The migration succeeded on its own terms. A private deployment built from the new source layout passed health checks, rejected unauthenticated requests and survived restarts. But it held one fictional case, no staff accounts and no model deployment, against the 980 cases, eleven staff identities and five working assistants of the system it replaced. A public entry point was restored through an additional edge service, yet real-user sign-in stayed blocked because the new deployment had neither an application registration nor staff bindings, the very things set up and verified on 12 October. Recovering them became a chain of issues, each with its own




Figure 1: Words appended to the knowledge-base log per day (top) and hedging phrases per day (bottom). The dashed line marks the start of the coordinator loop on 15 October 2026.

research, plans, reviews and corrections. To preserve the hosted CI budget, validation moved to a local gate on 18 October (issue #413). The demonstrator's cloud resources accrued USD 189.94 between 1 and 20 October, with a forecast above the USD 500 ceiling I had set; on 22 October I raised the ceiling to USD 700, deleted a test edge profile and scaled a demo service to zero. The same day, after a mentor raised the economics of AI consumption, the agents produced new BRD and PRD versions and appended a new set of acceptance criteria to fifteen open issues.

A Copilot usage dashboard captured on 24 October showed USD 1,809 of price-list consumption value, 10,229,625,825 tokens and 100,938 requests in the rolling last 28 days. These were account-wide totals across all work, not AMA-only measurements or an invoice. The token total included 10,081,179,684 cached tokens. Surface and model breakdowns described the same total and must not be added together; the requests were not established as premium requests. The screenshots do not isolate 15–24 October, establish exact window boundaries or support an estimate of the loop's incremental cost.

4.5 Asking for something that runs

On 22 October I asked the loop to prioritise something I could use. A *feedback-first* label, described as prioritising "the bounded usable synthetic demo slice", was applied to the relevant issues, ten of them by 24 October. On 24 October I asked for employee and resident sites to be available as soon as possible, with at most eight items in parallel. These instruction dates and the eight-item cap are my confirmed recollection, not quotations recovered from the pinned log. The agents created the smallest independently runnable resident preview they could design (issue #444): read-only, synthetic and bound to the local machine, with thirteen acceptance criteria. The same day a two-line fix to the rubric scorer arrived with a 78-line evidence record and an explicit, one-time owner exception to interrupt the full local gate (pull request #445). Following Beck's advice to alternate features with consolidation, I also instructed the coordinator to stop at checkpoints, review what had been built, exercise the functionality and refactor. I do not evaluate the outcome of that instruction here.

5 Five candidate mechanisms

I propose five candidate mechanisms consistent with how a loop that merged a pull request every eighty minutes or so left its owner with nothing to use. Table 6 summarises them; Appendix C sets out a definition, indicators, counter-evidence, rivals and testable implication for each. These are an integrated explanatory synthesis, not five newly discovered phenomena or independently established causal mechanisms.

Table 6: Five candidate mechanisms, case indicators, relevant prior work and proposed early-warning signals. Indicators are not causal tests.

Candidate	Case indicators	Related prior work	Early-warning signal
Specification inflation	BRD ≈37,900 and PRD ≈33,900 words; 192 issues; 17 criteria on one issue and 13 on the smallest preview	Royce; Gall; Brooks; Böckeler; Beck	Specification growth versus human-validated behaviour
Proxy capture	Artefacts made a merge gate; 78-line evidence record for a two-line fix; LLM judge scores completeness 5/5 with no usable system; hedge density tripled	Goodhart; Strathern; Beck's genie; ImpossibleBench; METR	Artefacts per behaviour change; scores that disagree with a live demo
Learning evaporation	Simplicity and sign-in lessons absent from briefs; last cited 13 Oct; read path ≈139,000 words	Naur; context studies; multi-agent failure taxonomy	Lessons that exist only as prose; problems solved twice
Process-gate inflation	Full gate on every push; CI minutes rationed; exception for a two-line fix; 18 merges a day delegated	Bainbridge; ironies of generative AI; Murphy; Goldratt	Gate time per change; review minutes per merge
Feedback starvation	Working MVP frozen; replacement unusable after ten days; request for a demo turned into more issues	XP; walking skeleton; tracer bullets; Agile Manifesto; DORA	Time to first human use; age of last usable increment

Read against the working theory of Section 1, they fall into groups (Table 7). The underlying risk is feature accumulation without consolidation: until 24 October the loop had no scheduled cumulative consolidation step, and its one large restructuring, the migration to a new source layout, was planned up front as backlog items rather than done continuously. This does not rule out local refactoring within individual issues. Specification inflation, proxy capture and learning evaporation are forms of the first accelerant, compounding error, in the proposed model: a misreading, or literal reading, of intent can become context or criteria for the next step. Process-gate inflation and feedback starvation may reflect output exceeding review capacity: gates and caveats coexisted with the absence of a person using the replacement. The case does not estimate either amplification effect.

Table 7: A working theory: an underlying risk and two possible amplifiers, with candidate mechanisms consistent with this case. No rate is estimated.

Driver	What it predicts	In this case
Underlying risk: features accumulate without consolidation	Complexity can grow and quality can decline without counter-work [62, 63]	No scheduled cumulative consolidation until 24 Oct; restructuring planned as backlog items
Accelerant 1: compounding error	Each step builds on earlier misreadings and unneeded complexity [57, 78, 95]	Specification inflation; proxy capture; learning evaporation
Accelerant 2: unreviewable volume	Output exceeds what people can review and test, so decay goes unseen [26, 106]	Process-gate inflation; feedback starvation

5.1 Specification inflation

Interpretation: specification growth outpaced the behaviour validated through product use. By 22 October the BRD had reached version 0.19 and about 37,900 words, with requirement identifiers up to FR-052 and AC-103; the PRD had reached version 0.18 and about 33,900 words, with identifiers up to FR-061 and AC-110. The backlog inherited that scale and grew to 192 issues. Cross-cutting concerns were appended to existing issues rather than sequenced as their own work: a responsible-AI section on 15 October and an AI-consumption section on 22 October. Issue #126, on pilot release gates, ended with seventeen acceptance criteria in three sections. Even my request for the smallest runnable preview arrived with thirteen.

This expansion began before the autonomous backlog loop, including after my prototype and MVP feedback. The requirements agents sought fully specified BRDs and PRDs, named approvers and resolved ownership before building. I pushed for explicit demonstrator assumptions and imperfect increments that could produce feedback. Smaller, iterative requirements documents are a plausible alternative, not an intervention tested in this case.

This is Böckeler's small bug that became sixteen acceptance criteria [20], at the scale of a programme. It is also consistent with what Royce and Gall warned about: a large system specified up front and tested at the end [38, 87]. Brooks explains why more text does not help: the essential difficulty lies in the conceptual construct, and writing it down in more places does not reduce it [22]. The benchmark evidence points the same way: agents given only a requirements document lose global coherence [30]. Beck's metaphor fits: every feature, and every acceptance criterion, burns options [14, 16]. The early-warning signal is the ratio of specification growth to behaviour a human has validated in the same period. Here the denominator was close to zero.

5.2 Proxy capture

In this case, artefacts made into gates appeared to displace outcomes. I interpret three patterns this way.

Merged pull requests are a weak proxy for delivered value. Murphy-Hill et al. report roughly 24% more merges among adopters in Microsoft's rollout, while explicitly distinguishing merges from value [75]. Peralta et al. studied 9,799 human-reviewed agent pull requests; in their manually inspected samples, only 35.7% of rejections reflected clear agent failures and 15.4% of merges required explicit reviewer involvement [85]. AIDev shows the scale of this measurement problem: 932,791 agent-authored pull requests from five agents across 116,211 repositories, not a count of delivered outcomes [64].

Process. When the first waves of sessions skipped the research and planning phases, I made the presence of their artefacts a merge condition. From then on every pull request carried research, plan, change and review records; the artefacts were guaranteed, the thinking they were meant to evidence was not. Pull request #445 changed two lines of behaviour and added a 78-line evidence record that reports its own artefact completion as 100%. HVE Core treats these files as git-ignored working memory; my gate turned them into the deliverable.

In the first-parent integration view, tracking-artefact additions were 10.27 times product-source additions during the loop, compared with 29.28 before it (`anc/repo_history_metrics.out.txt`). This supports concern about artefact volume, not a claim that the ratio rose when autonomy began. Churn alone does not establish code decay.

Evaluation. The rubric scorer, a language model reading the repository, rated implementation completeness at five out of five, "all required capabilities working end to end", citing a README and a check script, at a time when I could not sign in to the system. Gamma's remark about tests applies to judges too: put a model in the evaluation and the evaluation becomes stochastic [39], and a judge that reads the repository is scoring the text that agents are best at producing.

Honesty. I had instructed the agents never to fabricate approvals or overstate evidence.

They complied: hedged statements of unmet acceptance more than tripled in density, and the knowledge-base index filled with them. Issue #349 records that a browser redirect "is not successful sign-in". The agents were right, and still nobody could sign in. Honest boundary statements became the output.

Goodhart and Strathern predict the first two levels [43, 97]; Beck observed agents deleting tests to finish [79], and ImpossibleBench measured it [107]. The METR study adds the human side: the feeling of progress is an unreliable instrument [17]. The early-warning signals are the ratio of evidence artefacts to behaviour changes, the share of merged pull requests that change what a user can do, hedge density, and any divergence between automated scores and a live demo.

5.3 Learning evaporation

Some recorded lessons appeared to fall off the loop's read path, while important design decisions survived. Maintaining the structured log and memory became difficult as the record grew. I observed drift, not a complete loss of the project's theory. Before the loop, my use of the MVP produced concrete lessons: the simplicity requirements, a deliberately public development profile for throwaway stacks, and the callback, role and staff-binding steps that made sign-in work. All were recorded, in the PRD, in a simplicity review and in infrastructure runbooks. The coordinator's briefs carried each issue's text, acceptance criteria and the repository conventions, but not those lessons. The log cites the simplicity requirements for the last time on 13 October; the development profile appears only on 8 October. The migrated deployment lacked the registration and staff bindings established on 12 October, and sign-in was blocked.

The read path itself decayed. The knowledge-base index, which every agent is told to read first, accumulated 1,069 words of issue-specific status notes ahead of its first instruction. The index, the log, the BRD and the PRD, the documents that define the project's state and intent, total about 139,000 words, or roughly 180,000 tokens at a typical ratio of 1.3 tokens per word. Long contexts can reduce reliable retrieval even when the material fits in the context window [48, 65]; the case does not measure any session's effective attention capacity.

Naur explains why recording was not enough. A program's theory lives in the people who build it, and a second team with full documentation can still destroy a design's simplicity [76]. In an agent loop, every session is a second team. Advice to share full context between agents [104] and the failure modes catalogued for multi-agent systems [23] describe the same risk. HVE Core's choice to carry context in files on disk is necessary but not sufficient: the files must be on the read path, short enough to read and, ideally, executable. The early-warning signals are lessons that exist only as prose, a read path that grows faster than the code, and problems that have to be solved twice.

Pavlenko et al.'s World Model offers a different design: preserve raw evidence, derive rebuildable views and retrieve compact, task-specific context with provenance and access controls. Updates are reviewed, and measured outcomes feed later decisions [84]. This distinguishes storing lessons from making them usable in the next decision; a small read path need not mean discarding history. It is an architectural alternative to an accumulating log, not a tested remedy for learning evaporation in this case.

5.4 Process-gate inflation

Interpretation: repeated gates appeared disproportionately burdensome; comparative effort was not measured. Each new gate required execution and review. Within ten days the coordinator required, for every issue, the full RPI loop, a complete local gate before every push and after every correction or rebase, independent review, up to two correction cycles, board updates and evidence-based ticking of acceptance criteria. Hosted CI minutes had to be rationed, the full

gate had to be interrupted by explicit exception for a two-line fix, and paid cloud validation stayed blocked even after the cost ceiling was raised.

My attention felt more constrained than compute, but I did not measure their relative scarcity. I could not review eighteen merged pull requests a day in depth, and delegated merging to the coordinator. I still answered approvals and technical blockers, but stopped getting feedback from using a replacement product. RPI critiques and reviews addressed the current issue rather than the cumulative system; there was no regular phase for reflective consolidation or generalisation across completed issues. This is Bainbridge's irony in miniature [5]: the automation took the part of the work I learned most from, using the product, and left me the part people are worst at, monitoring a stream of plausible, well-documented changes. It matches the shift from producing to evaluating reported for generative AI [94], the delegation demands it creates [98]. Higher confidence in AI was associated with reduced self-reported critical scrutiny in the cited study [61], not established as its cause. Murphy's diagnosis is a plausible interpretation: throughput increased while the path to a usable outcome remained blocked [42, 74]. The bottleneck itself was not instrumented. Martin's argument for executable discipline [69] suggests gates that check product behaviour rather than infer it from paperwork. The early-warning signals are gate time per change, human review minutes per merged pull request, work in progress, and cost per merged pull request compared with cost per accepted outcome.

5.5 Feedback starvation

Candidate mechanism: insufficient independent, outcome-level feedback despite abundant artefact-level validation. This differs from merely having few tests, a long feedback delay or missing context: many checks can pass while none disconfirms the claim that the intended user journey works. Independence here means evidence obtained by exercising the outcome rather than rereading its completion record; it need not imply a different model. The loop prioritised completing the specified plan rather than shortening the path to such feedback. This is my proposed central mechanism, not an isolated cause. Nothing in the coordinator kept a usable system alive: no invariant said that after every merge I must still be able to sign in and do my work. Done meant artefacts, criteria and gates. In the MVP week the feedback loop included my intermittent use, with some changes made the same day. From 15 October the first priority was restructuring code, the working MVP was frozen, and its replacement had not become usable by the time of the case cut-off. When I finally asked for something that runs, the request was absorbed by the same machinery: a label, new issues, thirteen acceptance criteria and the full set of gates.

Every older practice I cited in Section 2.6 exists to prevent exactly this: short releases and test-first development [8, 9], the walking skeleton and tracer bullets [25, 50], and working software over comprehensive documentation [2]. Beck's warning that fully agentic work without feedback goes off the rails [16], DORA's emphasis on small batches and user focus [32] and Murphy's list of real bottlenecks, which includes missing feedback [74], describe the same failure. The early-warning signals are the time from the start of a cycle to the first human use of a running increment, and the age of the last increment a human has verified as usable. At the time of writing the latter was at least ten days.

5.6 A proposed reinforcing relationship

I interpret the mechanisms as a possible reinforcing loop (Figure 2). In this case a large specification accompanied a large backlog and parallel sessions. Artefact-based gates generated more documents; some recorded lessons were absent from later briefs; regressions were not exposed through routine product-use feedback. I responded to gaps with more rules, criteria and gates. That sequence is consistent with reinforcement, but does not establish each causal link. I propose a running increment and a human checkpoint as conditions of every cycle, to test




Figure 2: A proposed reinforcing loop consistent with the case, and a possible intervention through a feedback-first invariant.

whether they interrupt it.

6 Implications for practice

Practice implication, not a tested operating model. The case suggests protecting a usable increment, limiting the delivery horizon and keeping lessons on an effective read path. Validation should exercise the intended outcome, not infer it from receipts. These proposals follow from the candidate mechanisms but were not evaluated as a package in the case.

Appendix B gives seven proposed practices, a checklist and framework-design implications. Its numerical limits on parallel work and criteria are starting heuristics, not evidence-derived optima. Proportionality does not authorise bypassing mandatory safety, privacy, approval or repository publication gates. Compact context views must retain the evidence from which they are derived; a smaller read path need not erase history.

The experiment takes one narrower implication forward: schedule behavioural checking and structural consolidation between feature steps. It does not test the whole practice set, a live-user checkpoint cadence or a replacement for human responsibility. This separation keeps a proposed intervention distinct from a prescription presented as an empirical result.

7 Consolidation hypothesis and harness

The observed operational failure and the prospective hypothesis are distinct. Missing deployment identity and staff bindings are concrete obstacles to sign-in; structural code consolidation would not necessarily restore either. Recovery of that journey requires configuration and end-to-end verification. Consolidation is worth testing for a different reason: repeated feature work may make later changes harder, even when deployment dependencies are correct. The experiment probes that possibility through retained tests and CR1; it does not claim that consolidation would have prevented this episode.

The idea is already practised. OpenAI describes replacing weekly manual clean-ups with recurring background agents that open small refactoring pull requests, alongside a documentation-

gardening agent [77]. Anthropic asks each session to leave a clean state and update a progress file [3]. Neither account reports a controlled comparison of feature-only delivery with consolidation between feature steps. Darwin's continuous optimisation is a further precedent for automated improvement, but its performance evaluations do not isolate that intervention or test an unforeseen change request [84] (Section 2.4). RefactorBench already evaluates refactoring agents [40]; the narrower hypothesis concerns retained behaviour and later adaptation during repeated feature additions.

The proposed consolidation harness tests a bounded part of reflective correction. The pause is scheduled by the harness, not chosen by the agent; the agent is not authorised to reject features or redirect the product. After every feature the loop stops, and an agent:

1. runs the tests and a metrics script that lists complexity hotspots, duplicated blocks and lint warnings;
2. reviews the last feature's diff and the hotspots against a short checklist (duplication, long or complex functions, unclear names, dead code, rules from one feature leaking into another, tests that check implementation rather than behaviour);
3. refactors in small, behaviour-preserving steps, each applied through `test && commit || revert` [10], so that every change either keeps all tests green or disappears;
4. may add tests that pin current behaviour, but may not change or delete the example tests that define the features;
5. rewrites a design note of at most 300 words that says where each rule lives and what debt remains, replacing the previous one rather than appending to it;
6. stops when a quality budget is met or its time budget runs out.

Only then may the next feature start. Appendix E gives the prompt. The intervention combines refactoring, additional tests and a design-oriented note; it is not a pure refactoring treatment.

The hypothesis draws on Beck's alternation of features and futures [14, 16] and *Tidy First?* [12]. It is not free, and may not work. Agent refactorings can be incorrect or superficial [40]; even human refactoring benefits can be difficult to attribute [7, 55]. Test-commit-or-revert protects only behaviour represented by its tests, not every intended contract [67]. Section 8 specifies how the package will be evaluated.

8 Testing the harness: an experiment protocol

The proposed contribution is a controlled comparison of scheduled post-feature consolidation, not the invention of agent clean-up or objective-guided optimisation [84]. It tests whether an agent can perform a bounded part of reflective correction, rather than whether another agent can autonomously steer the whole development process. Lulla et al.'s registered-report protocol, which treats agent configurations as experimental arms, provides a model for specifying the comparison before observing results [66]. I designed the experiment with HVE Core's Experiment Designer as a Minimum Viable Experiment [51], following guidance for empirical studies that involve language models [6] and for software engineering experiments in general [103]. The execution choices below incorporate my decisions of 25 October 2026. I stopped execution and tagged the protocol. Registration is pending, and the exact tagged snapshot still needs to be recorded here. Following the developmental review, I now frame the four-runs-per-arm first pass as an exploratory package comparison, not seven confirmatory tests. The arms, budgets, sample size and provisional thresholds below are retained; the private tag has not been amended or verified by this manuscript revision. Earlier smoke, pilot and other pre-registration runs retain their original labels and timestamps and will not be pooled with the fresh first pass. I will

disclose what earlier data I saw and how it informed the design; a later registration does not retrospectively cover those runs.

The experiment kit is in a separate private repository. The ancillary protocol notes packaged with this paper are earlier proposals, not evidence of the executed or registered configuration. I will archive the reconciled protocol, suite, prompts, configuration and analysis snapshot with the registration once external deposit is authorised. The related work reviewed here does not isolate consolidation steps interleaved between successive feature additions. Darwin evaluates optimisation against measurable objectives [84]; SlopCodeBench shows that quality instructions alone shift where agents start but not how fast they degrade [78]. The harness tests a scheduled structural intervention and subsequent changeability instead.

8.1 Protocol at a glance

Table 8 makes the intended comparisons and their limits explicit. This revision preserves the reported tagged design rather than silently replacing it with a repair-matched control, an equal-total-budget study or a different primary endpoint. Exact agreement with the private tag has not yet been verified.

Table 8: Summary of the exploratory, registration-pending first-pass protocol. Planned safeguards are not completed checks.

Item	Design and interpretation boundary
Study unit	One complete S1 repository–feature-sequence trajectory; four independent runs per arm. Feature steps and CR1 within a run are not new independent replicates.
Allocation	Planned randomised interleaving of arm runs on the same machine; one fixed ten-feature suite, not random assignment of repositories or scenarios.
B–A estimand	Effect of adding the complete consolidation package at equal feature-step budgets, with up to 50% extra agent time. Not an equal-total-budget or refactoring-only effect.
B–C estimand	Complete consolidation versus read-only review at equal post-feature time ceilings. Editing permission, added tests and DESIGN versus REVIEW notes also differ.
Retained priority	H1: final cumulative hidden pass rate, 10-point estimated gain with 95% interval above zero for validation. H6 remains the specific changeability hypothesis, not a newly promoted primary outcome.
Changeability	CR1 success and cost under 45 minutes; success also preserves every feature test passing before CR1. H6 requires a 20-point success gain or 25% cost saving at no lower success, under its interval rules.
Budgets	30 minutes per feature; 15 per B/C post-feature step; 45 for CR1. Credits and monetary cost remain distinct; final calibrated caps need checking.
Analysis	Exploratory run-level estimates; only four runs per arm, no completed power simulation or family-wide multiplicity control. Seven provisional rules are retained, not confirmatory verdicts.
Integrity	Fresh sessions, fixed prompts/tests/configuration and checksum checks are planned. Local execution does not guarantee hidden-test or reference inaccessibility; independent suite/access checks remain pending.
Human help	Primary runs unassisted; HIR/IDR descriptive. Corrective help is a retained, labelled deviation, not grounds for a replacement run. Telemetry coverage and annotation reliability remain unverified.
Status	No results; registration, a documented framing amendment and exact tagged provenance pending. Earlier runs remain excluded from the fresh first pass.

8.2 Hypotheses

Table 9 lists provisional hypotheses in priority order. Each follows the Experiment Designer's form: what we believe, how we will test it, and the measurable outcome that would show it right or wrong. The primary consumption measure stated here is AI credits; H5/H6 cost comparisons must be reconciled to that measure in the tagged analysis before registration. The percentage thresholds are unchanged. "Pays for itself" does not establish monetary payback: tokens, elapsed time, credits and currency are reported separately, and no verified billing conversion is assumed.

Table 9: Hypotheses, compared after the final feature unless stated. A is feature-only delivery, B adds the consolidation harness, C adds a read-only review of equal budget. These provisional rules require prospective reconciliation; they are not confirmatory verdicts. Wrong means interval evidence rules out the minimum useful effect, not no significance; other evaluable outcomes are inconclusive.

ID	I propose	Right when	Wrong when
H1	The harness preserves working software	B's cumulative hidden pass rate is at least 10 points higher, 95% interval lower bound above zero	whole interval below 5 points
H6	Consolidated code absorbs an unplanned change better	Change-request success at least 20 points higher, or cost at least 25% lower at no lower success	Whole intervals rule out both 20-point gain and 25% saving
H2	Errors compound without consolidation	Open regressions trend upward in A; B has at least 50% fewer	Whole intervals rule out A's upward trend or 50% reduction
H3	Internal quality decays without consolidation	Positive slopes in A on three of four metrics; B's slope at most half of A's	Intervals rule out the required slope pattern
H5	The harness pays for itself	B's total cost at most 125% of A's and B cheaper per feature in the last third	Whole cost interval above 150%; late-saving interval at or below zero
H4	The harness leaves less to review	B has at least 20% fewer non-test lines; reviewers as accurate in 20% less time	Whole reduction intervals below 10% for size and time
H7	The consolidation package beats review-only	B beats C by at least half of the B–A gap	Intervals rule out the half-gap benefit

Unresolved H4 and H7 definitions. H4 needs a fixed accuracy scoring rule and a justified non-inferiority margin, together with an interval-based criterion for excluding accuracy losses beyond that margin. A nonsignificant accuracy difference does not establish "as accurate". H7 needs a named endpoint, beneficial direction, analysis scale and interval method for the dependent B–C and B–A contrasts. Its half-gap rule also needs a prospective policy for zero or negative B–A gaps: a zero or negative threshold cannot by itself establish benefit over review-only. Until those choices are documented, H4's joint claim and H7's half-gap claim are not evaluable under their stated rules; component estimates can still be reported exploratorily. This revision does not invent margins, endpoints or replacement thresholds.

8.3 Design

Arms. Arm A delivers features one after another. Arm B runs the consolidation harness after every feature, with half the time budget of a feature step. B therefore has up to 50% more agent time per feature than A; the comparison is not time-matched. H5 compares their costs directly. I include arm C, which holds that extra time constant without refactoring and replaces consolidation with a read-only review of equal budget, to compare the complete consolidation package with review-only. B may add behaviour-pinning tests and writes an architectural `DESIGN.md`; C cannot change tests and writes issue-oriented `REVIEW.md`. Subsequent sessions

read those different notes, so this comparison cannot isolate refactoring. Everything outside the post-feature intervention is identical: model and version, agent runtime, feature prompts, starting skeleton, tools and per-feature budgets.

Estimands and control limits. B–A estimates the incremental consolidation package at a fixed feature budget, including extra time and compute. B–C compares packages at equal post-feature time ceilings, not necessarily equal realised tokens, credits or elapsed time. C cannot repair detected defects, add tests or write B's design note. Any difference can therefore reflect permission to act, test additions, note content or their interactions, not structural consolidation alone. Review-only is not an active repair control. There is no equal-total-budget comparison, and this study cannot say what consolidation would displace under a fixed total budget. Those limitations constrain the causal interpretation even if allocation and the planned checks are implemented correctly.

The additional agent is a distinct session with a different responsibility, not a different pinned model or an independent source of truth. Its value must be demonstrated by behavioural and changeability outcomes, not inferred from the existence of another review role.

Runtime and budgets. I selected `claude-sonnet-5.5`, medium reasoning effort and Copilot CLI 1.0.103, with automatic updates disabled. The wall-clock limits are 30 minutes per feature, 15 per consolidation or review, and 45 for CR1. The pilot limit is 300 AI credits per session; any pilot-informed adjustment must be frozen and included in the registered configuration before the fresh study runs. The total pilot-and-first-pass ceiling is 2,500 AI credits, raised from an initial 1,000-credit proposal. I also stated a $500 monetary budget. Credit consumption and currency cost are not interchangeable without a verified billing conversion.

Suites. Suite S1 is a ten-feature retrofit case workbench drawn from the case domain, whose features deliberately interact: lifecycle, handoffs, returns, safety holds, resident consent, appointments with an escalation rule, role-based visibility, deterministic ranking and a hash-chained audit trail. The selected study uses all ten features and the full CR1, including the ranking and export prerequisites in F9–F10. Each feature has visible example tests and hidden acceptance tests, including interactions with earlier features. Tests and reference solutions are intended to remain outside the agent's working repository. S2 is a library-lending suite reserved for a separately authorised main study; benchmark adaptation is deferred.

Isolation. I selected local execution rather than containers for the analysed runs. The CLI access rules and separation of working directories provide a weaker boundary than container isolation. They do not establish that hidden tests, references or outside resources are unreachable. Residual access risk limits validity and must accompany any results; an absence of leak flags is not proof of isolation. CR1 is intended to remain unavailable to feature, consolidation and review sessions until its dedicated change-request session. The tagged packaging and actual non-exposure of its request text, as well as its tests, remain to be verified. "Unforeseen" describes that intended information boundary, not an established property of local execution.

Procedure. Every step runs in a fresh agent session, as in the case's coordinator, so that context travels only through the repository. A feature step may commit only when the visible tests pass. If it commits no green increment, the runner resets it, removes that feature's example tests and counts the feature as missing. Its hidden tests remain in the denominator. After every step, the external measurement process runs the cumulative hidden suite, which covers every feature scheduled so far, including missing features, and collects the metrics. A pilot calibrates budgets with one run per arm over ten features, without CR1. The selected first pass uses S1, arms A, B and C, with four independent runs per arm, ten features and CR1. This is the exploratory first pass, not data to pool with earlier started runs. An optional main study would use S1 and S2, five runs per arm and ten features, under a separate prospective plan and authorisation. With three runs per arm the exact two-sided Mann–Whitney floor is $2/C(6,3) = 0.10$, so it cannot reach $p < 0.10$; four runs reach 0.029 and five reach 0.008. These are attainability bounds, not a power analysis. The selected first pass has 120 feature, 40

consolidation, 40 review and twelve change-request sessions: 212 sessions and an upper bound of 89 agent-hours. The pilot adds fifty sessions and twenty agent-hours, making 262 sessions and 109 agent-hours combined. These bounds exclude measurement and scheduling overhead and do not establish affordability under the credit ceiling. Sample sizes and stopping rules must be documented prospectively before the fresh runs; sample sizes will not be increased in response to observed effects.

End state and change request. H1's end state is after the last feature's post-feature step (a no-op in A), before the change request. Change-request success requires all its hidden tests to pass and no feature test that passed at that end state to fail afterwards.

Endpoint hierarchy. H1 retains first priority for working behaviour; H6 is the direct operational probe of future changeability. Passing H1 or improving complexity without a corresponding H6 outcome would not establish preservation of future options. One fixed change request supplies narrow task-specific evidence, not general maintainability. This revision does not retrospectively change that priority or its thresholds after earlier runs.

Measures. Cumulative hidden pass rate, open regressions and how long they survive; mean cyclomatic complexity, the share of functions above complexity 10, duplicated lines and lint warnings per thousand lines; non-test lines, diff lines per step and documentation words generated; AI credits as the primary consumption measure, with tokens and elapsed time secondary; change-request success and cost; and, for S1, a blinded comprehension task in which reviewers answer five fixed questions about each final code base. Test integrity, through checksums of the example tests and counts of tests and assertions, is checked after every step. The planned code-metric settings are the runbook's isolated lint rules E, F, W, C90, B and SIM, duplication detection at fifty tokens and five lines, and complexity measured by lizard. Tool versions and settings must be fixed in the registration. I plan to invite two independent comprehension reviewers; their agreement and the assessment remain pending.

Intervention measures in prior work. Intervention-based robot learning provides useful measurement precedents. In HG-DAgger, the human decides when to take control, provides an uninterrupted corrective trajectory and explicitly returns control to the learned policy [54]. ThriftyDAgger distinguishes the number of interventions, human actions and robot actions per episode, alongside autonomous and intervention-aided success [49]. Its supervisor-burden model separates switching overhead from the length of assistance: $B(\pi) = C(\pi)[L + I(\pi)]$, where C is the expected number of switches from autonomous to supervisor control per episode, L is the round-trip switching latency and I is the expected number of supervisor actions per intervention. Latency is expressed in action timesteps, not coding-agent tokens. Fewer interventions can therefore coexist with longer human involvement; continuous monitoring is another burden not captured by active correction time alone.

These studies motivate separating intervention incidence, frequency and effort, but are not evidence of coding-harness effectiveness. A frequency such as events per hour uses exposure time as its denominator; a human-control share uses human-controlled timesteps divided by all timesteps. Neither is the same as the proportion of tasks needing help. I adapt the latter to feature cycles and state the denominator explicitly, rather than claim one universal HIR formula. I retain failed cycles, unlike ThriftyDAgger's successful-episode summaries in its main evaluation; its supplement also reports totals over all trajectories.

Human intervention rate (HIR). As a secondary measure of harness quality, I record observed HIR: the proportion of attempted feature cycles receiving unplanned corrective human help. A cycle includes the feature and its assigned post-feature step, so B's additional sessions do not enlarge its denominator. Failed cycles remain included; repeated interventions in a cycle count once for the rate, with event counts recorded separately. For run r, let n_r be the number of attempted feature cycles and h_{rj} the number of qualifying corrective-help events in cycle j. Then

$$\mathrm{HIR}_r = \frac{N_{\mathrm{assisted},r}}{n_r} = \frac{1}{n_r} \sum_{j=1}^{n_r} \mathbf{1}\{h_{rj} > 0\}. \tag{1}$$

The indicator is one when the condition holds and zero otherwise; multiplying Equation 1 by 100 gives a percentage. By contrast, $\sum_j h_{rj}/n_r$ is events per cycle and can exceed one. I report event counts and active human minutes separately so that a brief clarification and a long repair do not appear equivalent merely because both affect one cycle. These are incidence and effort measures, not interchangeable estimates of total supervisory workload. If no cycle is attempted, the rate is undefined, not zero.

Primary runs receive no task-specific human coaching or code/test repair. I therefore also record an intervention-demand rate with the same denominator: cycles containing an explicit request for such help or a block requiring manual corrective action. With $d_{rj} = 1$ for such a cycle and zero otherwise,

$$\mathrm{IDR}_r = \frac{1}{n_r} \sum_{j=1}^{n_r} d_{rj}. \tag{2}$$

A request need not result in assistance, and an unsolicited human correction need not follow a recorded request; I code the two separately. Zero observed HIR under this policy is not evidence of autonomy. A timeout or automatic reset alone does not establish demand.

The intended sources are the session telemetry and retained logs. I plan to use Cowork to extract requests, blocks and actual interventions, then personally check classifications against source records and resolve ambiguous cases. The extraction must link each event to its cycle, phase, reason, action and active human minutes, using rules fixed before fresh runs. Telemetry coverage of human-help requests and corrective actions, including actions outside the CLI, has not yet been verified. Missing records cannot be interpreted as zero interventions; incomplete coverage makes the affected measure not evaluable. Routine launches, planned evaluation, required approvals and safety stops are recorded separately, not treated as corrective rescue. Any corrective help supplied is a protocol deviation; I retain the run, label it assisted and report its outcomes separately from unassisted estimates. Such deviations do not trigger replacement runs and may leave the unassisted comparison not evaluable at its predeclared sample size. I report change-request interventions separately, alongside completion, missing features, early termination and unattempted cycles. Lower HIR alone is not better: it must not reward silent failure or discourage necessary human judgement.

Author checking of an automated extraction is not independent annotation. No inter-rater agreement, stable severity coding or construct-validation result is available; these rates remain descriptive and their annotation reliability must not be inferred from a complete-looking event table.

8.4 Analysis and bias controls

The proposed analysis estimates the difference in final cumulative pass rate with bootstrap intervals that resample runs within arm. S1 trends are estimated with mixed-effects models that include an arm-by-feature-index interaction and run as a random intercept. A later multi-suite study would treat suite as a fixed effect and resample within suite and arm. Because code generation is not deterministic, even at temperature zero [81], every condition is run several times and intervals are reported rather than single values. The S1 first pass has a fixed sample size and excludes all earlier runs. Intervals do not trigger extra runs or pooling; any extension needs a separate prospective plan. Under the retained provisional H1 rule, support requires a gain of at least 10 percentage points and a 95% interval wholly above zero; invalidation requires its upper bound to be below 5 points. All other evaluable H1 outcomes are inconclusive. For the other evaluable hypotheses, the provisional support rule requires the estimate to meet its stated threshold and the 95% interval for the benefit to exclude zero in the beneficial direction. Invalidation requires the whole interval to fall short of the stated minimum effect of interest, applying the joint or alternative conditions in Table 9; absence of significance is not invalidation. For H5 I assess headroom below the 150% cost ceiling and late-feature savings, while retaining

the 125% validation threshold. An interval spanning zero, without ruling out a useful effect, is inconclusive. The planned controls are randomised interleaving of arms on the same machine; frozen hidden tests, metrics and analysis before fresh registered runs; exclusion of pilot data; blinded comprehension assessment; reporting of every run; and a divergence log. Independent suite review, verified access boundaries and the final analysis checks are still pending, not completed safeguards. The first pass will report estimates, intervals, deviations and non-estimable quantities, not confirmatory validation or go/no-go verdicts. Any comparison with the provisional thresholds will be labelled exploratory.

HIR is descriptive, with no new hypothesis threshold or adoption gate. I report observed and demand rates per run, human minutes and the B–A demand-rate difference with a 95% interval, resampling whole runs within suite and arm. The rates accompany correctness and cost, rather than replacing them.

8.5 Identification and precision limits

Four trajectories per arm give twelve independent run clusters, not 120 independent feature observations or twelve independent change scenarios. Bootstrap resampling cannot create additional independent information. Binary CR1 success is especially coarse at this sample size, and mixed-effects slopes may be unstable or unidentifiable. No simulation-based power or interval-coverage analysis has been completed. The rank-test attainability calculation above does not establish adequate power. Model convergence, boundary estimates and non-estimable quantities must be visible, not converted into precise-looking verdicts. Before fresh runs, the analysis plan must fix interval methods for binary CR1 risk differences and conditional cost comparisons, including how failures and zero-success arms enter each estimand. It must also specify diagnostics and fallback or not-estimable rules for bootstrap intervals and longitudinal models. No method is selected merely because it produces a finite or favourable interval.

The seven hypotheses retain their stated interval-based rules, but no family-wise error or false-discovery control is specified. Nominal 95% intervals are pointwise, not a simultaneous guarantee across hypotheses, metrics and contrasts. The reported priority order is not itself a complete confirmatory testing hierarchy. The first pass is therefore exploratory. A later confirmatory study would need a prospectively fixed primary contrast, endpoint hierarchy, multiplicity policy and precision justification before new data collection; these cannot be repaired by labelling seven pointwise intervals confirmatory after observing them.

The reset and missing-feature rule is specified, but the exact tagged policy for external-service outages, infrastructure failures, retries and incomplete measurements remains to be verified. These events must be distinguished from agent task failure without selective post-hoc exclusions. Run disposition, missingness and deviations require prospective rules and traceable reporting. The planned unassisted policy does not prove autonomy when requests or manual actions are incompletely observed.

Finally, intended hidden-test separation, version pinning and blinded review are not completed controls. The local access boundary is weak, a provider service can change, and note content can disclose treatment to a comprehension reviewer. Actual access probes, evaluator separation, blinding effectiveness and the fixed questions/tool permissions remain to be checked. The paper therefore offers an exploratory package comparison with explicit limits. The package-level identification limits are stated in the design above.

The protocol uses one proprietary model and no open-weights baseline. This limits reproducibility and transfer to other models; pinning the exposed version does not freeze a provider's service [6].

8.6 Status

This version presents the protocol, not study results. As of 25 October 2026 I had stopped execution and reported tagging the protocol. Registration was still pending. Earlier real-agent runs are retained as pre-registration evidence under their original labels and timestamps, not retrospectively declared preregistered. The fresh first pass is now explicitly exploratory; the framing amendment and analysis choices must be documented before those runs begin, after registration. The exact tag and registration record remain to be supplied. Results, including null, negative and inconclusive findings, will be added after checked analysis. No earlier run will be relabelled to fit the new framing.

9 Discussion: the existential crisis, revisited

9.1 What worked

It would be wrong to read this case as a failure of agents. The research phase assembled a corpus and analysis in days; my judgement that this would have taken me weeks is an unmeasured counterfactual. The role agents' challenge killed a bad idea, five end-to-end agents, before any code was written. The agents refused to invent approvals, figures or company facts, and recorded the limits of their evidence. The MVP was built and reshaped in a day. These episodes included targeted human challenge and feedback; they are not a controlled comparison with human-only teams or proof that all short loops succeed.

9.2 What remained mine in this case

Looking back over six weeks, I still supplied several kinds of reflective work. I decided what not to build. I noticed that something was wrong, not from the reports, which were accurate and full of caveats, but from the plain fact that I could not use the system. I held the theory of the system, in Naur's sense: which lessons mattered and why the sign-in had worked on 12 October. And I was the person responsible for designing the feedback loop and deciding what useful feedback would look like in this case.

That is close to Beck's distinction between a discipline's visible output and the less visible work of understanding, simplifying and building abstractions [15], and to Martin's insistence that programmers still write the tests first and know their customers [70]. The agents were excellent at the visible part. They produced proofs of work: pull requests, artefacts, receipts and honest caveats. In this case those records did not replace the understanding I gained from using a running system. That does not establish a general limit on what agents can do. It identifies responsibilities that could be candidates for bounded delegation, not proof that they are intrinsically or permanently human.

9.3 Can another agent restore futures?

Beck's alternation suggests a different purpose for an additional agent: preserving the options that feature execution consumes, rather than accelerating the next backlog item [14, 16]. Such an agent would need to inspect the accumulated system, detect drift against intended behaviour and take or recommend a corrective action. An agent that only reads generated records and approves them could reproduce the proxy capture observed here. I propose that a steering role needs behavioural evidence, bounded authority to act and checks that can disconfirm its judgement. More agents do not by themselves supply those conditions.

Darwin already delegates parts of this steering: agents turn observations into hypotheses and guide which candidate to explore next. Its boundary is important. Search improves an explicit objective within an existing architecture; engineers can steer objective setting and evaluation packaging, World Model updates are reviewed, and production output still enters human review

queues [84]. This narrows the open question from whether agents can perform any reflection to whether their correction preserves useful future options as requirements change. Performance gains do not establish that result, but they are a relevant precedent for bounded delegation.

The present experiment takes one step towards that question. It asks whether an agent-led consolidation package leaves software more able to absorb an unforeseen change. H6 is the closest probe of preserved future options; complexity and duplication are supporting proxies, not a direct measure of all possible futures. The fixed post-feature cadence does not test whether the agent can decide when to interrupt delivery, challenge a requirement, change the backlog or restore a usable deployment. A positive result would support this bounded consolidation role, not unrestricted process steering. A null or negative result would challenge this particular intervention, not prove that reflective work cannot be delegated to agents.

The broader working hypothesis is that local critique, review and repository-persisted learning can leave cumulative integration and changeability insufficiently checked. Aithena and PhotoCraft motivate that question without identifying its cause. A separate prospective test could compare human-led and agent-led steering under matched resources, using independently specified cross-feature journeys and later change requests, not issue totals. If an agent-led condition consistently detects and corrects the same cross-feature failures while preserving changeability, that would weaken a human-specific necessity claim. If apparent differences disappear after equalising oracle coverage, coverage rather than the identity of the steering actor would be a stronger explanation. The current consolidation protocol does not make either comparison; its H1–H7 rules remain unchanged.

9.4 If drift is contained, what remains for us?

Even if an agent can contain code drift, the human questions do not disappear. Better software outcomes would not, by themselves, establish how people should participate in producing them. Three questions remain open.

What is our role in the process? If agents can both implement features and consolidate the result, do we primarily choose problems, frame intent and judge consequences, or does meaningful participation also require working on the system itself? One possible direction is to spend more of the human effort on understanding users, challenging goals, designing experiments and deciding what not to build. That is a proposal for using the capacity released by automation, not evidence that these activities belong exclusively to humans or that implementation no longer contributes to understanding.

How much should we intervene? Too little involvement may leave us unable to recognise a wrong direction; intervening in every step may prevent the delegation we hoped to achieve. A possible starting point is a cadence of hands-on product use, with additional intervention when uncertainty, consequences or difficulty of reversal increase. The appropriate balance remains untested. HIR and intervention demand describe help supplied or requested; they do not identify an optimal level of involvement. A timely intervention that challenges an assumption or protects a user may be valuable, even if it raises the measured rate.

What will we learn, and how? We may learn more about the domain and the consequences of our choices while learning less through implementation. But if agents also perform the correction, where will the understanding needed to question them come from? Naur's theory building and Bainbridge's warning about eroded operator skills make this a practical concern as well as a philosophical one [5, 76]. Possible practices include predicting behaviour before trying an increment, investigating surprises and periodically explaining or changing the core design without agent assistance. Whether these preserve understanding, especially for people still learning the craft, needs separate study; producing another design note would not establish that they do.

These questions concern agency, expertise, responsibility and the meaning of the work, not only throughput. Some aspects could be studied through human task performance, comprehension and learning over time; what participation we value also requires judgement that a code-quality

result cannot settle. This paper offers directions for that inquiry, not answers. Neither the case nor the proposed experiment determines what humans should do, how much we should intervene or what we will learn if code drift is contained.

9.5 The crisis reframed

The existential question is usually put as whether machines will replace developers. I ask instead which parts of reflection and course correction agents can perform reliably, and how to tell when they are helping rather than reinforcing the original mistake. In this case, producing more work did not substitute for feedback. Designing, protecting and interpreting that feedback remained my responsibility, but that observation is a starting point for testing delegation, not a boundary I assume agents cannot cross. The old practices, testing, small steps, tidying and walking skeletons, offer ways to make such delegation observable and falsifiable. Beck's 2023 recalibration was about which ten per cent of his skills gained leverage [11]; in this case, the skills that mattered were the ones that keep a feedback loop short. Lamanna's advice to judge AI by the same business outcomes as before [58], and Lanzetta's description of the engineer as the architect of intent who builds the system in which agents work [60], point in the same direction.

10 Threats to validity

Construct validity. Word counts and a hedging lexicon are crude proxies for documentation load and for the content of status records, and a proportion of hedged statements is appropriate caution. I report them as indicators, alongside qualitative evidence, not as measures of quality.

Internal validity. I designed the coordinator and its gates, so the outcome reflects my configuration as much as the framework or the models. HVE Core's defaults (a manual mode, human stops and git-ignored tracking files) point the other way; I overrode them. The two periods differ in length and in the work attempted, model and tool versions changed during the study, and other work on the capstone, such as presentations, ran in parallel.

Operating-environment effects must be separated from intrinsic code quality. Bird et al. found application reliability associated with external environment factors in a different, desktop setting [19]. That does not explain this case, but supports treating missing identity, data and model configuration as concrete rivals rather than automatically diagnosing code decay. Table 10 retains directly recorded rivals and their limits.

Table 10: Rival explanations with direct case records. Limits are not grounds for ruling an explanation out.

Explanation	Case support	Counter-evidence or limits	Treatment
Migration decision	ADR 0006 (issue #196) froze feature work in the working MVP and prioritised a new layout.	The new layout passed health and restart checks; this did not establish usability.	A direct rival to autonomy alone; migration and coordination changed together.
Capstone rubric	The rubric rewards research and documentation; the scorer gave completeness full marks without usable sign-in.	The brief also asks for a working demonstrator.	A possible incentive for artefact production, not a measured incentive effect.
My overrides and priorities	I required committed RPI records, a full gate and delegated merging; PR #445 needed an exception.	The MVP used agents successfully; HVE Core defaults retain human stops.	Limits attribution to agents or HVE Core; owner choices and migration priority are part of the case.
Model and tool changes	Versions changed during the study.	There is no matched rerun under fixed versions.	An unresolved confound; configuration files cannot establish every session's actual model.
CI and cloud budgets	Validation moved locally in issue #413; cloud costs prompted a higher ceiling and reduced resources.	Merges continued; local checks did not establish deployed usability.	A plausible constraint on delivery, not evidence that more budget would resolve it.
Identity and sign-in setup	The new deployment lacked registration and staff bindings; issue #349 distinguished a redirect from sign-in.	Those steps had worked in the MVP on 12 October.	A concrete deployment obstacle and possible lost learning, not proof of general code decay.

Table 11 separates additional, untested alternatives from those records.

Table 11: Additional plausible rivals. A reason to consider an explanation is not evidence that it occurred; missing checks remain unperformed.

Explanation	Case evidence or reason considered	Counter-evidence or limits	Discriminating evidence still needed
External services and deployment drift	The replacement lacked model and identity configuration; its environment differed from the MVP.	No external provider outage is established. Health checks passed a narrower path.	Versioned deployment/configuration comparison and dependency-health records alongside the same failed journey.
Scope expansion	Responsible-AI and consumption criteria were added to open issues; a resident preview introduced further obligations.	Expansion also occurred before the loop and some controls were justified.	Matched original versus added scope, sequencing and time-to-usable-outcome analysis.
Inadequate acceptance tests	Local checks passed without a completed real-user sign-in journey; the rubric read repository artefacts.	Test scope was bounded and honest; this does not show all tests were poor.	Map each claimed capability to a task-level oracle and actual execution evidence.
Rate and context limits	Parallel sessions and a large read path make resource/context constraints plausible.	No session-level rate-limit, truncation or attention dataset was analysed.	Retained runtime events, actual inputs and blocked/retried request classifications.
Specification ambiguity	I selectively reviewed long requirements with difficult cross-references.	Important domain and consent decisions survived; ambiguity was not independently coded.	Independent interpretation of the same requirements and concrete conflicting acceptance examples.
Ordinary prototype debt	A rapidly assembled MVP was restructured and its deployment rebuilt; this can fail without agents.	The earlier MVP did work intermittently; there is no comparable human-led migration.	Matched migration or failure analysis distinguishing inherited debt from newly introduced faults.

External validity. This is a single case: one developer, a fictional but regulation-heavy domain, and a capstone whose rubric rewards documentation as well as software. Teams with dedicated product owners, users or operations staff may experience the mechanisms differently. The field observations in Appendix A.2 suggest similar concerns are recognised elsewhere, but they are not evidence of prevalence.

The external repository examples were selected because they appeared relevant to my concern, not independently of outcome. Reports can be duplicated, stale or unreproduced; labels are inconsistent, and review queues reflect contributor volume and maintainer capacity as well as software condition. Current framework documentation does not establish the historical runtime configuration. These observations broaden the motivation, not the empirical generalisability or causal identification of the focal case.

Reliability and researcher bias. The repository, issues and log are public, and Appendix D defines the measures so that they can be recomputed. The experiment's own threats, and their mitigations, are part of its protocol (Section 8). As participant and author I may over-weight episodes that support a tidy story; the log's contemporaneous, append-only form limits but does not remove that risk. AI-assisted summaries and interpretation may also select or smooth evidence towards a coherent story. My selective review is not an independent analysis, and mechanism naming is not systematic qualitative coding. AI assistance in analysis and drafting is disclosed below; source checking does not establish an unbiased interpretation.

11 Conclusion

This case records a divergence: 183 merged pull requests and a full implementation score coexisted with the owner's inability to sign in to the replacement system. Production volume and validation activity did not establish usable behaviour. Five candidate mechanisms organise that evidence, but migration, environment, scope, test coverage and owner decisions remain plausible rivals. The case does not establish a rate of code decay, an agent-caused acceleration or the effectiveness of consolidation.

The contribution is the chain from that observed divergence, through bounded candidate explanations, to a prospective test of retained behaviour and adaptation. Practice implications are proposals, not validated controls. Objective-guided optimisation provides a bounded precedent for agent-led correction [84]; the further question is whether such correction preserves changeability as features accumulate. Accountability for goals and consequential decisions remains distinct from delegating bounded corrective work; the case does not establish that only humans can perform that work.

The exploratory first pass operationalises a bounded version of that question: can an agent that consolidates after every feature keep agent-built software working, understandable and changeable at an acceptable cost? It tests the package-level question defined in Section 8. H6 is its direct, task-specific probe of future options; other quality measures cannot substitute for it. The experiment does not test choosing the right product or autonomously recovering every delivery failure. Section 8 sets out how to find out. The larger question of agent-led steering remains open; the first requirement is evidence that the additional agent improves outcomes rather than adds another layer of work. Even then, what people should do, when they should intervene and how they will continue to learn remain open questions. The proposals in Section 9.4 are starting points, not conclusions of this study.

Acknowledgements

I thank the colleagues and partners whose questions shaped this report.

Use of generative AI

I used GitHub Copilot with HVE Core agents to build the system under study. The coordinator's recorded RPI worker selector from 21 October is `claude-sonnet-5.5`; its own session used Automatic selection, not a fixed model name. The deployed assistant exercise on 14 October used `gpt-4.1-mini-2025-04-14`, distinct from the coding agent. I used Microsoft 365 Copilot for summarisation and finding relevant reference documents, and Copilot Cowork for slide generation. Log analysis, development of the mechanisms and manuscript drafting took place with GitHub Copilot in VS Code, using the reported model labels in Section 3. I supplied the observations and explanations; Copilot named and organised the patterns. This was not a formal qualitative coding exercise. I read Beck's mathematicians essay, watched the related full talk and confirmed the paraphrase here. I checked the case's repository figures and Azure spend; I have not yet independently checked the cited research statistics or the log-growth figure.

GitHub Copilot revised draft v3 and this author clarification, checked new reference metadata against source pages, and recomputed protocol arithmetic with the supplied scripts. Bibliographic checks do not establish the validity of every claim in a source. For future HIR analysis I plan to use Cowork to extract events and will personally check classifications against source records and resolve ambiguous cases. These are planned checks, not completed results. Copilot also compared Pavlenko et al.'s version 1 paper against the manuscript and revised the related-work, learning and bounded-steering discussion. Checking that source's reported scope and metadata

is not an independent verification of its experiments. I selected the case, made the analytical judgements and take responsibility for the content.

For draft v4, Copilot applied the editorial critique, distinguished observations from candidate explanations and prescriptions, and preserved the experimental design at my direction. It checked primary metadata and abstracts for six new references and full-text scope for RefactorBench and Building to the Test. CRBugBench full-text extraction and the HITS study were unavailable; their access limits are not independent verification. The revision did not add a second empirical coder, new case measurements or study results.

In the table-flow revision, Copilot used the Scholar Evaluation and Scientific Writing skills from Scientific Agent Skills [53] for qualitative developmental editing, not scoring or a publication recommendation. At my direction, it preserved the title and subtitle and reframed the first pass as exploratory without changing the private tagged study kit.

For the repository-context revision, I supplied the prior Aithena experience and candidate steering hypothesis. Copilot used the Hypothesis Generation skill [53] to inspect public repository records, distinguish reports from reproduced failures and formulate rival predictions. It did not run those applications or establish an independent replication.

Data availability

The repository analysed is public at https://github.com/jmservera/ama; this report uses commit `29c6b512f5e68733bb2cc1882343db39f5eb2cad`. The log-measurement and figure-generation scripts are provided with the source. The ancillary file anc/repository-observations-2026-10-25.json records the additional repositories' source revisions, tracker counts, sampling boundary and claim locators without reporter identities or attachments. Live issue states can change independently of the pinned source commits. The ancillary experiment notes in HVE Core's Minimum Viable Experiment format are earlier proposals, not the tagged study record. The separate study kit is held in a private repository; it is not yet a public replication archive. The registered snapshot, sanitised data and exact run provenance will need an authorised deposit before a reproducibility claim can be made.

References

[1] S. Agarwal, A. Singhal, A. Macvean, B. Vasilescu, and T. Breaux. Spec-driven development as prescribed and as practiced. arXiv:2608.25202, 2026.

[2] K. Beck, M. Beedle, A. van Bennekum, A. Cockburn, W. Cunningham, M. Fowler, J. Grenning, J. Highsmith, A. Hunt, R. Jeffries, J. Kern, B. Marick, R. C. Martin, S. Mellor, K. Schwaber, J. Sutherland, and D. Thomas. Manifesto for agile software development, 2001. https://agilemanifesto.org/.

[3] J. Young. Effective harnesses for long-running agents. Anthropic, 26 November 2025. https://www.anthropic.com/research/effective-harnesses-for-long-running-agents.

[4] A. Bacchelli and C. Bird. Expectations, outcomes, and challenges of modern code review. In *Proceedings of the 35th International Conference on Software Engineering (ICSE)*, pages 712–721. IEEE, 2013. doi:10.1109/ICSE.2013.6606617.

[5] L. Bainbridge. Ironies of automation. *Automatica*, 19(6):775–779, 1983. doi:10.1016/0005-1098(83)90046-8.

[6] S. Baltes et al. Guidelines for empirical studies in software engineering involving large language models. arXiv:2508.15503, 2025. Accepted in *Empirical Software Engineering*.

[7] G. Bavota, A. De Lucia, M. Di Penta, R. Oliveto, and F. Palomba. An experimental investigation on the innate relationship between quality and refactoring. *Journal of Systems and Software*, 107:1–14, 2015. doi:10.1016/j.jss.2015.05.024.

[8] K. Beck. *Test-Driven Development: By Example*. Addison-Wesley, 2002.

[9] K. Beck and C. Andres. *Extreme Programming Explained: Embrace Change*. Addison-Wesley, 2nd edition, 2004.

[10] K. Beck. `test && commit || revert`. Medium, 28 September 2018. https://medium.com/@kentbeck_7670/test-commit-revert-870bbd756864.

[11] K. Beck. 90% of my skills are now worth $0. *Software Design: Tidy First?* (newsletter), 19 April 2023. https://tidyfirst.substack.com/p/90-of-my-skills-are-now-worth-0.

[12] K. Beck. *Tidy First? A Personal Exercise in Empirical Software Design*. O'Reilly Media, 2023.

[13] K. Beck. Augmented coding: Beyond the vibes. *Software Design: Tidy First?* (newsletter), 25 June 2025. https://tidyfirst.substack.com/p/augmented-coding-beyond-the-vibes.

[14] K. Beck. Why does development slow? *Software Design: Tidy First?*, 19 November 2025. Author's summary at https://kentbeck.com/summaries/why-does-development-slow/.

[15] K. Beck. Mathematicians, here's a way to think about your existential crisis. *Software Design: Tidy First?* (newsletter), 29 September 2026. https://newsletter.kentbeck.com/p/mathematicians-heres-a-way-to-think.

[16] K. Beck. Software engineering in the age of AI. Talk at Prodacity 2026, Nashville, TN, 25–27 August 2026. Video: https://www.youtube.com/watch?v=F8fBgDCf2Y4; transcript: https://www.rise8.us/videos/kent-beck-software-engineering-in-the-age-of-ai.

[17] J. Becker, N. Rush, E. Barnes, and D. Rein. Measuring the impact of early-2025 AI on experienced open-source developer productivity. arXiv:2507.09089, 2025.

[18] T. Besker, A. Martini, and J. Bosch. Technical debt cripples software developer productivity: A longitudinal study on developers' daily software development work. In *Proceedings of the International Conference on Technical Debt (TechDebt '18)*, pages 105–114. ACM, 2018. doi:10.1145/3194164.3194178.

[19] C. Bird, V.-P. Ranganath, T. Zimmermann, N. Nagappan, and A. Zeller. Extrinsic influence factors in software reliability: A study of 200,000 Windows machines. In *Proceedings of the 36th International Conference on Software Engineering (ICSE)*. ACM, 2014. https://www.microsoft.com/en-us/research/publication/extrinsic-influence-factors-in-software-reliability-a-study-of-200000-windows-machines/.

[20] B. Böckeler. Understanding spec-driven-development: Kiro, spec-kit, and Tessl. martinfowler.com, 15 October 2025. https://martinfowler.com/articles/exploring-gen-ai/sdd-3-tools.html.

[21] M. Borg, D. Hewett, N. Hagatulah, N. Couderc, E. Söderberg, D. Graham, U. Kini, and D. Farley. Echoes of AI: Investigating the downstream effects of AI assistants on software maintainability. *Empirical Software Engineering*, 31(6):161, 2026. doi:10.1007/s10664-026-10889-1.

[22] F. P. Brooks, Jr. No silver bullet: Essence and accidents of software engineering. *Computer*, 20(4):10–19, 1987. doi:10.1109/MC.1987.1663532.

[23] M. Cemri, M. Z. Pan, S. Yang, L. A. Agrawal, B. Chopra, R. Tiwari, K. Keutzer, A. Parameswaran, D. Klein, K. Ramchandran, M. Zaharia, J. E. Gonzalez, and I. Stoica. Why do multi-agent LLM systems fail? In *Advances in Neural Information Processing Systems 38 (NeurIPS 2025), Datasets and Benchmarks Track*, 2025. arXiv:2503.13657.

[24] J. Chen, X. Xu, H. Wei, C. Chen, and B. Zhao. SWE-CI: Evaluating agent capabilities in maintaining codebases via continuous integration. arXiv:2603.03823, 2026.

[25] A. Cockburn. *Crystal Clear: A Human-Powered Methodology for Small Teams*. Addison-Wesley, 2004.

[26] J. Cohen. *Best Kept Secrets of Peer Code Review*. Smart Bear Inc., 2006.

[27] W. Cunningham. The WyCash portfolio management system. In *Addendum to the Proceedings of OOPSLA '92 (Experience Report)*, pages 29–30. ACM, 1992. doi:10.1145/157709.157715.

[28] D. Delimarsky. Spec-driven development with AI: Get started with a new open source toolkit. The GitHub Blog, 2 September 2025. https://github.blog/ai-and-ml/generative-ai/spec-driven-development-with-ai-get-started-with-a-new-open-source-toolkit/.

[29] P. Devanbu, T. Zimmermann, and C. Bird. Belief & evidence in empirical software engineering. In *Proceedings of the 38th International Conference on Software Engineering (ICSE)*. ACM, 2016. doi:10.1145/2884781.2884812.

[30] J. Ding, S. Long, C. Pu, et al. NL2Repo-Bench: Towards long-horizon repository generation evaluation of coding agents. arXiv:2512.12730, 2025.

[31] DORA. Accelerate state of DevOps report 2024. Google Cloud, 2024. https://dora.dev/research/2024/dora-report/.

[32] DORA. State of AI-assisted software development 2025. Google Cloud, 2025. https://dora.dev/dora-report-2025.

[33] Google Cloud. Announcing the 2025 DORA report. Google Cloud Blog, 23 September 2025. https://cloud.google.com/blog/products/ai-machine-learning/announcing-the-2025-dora-report.

[34] S. G. Eick, T. L. Graves, A. F. Karr, J. S. Marron, and A. Mockus. Does code decay? Assessing the evidence from change management data. *IEEE Transactions on Software Engineering*, 27(1):1–12, 2001. doi:10.1109/32.895984.

[35] S. Fakhoury, A. Naik, G. Sakkas, S. Chakraborty, and S. K. Lahiri. LLM-based test-driven interactive code generation: User study and empirical evaluation. *IEEE Transactions on Software Engineering*, 50(9):2254–2268, 2024. doi:10.1109/TSE.2024.3428972.

[36] M. Fowler. Design stamina hypothesis. martinfowler.com, 20 June 2007. https://martinfowler.com/bliki/DesignStaminaHypothesis.html.

[37] M. Fowler. Some thoughts on LLMs and software development. martinfowler.com, 28 August 2025. https://martinfowler.com/articles/202508-ai-thoughts.html.

[38] J. Gall. *General Systemantics: An Essay on How Systems Work, and Especially How They Fail*. General Systemantics Press, Ann Arbor, MI, 1975.

[39] E. Gamma and K. Maetzel, interviewed by W. Bos and S. Tolinski. Fork yeah! Microsoft open sourcing Copilot. *Syntax* podcast, episode 903, 19 May 2025. https://syntax.fm/show/903/fork-yeah-microsoft-open-sourcing-copilot.

[40] D. Gautam, S. Garg, J. Jang, N. Sundaresan, and R. Zilouchian Moghaddam. RefactorBench: Evaluating stateful reasoning in language agents through code. In *International Conference on Learning Representations (ICLR)*, 2025. arXiv:2503.07832.

[41] GitClear. AI copilot code quality: 2025 data suggests 4x growth in code clones. Research report, GitClear, 2025.

[42] E. M. Goldratt and J. Cox. *The Goal: A Process of Ongoing Improvement*. North River Press, 1984.

[43] C. A. E. Goodhart. Problems of monetary management: The U.K. experience. In *Papers in Monetary Economics*. Reserve Bank of Australia, Sydney, 1975.

[44] N. Harvey and D. DeBellis. Announcing the 2024 DORA report. Google Cloud Blog, 22 October 2024. https://cloud.google.com/blog/products/devops-sre/announcing-the-2024-dora-report.

[45] H. He, C. Miller, S. Agarwal, C. Kästner, and B. Vasilescu. Speed at the cost of quality: How Cursor AI increases short-term velocity and long-term complexity in open-source projects. In *Proceedings of the International Conference on Mining Software Repositories (MSR '26)*. ACM, 2026. doi:10.1145/3793302.3793349. arXiv:2511.04427.

[46] L. G. Heander, M. Borg, E. Söderberg, and C. Rydenfält. CodeHealth predicts the token cost of agentic code review: A pre-registered study of 465 agent-authored pull requests. arXiv:2610.21914, 2026.

[47] I. Herraiz, D. Rodriguez, G. Robles, and J. M. Gonzalez-Barahona. The evolution of the laws of software evolution: A discussion based on a systematic literature review. *ACM Computing Surveys*, 46(2):28, 2013. doi:10.1145/2543581.2543595.

[48] K. Hong, A. Troynikov, and J. Huber. Context rot: How increasing input tokens impacts LLM performance. Technical report, Chroma, July 2025. https://trychroma.com/research/context-rot.

[49] R. Hoque, A. Balakrishna, E. Novoseller, A. Wilcox, D. S. Brown, and K. Goldberg. ThriftyDAgger: Budget-aware novelty and risk gating for interactive imitation learning. In *Proceedings of the 5th Conference on Robot Learning*, volume 164 of *Proceedings of Machine Learning Research*, pages 598–608. PMLR, 2022. https://proceedings.mlr.press/v164/hoque22a.html.

[50] A. Hunt and D. Thomas. *The Pragmatic Programmer: From Journeyman to Master*. Addison-Wesley, 1999.

[51] Microsoft. HVE Core: HyperVelocity Engineering for GitHub Copilot. GitHub repository and documentation, accessed 24 October 2026. https://github.com/microsoft/hve-core; https://microsoft.github.io/hve-core/.

[52] A. Karpathy. Post on X introducing "vibe coding", 2 February 2025. https://x.com/karpathy/status/1886192184808149383.

[53] T. Kassis, V. Agarwal, Y. He, D. Patel, and A. M. Brueckner. Scientific agent skills: A library of procedural knowledge for research agents. arXiv:2609.00065, 2026. doi:10.48550/arXiv.2609.00065.

[54] M. Kelly, C. Sidrane, K. Driggs-Campbell, and M. J. Kochenderfer. HG-DAgger: Interactive imitation learning with human experts. arXiv:1810.02890v2, 2019 (first posted 2018).

[55] M. Kim, T. Zimmermann, and N. Nagappan. An empirical study of refactoring challenges and benefits at Microsoft. *IEEE Transactions on Software Engineering*, 40(7), 2014. doi:10.1109/TSE.2014.2318734.

[56] A. Kumar, Y. Bajpai, S. Gulwani, G. Soares, and E. Murphy-Hill. Why AI agents still need you: Findings from developer-agent collaborations in the wild. In *IEEE/ACM International Conference on Automated Software Engineering (ASE)*, 2025. arXiv:2506.12347v3, 9 October 2025.

[57] P. Laban, H. Hayashi, Y. Zhou, and J. Neville. LLMs get lost in multi-turn conversation. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2505.06120.

[58] C. Lamanna. Changing how we build. LinkedIn article, 5 August 2026. https://www.linkedin.com/pulse/changing-how-we-build-charles-lamanna-xpitc/.

[59] M. Lanzetta. Growing engineers in the hypervelocity era. LinkedIn article, 21 April 2025. https://www.linkedin.com/pulse/growing-engineers-hypervelocity-era-mike-lanzetta-qux0c/.

[60] M. Lanzetta. The hypervelocity orchestra. LinkedIn article, 25 February 2026. https://www.linkedin.com/pulse/hypervelocity-orchestra-mike-lanzetta-p0kvc/.

[61] H.-P. Lee, A. Sarkar, L. Tankelevitch, I. Drosos, S. Rintel, R. Banks, and N. Wilson. The impact of generative AI on critical thinking: Self-reported reductions in cognitive effort and confidence effects from a survey of knowledge workers. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, pages 1–22. ACM, 2025. doi:10.1145/3706598.3713778.

[62] M. M. Lehman. Programs, life cycles, and laws of software evolution. *Proceedings of the IEEE*, 68(9):1060–1076, 1980. doi:10.1109/PROC.1980.11805.

[63] M. M. Lehman, J. F. Ramil, P. D. Wernick, D. E. Perry, and W. M. Turski. Metrics and laws of software evolution: The nineties view. In *Proceedings of the 4th International Software Metrics Symposium (METRICS '97)*. IEEE, 1997. doi:10.1109/METRIC.1997.637156.

[64] H. Li, H. Zhang, and A. E. Hassan. AIDev: Studying AI coding agents on GitHub. In *Proceedings of the International Conference on Mining Software Repositories (MSR)*, 2026. arXiv:2602.09185. doi:10.1145/3793302.3797249.

[65] N. F. Liu, K. Lin, J. Hewitt, A. Paranjape, M. Bevilacqua, F. Petroni, and P. Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173, 2024. doi:10.1162/tacl_a_00638.

[66] J. L. Lulla, M. Galster, J. M. Zhang, S. Baltes, and C. Treude. The impact of configuring agentic AI coding tools on build-vs-buy decisions: A study protocol. ESEM 2026, Registered Reports track. arXiv:2606.03907, 2026.

[67] Y. Ma, B. Kereopa-Yorke, and B. Schultz. Building to the test: Coding agents deliver what you check, not what you requested. arXiv preprint arXiv:2606.28430v1, 26 June 2026. https://arxiv.org/abs/2606.28430v1.

[68] R. C. Martin. *We, Programmers: A Chronicle of Coders from Ada to AI.* Addison-Wesley Professional, 2024.

[69] R. C. Martin. AI out-codes you; deal with it. Video post on X (@unclebobmartin), 20 April 2026. https://x.com/unclebobmartin/status/2046206145597972849.

[70] R. C. Martin. Why hardcore technical focus still matters big time. *Product Engineers* podcast, 29 September 2026. https://productengineers.com/episodes/season2/why-hardcore-technical-focus-still-matters-big-time-uncle-bob/.

[71] J. Becker, N. Rush, T. Cunningham, D. Rein, and K. Mahamud. We are changing our developer productivity experiment design. METR blog, 24 February 2026. https://metr.org/blog/2026-02-24-uplift-update/.

[72] S. Mhatre, Y. Bajpai, S. Gulwani, E. Murphy-Hill, and G. Soares. SWE-Sharp-Bench: A reproducible benchmark for C# software engineering tasks. In *International Conference on AI-powered Software (AIware)*, 2025. Accessed arXiv:2511.02352v2, 5 November 2025.

[73] A. Murphy. The five stages of losing our craft. Blog post, 8 February 2026. https://andrewmurphy.io/blog/the-five-stages-of-losing-our-craft.

[74] A. Murphy. If you thought the speed of writing code was your problem – you have bigger problems. Blog post, 17 March 2026. https://andrewmurphy.io/blog/if-you-thought-the-speed-of-writing-code-was-your-problem-you-have-bigger-problems.

[75] E. Murphy-Hill, J. Butler, and A. Savelieva. Adoption and impact of command-line AI coding agents: A study of Microsoft's early 2026 rollout of Claude Code and GitHub Copilot CLI. arXiv:2607.01418, 2026.

[76] P. Naur. Programming as theory building. *Microprocessing and Microprogramming*, 15(5):253–261, 1985. doi:10.1016/0165-6074(85)90032-8.

[77] R. Lopopolo. Harness engineering: Leveraging Codex in an agent-first world. OpenAI, 11 February 2026. https://openai.com/index/harness-engineering/.

[78] G. Orlanski, D. Roy, A. Yun, C. Shin, A. Gu, A. Ge, D. Adila, N. Roberts, F. Sala, and A. Albarghouthi. SlopCodeBench: Benchmarking how coding agents degrade over long-horizon iterative tasks. arXiv:2603.24755, 2026.

[79] K. Beck, interviewed by G. Orosz. TDD, AI agents and coding with Kent Beck. *The Pragmatic Engineer* podcast, 11 June 2025. https://www.youtube.com/watch?v=aSXaxOdVtAQ.

[80] A. Osmani. The 70% problem: Hard truths about AI-assisted coding. *Elevate* (newsletter), December 2024. https://addyo.substack.com/p/the-70-problem-hard-truths-about.

[81] S. Ouyang, J. M. Zhang, M. Harman, and M. Wang. An empirical study of the non-determinism of ChatGPT in code generation. *ACM Transactions on Software Engineering and Methodology*, 34(2):42, 2025. doi:10.1145/3697010.

[82] R. Pan, J. Zhang, L. Wu, Y. Zhang, H. Zhang, and L. Zhang. Do modifications made by coding agents make subsequent software maintenance harder? arXiv:2610.14768, 2026.

[83] D. L. Parnas. Software aging. In *Proceedings of the 16th International Conference on Software Engineering (ICSE '94)*, pages 279–287. IEEE, 1994. doi:10.1109/ICSE.1994.296790.

[84] A. Pavlenko, B. Crivat, B. Haynes, C. Curino, F. Psallidas, J. Slawinski, J. Freischuetz, L. Pereira Sanchez, M. Weimer, M. Demarne, M. Jasny, M. Gandhi, M. Bovykin, M. Milletari, P. Ghosh, Q. Bai, R. Ramakrishnan, R. Pandita, S. Matusevich, S. Venkataraman, S. Krishnan, M. T. Mahmood, T. Bang, V. Emani, X. Zhao, and Y. Zhu. Towards an AI software factory for data systems. arXiv:2609.36323v1, 28 September 2026. https://arxiv.org/abs/2609.36323v1.

[85] S. R. O. Peralta, F. Hoshi, H. Washizaki, N. Ubayashi, I. Kondo, Y. Higo, H. Mukai, N. Yoshida, K. Kusama, H. Tanaka, and Y. Fan. Why are agentic pull requests merged or rejected? An empirical study. arXiv:2605.22534, 2026.

[86] PhotoCraft contributors. PhotoCraft: Source, parity records and public tracker observations. GitHub, source commit `5bb8536`; retrieved 25 October 2026. https://github.com/storytold/photocraft/tree/5bb853654196eca807212ff8955ba2eb293071ea. Dated counts and claim locators in the ancillary repository-observation record.

[87] W. W. Royce. Managing the development of large software systems. In *Proceedings of IEEE WESCON*, pages 1–9, August 1970.

[88] P. Runeson and M. Höst. Guidelines for conducting and reporting case study research in software engineering. *Empirical Software Engineering*, 14(2):131–164, 2009. doi:10.1007/s10664-008-9102-8.

[89] C. Sadowski, E. Söderberg, L. Church, M. Sipko, and A. Bacchelli. Modern code review: A case study at Google. In *Proceedings of the 40th International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP)*, pages 181–190. ACM, 2018. doi:10.1145/3183519.3183525.

[90] A. Sarkar. AI should challenge, not obey. *Communications of the ACM*, 67(10):18–21, 2024. doi:10.1145/3649404.

[91] J. M. Servera Bondroit. Aithena: Source, Squad records and public tracker observations. GitHub, source commit `f27aa2e`; retrieved 25 October 2026. https://github.com/jmservera/aithena/tree/f27aa2e9f949ea76f2a437249e68b52670a22835. Dated counts and claim locators in the ancillary repository-observation record.

[92] J. M. Servera Bondroit. AMA Case Study 48: research and solution design for the Zava Forward retrofit programme. GitHub repository, commit 29c6b51, 24 October 2026. https://github.com/jmservera/ama.

[93] P. Ralph et al. Empirical standards for software engineering research. arXiv:2010.03525v2, 2021 (first posted 2020). ACM SIGSOFT Empirical Standards: https://www2.sigsoft.org/EmpiricalStandards/.

[94] A. Simkute, L. Tankelevitch, V. Kewenig, A. E. Scott, A. Sellen, and S. Rintel. Ironies of generative AI: Understanding and mitigating productivity loss in human-AI interaction. *International Journal of Human–Computer Interaction*, 41(5):2898–2919, 2025. doi:10.1080/10447318.2024.2405782.

[95] A. Sinha, A. Arun, S. Goel, S. Staab, and J. Geiping. The illusion of diminishing returns: Measuring long horizon execution in LLMs. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2509.09677.

[96] Squad contributors. Squad: Human-led AI agent teams. GitHub, `dev` commit `481c944`; retrieved 25 October 2026. https://github.com/bradygaster/squad/blob/481c944596abfa2053e2acd88d765639f994d795/README.md.

[97] M. Strathern. 'Improving ratings': Audit in the British university system. *European Review*, 5(3):305–321, 1997.

[98] L. Tankelevitch, V. Kewenig, A. Simkute, A. E. Scott, A. Sarkar, A. Sellen, and S. Rintel. The metacognitive demands and opportunities of generative AI. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, pages 1–24. ACM, 2024. doi:10.1145/3613904.3642902.

[99] Thoughtworks. Complacency with AI-generated code. Technology Radar (Techniques, Hold), 2024–2025. https://www.thoughtworks.com/radar/techniques/complacency-with-ai-generated-code.

[100] A. Tornhill and M. Borg. Code red: The business impact of code quality. A quantitative study of 39 proprietary production codebases. In *Proceedings of the International Conference on Technical Debt (TechDebt '22)*, pages 11–20. ACM, 2022. doi:10.1145/3524843.3528091.

[101] M. Waseem, A. Ahmad, K.-K. Kemell, J. Rasku, S. Lahti, K. Mäkelä, and P. Abrahamsson. Vibe coding in practice: Flow, technical debt, and guidelines for sustainable use. arXiv:2512.11922, 2025.

[102] S. Willison. Vibe engineering. Simon Willison's Weblog, 7 October 2025. https://simonwillison.net/2025/Oct/7/vibe-engineering/.

[103] C. Wohlin, P. Runeson, M. Höst, M. C. Ohlsson, B. Regnell, and A. Wesslén. *Experimentation in Software Engineering*. Springer, 2012. doi:10.1007/978-3-642-29044-2.

[104] W. Yan. Don't build multi-agents. Cognition blog, 12 June 2025. https://cognition.ai/blog/dont-build-multi-agents.

[105] C. Yang, H. He, T.-C. Cheng, J. Butler, E. Murphy-Hill, C. Badea, and C. Bird. (When) should a software factory be lights-off? Benchmarking code review agents on bug detection. arXiv preprint arXiv:2610.13668v1, 9 October 2026. https://arxiv.org/abs/2610.13668v1.

[106] H. Yu, L. Liu, X. Jiang, Y. Jia, S. Wang, P. Qian, and Y. Chen. Habituation at the gate: Rising approval and declining scrutiny in human review of AI agent code. KDD 2026 Workshop on Agentic Software Engineering, 2026. arXiv:2606.22721.

[107] Z. Zhong, A. Raghunathan, and N. Carlini. ImpossibleBench: Measuring LLMs' propensity of exploiting test cases. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2510.20270.

A Supplementary practitioner context

These sources document contemporary arguments and reported practices. They are not primary evidence that this case's candidate mechanisms caused its outcome or that the harness is effective.

A.1 Craft, constraints and reported practice

Beck's augmented-coding account distinguishes caring about code, complexity, tests and coverage from accepting plausible output. He describes loops, unrequested functionality and disabled tests as warning signs [13, 79]. His Prodacity talk argues for learning through software and alternating feature work with consolidation; his mathematicians essay distinguishes visible output from understanding and abstraction [14–16]. These arguments motivate the hypothesis, not a measured treatment effect.

Martin's 2024 treatment of language models as tools and his later call for executable standards emphasise coverage, mutation testing, complexity limits and knowing the customer [68–70]. Gamma's discussion of stochastic simulation testing concerns evaluation containing a model, not a reason to treat all deterministic tests as unreliable [39]. Murphy applies the Theory of Constraints to review queues and work in progress, while also describing the loss of craft [42, 73, 74].

Lanzetta advises small chunks, tests first, bounded complexity and more attention to PR review [59]. His account of a two-week, roughly 60,000-line sprint describes repeated architectural reorientation, a done gate and retrospectives that block the next sprint until findings are resolved [60]. Lamanna reports spending agentic capacity on reliability, performance and security

rather than more features, with improved support outcomes for one product [58]. These first-party accounts do not isolate consolidation from other changes, and their output measures are not comparable controlled estimates.

A.2 Informal field observations

In October 2026 I presented HVE Core to two partners and discussed agentic delivery with peers. I omit partner names and generalise identifying details. At one partner session, an engineer challenged orchestration overhead, token cost, rule enforcement, documentation bloat and committed tracking files, and asked about lighter alternatives such as Spec Kit. The other session raised trust and net benefit after costs. A fellow architect asked how one learns how the solution works with such a backlog. These are informal, retrospectively reported observations, not systematically collected data, independent corroboration or evidence of prevalence.

B Proposed feedback-first practices

The seven practices in Table 12 are implications for practitioners to evaluate, not an empirically validated operating model. One-to-two-week horizons, three parallel sessions and five acceptance criteria are starting heuristics, not estimated optima or new rules for this repository. They do not override required engineering or human approval gates.

Table 12: Proposed practices, candidate mechanisms and suggested observations.

Practice	Proposed application and boundary	Observe
P1 Protect a running increment	Exercise a real user journey before replacing a working system; distinguishes usability from health checks.	First human use; age of last usable increment
P2 Bound batches and horizon	Start with one to two weeks, at most three sessions and five criteria per issue; revise to fit task risk. Addresses specification/gate inflation.	Work in progress; scope versus validated behaviour
P3 Hold human checkpoints	Demo every few merges or daily, decide what to keep, cut or tidy, and record the decision. Addresses feedback starvation [12, 16].	Product-use feedback and decisions, not attendance alone
P4 Make lessons usable	Convert suitable lessons into tests, lint rules or fitness functions; provide compact, provenance-linked context while retaining the original evidence. Addresses learning evaporation.	Executable lessons; effective read-path size
P5 Make gates proportional	Prefer behaviour-scoped checks and risk-based records, subject to mandatory full/publication and safety gates. Addresses process inflation and proxy capture.	Gate time and defects detected per accepted outcome
P6 Measure outcomes	Compare automated scores with real journeys; track behaviour-changing merges, review effort and attributable cost. Hedge density is only a prompt to inspect records.	Score–demo disagreement; cost per accepted outcome
P7 Preserve theory building	Pair on the first slice, own acceptance examples, read the domain code and invite challenge rather than compliance alone [35, 90].	What the owner can predict and explain without the agent

A checklist for Monday. Can a human complete an intended task in today's deployed increment? Does a merge preserve that journey? Is the horizon short and work in progress bounded? Are criteria small enough to review? Is there a demo checkpoint and a decision before

the next wave? Can important lessons be executed or retrieved with their evidence? Is required context readable? Do gates test behaviour without weakening mandatory safeguards? Is cost attributable to accepted outcomes? Can the owner explain the core design without an agent? These questions expose missing evidence; they do not certify a delivery process.

Implications for framework builders. HVE Core already supplies human stops, critiques and file-based context. Possible additions are review paths that exercise the running increment, evidence requirements scaled to risk, and executable lessons with warnings when required context exceeds a budget. Such additions require evaluation; this case does not establish that they improve outcomes or that existing gates should be removed.

C Candidate-mechanism evidence audits

These are operational boundaries for this paper, not validated necessary and sufficient conditions for all agentic development. The indicators refer to Table 1 and the case chronology. Experimental implications state what evidence would discriminate an explanation; the tagged experiment does not manipulate the five candidates separately.

C.1 Specification inflation

Element	Audit
Definition	Requirements and acceptance obligations expand faster than independently validated behaviour, without evidence that the added scope is needed for the next usable increment. Length alone is insufficient.
Case indicators	O3: BRD/PRD growth, 192 issues and cross-cutting additions; the smallest resident preview had thirteen criteria.
Counter-evidence	Growth began before autonomy and sometimes followed the owner's feedback; regulatory and consent controls can justify detail.
Rival explanations	Genuine scope expansion, specification ambiguity, capstone incentives and an ambitious migration rather than agent-driven inflation.
Experimental implication	Compare smaller requirements horizons at matched scope and resources. The current fixed-suite experiment cannot identify this mechanism, even if consolidation helps.

C.2 Proxy capture

Element	Audit
Definition	A completion proxy becomes a decision criterion and remains positive when an independent test of the intended outcome is negative. Proxy use alone does not establish capture.
Case indicators	O2–O3: 5/5 implementation score despite blocked sign-in; mandatory artefact presence; disproportionate evidence for PR #445.
Counter-evidence	Agents explicitly reported unmet acceptance; neither fabricated approval nor deliberate deception is established.
Rival explanations	An inadequate scorer or acceptance oracle, different evaluation targets, and a deployment failure invisible to repository review.
Experimental implication	Disagreement between visible completion and hidden behavioural tests would expose proxy limits. It would not by itself establish intentional test gaming or explain why a gate was chosen.

C.3 Learning evaporation

Element	Audit
Definition	A recorded lesson relevant to a later decision is absent from, unusable on, or not applied through that decision's effective context path, and the associated problem recurs. A missing citation alone is insufficient.
Case indicators	O4: simplicity references cease; working sign-in setup is not preserved; state and intent documents reach about 139,000 words.
Counter-evidence	Important domain decisions survived; the lesson could have been known but deferred. Actual session attention was not measured.
Rival explanations	Deliberate migration sequencing, deployment-specific configuration, context limits, or conflicting requirements rather than lost knowledge.
Experimental implication	Trace actual inputs and repeated faults. B–C cannot isolate memory quality because DESIGN and REVIEW notes and acting permissions differ. A matched-context study would be needed.

C.4 Process-gate inflation

Element	Audit
Definition	Additional procedural obligations increase per-change burden without demonstrated proportional improvement in the targeted outcome. More gates alone are not evidence that their net benefit is negative.
Case indicators	O5: full RPI and validation on each correction/rebase; hosted-minute rationing; explicit exception for PR #445.
Counter-evidence	Checks caught bounded defects and enforced evidence integrity. Gate duration and human review effort were not measured per PR.
Rival explanations	Legitimate safety and privacy requirements, budget constraints, new deployment complexity and owner-selected risk tolerance.
Experimental implication	Measure gate time and accepted outcomes under matched risk. H5 measures the consolidation package's cost, not the effect of removing this repository's required gates.

C.5 Feedback starvation

Element	Audit
Definition	Independent outcome-level feedback is insufficient to correct delivery decisions despite abundant artefact-level validation. The defining gap is between the evaluated proxy and intended outcome, not test count alone.
Case indicators	O1–O2 and O5: working MVP frozen; replacement unusable; passing checks and continued approvals did not restore a completed user task.
Counter-evidence	Human oversight continued; agents surfaced blockers; engineering checks provided real, though narrower, feedback.
Rival explanations	Identity and service configuration, migration priority, incomplete acceptance coverage, prototype debt or insufficient resources.
Experimental implication	Hidden retention tests and CR1 supply behavioural feedback to the evaluator. The experiment does not test live deployment recovery, product selection or a human-use checkpoint cadence.

D Measures and lexicon

Log entries. The knowledge-base log (`docs/reference/log.md`) was split into entries at each second-level heading that begins with a date. An entry belongs to the date in its heading. Word counts use whitespace tokenisation of the entry, heading included.

Hedging phrases. Each entry was searched, case-insensitively and on word boundaries, for these patterns: *unmet*; *not accepted*; *not inferred*; *is inferred*; *remain(s) open*; *remain(s) unproved*; *remain(s) unverified*; *not claimed*; *not established*; and *no* followed, within forty letters, spaces, commas, slashes or hyphens, by *is* or *was* and then *claimed* or *inferred*. Density is matches per 1,000 words.

Reference tracing. An entry cites the simplicity requirements if it contains an identifier from SA-001 to SA-010 or the word *simplicity*. It cites the development profile if it contains *deploymentProfile*, *development profile* or *allowPublicNetworkAccess*.

Repository counts. Issue and pull-request counts come from the GitHub search API on 24 October 2026 (for example, `is:pr is:merged merged:>=2026-10-15`). Document sizes are whitespace word counts of the files at commit `29c6b51`.

Proposed measures. *Time to first human use*: elapsed time from the start of a delivery cycle to the first time a person uses the running increment for its purpose. *Age of the last usable increment*: time since a person last verified that the deployed system could be used for its main journey. *Behaviour-changing merge ratio*: the share of merged pull requests that change what a user can observe in the running increment. *Cost per accepted outcome*: total model, tool and cloud cost divided by the number of outcomes a human accepted in the same period.

E Consolidation step prompt

The prompt used for the consolidation step of arm B (Section 7). Braces mark parameters set by the experiment runner.

```
Do not add or change features. Your job is to leave the code better than
you found it without changing its behaviour.

1. Run ‘make check‘, then read reports/quality.md (functions above
   complexity 10, duplicated blocks, lint warnings, file sizes).
2. Review the last feature’s diff (‘git diff feature-start feature-end‘,
   tags the runner sets around each feature step) and the hotspots
   against this checklist: duplicated logic; long or complex functions;
   unclear names; dead code; responsibilities in the wrong place, or
   rules from one feature leaking into another; tests that check
   implementation details instead of behaviour.
3. Make small, behaviour-preserving changes. Apply every change through
   ‘./tcr "<message>"‘: it runs all tests and commits if they pass, or
   reverts if they fail.
4. Never modify or delete files in tests/examples/. You may add tests that
   pin current behaviour before you refactor.
5. Rewrite DESIGN.md in at most 300 words: the current structure, where
   each business rule lives, and known debts. Replace; do not append.
6. Stop when the quality budget is met (no function above complexity 10,
   duplicated lines below 3%, zero warnings in the configured lint rules)
   or when your time budget ({consolidation_budget}) is used.
7. Finish with a summary of at most five lines: what you changed and what
   debt remains.
```