Everything but the Software:

Feature-Driven Decay in an Agentic Coding Loop. An Exploratory Case Study and an Experiment Protocol

Juan Manuel Servera Bondroit*

Senior Partner Solution Architect, Microsoft Schweiz, Zurich

Draft of 26 October 2026

Abstract

When does apparent agentic delivery progress cease to represent software progress? I examine a traceable exploratory case in which artefact-level completion diverged from usable behaviour, then present a prospective consolidation experiment. Over six weeks I used agents, centred on Microsoft's HyperVelocity Engineering (HVE Core) framework, to research a fictional housing retrofit programme, write requirements and deploy an MVP. A coordinator then ran parallel research–plan–implement–review loops over a backlog that grew to 192 issues. In ten days it merged 183 pull requests and the log grew by about 37,000 words, yet I could not sign in to the replacement system; an automated rubric separately rated implementation completeness five out of five. Its assessed release and capability scope have not yet been matched to that failed journey. Five candidate mechanisms organise the evidence: specification inflation, proxy capture, learning evaporation, process-gate inflation and feedback starvation. The confounded participant-observer case establishes neither accelerated code decay nor the effectiveness of a remedy. Feature-driven decay is the hypothesis, not an observed case result. It motivates a test of scheduled, behaviour-preserving consolidation after each feature. The unregistered, exploratory first-pass protocol compares feature-only, consolidation and review-only arms on retained behaviour, an unforeseen change request, internal quality, intervention demand and cost. Its contrasts estimate a consolidation package, including extra resources and different notes, not refactoring alone. No study results are reported. The contribution is the chain from observed divergence, through candidate explanations, to a falsifiable test of retained behaviour and future changeability, not evidence that more agents restore either.

Keywords: agentic software engineering; coding agents; spec-driven development; software evolution; technical debt; refactoring; feedback loops; human–AI interaction; exploratory case study; experiment protocol.

1 Introduction

On 15 October 2026 I started an agent coordinator against a backlog of more than 180 GitHub issues and let it run. Each issue went into its own git worktree, where an agent session ran a full research, plan, implement and review loop, passed a local validation gate and published a pull request. The coordinator assessed each candidate, merged it when every gate was green, rebased the remaining branches and started the next wave of work. Ten days later, 183 pull requests had been merged. I could not sign in to a running version of the system I was building.

That gap, between an extraordinary volume of activity and the absence of usable replacement behaviour, is the subject of this report. Beck's distinction between plausible code and working

*The views expressed are the author's own and do not necessarily reflect those of Microsoft. The case organisation, Zava North Homes, is fictional.

software, and his emphasis on learning through product use, motivate the question [16, 79]. The case concerns a configuration I designed, not a general evaluation of coding agents or a finding that its recorded activity had no value.

The hypothesis predates this repository. My earlier experience with Aithena and later selected observations of public repositories provide motivation, not a framework comparison or additional sampled cases (Appendix B). AMA is the focal, traceable case.

The central question is how feature-centric agentic delivery can produce strong completion signals while failing to preserve a usable and adaptable system. The argument follows one chain: observed divergence, candidate mechanisms, a consolidation hypothesis and a prospective controlled test. The case documents loss of access to a usable replacement; it does not measure a rate of structural code decay or identify an agent-caused acceleration. The subtitle names the hypothesis motivated by this small observational base, not an established causal finding. Section 7.4 proposes how the experiment can measure deterioration rather than infer it from output volume or incomplete implementation.

My working theory draws on software evolution: feature accumulation can increase complexity and the cost of later changes unless counter-work is done [27, 34, 62, 83]. Two possible amplifiers are compounding errors and output exceeding review capacity. Earlier misreadings can become the context for later steps, as in Beck's literal-minded genie [79]; high volume can obscure the gap between recorded completion and observed behaviour. These are propositions, not effects estimated by this case. Scheduled review and consolidation are a plausible intervention [12, 14, 16], not an established remedy.

The prospective question is whether an additional agent can preserve working behaviour and options for later change through that bounded intervention. I use reflection to mean checking assumptions and a working model against observed behaviour, not generating another approval record. The experiment tests a scheduled consolidation package, not autonomous product steering or the replacement of human judgement.

The case is unusually well documented. The repository is public, every change went through a pull request, an append-only log recorded what the agents did and why, and the coordinator's own instructions are versioned with the code [92]. I approach the central question through three more specific questions:

- **RQ1.** What did a long-running, autonomous, spec-driven delivery loop produce, and what did it fail to produce?
- **RQ2.** Which candidate mechanisms are consistent with the gap, and what counter-evidence and rival explanations limit each interpretation?
- **RQ3.** Can an additional agent preserve correctness and future changeability through a consolidation step after every feature, and at what cost? The experiment tests this bounded form of correction, not general autonomous steering.

The report makes three linked contributions:

1. A documented case of one architect working with agents for six weeks, from desk research to a deployed MVP and then a ten-day autonomous delivery loop, with descriptive measures, bounded within-case contrasts and an observation–interpretation–proposition audit trail (Sections 3 and 4).
2. An integrated model of five candidate mechanisms, with operational boundaries, case indicators, counter-evidence and rival explanations. The individual phenomena are not claimed as new (Section 5).
3. A consolidation harness and a prospective controlled protocol to test an intervention whose effect between feature steps is not isolated in the related work reviewed here [3, 77, 84]. The protocol follows the registered-report example of Lulla et al. [66] and HVE Core's Minimum

Viable Experiment method. It retains the tagged design and makes its identification and precision limits explicit; prospective documentation and fresh exploratory runs remain pending (Sections 6 and 7).

Practice implications are proposals, not a separately validated operating model (Section 8.4). The broader question of reflective delegation and human accountability is discussed, not answered, in Section 8.

This is not an evaluation of the tools I used. The framework at the centre of the case keeps a human between its phases by default; the failures described here occurred in a configuration I designed that delegated delivery and merge decisions (Section 2.7). I still handled approvals and technical blockers, but no longer learned from using the replacement product. I cannot isolate that change from the others.

2 Background

2.1 Software that only grows

That software decays when it only accumulates features is one of the oldest observations in our field. Lehman's laws of software evolution hold that a program in real-world use must keep changing, and that its complexity grows as it evolves unless work is done to maintain or reduce it [62]; a later formulation adds that its quality will appear to decline unless it is rigorously maintained and adapted [63]. Parnas called the result software aging, and blamed in part the changes made by people who do not understand the original design [83]. Eick and colleagues found mixed but, on the whole, persuasive evidence of code decay in fifteen years of change data from a large telephone-switching system [34]. Cunningham's technical-debt metaphor framed the cost of not consolidating as interest paid on every later change [27], and Fowler's design stamina hypothesis holds that without attention to design, adding features eventually becomes slower than it would have been with it [36]. Studies have since put numbers on the interest: across 39 proprietary code bases, low-quality code had fifteen times more defects and took 124% longer to develop than high-quality code [100], and developers in a longitudinal study lost about 23% of their working time to technical debt [18].

The evidence is not universal. Increasing complexity and declining quality are among the less strongly supported of Lehman's laws, and some systems have grown without the predicted decay [47]. Several findings above are observational, and their estimates belong to the studied settings, not every code base. They motivate measuring decay in this experiment; they do not establish that it occurred in the case or that consolidation will prevent it.

2.2 Why agents might accelerate the decay

Long-task and multi-turn studies motivate concern about errors inherited from earlier steps [57, 95]. SlopCodeBench and SWE-CI examine iterative degradation and regressions at repository scale [24, 78]. However, a randomised maintainability study found no significant downstream difference, and chained maintenance tasks point to inherited test failures rather than complexity alone [21, 82]. Neither deterioration nor a benefit from consolidation should be assumed across settings.

Review capacity supplies a second possible constraint. Understanding changes is a major challenge of code review; habituation, fragmented context and uneven retrieval from long contexts may limit scrutiny as output grows [4, 23, 48, 65, 106]. These are plausible amplifiers, not effects measured in this case. Further empirical and practitioner context is retained in Appendix A.

2.3 Refactoring, review and evaluation boundaries

Agentic refactoring, review and human correction are already studied. RefactorBench evaluates 100 handcrafted multi-file refactoring tasks across nine Python repositories, not scheduled consolidation between feature additions [40]. Kumar et al.'s ASE 2025 study observed developers collaborating with agents on existing issues: incremental, active collaboration was associated with greater success, not randomly assigned to establish an optimal intervention rate [56]. SWE-Sharp-Bench supplies a reproducible C# issue-resolution benchmark and curation pipeline [72]; reproducible repository-scale evaluation itself is not a contribution claimed here.

Two recent preprints sharpen the evaluation problem. CRBugBench evaluates review agents on 1,000 open-source and 800 proprietary tasks from one company, reporting weaker detection on complex, non-local and proprietary-context changes [105]. It is a 9 October 2026 preprint, not an independently replicated result establishing that review cannot work. *Building to the Test* reports near-perfect behavioural scores for demos while the requested reusable library was unused or absent. Its unchanged, source-hidden oracle did not check that delivery contract [67]. This is distinct from altering tests, as examined in ImpossibleBench [107]: test integrity and adequate outcome coverage are separate safeguards.

These studies narrow the proposed novelty to the case trace and the specific prospective package comparison, including an unforeseen change request. They also caution against assuming that another reviewer, a stricter check or a high hidden-test score necessarily certifies the intended deliverable. The literature discussion is focused, not systematic. Preprints, observational studies, practitioner accounts and first-party industrial reports have different evidential roles; none substitutes for the planned controlled comparison.

2.4 Optimisation with behavioural feedback

Pavlenko et al.'s *Towards an AI Software Factory for Data Systems* offers a complementary case [84]. Hotspan packages optimisation targets from telemetry, analysis and reviews; Darwin explores candidate changes through code–test–debug–reflect cycles. The setting is existing, human-architected systems with stable semantics and measurable objectives such as latency. Reported optimisation gains are evidence against treating high agent throughput as inherently unproductive, not a controlled estimate of end-to-end productivity, general maintainability or future changeability. Their application-work productivity calculation excludes infrastructure and onboarding time, and output enters engineering review. The work establishes a precedent for bounded agent-led correction; it does not isolate consolidation between feature additions or product-goal selection.

2.5 The practitioner conversation

Waseem et al. describe rapid generation alongside architectural inconsistency, security concerns and maintenance overhead [101]. That trade-off is not claimed as new here; the contribution is the case trace and prospective package comparison.

Beck supplies the conceptual bridge: augmented coding retains care for code, complexity and tests; alternating features with consolidation aims to restore options consumed by additions [13, 14, 16]. Learning through use, understanding and abstraction are distinct from producing more artefacts [15]. These arguments motivate testing bounded reflective work, not an established remedy or a permanent human–agent boundary. Extended practitioner accounts remain in Appendix A.

Spec-driven development adds structure, but not an automatic outcome oracle. Spec Kit proposes specification, planning, tasks and implementation; Böckeler describes both ignored and over-followed instructions; and a study of practice reports reliability benefits alongside planning and review costs [1, 20, 28].

2.6 Older theory

Naur distinguishes a programmer's theory of the system from its documentary record; Brooks locates essential difficulty in the conceptual construct, not its representation [22, 76]. Royce and Gall motivate early experience of working behaviour; XP, walking skeletons, tracer bullets and Agile practice make short feedback loops concrete [2, 8, 9, 25, 38, 50, 87]. Small reversible structural changes supply a consolidation practice [12].

Automation can shift effort from producing to monitoring and intervention, with substantial metacognitive demands [5, 94, 98]. Associations between confidence in AI and reduced scrutiny do not establish causation [61]. Goodhart and Strathern motivate checking completion proxies against their intended outcomes [43, 97].

2.7 HyperVelocity Engineering (HVE Core)

HVE Core is an open-source framework from Microsoft that describes itself as an opinionated agentic software development lifecycle built on GitHub Copilot, guided by the principle "AI carries the rules, humans keep the judgment" [51]. Its central workflow is Research, Plan, Implement and Review (RPI): research when evidence is missing, a plan with a default critique, implementation, review and follow-up. Each phase writes dated artefacts under a `.copilot-tracking` folder, so that context travels through files rather than chat history, and the framework treats these artefacts as git-ignored working memory by default. Its RPI agent runs in a manual mode by default; a fully automatic mode must be confirmed explicitly and still stops for blockers, required human review, and destructive or externally visible actions. The framework describes itself as a lifecycle wrapper rather than a dispatcher of autonomous worker agents. Around RPI it offers product-side agents: a Design Thinking coach, builders for business and product requirements documents (BRD and PRD), a Socratic assistant for architecture decision records (ADRs) and a backlog manager for GitHub, Azure DevOps and Jira. The project warns that it evolves quickly and is best treated as a source of patterns [51]. Its experimental collection includes an Experiment Designer agent that coaches a team through a Minimum Viable Experiment: falsifiable hypotheses with success thresholds set before any run, vetting against red flags, a minimal design, and an evaluation of the outcome against the precommitted criteria [51]. Section 7 uses it. I used the HVE Core plugin snapshot `plugins-v3.3.106` throughout the case. Its snapshot commit is `2df5013e29ebfd2ce61bcd0cf021d8c8186482eb`, generated from source commit `e9af018fe5ffbfbc72321a8bca21fb987359af08`. Historical use is my account; the snapshot identifiers do not establish an installation date.

3 Case and method

3.1 Setting

The case is my capstone for Microsoft's *Azure Master Architect* (AMA) programme. Its name is public in the Microsoft Employee Learning badge listing.[1] That public listing does not authorise publication of internal assessment material or this paper. The brief, Case Study 48, describes Zava North Homes, a fictional not-for-profit housing association that manages about 60,000 homes in the North of England. It must improve the energy efficiency of its stock while meeting statutory response times for hazards such as damp and mould, and it coordinates retrofit assessment, grants, procurement, resident consent and quality assurance in spreadsheets. The brief asks for a research-backed proposal, business requirements, an agent architecture, a delivery plan, a working demonstrator and an executive presentation. The programme's rubric has twenty criteria; the top descriptor for implementation completeness is "all required capabilities working end to end".

[1] https://www.credly.com/org/microsoft-employee-learning/badge/azure-master-architect

I worked alone, as architect and product owner, from 11 September to 24 October 2026. Agents did almost all of the research synthesis, writing and coding. The repository also contains an automated scorer: a GitHub agentic workflow that asks a language model to score each pull request against the rubric and records the result [92].

3.2 Workflow and tools

For interactive development I used GitHub Copilot in VS Code, mainly Opus 5.5 during the first two weeks and then GPT-6.1 Sol through the case cut-off. These are the model labels I recall using, not verified provider build identifiers or an exact switch date.

- **Research.** Sixteen official legislation, regulator, policy, standards and funding documents were downloaded, converted to Markdown and organised, with agent-written sector and company research, into a knowledge base: an index, immutable sources, maintained syntheses, an owner-curated memory file and an append-only log of every change.
- **Challenge.** Eight agents role-playing the case organisation's stakeholders (asset management, programme delivery, finance, procurement, data, building safety, neighbourhood housing and resident engagement) and HVE Core's Design Thinking coach challenged each idea. Their first verdict was that none of the five end-to-end agents requested in the brief should be built as such.
- **Requirements and decisions.** HVE Core's BRD and PRD builders, a BRD quality reviewer and the ADR assistant produced and revised the requirements and six architecture decision records.
- **Prototypes and MVP.** Several prototypes were built, reviewed by the role agents and kept as evidence. An MVP followed and was deployed to Azure.
- **Backlog.** HVE Core's backlog manager turned the requirements and decisions into GitHub issues with epics, features, acceptance criteria and dependencies, labelled by how much of each item already existed in the MVP.
- **Coordinator.** On 15 October I added a coordinator agent of my own design to deliver the backlog (Section 3.3).

3.3 The coordinator

The coordinator ran through Copilot CLI on a VM. It selected waves of issues whose dependencies were merged and launched parallel worker CLI sessions through `tmux`, each in an isolated git worktree with HVE Core's RPI agent and one issue as its brief. I used Sonnet 5.5 for the workers, including before the explicit pin. At the pinned repository commit the worker selector is `claude-sonnet-5.5`; PR #420 introduced that requirement on 21 October. The earlier use is my recollection; the committed selector independently records the later configuration. The coordinator used Auto selection with the Intelligence setting. I observed it tending to select GPT-6.1 Sol, but this was not a guaranteed model pin or proof of every session's actual model or provider build. Within its first day I added four rules, each in response to an observed problem. First, it could merge its own pull requests through a gate it verified itself, because repository auto-merge was unavailable. Second, the full research, plan, implement and review loop became mandatory for every issue, and the presence of the loop's `.copilot-tracking` artefacts in the pull request became a merge condition, because the first waves of sessions had implemented directly without them. Third, it updated the project board and ticked only the acceptance criteria that reviewed evidence proved. Fourth, it monitored sessions on a schedule instead of blocking. Later rules required a complete local validation gate before every push, including documentation-only changes, covering five source projects, infrastructure templates, a disposable

SQL Server, browser accessibility checks, migrations, four container images, vulnerability scans and a software bill of materials, to be rerun after every correction or rebase. An issue stopped only on a *human blocker*: an owner decision, a named approval, a missing credential, or a review finding still open after two correction cycles. On the same day an accepted ADR made migrating the working MVP into a new source layout the first priority and barred new feature code from the MVP.

3.4 Data and analysis

I use an exploratory single-case design, with myself as participant-observer. The case is the delivery of this repository from 11 September to 24 October 2026. The unit of analysis is the autonomous loop of 15–24 October. The MVP period of 8–14 October, when I used the system intermittently to refine ideas and the user experience, provides a within-case contrast, not a control group. I chose the case because it is revelatory: a public, contemporaneous trace of an autonomous agent loop.

I analysed the public repository at commit `29c6b51` (24 October 2026, 16:19 UTC) [92] with issue and pull-request metadata retrieved from the GitHub API on the same day. The main sources are the append-only knowledge-base log (368 dated entries and about 57,000 words from 11 September to 22 October; entries before 25 September were reconstructed from history), the knowledge-base index, the BRD (version 0.19), the PRD (version 0.18), the coordinator's definition, issue bodies and the rubric scorer's latest result. I used descriptive counts; a hedging lexicon applied to each log entry (Appendix F); reference tracing, in which I followed the identifiers of recorded learnings through the log by date; and AI-assisted interpretation of my observations. I described the candidate mechanisms, possible amplifiers and consolidation hypothesis. GitHub Copilot in VS Code organised those explanations, named the five patterns and drafted the account, using Opus 5.5 and then GPT Sol 6 and 6.1 as reported interface labels. Microsoft 365 Copilot helped summarise material and find relevant reference documents; it did not perform the log analysis or develop the mechanisms. This was not a systematic entry-by-entry qualitative coding study. I reviewed important specification sections selectively, especially the addendum, rather than auditing the full BRD and PRD. Their identifiers and cross-references made the overall design difficult to follow. I have checked the repository figures and Azure expenditure reported here. Independent author checks of numerical findings from cited studies and of the log-growth figure remain pending. The central discrepancy needs a compact, release-linked evidence package: the dated score and its assessed capability scope, the deployment revision and configuration, and dated evidence of the failed sign-in journey. The retained account does not yet establish that the scorer assessed the same release and capability claim as the usability observation. Until those links are checked, I report their coexistence in the case chronology, not a verified same-release contradiction. The report is informed by established guidance for case study research in software engineering [88] and the ACM SIGSOFT Empirical Standards [93]. As the sole developer and author I am a participant-observer; Section 5.7 discusses what that implies.

The contextual observations in Section B were added on 25 October after the case analysis. They use purposively selected public repositories, pinned source files, GitHub tracker counts, and ten newest plus five oldest open `bug`-labelled PhotoCraft reports. They are not a systematically sampled multi-case study and are not pooled with AMA's measurements. The ancillary repository-observation record states the retrieval boundary, locators and exclusions. No external application, original Photoshop installation or reference-parity suite was executed.

3.5 Constructs and evidential boundaries

Working behaviour means completing an intended task through the running system, including the identity, data and service dependencies needed for that task. A healthy endpoint or a passing repository test alone does not establish it. *Decay* denotes loss of previously working behaviour or

increasing difficulty of understanding and changing a system. The case documents a usability discontinuity during replacement, not a measured decline in intrinsic code quality; deployment drift could produce the same observation. *Adaptability* is operationalised prospectively as success and cost on the fixed-budget, unforeseen change request, not as a universal measure of maintainability. *Consolidation* means scheduled structural work intended to preserve observable behaviour, with tests checking that intention; passing finite tests cannot prove semantic equivalence.

I keep five measurement categories separate. PRs, lines and words describe *production volume*; checks, reviews and receipts describe *validation activity*; observed user tasks describe *system behaviour*; code metrics and the change request probe *internal quality and changeability*; and corrective help requested or supplied describes *intervention*. Only the first three have case observations. The case has no longitudinal complexity measure, controlled changeability task or systematically coded intervention dataset. Neither volume nor validation activity is used as a direct estimate of decay.

3.6 Chain of evidence and reflexivity

Table 1 separates observations, interpretations and propositions. It indexes evidence already described here, not a newly coded dataset. Repository sources refer to the pinned commit unless identified as author reports. Log entries before 25 September are retrospective reconstructions; later dated entries are the project's contemporaneous record, not independent corroboration of every statement they contain. The 22 and 24 October instructions, historical model use and intermittent product use remain author reports where original records have not been recovered.

Table 1: Observation–interpretation–proposition audit trail. Interpretations are contestable; the proposed tests have not been performed.

ID	Observation and provenance	Interpretation	Proposition or discriminating evidence
O1	Log, 8–14 Oct, plus author report: an MVP with sign-in and realistic synthetic data was used; 16 Oct record: replacement has one case, no staff and no model.	Recorded engineering completion did not preserve the owner's usable workflow.	Independently execute the same journey before and after migration; separate configuration failure from code regression.
O2	GitHub metadata: 183 PRs merged, 15–24 Oct; scorer records 5/5 completeness; author could not sign in. Dated API/scorer captures and their release/scope correspondence remain unverified.	Recorded completion and usability differed in the chronology; a same-release discrepancy is not yet established.	Link score, capability scope, deployment/configuration and the failed journey before testing agreement.
O3	BRD/PRD versions and log: growth before and during the loop; PR #445: two changed lines and a 78-line evidence record.	Requirements and process records may consume attention without delivering equivalent feedback.	Compare review effort and validated behaviour, not word counts alone.
O4	Log reference tracing: last simplicity citation on 13 Oct; missing registration/staff bindings in the replacement.	Some lessons may have fallen off the effective read path. Absence of a citation is not proof of absence of knowledge.	Inspect actual session inputs and test whether the prior lesson was available, understood and executable.
O5	Coordinator definition and ADR 0006: committed RPI records, full gates, delegated merging and migration priority; author still resolved blockers.	Reduced product-use feedback coexisted with substantial oversight.	Distinguish outcome-level feedback from approval activity; test the consolidation package separately from the migration.

I selected the episodes, designed the coordinator and wanted the capstone to succeed. Those roles make a coherent retrospective explanation attractive. Developers' experience-based beliefs need not correspond with project evidence [29]; that methodological caution applies to my

own account, not only to agent-generated claims. AI-written project records are data about recorded activity, not independent judges of success; AI-assisted synthesis is analysis assistance, not another observer. No independent second coding or empirical peer-debrief pass has been completed. The supplied editorial critique prompted stronger boundaries and explicit rival explanations, but does not fill that gap. An independent check of O1–O5 against retained source and execution records remains necessary before presenting the interpretations as independently corroborated.

4 What happened

Table 2 summarises the case and Table 3 compares the periods before and during the delivery loop.

Table 2: Timeline of the case (all dates 2026).

Dates	Phase	What happened
11 Sep – 7 Oct	Research and requirements	Sixteen regulatory sources converted; role agents reject five end-to-end agents (26 Sep); BRD and PRD drafted and repeatedly revised; prototypes reviewed; my usability feedback recorded (7 Oct).
8 – 14 Oct	A usable MVP	MVP built and reshaped through several feedback passes in one day (8 Oct); running on Azure with SQL, blob storage and two replicas over 980 synthetic cases (9 Oct); rebuilt with Entra ID sign-in, which I used (12–13 Oct); five assistant paths exercised against a real model (14 Oct).
14 – 15 Oct	Backlog and coordinator	Backlog generated as GitHub issues; coordinator created and hardened within a day; an ADR makes migrating the MVP to a new source layout the first priority.
15 – 22 Oct	The loop at scale	Pull requests merged at about eighteen a day; the log grows by about 37,000 words; the migrated deployment holds one fictional case, no staff and no model deployment (16 Oct); browser sign-in blocked; validation moved off hosted CI to save budget (18 Oct); cloud cost ceiling raised (22 Oct); new cross-cutting requirements appended to open issues (22 Oct).
22 – 24 Oct	Asking for something that runs	Ten issues labelled *feedback-first*; instruction to make employee and resident sites available as soon as possible with at most eight parallel items; checkpoint and refactoring instruction (24 Oct).

Table 3: Before and during the delivery loop. Counts from the repository at commit `29c6b51` and the GitHub API on 24 October 2026; hedging phrases as defined in Appendix F.

Measure	Before the loop	During the loop
Pull requests merged	52 (26 Sep – 14 Oct; 2.7 a day)	183 (15 – 24 Oct; 18.3 a day)
Knowledge-base log entries	126 (to 14 Oct)	242 (15 – 22 Oct)
Words appended to the log	19,967 to 14 Oct (about 1,000 a day from 25 Sep)	36,755 (15 – 22 Oct; about 4,600 a day)
Hedging phrases per 1,000 log words	1.2	3.8
Log entries citing my simplicity requirements	4 (last on 13 Oct)	0
Deployment I could use	Entra sign-in, 980 synthetic cases, live model calls (12 – 14 Oct)	One fictional case, no staff, no model deployment (16 Oct); sign-in blocked

4.1 Research, requirements and a usable MVP

Table 4 adds code-level activity from the pinned history. The script classifies paths and compares each selected first-parent commit with its first parent, detecting renames. The integration view includes multi-parent merges and PR-numbered squash commits: 31 before the loop and 177 during it. These are not the API pull-request counts in Table 3; the literal-merge subset, seven in each period, is also reported in `anc/repo_history_metrics.out.txt`. Classification rules and commands are printed there. The additions and removals show work volume, not net code size, maintainability or delivered value. No complexity comparison was made because `lizard` was not installed.

Table 4: Text lines added and removed in first-parent integrations, including PR-numbered squash commits, through `29c6b51`. Detected pure renames add no lines; binary deltas are excluded.

Path class	8–14 Oct		15–24 Oct	
	Added	Removed	Added	Removed
Product source	8,136	421	23,408	2,184
Tests	6,871	537	73,478	1,416
Documentation	12,065	1,297	25,210	2,455
Tracking artefacts	238,185	2,642	240,369	1
Infrastructure	2,708	73	6,162	485
CI and workflows	240	64	897	246
Other	25,320	1,099	72,711	1,776

The September work was research and requirements preparation, not application building or a project-free baseline. The agents assembled a regulatory corpus, sector baselines and a modelled customer profile, and the role agents produced a genuinely useful early verdict: each requested *end-to-end* agent bundled deterministic controls, accountable human decisions and a smaller set of tasks suited to bounded AI, so none should be built as such. Requirements were written, reviewed by an automated quality reviewer and revised many times. Application prototypes followed in October.

On 7 October I used the latest prototype myself and recorded what was wrong with it. The next day the agents combined my notes with critiques of three prototypes by the UX, Design Thinking and role agents into ten simplicity requirements (SA-001 to SA-010): a default view listing only my cases, each with one plain status and one next action; a case that opens full

screen; blockers explained in plain words with an owner; no role simulator in user views; optional AI that never blocks manual work; and so on. On 8 October they built an MVP that followed those requirements and then reshaped it through several rounds of my feedback the same day: filters, an overview map, visits, handover suggestions and document uploads. On 9 October it ran on Azure with Azure SQL, blob storage and two replicas over 980 synthetic cases. On 12 October the stack was rebuilt from an empty resource group with Entra ID sign-in; I signed in and used it, and the problems I reported, a missing logo and an account switch that only signed me out, were fixed within a day. On 14 October five assistant paths produced cited proposals through a real model deployment, using 6,884 tokens across five calls. I tested the initial proof of concept for a couple of days, discarded it, then used the MVP for a few days to refine ideas and the user experience. This was intermittent use, not daily use throughout the week. I then carried those ideas into requirements, ADRs and the hierarchical backlog.

I treat 8–14 October as a within-case contrast with 15–24 October: intermittent use of a usable MVP versus no realistic end-to-end task completed in the replacement during the autonomous loop. I remained involved, mainly answering approval requests and resolving technical blockers to keep the loop running. The contrast concerns product-use feedback, not the complete removal of human oversight. It is consistent with the importance of feedback, but cannot establish that removing product-use feedback caused the outcome: the migration, workload, gate rules, models and deployment conditions also changed, and the periods were not assigned at random.

4.2 Bounded within-case contrasts

Table 5 compares episodes and negative cases already in the chronology. It is an analytical contrast, not a new PR-cohort study or an exhaustive search for disconfirming cases. In particular, documentation expansion preceded autonomy and the tracking/source churn ratio fell during the loop. Both limit a story in which autonomous coordination alone created the problem. The successful health and restart checks are also real successes; they did not exercise the same outcome as the blocked sign-in journey.

Table 5: Within-case contrasts and their limits, using the existing chronology and measurements.

Contrast	Recorded difference or negative case	What it can and cannot discriminate
Product use, 8–14 versus 15–24 Oct	Intermittent MVP use and same-day feedback versus no completed realistic replacement journey.	Consistent with feedback starvation; migration, environment, workload and models changed at the same time.
Requirements before versus during the loop	Growth and review overhead already existed before autonomous coordination.	Weakens an autonomy-onset explanation; there is no matched small-specification comparison.
Integration artefacts, 8–14 versus 15–24 Oct	Tracking/product-source additions fell from 29.28 to 10.27 while absolute output remained high.	Volume is not a monotonic decay measure; churn does not assess understanding or usability.
Replacement engineering checks versus user task	Health, restart and unauthenticated-request rejection passed; real-user sign-in remained blocked.	Shows the boundary of those checks, not that passing checks were fabricated or that intrinsic code quality declined.
Domain challenge versus backlog execution	Early role agents rejected the five-agent proposal; later sessions delivered the specified issues.	Negative case against inevitable agent compliance; role, task and human interaction differ, so this is not a treatment comparison.

4.3 The backlog and the coordinator

Late on 14 October the backlog manager generated the backlog from the BRD, PRD and ADRs. Many issues carried a label stating that part of the work already existed in the MVP. On




Figure 1: Words appended to the knowledge-base log per day (top) and lexical hedge matches per 1,000 words that day (bottom), from the packaged daily data. Days with no logged words have undefined density and no lower bar. The dashed line marks the coordinator's start on 15 October 2026.

15 October I created the coordinator and, as Section 3.3 describes, hardened it within the day. The log recorded 91 entries that day, against at most 19 on any earlier day. The accepted source-layout ADR made the migration of the MVP's code the first priority; the MVP itself was to be retired.

4.4 The loop at scale

From 15 to 24 October, 183 pull requests were merged, compared with 52 in the nineteen days before. The knowledge-base log grew by 36,755 words between 15 and 22 October, 31,005 of them in the first three days (Figure 1). The share of hedged statements, such as "remains unmet", "not inferred" or "not accepted", rose from 1.2 to 3.8 per thousand words.

The migration succeeded on its own terms. A private deployment built from the new source layout passed health checks, rejected unauthenticated requests and survived restarts. But it held one fictional case, no staff accounts and no model deployment, against the 980 cases, eleven staff identities and five working assistants of the system it replaced. A public entry point was restored through an additional edge service, yet real-user sign-in stayed blocked because the new deployment had neither an application registration nor staff bindings, the very things set up and verified on 12 October. Recovering them became a chain of issues, each with its own research, plans, reviews and corrections. To preserve the hosted CI budget, validation moved to a local gate on 18 October (issue #413). The demonstrator's cloud resources accrued USD 189.94 between 1 and 20 October, with a forecast above the USD 500 ceiling I had set; on 22 October I raised the ceiling to USD 700, deleted a test edge profile and scaled a demo service to zero. The same day, after a mentor raised the economics of AI consumption, the agents produced new BRD and PRD versions and appended a new set of acceptance criteria to fifteen open issues.

A Copilot usage dashboard captured on 24 October showed USD 1,809 of price-list consumption value, 10,229,625,825 tokens and 100,938 requests in the rolling last 28 days. These were account-wide totals across all work, not AMA-only measurements or an invoice. The token total included 10,081,179,684 cached tokens. Surface and model breakdowns described the same total and must not be added together; the requests were not established as premium requests. The

screenshots do not isolate 15–24 October, establish exact window boundaries or support an estimate of the loop's incremental cost.

4.5 Asking for something that runs

On 22 October I asked the loop to prioritise something I could use. A *feedback-first* label, described as prioritising "the bounded usable synthetic demo slice", was applied to the relevant issues, ten of them by 24 October. On 24 October I asked for employee and resident sites to be available as soon as possible, with at most eight items in parallel. These instruction dates and the eight-item cap are my confirmed recollection, not quotations recovered from the pinned log. The agents created the smallest independently runnable resident preview they could design (issue #444): read-only, synthetic and bound to the local machine, with thirteen acceptance criteria. The same day a two-line fix to the rubric scorer arrived with a 78-line evidence record and an explicit, one-time owner exception to interrupt the full local gate (pull request #445). Following Beck's advice to alternate features with consolidation, I also instructed the coordinator to stop at checkpoints, review what had been built, exercise the functionality and refactor. I do not evaluate the outcome of that instruction here.

5 Five candidate mechanisms

I propose five candidate mechanisms consistent with how a loop that merged a pull request every eighty minutes or so left its owner without a usable replacement. Table 6 summarises them; Appendix E sets out a definition, indicators, counter-evidence, rivals and testable implication for each. These are an integrated explanatory synthesis, not five newly discovered phenomena or independently established causal mechanisms.

Table 6: Five candidate mechanisms, case indicators, relevant prior work and proposed early-warning signals. Indicators are not causal tests.

Candidate	Case indicators	Related prior work	Early-warning signal
Specification inflation	BRD ≈37,900 and PRD ≈33,900 words; 192 issues; 17 criteria on one issue and 13 on the smallest preview	Royce; Gall; Brooks; Böckeler; Beck	Specification growth versus human-validated behaviour
Proxy capture	Artefacts made a merge gate; 78-line evidence record for a two-line fix; score 5/5 while sign-in is blocked (release/scope linkage pending); hedge density tripled	Goodhart; Strathern; Beck's genie; ImpossibleBench; METR	Artefacts per behaviour change; scores that disagree with a live demo
Learning evaporation	Lessons not carried in the described briefs; last cited 13 Oct; read path ≈139,000 words	Naur; context studies; multi-agent failure taxonomy	Lessons that exist only as prose; problems solved twice
Process-gate inflation	Full gate on every push; CI minutes rationed; exception for a two-line fix; 18 merges a day delegated	Bainbridge; ironies of generative AI; Murphy; Goldratt	Gate time per change; review minutes per merge
Feedback starvation	Working MVP frozen; replacement unusable after ten days; request for a demo turned into more issues	XP; walking skeleton; tracer bullets; Agile Manifesto; DORA	Time to first human use; age of last usable increment

Read against the working theory of Section 1, they fall into groups (Table 7). The underlying risk is feature accumulation without consolidation: until 24 October the loop had no scheduled cumulative consolidation step, and its one large restructuring, the migration to a new source layout, was planned up front as backlog items rather than done continuously. This does not rule out local refactoring within individual issues. Specification inflation, proxy capture and learning evaporation are forms of the first accelerant, compounding error, in the proposed model:

a misreading, or literal reading, of intent can become context or criteria for the next step. Process-gate inflation and feedback starvation may reflect output exceeding review capacity: gates and caveats coexisted with the absence of a person using the replacement. The case does not estimate either amplification effect.

Table 7: A working theory: an underlying risk and two possible amplifiers, with candidate mechanisms consistent with this case. No rate is estimated.

Driver	What it predicts	In this case
Underlying risk: features accumulate without consolidation	Complexity can grow and quality can decline without counter-work [62, 63]	No scheduled cumulative consolidation until 24 Oct; restructuring planned as backlog items
Accelerant 1: compounding error	Each step builds on earlier misreadings and unneeded complexity [57, 78, 95]	Specification inflation; proxy capture; learning evaporation
Accelerant 2: unreviewable volume	Output exceeds what people can review and test, so decay goes unseen [26, 106]	Process-gate inflation; feedback starvation

5.1 Specification inflation

Interpretation: specification growth outpaced the behaviour validated through product use. By 22 October the BRD had reached version 0.19 and about 37,900 words, with requirement identifiers up to FR-052 and AC-103; the PRD had reached version 0.18 and about 33,900 words, with identifiers up to FR-061 and AC-110. The backlog inherited that scale and grew to 192 issues. Cross-cutting concerns were appended to existing issues rather than sequenced as their own work: a responsible-AI section on 15 October and an AI-consumption section on 22 October. Issue #126, on pilot release gates, ended with seventeen acceptance criteria in three sections. Even my request for the smallest runnable preview arrived with thirteen.

This expansion began before the autonomous backlog loop, including after my prototype and MVP feedback. The requirements agents sought fully specified BRDs and PRDs, named approvers and resolved ownership before building. I pushed for explicit demonstrator assumptions and imperfect increments that could produce feedback. Smaller, iterative requirements documents are a plausible alternative, not an intervention tested in this case.

This is Böckeler's small bug that became sixteen acceptance criteria [20], at the scale of a programme. It is also consistent with what Royce and Gall warned about: a large system specified up front and tested at the end [38, 87]. Brooks explains why more text does not help: the essential difficulty lies in the conceptual construct, and writing it down in more places does not reduce it [22]. The benchmark evidence points the same way: agents given only a requirements document lose global coherence [30]. Beck's metaphor fits: every feature, and every acceptance criterion, burns options [14, 16]. The early-warning signal is the ratio of specification growth to behaviour a human has validated in the same period. Here the denominator was close to zero.

5.2 Proxy capture

In this case, artefacts made into gates appeared to displace outcomes. I interpret three patterns this way.

Merged pull requests are a weak proxy for delivered value. Murphy-Hill et al. report roughly 24% more merges among adopters in Microsoft's rollout, while explicitly distinguishing merges from value [75]. Peralta et al. studied 9,799 human-reviewed agent pull requests; in their manually inspected samples, only 35.7% of rejections reflected clear agent failures and 15.4% of merges required explicit reviewer involvement [85]. AIDev shows the scale of this measurement

problem: 932,791 agent-authored pull requests from five agents across 116,211 repositories, not a count of delivered outcomes [64].

Process. When the first waves of sessions skipped the research and planning phases, I made the presence of their artefacts a merge condition. From then on every pull request carried research, plan, change and review records; the artefacts were guaranteed, the thinking they were meant to evidence was not. Pull request #445 changed two lines of behaviour and added a 78-line evidence record that reports its own artefact completion as 100%. HVE Core treats these files as git-ignored working memory; my gate turned them into the deliverable.

In the first-parent integration view, tracking-artefact additions were 10.27 times product-source additions during the loop, compared with 29.28 before it (`anc/repo_history_metrics.out.txt`). This supports concern about artefact volume, not a claim that the ratio rose when autonomy began. Churn alone does not establish code decay.

Evaluation. The rubric scorer, a language model reading the repository, rated implementation completeness at five out of five, "all required capabilities working end to end", citing a README and a check script, at a time when I could not sign in to the replacement. The score's release and capability scope have not yet been linked to that deployment and journey (Section 3.6); this is chronological coexistence, not a verified same-release contradiction. Gamma's remark about tests applies to judges too: put a model in the evaluation and the evaluation becomes stochastic [39], and a judge that reads the repository is scoring the text that agents are best at producing.

Honesty. I had instructed the agents never to fabricate approvals or overstate evidence. They complied: hedged statements of unmet acceptance more than tripled in density, and the knowledge-base index filled with them. Issue #349 records that a browser redirect "is not successful sign-in". The agents were right, and still nobody could sign in. Honest boundary statements became the output.

Goodhart and Strathern predict the first two levels [43, 97]; Beck observed agents deleting tests to finish [79], and ImpossibleBench measured it [107]. The METR study adds the human side: the feeling of progress is an unreliable instrument [17]. The early-warning signals are the ratio of evidence artefacts to behaviour changes, the share of merged pull requests that change what a user can do, hedge density, and any divergence between automated scores and a live demo.

5.3 Learning evaporation

Some recorded lessons appeared to fall off the loop's read path, while important design decisions survived. Maintaining the structured log and memory became difficult as the record grew. I observed drift, not a complete loss of the project's theory. Before the loop, my use of the MVP produced concrete lessons: the simplicity requirements, a deliberately public development profile for throwaway stacks, and the callback, role and staff-binding steps that made sign-in work. All were recorded, in the PRD, in a simplicity review and in infrastructure runbooks. The coordinator's briefs carried each issue's text, acceptance criteria and the repository conventions, but not those lessons. The log cites the simplicity requirements for the last time on 13 October; the development profile appears only on 8 October. The migrated deployment lacked the registration and staff bindings established on 12 October, and sign-in was blocked.

The read path grew. The knowledge-base index, which every agent is told to read first, accumulated 1,069 words of issue-specific status notes ahead of its first instruction. The index, the log, the BRD and the PRD, the documents that define the project's state and intent, total about 139,000 words, or roughly 180,000 tokens at a typical ratio of 1.3 tokens per word. Long contexts can reduce reliable retrieval even when the material fits in the context window [48, 65]; the case does not measure any session's effective attention capacity.

Naur explains why recording was not enough. A program's theory lives in the people who build it, and a second team with full documentation can still destroy a design's simplicity [76]. In an agent loop, every session may face an analogous reconstruction problem; this is an analogy,

not a measured loss of understanding. Advice to share full context between agents [104] and the failure modes catalogued for multi-agent systems [23] describe the same risk. HVE Core's choice to carry context in files on disk is necessary but not sufficient: the files must be on the read path, short enough to read and, ideally, executable. The early-warning signals are lessons that exist only as prose, a read path that grows faster than the code, and problems that have to be solved twice.

Pavlenko et al.'s World Model offers a different design: preserve raw evidence, derive rebuildable views and retrieve compact, task-specific context with provenance and access controls. Updates are reviewed, and measured outcomes feed later decisions [84]. This distinguishes storing lessons from making them usable in the next decision; a small read path need not mean discarding history. It is an architectural alternative to an accumulating log, not a tested remedy for learning evaporation in this case.

5.4 Process-gate inflation

Interpretation: repeated gates appeared disproportionately burdensome; comparative effort was not measured. Each new gate required execution and review. Within ten days the coordinator required, for every issue, the full RPI loop, a complete local gate before every push and after every correction or rebase, independent review, up to two correction cycles, board updates and evidence-based ticking of acceptance criteria. Hosted CI minutes had to be rationed, the full gate had to be interrupted by explicit exception for a two-line fix, and paid cloud validation stayed blocked even after the cost ceiling was raised.

My attention felt more constrained than compute, but I did not measure their relative scarcity. I could not review eighteen merged pull requests a day in depth, and delegated merging to the coordinator. I still answered approvals and technical blockers, but stopped getting feedback from using a replacement product. RPI critiques and reviews addressed the current issue rather than the cumulative system; there was no regular phase for reflective consolidation or generalisation across completed issues. This is Bainbridge's irony in miniature [5]: the automation took the part of the work I learned most from, using the product, and left me the part people are worst at, monitoring a stream of plausible, well-documented changes. It matches the shift from producing to evaluating reported for generative AI [94], the delegation demands it creates [98]. Higher confidence in AI was associated with reduced self-reported critical scrutiny in the cited study [61], not established as its cause. Murphy's diagnosis is a plausible interpretation: throughput increased while the path to a usable outcome remained blocked [42, 74]. The bottleneck itself was not instrumented. Martin's argument for executable discipline [69] suggests gates that check product behaviour rather than infer it from paperwork. The early-warning signals are gate time per change, human review minutes per merged pull request, work in progress, and cost per merged pull request compared with cost per accepted outcome.

5.5 Feedback starvation

Candidate mechanism: insufficient independent, outcome-level feedback despite abundant artefact-level validation. This differs from merely having few tests, a long feedback delay or missing context: many checks can pass while none disconfirms the claim that the intended user journey works. Independence here means evidence obtained by exercising the outcome rather than rereading its completion record; it need not imply a different model. The loop prioritised completing the specified plan rather than shortening the path to such feedback. This is my proposed central mechanism, not an isolated cause. Nothing in the coordinator kept a usable system alive: no invariant said that after every merge I must still be able to sign in and do my work. Done meant artefacts, criteria and gates. In the MVP week the feedback loop included my intermittent use, with some changes made the same day. From 15 October the first priority was restructuring code, the working MVP was frozen, and its replacement had not become usable




Figure 2: Hypothesised reinforcing relationships, not estimated causal links. Context overload is unmeasured. The proposed human-checkpoint intervention differs from the consolidation package tested in Section 7.

by the time of the case cut-off. When I finally asked for something that runs, the request was absorbed by the same machinery: a label, new issues, thirteen acceptance criteria and the full set of gates.

Every older practice I cited in Section 2.6 exists to prevent exactly this: short releases and test-first development [8, 9], the walking skeleton and tracer bullets [25, 50], and working software over comprehensive documentation [2]. Beck's warning that fully agentic work without feedback goes off the rails [16], DORA's emphasis on small batches and user focus [32] and Murphy's list of real bottlenecks, which includes missing feedback [74], describe the same failure. The early-warning signals are the time from the start of a cycle to the first human use of a running increment, and the age of the last increment a human has verified as usable. At the time of writing the latter was at least ten days.

5.6 A proposed reinforcing relationship

I interpret the mechanisms as a possible reinforcing loop (Figure 2). In this case a large specification accompanied a large backlog and parallel sessions. Artefact-based gates generated more documents; some recorded lessons were absent from later briefs; regressions were not exposed through routine product-use feedback. I responded to gaps with more rules, criteria and gates. That sequence is consistent with reinforcement, but does not establish each causal link. I propose a running increment and a human checkpoint as conditions of every cycle, to test whether they interrupt it.

5.7 Case validity and rival explanations

The five categories are not independent causes identified by these data. The same missing identity and staff bindings can indicate deferred migration work, incomplete deployment acceptance or a lost lesson. Discriminating them requires the deployment comparison and actual session-input trace identified in Table 1, not another count of documents or citations. Similarly, a growing read path does not demonstrate context overflow, and an expensive gate is not necessarily a

disproportionate gate. Per-change gate time, avoided defects and human effort were not measured.

The source-layout migration, owner-selected priorities and delegated merging changed alongside coordination. Scope additions, budget constraints, model/tool changes and deployment conditions also differ between periods. These are direct rivals to an autonomy-only account. Tables 12 and 13 in Appendix D retain the full register, separating recorded circumstances from plausible but untested alternatives. External-environment research motivates considering configuration effects, not diagnosing this case from another setting [19].

Construct validity is limited by whitespace counts, lexical indicators and selectively reviewed records. Appropriate caution can raise hedge density; missing references do not prove missing knowledge. As coordinator designer, participant and analyst, I selected the episodes and may favour a coherent retrospective explanation. AI synthesis is not an independent observer. Public records support recomputation but not independent corroboration of every statement. The single fictional-domain capstone and purposively selected external examples do not establish prevalence or general causal effects. The proposed experiment has separate identification limits in Section 7.6.

6 Consolidation hypothesis and harness

The observed operational failure and the prospective hypothesis are distinct. Missing deployment identity and staff bindings are concrete obstacles to sign-in; structural code consolidation would not necessarily restore either. Recovery of that journey requires configuration and end-to-end verification. Consolidation is worth testing for a different reason: repeated feature work may make later changes harder, even when deployment dependencies are correct. The experiment probes that possibility through retained tests and CR1; it does not claim that consolidation would have prevented this episode.

The idea is already practised. OpenAI describes replacing weekly manual clean-ups with recurring background agents that open small refactoring pull requests, alongside a documentation-gardening agent [77]. Anthropic asks each session to leave a clean state and update a progress file [3]. Neither account reports a controlled comparison of feature-only delivery with consolidation between feature steps. Darwin's continuous optimisation is a further precedent for automated improvement, but its performance evaluations do not isolate that intervention or test an unforeseen change request [84] (Section 2.4). RefactorBench already evaluates refactoring agents [40]; the narrower hypothesis concerns retained behaviour and later adaptation during repeated feature additions.

The proposed consolidation harness tests a bounded part of reflective correction. The pause is scheduled by the harness, not chosen by the agent; the agent is not authorised to reject features or redirect the product. After every feature the loop stops, and an agent:

1. runs the tests and a metrics script that lists complexity hotspots, duplicated blocks and lint warnings;
2. reviews the last feature's diff and the hotspots against a short checklist (duplication, long or complex functions, unclear names, dead code, rules from one feature leaking into another, tests that check implementation rather than behaviour);
3. refactors in small, behaviour-preserving steps, each applied through `test && commit || revert` [10], so that every change either keeps all tests green or disappears;
4. may add tests that pin current behaviour, but may not change or delete the example tests that define the features;
5. rewrites a design note of at most 300 words that says where each rule lives and what debt remains, replacing the previous one rather than appending to it;
6. stops when a quality budget is met or its time budget runs out.

Only then may the next feature start. Appendix G gives the prompt. The intervention combines refactoring, additional tests and a design-oriented note; it is not a pure refactoring treatment.

The hypothesis draws on Beck's alternation of features and futures [14, 16] and *Tidy First?* [12]. It is not free, and may not work. Agent refactorings can be incorrect or superficial [40]; even human refactoring benefits can be difficult to attribute [7, 55]. Test-commit-or-revert protects only behaviour represented by its tests, not every intended contract [67]. Section 7 specifies how the package will be evaluated.

7 Testing the harness: an experiment protocol

The proposed contribution is a controlled comparison of scheduled post-feature consolidation, not the invention of agent clean-up or objective-guided optimisation [84]. It tests whether an agent can perform a bounded part of reflective correction, rather than whether another agent can autonomously steer the whole development process. Lulla et al.'s registered-report protocol, which treats agent configurations as experimental arms, provides a model for specifying the comparison before observing results [66]. I designed the experiment with HVE Core's Experiment Designer as a Minimum Viable Experiment [51], informed by empirical-study guidance [6, 103]. The choices below incorporate my decisions of 25 October 2026.

Study status and provenance. No study results are reported. I stopped execution and reported tagging the private kit; the exact snapshot remains unverified and registration pending. The four-runs-per-arm first pass is exploratory, not seven confirmatory tests. This revision preserves the arms, budgets, sample and provisional thresholds without amending the private tag. Earlier smoke, pilot and other pre-registration runs retain their original labels and timestamps and are excluded from the fresh first pass. The record must disclose earlier data seen and design changes; later registration cannot cover those runs retrospectively. Packaged ancillary notes are earlier proposals, not the tagged protocol. An authorised archive must retain the reconciled protocol, suite, prompts, configuration and analysis snapshot. Section 7.7 groups the outstanding decisions before fresh runs. The related work reviewed here does not isolate consolidation steps interleaved between successive feature additions. Darwin evaluates optimisation against measurable objectives [84]; SlopCodeBench shows that quality instructions alone shift where agents start but not how fast they degrade [78]. The harness tests a scheduled structural intervention and subsequent changeability instead.

7.1 Protocol at a glance

Table 8 makes the intended comparisons and their limits explicit. This revision preserves the reported tagged design rather than silently replacing it with a repair-matched control, an equal-total-budget study or a different primary endpoint. Exact agreement with the private tag has not yet been verified.

Table 8: Summary of the exploratory, registration-pending first-pass protocol. Planned safeguards are not completed checks.

Item	Design and interpretation boundary
Study unit	One complete S1 repository–feature-sequence trajectory; four independent runs per arm. Feature steps and CR1 within a run are not new independent replicates.
Allocation	Planned randomised interleaving of arm runs on the same machine; one fixed ten-feature suite, not random assignment of repositories or scenarios.
B–A estimand	Effect of adding the complete consolidation package at equal feature-step budgets, with up to 50% extra agent time. Not an equal-total-budget or refactoring-only effect.
B–C estimand	Complete consolidation versus read-only review at equal post-feature time ceilings. Editing permission, added tests and DESIGN versus REVIEW notes also differ.
Retained priority	H1: final cumulative hidden pass rate, 10-point estimated gain with 95% interval above zero for validation. H6 remains the specific changeability hypothesis, not a newly promoted primary outcome.
Changeability	CR1 success and cost under 45 minutes; success also preserves every feature test passing before CR1. H6 requires a 20-point success gain or 25% cost saving at no lower success, under its interval rules.
Budgets	30 minutes per feature; 15 per B/C post-feature step; 45 for CR1. Credits and monetary cost remain distinct; final calibrated caps need checking.
Analysis	Exploratory run-level estimates; only four runs per arm, no completed power simulation or family-wide multiplicity control. Seven provisional rules are retained, not confirmatory verdicts.
Integrity	Fresh sessions, fixed prompts/tests/configuration and checksum checks are planned. Local execution does not guarantee hidden-test or reference inaccessibility; independent suite/access checks remain pending.
Human help	Primary runs unassisted; HIR/IDR descriptive. Corrective help is a retained, labelled deviation, not grounds for a replacement run. Telemetry coverage and annotation reliability remain unverified.
Status	No results; registration, a documented framing amendment and exact tagged provenance pending. Earlier runs remain excluded from the fresh first pass.

7.2 Hypotheses

Table 9 lists provisional hypotheses in priority order. Each follows the Experiment Designer's form: what we believe, how we will test it, and the measurable outcome that would show it right or wrong. The primary consumption measure stated here is AI credits; H5/H6 cost comparisons must be reconciled to that measure in the tagged analysis before registration. The percentage thresholds are unchanged. "Pays for itself" does not establish monetary payback: tokens, elapsed time, credits and currency are reported separately, and no verified billing conversion is assumed.

Table 9: Hypotheses, compared after the final feature unless stated. A is feature-only delivery, B adds the consolidation harness, C adds a read-only review of equal budget. These provisional rules require prospective reconciliation; they are not confirmatory verdicts. Wrong means interval evidence rules out the minimum useful effect, not no significance; other evaluable outcomes are inconclusive.

ID	I propose	Right when	Wrong when
H1	The harness improves final functional coverage	B's cumulative hidden pass rate is at least 10 points higher, 95% interval lower bound above zero	whole interval below 5 points
H6	Consolidated code absorbs an unplanned change better	Change-request success at least 20 points higher, or cost at least 25% lower at no lower success	Whole intervals rule out both 20-point gain and 25% saving
H2	Errors compound without consolidation	Open regressions trend upward in A; B has at least 50% fewer	Whole intervals rule out A's upward trend or 50% reduction
H3	Internal quality decays without consolidation	Positive slopes in A on three of four metrics; B's slope at most half of A's	Intervals rule out the required slope pattern
H5	The harness bounds overhead and lowers late-feature cost	B's total cost at most 125% of A's and B cheaper per feature in the last third	Whole cost interval above 150%; late-saving interval at or below zero
H4	The harness leaves less to review	B has at least 20% fewer non-test lines; reviewers as accurate in 20% less time	Whole reduction intervals below 10% for size and time
H7	The consolidation package beats review-only	B beats C by at least half of the B–A gap	Intervals rule out the half-gap benefit

Unresolved H4 and H7 definitions. H4 needs a fixed accuracy scoring rule and a justified non-inferiority margin, together with an interval-based criterion for excluding accuracy losses beyond that margin. A nonsignificant accuracy difference does not establish "as accurate". H7 needs a named endpoint, beneficial direction, analysis scale and interval method for the dependent B–C and B–A contrasts. Its half-gap rule also needs a prospective policy for zero or negative B–A gaps: a zero or negative threshold cannot by itself establish benefit over review-only. Until those choices are documented, H4's joint claim and H7's half-gap claim are not evaluable under their stated rules; component estimates can still be reported exploratorily. This revision does not invent margins, endpoints or replacement thresholds.

7.3 Design

Arms. Arm A delivers features one after another. Arm B runs the consolidation harness after every feature, with half the time budget of a feature step. B therefore has up to 50% more agent time per feature than A; the comparison is not time-matched. H5 compares their costs directly. I include arm C, which holds that extra time constant without refactoring and replaces consolidation with a read-only review of equal budget, to compare the complete consolidation package with review-only. B may add behaviour-pinning tests and writes an architectural `DESIGN.md`; C cannot change tests and writes issue-oriented `REVIEW.md`. Subsequent sessions

read those different notes, so this comparison cannot isolate refactoring. Everything outside the post-feature intervention is identical: model and version, agent runtime, feature prompts, starting skeleton, tools and per-feature budgets.

Estimands and control limits. B–A estimates the incremental consolidation package at a fixed feature budget, including extra time and compute. B–C compares packages at equal post-feature time ceilings, not necessarily equal realised tokens, credits or elapsed time. C cannot repair detected defects, add tests or write B's design note. Any difference can therefore reflect permission to act, test additions, note content or their interactions, not structural consolidation alone. Review-only is not an active repair control. There is no equal-total-budget comparison, and this study cannot say what consolidation would displace under a fixed total budget. Those limitations constrain the causal interpretation even if allocation and the planned checks are implemented correctly.

The additional agent is a distinct session with a different responsibility, not a different pinned model or an independent source of truth. Its value must be demonstrated by behavioural and changeability outcomes, not inferred from the existence of another review role.

Runtime and budgets. I selected `claude-sonnet-5.5`, medium reasoning effort and Copilot CLI 1.0.103, with automatic updates disabled. The wall-clock limits are 30 minutes per feature, 15 per consolidation or review, and 45 for CR1. The pilot limit is 300 AI credits per session; any pilot-informed adjustment must be frozen and included in the registered configuration before the fresh study runs. The total pilot-and-first-pass ceiling is 2,500 AI credits, raised from an initial 1,000-credit proposal. I also stated a $500 monetary budget. Credit consumption and currency cost are not interchangeable without a verified billing conversion.

Suites. Suite S1 is a ten-feature retrofit case workbench drawn from the case domain, whose features deliberately interact: lifecycle, handoffs, returns, safety holds, resident consent, appointments with an escalation rule, role-based visibility, deterministic ranking and a hash-chained audit trail. The selected study uses all ten features and the full CR1, including the ranking and export prerequisites in F9–F10. Each feature has visible example tests and hidden acceptance tests, including interactions with earlier features. Tests and reference solutions are intended to remain outside the agent's working repository. S2 is a library-lending suite reserved for a separately authorised main study; benchmark adaptation is deferred.

Isolation. I selected local execution rather than containers for the analysed runs. The CLI access rules and separation of working directories provide a weaker boundary than container isolation. They do not establish that hidden tests, references or outside resources are unreachable. Residual access risk limits validity and must accompany any results; an absence of leak flags is not proof of isolation. CR1 is intended to remain unavailable to feature, consolidation and review sessions until its dedicated change-request session. The tagged packaging and actual non-exposure of its request text, as well as its tests, remain to be verified. "Unforeseen" describes that intended information boundary, not an established property of local execution.

Procedure and information flow. The intended sequence below describes the reported design, not verified private-runner behaviour. Repository context is passed between fresh sessions; the evaluator is outside the working repository. Access separation and result visibility still require verification.

1. A feature session receives its fixed prompt, visible example tests and the repository left by the previous step, including the arm-specific note. It may commit only when the visible tests pass.

2. If no green increment is committed, the runner resets it, removes that feature's example tests and records the feature as missing. Hidden tests for that feature remain in the cumulative denominator. Continuation when later features depend on it is an unresolved runner-policy decision.

3. The external evaluator records cumulative hidden-test results and code metrics after the step. Whether any score, failure message, test identifier or report becomes visible to subsequent

agent sessions is unresolved; hidden test files being outside the repository does not settle this information boundary.

4. In B or C the assigned consolidation or review session precedes the next feature, with another external measurement afterwards. Whether it runs after a failed feature is unresolved. A has no post-feature session.

5. After the final scheduled post-feature step, preserve H1's end state; then start the dedicated CR1 session with the previously withheld request and its fixed budget. Score change success against the pre-CR1 passing tests.

All unresolved branches belong in the frozen runner and divergence rules before fresh runs, not in retrospective choices after inspecting outcomes. A pilot calibrates budgets with one run per arm over ten features, without CR1. The selected first pass uses S1, arms A, B and C, with four independent runs per arm, ten features and CR1. This is the exploratory first pass, not data to pool with earlier started runs. An optional main study would use S1 and S2, five runs per arm and ten features, under a separate prospective plan and authorisation. With three runs per arm the exact two-sided Mann–Whitney floor is $2/C(6,3) = 0.10$, so it cannot reach $p < 0.10$; four runs reach 0.029 and five reach 0.008. These are attainability bounds, not a power analysis. The selected first pass has 120 feature, 40 consolidation, 40 review and twelve change-request sessions: 212 sessions and an upper bound of 89 agent-hours. The pilot adds fifty sessions and twenty agent-hours, making 262 sessions and 109 agent-hours combined. These bounds exclude measurement and scheduling overhead and do not establish affordability under the credit ceiling. Sample sizes and stopping rules must be documented prospectively before the fresh runs; sample sizes will not be increased in response to observed effects.

End state and change request. H1's end state is after the last feature's post-feature step (a no-op in A), before the change request. Change-request success requires all its hidden tests to pass and no feature test that passed at that end state to fail afterwards.

Endpoint hierarchy. H1 retains first priority for working behaviour; H6 is the direct operational probe of future changeability. Passing H1 or improving complexity without a corresponding H6 outcome would not establish preservation of future options. One fixed change request supplies narrow task-specific evidence, not general maintainability. This revision does not retrospectively change that priority or its thresholds after earlier runs. Final cumulative pass rate combines feature acquisition, retention and repair; it is not a retention-only endpoint. The planned regression histories must distinguish tests that never passed from previously passing tests later lost or recovered. H2 provides the retention-specific hypothesis; any additional descriptive breakdown must be fixed in the reconciled analysis plan before fresh runs, without replacing H1 or its thresholds.

Measures. Cumulative hidden pass rate, open regressions and how long they survive; mean cyclomatic complexity, the share of functions above complexity 10, duplicated lines and lint warnings per thousand lines; non-test lines, diff lines per step and documentation words generated; AI credits as the primary consumption measure, with tokens and elapsed time secondary; change-request success and cost; and, for S1, a blinded comprehension task in which reviewers answer five fixed questions about each final code base. Test integrity, through checksums of the example tests and counts of tests and assertions, is checked after every step. The planned code-metric settings are the runbook's isolated lint rules E, F, W, C90, B and SIM, duplication detection at fifty tokens and five lines, and complexity measured by lizard. Tool versions and settings must be fixed in the registration. I plan to invite two independent comprehension reviewers; their agreement and the assessment remain pending. Code size and structural metrics must be interpreted alongside functional coverage: an incomplete implementation can be small without being better. For H2, a newly introduced failing test alone is not an observed loss of previously passing behaviour. Section 7.4 proposes regression eligibility, measurement points and reporting denominators for prospective reconciliation with the private kit.

Intervention measures in prior work. HG-DAgger distinguishes human takeover and return of control; ThriftyDAgger separates intervention counts, human actions and supervisor switching costs [49, 54]. They motivate separating incidence and effort, not coding-harness effectiveness. Here HIR is cycle-level incidence, not events per hour or a human-control time share. Failed cycles remain included, and event counts and active human minutes are separate measures; fewer events need not mean less human work or monitoring burden.

Human intervention rate (HIR). As a secondary measure of harness quality, I record observed HIR: the proportion of attempted feature cycles receiving unplanned corrective human help. A cycle includes the feature and its assigned post-feature step, so B's additional sessions do not enlarge its denominator. Failed cycles remain included; repeated interventions in a cycle count once for the rate, with event counts recorded separately. For run r, let n_r be the number of attempted feature cycles and h_{rj} the number of qualifying corrective-help events in cycle j. Then

$$\mathrm{HIR}_r = \frac{N_{\text{assisted},r}}{n_r} = \frac{1}{n_r} \sum_{j=1}^{n_r} \mathbf{1}\{h_{rj} > 0\}. \tag{1}$$

The indicator is one when the condition holds and zero otherwise; multiplying Equation 1 by 100 gives a percentage. By contrast, $\sum_j h_{rj}/n_r$ is events per cycle and can exceed one. I report event counts and active human minutes separately so that a brief clarification and a long repair do not appear equivalent merely because both affect one cycle. These are incidence and effort measures, not interchangeable estimates of total supervisory workload. If no cycle is attempted, the rate is undefined, not zero.

Primary runs receive no task-specific human coaching or code/test repair. I therefore also record an intervention-demand rate with the same denominator: cycles containing an explicit request for such help or a block requiring manual corrective action. With $d_{rj} = 1$ for such a cycle and zero otherwise,

$$\mathrm{IDR}_r = \frac{1}{n_r} \sum_{j=1}^{n_r} d_{rj}. \tag{2}$$

A request need not result in assistance, and an unsolicited human correction need not follow a recorded request; I code the two separately. Zero observed HIR under this policy is not evidence of autonomy. A timeout or automatic reset alone does not establish demand.

The intended sources are the session telemetry and retained logs. I plan to use Cowork to extract requests, blocks and actual interventions, then personally check classifications against source records and resolve ambiguous cases. The extraction must link each event to its cycle, phase, reason, action and active human minutes, using rules fixed before fresh runs. Telemetry coverage of human-help requests and corrective actions, including actions outside the CLI, has not yet been verified. Missing records cannot be interpreted as zero interventions; incomplete coverage makes the affected measure not evaluable. Routine launches, planned evaluation, required approvals and safety stops are recorded separately, not treated as corrective rescue. Any corrective help supplied is a protocol deviation; I retain the run, label it assisted and report its outcomes separately from unassisted estimates. Such deviations do not trigger replacement runs and may leave the unassisted comparison not evaluable at its predeclared sample size. I report change-request interventions separately, alongside completion, missing features, early termination and unattempted cycles. Lower HIR alone is not better: it must not reward silent failure or discourage necessary human judgement.

Author checking of an automated extraction is not independent annotation. No inter-rater agreement, stable severity coding or construct-validation result is available; these rates remain descriptive and their annotation reliability must not be inferred from a complete-looking event table.

7.4 Measuring decay prospectively

Proposed measurement amendment. Feature-driven decay means deterioration of previously achieved behaviour or increasing structural/change burden as features accumulate. The case motivates this hypothesis from a small, confounded observational base; it does not establish the effect. The proposal below operationalises the existing H2/H3 questions without replacing H1, changing their numerical thresholds or claiming that the private tag already contains these definitions. The author must reconcile and version the measurement amendment before fresh runs.

Follow previously working contracts, not only final scores. Freeze a hidden contract panel and a feature-by-test eligibility map before execution. Distinguish invariants from behaviour intentionally changed by a later feature; expected changes need prospectively versioned oracles, not post-hoc removal of failing tests. Save the state immediately after feature t (F_t) and after its consolidation/review step (P_t); in A, $P_t = F_t$. Evaluate the same eligible contracts at both checkpoints and keep evaluator outputs outside agent context under the agreed information policy.

For run r, let $\mathcal{R}_{r,t}$ contain eligible unchanged contracts that passed at least one earlier end-of-cycle checkpoint P_u, $u < t$. Let $S^p_{r,t}(q)$ be the recorded binary result for contract q at phase $p \in \{F, P\}$. Proposed open-loss count and density are

$$L^p_{r,t} = \sum_{q \in \mathcal{R}_{r,t}} \mathbf{1}\{S^p_{r,t}(q) = 0\}, \qquad d^p_{r,t} = \frac{L^p_{r,t}}{|\mathcal{R}_{r,t}|}. \tag{3}$$

The density is undefined when the risk set is empty, not zero decay. A test that never passed is an acquisition failure, not a regression. Recovery removes an open loss but not its recorded episode: retain onset, recovery, recurrence and duration in feature cycles. Also distinguish a newly introduced failure from a loss still open from an earlier cycle. Report F_t and P_t separately so successful repair does not hide feature-step damage. Log rejected/reset attempts separately from losses in the retained repository state. Separately flag a newly delivered contract that passes F_t but fails P_t: this is same-cycle loss during the post-feature step, even though it is not yet in the inherited cohort. Unobserved results remain missing, not passes or failures; apply the prospectively fixed outage and missing-measurement policy.

The proposed H2 reading uses $L^P_{r,t}$ for the longitudinal open-regression series and $L^P_{r,10}$ for its final count comparison. Keep densities and accumulated test-cycle losses as descriptive companions, not substitute thresholds. Show the eligible, ever-passed, never-passed and currently passing counts alongside every loss series and H1. Eligibility depends on what an arm managed to acquire: fewer at-risk contracts must not make an incomplete arm look healthier. These are test-weighted measures; retain feature/requirement groupings so many assertions for one feature do not masquerade as many independent capabilities. Runs, not tests or checkpoints, remain the units for uncertainty. A zero A-arm loss count provides no denominator for a claimed relative reduction; report absolute counts and differences instead. An upward count can reflect more contracts at risk rather than greater decay risk, so count and density trajectories must be interpreted together.

Separate structural deterioration from legitimate growth. Keep the four H3 metrics and frozen settings at every checkpoint, but also measure the independently checked cumulative reference implementation for each feature stage. Report raw trajectories and agent–reference gaps in the original metric units; do not combine them into an unvalidated decay score. Compare only compatible feature coverage, disclose omitted or missing features and retain all run outcomes. More code or complexity required by later features is not itself decay. H3's existing raw-slope rule remains provisional; the reference-gap analysis is a proposed sensitivity analysis, not a silent

replacement endpoint. If the reference or metric checks fail, label the affected interpretation unavailable.

Distinguish changeability from changeability decay. Final CR1 success and cost compare the arms' ability to change their final systems; one final task cannot establish that changeability declined over time. A separate proposed extension would run the same withheld core-contract change on disposable early and late snapshots, after that contract exists in both. Use fresh sessions, fixed budgets and evaluator rules, randomised execution order and no feedback or probe changes returned to the main trajectories. CR1 itself cannot simply move earlier because it requires F9–F10. This extension needs a fixed probe, extra sessions and a separately approved budget and analysis amendment; it is not included in the stated 212-session first pass.

Make the hypothesis capable of failing. First repeat oracle checks on unchanged snapshots and reference versions to expose flakiness or environment faults, using fixed repeat and failure rules. Within a trajectory, the paired checkpoints locate when losses appear and whether they are repaired; the arm contrasts test the consolidation package, not feature accumulation versus a randomised no-feature control. Stable retention and no structural excess would show no observed decay under this workload, not prove decay impossible. Better H1 without lower losses or structural deterioration supports improved implementation, not decay control. Growth matching the reference favours task complexity over deterioration; oracle instability leaves the affected decay measurement unresolved. Report these rival patterns, null outcomes and uncertainty rather than treating every final shortfall as support for the subtitle.

7.5 Analysis and bias controls

The proposed analysis estimates the difference in final cumulative pass rate with bootstrap intervals that resample runs within arm. S1 trends are estimated with mixed-effects models that include an arm-by-feature-index interaction and run as a random intercept. A later multi-suite study would treat suite as a fixed effect and resample within suite and arm. Because code generation is not deterministic, even at temperature zero [81], every condition is run several times and intervals are reported rather than single values. The S1 first pass has a fixed sample size and excludes all earlier runs. Intervals do not trigger extra runs or pooling; any extension needs a separate prospective plan. Under the retained provisional H1 rule, support requires a gain of at least 10 percentage points and a 95% interval wholly above zero; invalidation requires its upper bound to be below 5 points. All other evaluable H1 outcomes are inconclusive. For the other evaluable hypotheses, the provisional support rule requires the estimate to meet its stated threshold and the 95% interval for the benefit to exclude zero in the beneficial direction. Invalidation requires the whole interval to fall short of the stated minimum effect of interest, applying the joint or alternative conditions in Table 9; absence of significance is not invalidation. For H5 I assess headroom below the 150% cost ceiling and late-feature savings, while retaining the 125% validation threshold. An interval spanning zero, without ruling out a useful effect, is inconclusive. The planned controls are randomised interleaving of arms on the same machine; frozen hidden tests, metrics and analysis before fresh registered runs; exclusion of pilot data; blinded comprehension assessment; reporting of every run; and a divergence log. Independent suite review, verified access boundaries and the final analysis checks are still pending, not completed safeguards. The first pass will report estimates, intervals, deviations and non-estimable quantities, not confirmatory validation or go/no-go verdicts. Any comparison with the provisional thresholds will be labelled exploratory.

HIR is descriptive, with no new hypothesis threshold or adoption gate. I report observed and demand rates per run, human minutes and the B–A demand-rate difference with a 95% interval, resampling whole runs within suite and arm. The rates accompany correctness and cost, rather than replacing them.

7.6 Identification and precision limits

Four trajectories per arm give twelve independent run clusters, not 120 independent feature observations or twelve independent change scenarios. Bootstrap resampling cannot create additional independent information. Binary CR1 success is especially coarse at this sample size, and mixed-effects slopes may be unstable or unidentifiable. No simulation-based power or interval-coverage analysis has been completed. The rank-test attainability calculation above does not establish adequate power. Model convergence, boundary estimates and non-estimable quantities must be visible, not converted into precise-looking verdicts. Before fresh runs, the analysis plan must fix interval methods for binary CR1 risk differences and conditional cost comparisons, including how failures and zero-success arms enter each estimand. It must also specify diagnostics and fallback or not-estimable rules for bootstrap intervals and longitudinal models. No method is selected merely because it produces a finite or favourable interval.

The seven hypotheses retain their stated interval-based rules, but no family-wise error or false-discovery control is specified. Nominal 95% intervals are pointwise, not a simultaneous guarantee across hypotheses, metrics and contrasts. The reported priority order is not itself a complete confirmatory testing hierarchy. The first pass is therefore exploratory. A later confirmatory study would need a prospectively fixed primary contrast, endpoint hierarchy, multiplicity policy and precision justification before new data collection; these cannot be repaired by labelling seven pointwise intervals confirmatory after observing them.

The reset and missing-feature rule is specified, but the exact tagged policy for external-service outages, infrastructure failures, retries and incomplete measurements remains to be verified. These events must be distinguished from agent task failure without selective post-hoc exclusions. Run disposition, missingness and deviations require prospective rules and traceable reporting. The planned unassisted policy does not prove autonomy when requests or manual actions are incompletely observed.

Finally, intended hidden-test separation, version pinning and blinded review are not completed controls. The local access boundary is weak, a provider service can change, and note content can disclose treatment to a comprehension reviewer. Actual access probes, evaluator separation, blinding effectiveness and the fixed questions/tool permissions remain to be checked. The paper therefore offers an exploratory package comparison with explicit limits. The package-level identification limits are stated in the design above.

The protocol uses one proprietary model and no open-weights baseline. This limits reproducibility and transfer to other models; pinning the exposed version does not freeze a provider's service [6].

7.7 Pre-run decisions and status

Table 10 is an unresolved decision record, not evidence of implemented safeguards or permission to change the tagged study silently. Each decision needs an author-approved, versioned resolution before the affected fresh run or assessment. Unresolved claims remain not evaluable.

Table 10: Outstanding pre-run decisions. Existing arms, thresholds and budgets are not changed by this record.

Boundary	Resolution and evidence required
Provenance	Record the private tag/SHA, checksums, framing amendment, earlier data seen, registration and authorised archive; preserve prior-run labels.
Evaluator information	Review the suite/reference and actual access probes; fix whether hidden scores, messages, identifiers or reports reach agents.
Missing features	Specify B/C after a failed feature, prerequisite-dependent continuation, later recovery and test eligibility; retain missing features in the stated cumulative denominator.
Outages and deviations	Distinguish agent failure from infrastructure/service failure; fix retry, stopping, missing-measurement and assisted-run disposition.
Estimation	Fix binary CR1 intervals and cost treatment for failures and zero-success arms; bootstrap/model diagnostics and fallback rules; H2 observation points, regression eligibility and reduction denominator. Reconcile the proposed decay panel, checkpoint losses and reference-gap analysis in Section 7.4; the optional repeated-change probe needs separate scope and budget approval.
H4 and H7	Freeze H4 questions, accuracy scoring, non-inferiority margin, timing and reviewer allocation/order; fix H7 endpoint, scale, dependent-contrast intervals and zero/negative-gap policy.
Resources and versions	Verify calibrated credit caps against the separate currency budget; freeze exposed runtime, model, prompts and metric settings.
Human-help telemetry	Verify requests and outside-CLI actions are observable; freeze event extraction/adjudication; missing records are not zero help.

No fresh first-pass results are reported. The status and prior-run boundary are stated at the start of Section 7. Fresh runs remain pending the documented decisions above and registration; checked results will include null, negative and inconclusive findings without relabelling earlier runs.

8 Discussion

8.1 What worked

It would be wrong to read this case as a failure of agents. The research phase assembled a corpus and analysis in days; my judgement that this would have taken me weeks is an unmeasured counterfactual. The role agents' challenge killed a bad idea, five end-to-end agents, before any code was written. The agents refused to invent approvals, figures or company facts, and recorded the limits of their evidence. The MVP was built and reshaped in a day. These episodes included targeted human challenge and feedback; they are not a controlled comparison with human-only teams or proof that all short loops succeed.

8.2 What remained mine in this case

Looking back over six weeks, I still supplied several kinds of reflective work. I decided what not to build. I noticed that something was wrong, not from the reports, which were accurate and full of caveats, but from the plain fact that I could not use the system. I held the theory of the system, in Naur's sense: which lessons mattered and why the sign-in had worked on 12 October. And I was the person responsible for designing the feedback loop and deciding what useful feedback would look like in this case.

That is close to Beck's distinction between a discipline's visible output and the less visible work of understanding, simplifying and building abstractions [15], and to Martin's insistence that programmers still write the tests first and know their customers [70]. The agents were excellent at the visible part. They produced proofs of work: pull requests, artefacts, receipts

and honest caveats. In this case those records did not replace the understanding I gained from using a running system. That does not establish a general limit on what agents can do. It identifies responsibilities that could be candidates for bounded delegation, not proof that they are intrinsically or permanently human.

8.3 Can another agent restore futures?

Beck's alternation suggests a different purpose for an additional agent: preserving the options that feature execution consumes, rather than accelerating the next backlog item [14, 16]. Such an agent would need to inspect the accumulated system, detect drift against intended behaviour and take or recommend a corrective action. An agent that only reads generated records and approves them could reproduce the proxy capture observed here. I propose that a steering role needs behavioural evidence, bounded authority to act and checks that can disconfirm its judgement. More agents do not by themselves supply those conditions.

Darwin already delegates parts of this steering: agents turn observations into hypotheses and guide which candidate to explore next. Its boundary is important. Search improves an explicit objective within an existing architecture; engineers can steer objective setting and evaluation packaging, World Model updates are reviewed, and production output still enters human review queues [84]. This narrows the open question from whether agents can perform any reflection to whether their correction preserves useful future options as requirements change. Performance gains do not establish that result, but they are a relevant precedent for bounded delegation.

The present experiment takes one step towards that question. It asks whether an agent-led consolidation package leaves software more able to absorb an unforeseen change. H6 is the closest probe of preserved future options; complexity and duplication are supporting proxies, not a direct measure of all possible futures. The fixed post-feature cadence does not test whether the agent can decide when to interrupt delivery, challenge a requirement, change the backlog or restore a usable deployment. A positive result would support this bounded consolidation role, not unrestricted process steering. A null or negative result would challenge this particular intervention, not prove that reflective work cannot be delegated to agents.

Whether steering needs human-specific judgement is a separate question. A matched-resource comparison of human-led and agent-led steering with equal oracle coverage could investigate it; the current protocol does not.

8.4 Implications for practice

The case motivates protecting a usable increment, bounding the delivery horizon and keeping lessons retrievable or executable. These are proposals, not a tested operating model. Appendix C supplies a practical checklist; its numerical limits are starting heuristics, not estimated optima. Proportionality never overrides mandatory safety, privacy, approval or publication gates, and compact context views must retain their source evidence. The experiment tests only scheduled consolidation, not this practice set or a live-user checkpoint cadence.

8.5 If drift is contained, what remains for us?

Better software outcomes would not establish how people should participate. Three questions remain a research agenda rather than conclusions of this study.

Role. If agents implement and consolidate, does meaningful human participation centre on choosing problems and judging consequences, or also require working on the system? More domain discovery and experimentation are possible uses of released capacity, not inherently human-only responsibilities.

Intervention. Hands-on product use, with additional attention as uncertainty, consequences or irreversibility increase, is a possible starting practice. HIR and intervention demand describe assistance; they do not identify an optimal cadence or make lower intervention inherently better.

Learning. If agents also correct the code, where does the understanding needed to challenge them come from? Naur and Bainbridge motivate studying human prediction, explanation and unaided change tasks over time [5, 76]. Whether such practices preserve expertise needs separate evidence. What participation we value also remains a human judgement, not an outcome settled by a code-quality result.

8.6 The crisis reframed

The existential question is usually put as whether machines will replace developers. I ask instead which parts of reflection and course correction agents can perform reliably, and how to tell when they are helping rather than reinforcing the original mistake. In this case, producing more work did not substitute for feedback. Designing, protecting and interpreting that feedback remained my responsibility, but that observation is a starting point for testing delegation, not a boundary I assume agents cannot cross. The old practices, testing, small steps, tidying and walking skeletons, offer ways to make such delegation observable and falsifiable. Beck's 2023 recalibration was about which ten per cent of his skills gained leverage [11]; in this case, the skills that mattered were the ones that keep a feedback loop short. Lamanna's advice to judge AI by the same business outcomes as before [58], and Lanzetta's description of the engineer as the architect of intent who builds the system in which agents work [60], point in the same direction.

9 Conclusion

This case records a divergence: 183 merged pull requests and a full implementation score coexisted with the owner's inability to sign in to the replacement system. Production volume and validation activity did not establish usable behaviour. Five candidate mechanisms organise that evidence, but migration, environment, scope, test coverage and owner decisions remain plausible rivals. The case does not establish a rate of code decay, an agent-caused acceleration or the effectiveness of consolidation.

The contribution is the chain from that observed divergence, through bounded candidate explanations, to a prospective test of retained behaviour and adaptation. Practice implications are proposals, not validated controls. Objective-guided optimisation provides a bounded precedent for agent-led correction [84]; the further question is whether such correction preserves changeability as features accumulate. Accountability for goals and consequential decisions remains distinct from delegating bounded corrective work; the case does not establish that only humans can perform that work.

The exploratory first pass operationalises a bounded version of that question: can an agent that consolidates after every feature keep agent-built software working, understandable and changeable at an acceptable cost? It tests the package-level question defined in Section 7. H6 is its direct, task-specific probe of future options; other quality measures cannot substitute for it. The experiment does not test choosing the right product or autonomously recovering every delivery failure. Section 7 sets out how to find out. The larger question of agent-led steering remains open; the first requirement is evidence that the additional agent improves outcomes rather than adds another layer of work. Even then, what people should do, when they should intervene and how they will continue to learn remain open questions. The proposals in Section 8.5 are starting points, not conclusions of this study.

Acknowledgements

I thank the colleagues and partners whose questions shaped this report.

Use of generative AI

GitHub Copilot with HVE Core agents supported development of the system under study. The case method distinguishes reported interface labels from recorded selectors; the deployed assistant exercise used `gpt-4.1-mini-2025-04-14`, not the coding-agent model. Microsoft 365 Copilot supported summarisation and reference discovery.

GitHub Copilot in VS Code assisted log analysis, mechanism naming and organisation, manuscript drafting and revision, bibliographic checks, public repository inspection, figure preparation and local validation. Scientific Agent Skills supplied developmental writing, evaluation and hypothesis guidance [53]. AI assistance supplied neither an independent empirical coder nor replicated application or study results. The package README retains the revision-by-revision account and source-access limits.

I supplied the observations, selected the case and made the analytical judgements. I checked the repository figures and Azure expenditure, and confirmed the Beck paraphrase after reading the essay and watching the talk. Independent author checking of cited research statistics and the log-growth figure remains pending. Metadata checks do not establish claim support; source comparison does not independently validate a source's experiments. I take responsibility for the content. Further disclosure must follow the actual submission venue's policy, which has not been assessed here.

Data availability

The repository analysed is public at https://github.com/jmservera/ama; this report uses commit `29c6b512f5e68733bb2cc1882343db39f5eb2cad`. The log-measurement and figure-generation scripts are provided with the source. The ancillary file anc/repository-observations-2026-10-25.json records the additional repositories' source revisions, tracker counts, sampling boundary and claim locators without reporter identities or attachments. Live issue states can change independently of the pinned source commits. The ancillary experiment notes in HVE Core's Minimum Viable Experiment format are earlier proposals, not the tagged study record. The separate study kit is held in a private repository; it is not yet a public replication archive. The registered snapshot, sanitised data and exact run provenance will need an authorised deposit before a reproducibility claim can be made.

References

[1] S. Agarwal, A. Singhal, A. Macvean, B. Vasilescu, and T. Breaux. Spec-driven development as prescribed and as practiced. arXiv:2608.25202, 2026.

[2] K. Beck, M. Beedle, A. van Bennekum, A. Cockburn, W. Cunningham, M. Fowler, J. Grenning, J. Highsmith, A. Hunt, R. Jeffries, J. Kern, B. Marick, R. C. Martin, S. Mellor, K. Schwaber, J. Sutherland, and D. Thomas. Manifesto for agile software development, 2001. https://agilemanifesto.org/.

[3] J. Young. Effective harnesses for long-running agents. Anthropic, 26 November 2025. https://www.anthropic.com/research/effective-harnesses-for-long-running-agents.

[4] A. Bacchelli and C. Bird. Expectations, outcomes, and challenges of modern code review. In *Proceedings of the 35th International Conference on Software Engineering (ICSE)*, pages 712–721. IEEE, 2013. doi:10.1109/ICSE.2013.6606617.

[5] L. Bainbridge. Ironies of automation. *Automatica*, 19(6):775–779, 1983. doi:10.1016/0005-1098(83)90046-8.

[6] S. Baltes et al. Guidelines for empirical studies in software engineering involving large language models. arXiv:2508.15503, 2025. Accepted in *Empirical Software Engineering*.

[7] G. Bavota, A. De Lucia, M. Di Penta, R. Oliveto, and F. Palomba. An experimental investigation on the innate relationship between quality and refactoring. *Journal of Systems and Software*, 107:1–14, 2015. doi:10.1016/j.jss.2015.05.024.

[8] K. Beck. *Test-Driven Development: By Example*. Addison-Wesley, 2002.

[9] K. Beck and C. Andres. *Extreme Programming Explained: Embrace Change*. Addison-Wesley, 2nd edition, 2004.

[10] K. Beck. `test && commit || revert`. Medium, 28 September 2018. https://medium.com/@kentbeck_7670/test-commit-revert-870bbd756864.

[11] K. Beck. 90% of my skills are now worth $0. *Software Design: Tidy First?* (newsletter), 19 April 2023. https://tidyfirst.substack.com/p/90-of-my-skills-are-now-worth-0.

[12] K. Beck. *Tidy First? A Personal Exercise in Empirical Software Design*. O'Reilly Media, 2023.

[13] K. Beck. Augmented coding: Beyond the vibes. *Software Design: Tidy First?* (newsletter), 25 June 2025. https://tidyfirst.substack.com/p/augmented-coding-beyond-the-vibes.

[14] K. Beck. Why does development slow? *Software Design: Tidy First?*, 19 November 2025. Author's summary at https://kentbeck.com/summaries/why-does-development-slow/.

[15] K. Beck. Mathematicians, here's a way to think about your existential crisis. *Software Design: Tidy First?* (newsletter), 29 September 2026. https://newsletter.kentbeck.com/p/mathematicians-heres-a-way-to-think.

[16] K. Beck. Software engineering in the age of AI. Talk at Prodacity 2026, Nashville, TN, 25–27 August 2026. Video: https://www.youtube.com/watch?v=F8fBgDCf2Y4; transcript: https://www.rise8.us/videos/kent-beck-software-engineering-in-the-age-of-ai.

[17] J. Becker, N. Rush, E. Barnes, and D. Rein. Measuring the impact of early-2025 AI on experienced open-source developer productivity. arXiv:2507.09089, 2025.

[18] T. Besker, A. Martini, and J. Bosch. Technical debt cripples software developer productivity: A longitudinal study on developers' daily software development work. In *Proceedings of the International Conference on Technical Debt (TechDebt '18)*, pages 105–114. ACM, 2018. doi:10.1145/3194164.3194178.

[19] C. Bird, V.-P. Ranganath, T. Zimmermann, N. Nagappan, and A. Zeller. Extrinsic influence factors in software reliability: A study of 200,000 Windows machines. In *Proceedings of the 36th International Conference on Software Engineering (ICSE)*. ACM, 2014. https://www.microsoft.com/en-us/research/publication/extrinsic-influence-factors-in-software-reliability-a-study-of-200000-windows-machines/.

[20] B. Böckeler. Understanding spec-driven-development: Kiro, spec-kit, and Tessl. martinfowler.com, 15 October 2025. https://martinfowler.com/articles/exploring-gen-ai/sdd-3-tools.html.

[21] M. Borg, D. Hewett, N. Hagatulah, N. Couderc, E. Söderberg, D. Graham, U. Kini, and D. Farley. Echoes of AI: Investigating the downstream effects of AI assistants on software maintainability. *Empirical Software Engineering*, 31(6):161, 2026. doi:10.1007/s10664-026-10889-1.

[22] F. P. Brooks, Jr. No silver bullet: Essence and accidents of software engineering. *Computer*, 20(4):10–19, 1987. doi:10.1109/MC.1987.1663532.

[23] M. Cemri, M. Z. Pan, S. Yang, L. A. Agrawal, B. Chopra, R. Tiwari, K. Keutzer, A. Parameswaran, D. Klein, K. Ramchandran, M. Zaharia, J. E. Gonzalez, and I. Stoica. Why do multi-agent LLM systems fail? In *Advances in Neural Information Processing Systems 38 (NeurIPS 2025), Datasets and Benchmarks Track*, 2025. arXiv:2503.13657.

[24] J. Chen, X. Xu, H. Wei, C. Chen, and B. Zhao. SWE-CI: Evaluating agent capabilities in maintaining codebases via continuous integration. arXiv:2603.03823, 2026.

[25] A. Cockburn. *Crystal Clear: A Human-Powered Methodology for Small Teams*. Addison-Wesley, 2004.

[26] J. Cohen. *Best Kept Secrets of Peer Code Review*. Smart Bear Inc., 2006.

[27] W. Cunningham. The WyCash portfolio management system. In *Addendum to the Proceedings of OOPSLA '92 (Experience Report)*, pages 29–30. ACM, 1992. doi:10.1145/157709.157715.

[28] D. Delimarsky. Spec-driven development with AI: Get started with a new open source toolkit. The GitHub Blog, 2 September 2025. https://github.blog/ai-and-ml/generative-ai/spec-driven-development-with-ai-get-started-with-a-new-open-source-toolkit/.

[29] P. Devanbu, T. Zimmermann, and C. Bird. Belief & evidence in empirical software engineering. In *Proceedings of the 38th International Conference on Software Engineering (ICSE)*. ACM, 2016. doi:10.1145/2884781.2884812.

[30] J. Ding, S. Long, C. Pu, et al. NL2Repo-Bench: Towards long-horizon repository generation evaluation of coding agents. arXiv:2512.12730, 2025.

[31] DORA. Accelerate state of DevOps report 2024. Google Cloud, 2024. https://dora.dev/research/2024/dora-report/.

[32] DORA. State of AI-assisted software development 2025. Google Cloud, 2025. https://dora.dev/dora-report-2025.

[33] Google Cloud. Announcing the 2025 DORA report. Google Cloud Blog, 23 September 2025. https://cloud.google.com/blog/products/ai-machine-learning/announcing-the-2025-dora-report.

[34] S. G. Eick, T. L. Graves, A. F. Karr, J. S. Marron, and A. Mockus. Does code decay? Assessing the evidence from change management data. *IEEE Transactions on Software Engineering*, 27(1):1–12, 2001. doi:10.1109/32.895984.

[35] S. Fakhoury, A. Naik, G. Sakkas, S. Chakraborty, and S. K. Lahiri. LLM-based test-driven interactive code generation: User study and empirical evaluation. *IEEE Transactions on Software Engineering*, 50(9):2254–2268, 2024. doi:10.1109/TSE.2024.3428972.

[36] M. Fowler. Design stamina hypothesis. martinfowler.com, 20 June 2007. https://martinfowler.com/bliki/DesignStaminaHypothesis.html.

[37] M. Fowler. Some thoughts on LLMs and software development. martinfowler.com, 28 August 2025. https://martinfowler.com/articles/202508-ai-thoughts.html.

[38] J. Gall. *General Systemantics: An Essay on How Systems Work, and Especially How They Fail*. General Systemantics Press, Ann Arbor, MI, 1975.

[39] E. Gamma and K. Maetzel, interviewed by W. Bos and S. Tolinski. Fork yeah! Microsoft open sourcing Copilot. *Syntax* podcast, episode 903, 19 May 2025. https://syntax.fm/show/903/fork-yeah-microsoft-open-sourcing-copilot.

[40] D. Gautam, S. Garg, J. Jang, N. Sundaresan, and R. Zilouchian Moghaddam. RefactorBench: Evaluating stateful reasoning in language agents through code. In *International Conference on Learning Representations (ICLR)*, 2025. arXiv:2503.07832.

[41] GitClear. AI copilot code quality: 2025 data suggests 4x growth in code clones. Research report, GitClear, 2025.

[42] E. M. Goldratt and J. Cox. *The Goal: A Process of Ongoing Improvement*. North River Press, 1984.

[43] C. A. E. Goodhart. Problems of monetary management: The U.K. experience. In *Papers in Monetary Economics*. Reserve Bank of Australia, Sydney, 1975.

[44] N. Harvey and D. DeBellis. Announcing the 2024 DORA report. Google Cloud Blog, 22 October 2024. https://cloud.google.com/blog/products/devops-sre/announcing-the-2024-dora-report.

[45] H. He, C. Miller, S. Agarwal, C. Kästner, and B. Vasilescu. Speed at the cost of quality: How Cursor AI increases short-term velocity and long-term complexity in open-source projects. In *Proceedings of the International Conference on Mining Software Repositories (MSR '26)*. ACM, 2026. doi:10.1145/3793302.3793349. arXiv:2511.04427.

[46] L. G. Heander, M. Borg, E. Söderberg, and C. Rydenfält. CodeHealth predicts the token cost of agentic code review: A pre-registered study of 465 agent-authored pull requests. arXiv:2610.21914, 2026.

[47] I. Herraiz, D. Rodriguez, G. Robles, and J. M. Gonzalez-Barahona. The evolution of the laws of software evolution: A discussion based on a systematic literature review. *ACM Computing Surveys*, 46(2):28, 2013. doi:10.1145/2543581.2543595.

[48] K. Hong, A. Troynikov, and J. Huber. Context rot: How increasing input tokens impacts LLM performance. Technical report, Chroma, July 2025. https://trychroma.com/research/context-rot.

[49] R. Hoque, A. Balakrishna, E. Novoseller, A. Wilcox, D. S. Brown, and K. Goldberg. ThriftyDAgger: Budget-aware novelty and risk gating for interactive imitation learning. In *Proceedings of the 5th Conference on Robot Learning*, volume 164 of *Proceedings of Machine Learning Research*, pages 598–608. PMLR, 2022. https://proceedings.mlr.press/v164/hoque22a.html.

[50] A. Hunt and D. Thomas. *The Pragmatic Programmer: From Journeyman to Master*. Addison-Wesley, 1999.

[51] Microsoft. HVE Core: HyperVelocity Engineering for GitHub Copilot. GitHub repository and documentation, accessed 24 October 2026. https://github.com/microsoft/hve-core; https://microsoft.github.io/hve-core/.

[52] A. Karpathy. Post on X introducing "vibe coding", 2 February 2025. https://x.com/karpathy/status/1886192184808149383.

[53] T. Kassis, V. Agarwal, Y. He, D. Patel, and A. M. Brueckner. Scientific agent skills: A library of procedural knowledge for research agents. arXiv:2609.00065, 2026. doi:10.48550/arXiv.2609.00065.

[54] M. Kelly, C. Sidrane, K. Driggs-Campbell, and M. J. Kochenderfer. HG-DAgger: Interactive imitation learning with human experts. arXiv:1810.02890v2, 2019 (first posted 2018).

[55] M. Kim, T. Zimmermann, and N. Nagappan. An empirical study of refactoring challenges and benefits at Microsoft. *IEEE Transactions on Software Engineering*, 40(7), 2014. doi:10.1109/TSE.2014.2318734.

[56] A. Kumar, Y. Bajpai, S. Gulwani, G. Soares, and E. Murphy-Hill. Why AI agents still need you: Findings from developer-agent collaborations in the wild. In *IEEE/ACM International Conference on Automated Software Engineering (ASE)*, 2025. arXiv:2506.12347v3, 9 October 2025.

[57] P. Laban, H. Hayashi, Y. Zhou, and J. Neville. LLMs get lost in multi-turn conversation. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2505.06120.

[58] C. Lamanna. Changing how we build. LinkedIn article, 5 August 2026. https://www.linkedin.com/pulse/changing-how-we-build-charles-lamanna-xpitc/.

[59] M. Lanzetta. Growing engineers in the hypervelocity era. LinkedIn article, 21 April 2025. https://www.linkedin.com/pulse/growing-engineers-hypervelocity-era-mike-lanzetta-qux0c/.

[60] M. Lanzetta. The hypervelocity orchestra. LinkedIn article, 25 February 2026. https://www.linkedin.com/pulse/hypervelocity-orchestra-mike-lanzetta-p0kvc/.

[61] H.-P. Lee, A. Sarkar, L. Tankelevitch, I. Drosos, S. Rintel, R. Banks, and N. Wilson. The impact of generative AI on critical thinking: Self-reported reductions in cognitive effort and confidence effects from a survey of knowledge workers. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, pages 1–22. ACM, 2025. doi:10.1145/3706598.3713778.

[62] M. M. Lehman. Programs, life cycles, and laws of software evolution. *Proceedings of the IEEE*, 68(9):1060–1076, 1980. doi:10.1109/PROC.1980.11805.

[63] M. M. Lehman, J. F. Ramil, P. D. Wernick, D. E. Perry, and W. M. Turski. Metrics and laws of software evolution: The nineties view. In *Proceedings of the 4th International Software Metrics Symposium (METRICS '97)*. IEEE, 1997. doi:10.1109/METRIC.1997.637156.

[64] H. Li, H. Zhang, and A. E. Hassan. AIDev: Studying AI coding agents on GitHub. In *Proceedings of the International Conference on Mining Software Repositories (MSR)*, 2026. arXiv:2602.09185. doi:10.1145/3793302.3797249.

[65] N. F. Liu, K. Lin, J. Hewitt, A. Paranjape, M. Bevilacqua, F. Petroni, and P. Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173, 2024. doi:10.1162/tacl_a_00638.

[66] J. L. Lulla, M. Galster, J. M. Zhang, S. Baltes, and C. Treude. The impact of configuring agentic AI coding tools on build-vs-buy decisions: A study protocol. ESEM 2026, Registered Reports track. arXiv:2606.03907, 2026.

[67] Y. Ma, B. Kereopa-Yorke, and B. Schultz. Building to the test: Coding agents deliver what you check, not what you requested. arXiv preprint arXiv:2606.28430v1, 26 June 2026. https://arxiv.org/abs/2606.28430v1.

[68] R. C. Martin. *We, Programmers: A Chronicle of Coders from Ada to AI.* Addison-Wesley Professional, 2024.

[69] R. C. Martin. AI out-codes you; deal with it. Video post on X (@unclebobmartin), 20 April 2026. https://x.com/unclebobmartin/status/2046206145597972849.

[70] R. C. Martin. Why hardcore technical focus still matters big time. *Product Engineers* podcast, 29 September 2026. https://productengineers.com/episodes/season2/why-hardcore-technical-focus-still-matters-big-time-uncle-bob/.

[71] J. Becker, N. Rush, T. Cunningham, D. Rein, and K. Mahamud. We are changing our developer productivity experiment design. METR blog, 24 February 2026. https://metr.org/blog/2026-02-24-uplift-update/.

[72] S. Mhatre, Y. Bajpai, S. Gulwani, E. Murphy-Hill, and G. Soares. SWE-Sharp-Bench: A reproducible benchmark for C# software engineering tasks. In *International Conference on AI-powered Software (AIware)*, 2025. Accessed arXiv:2511.02352v2, 5 November 2025.

[73] A. Murphy. The five stages of losing our craft. Blog post, 8 February 2026. https://andrewmurphy.io/blog/the-five-stages-of-losing-our-craft.

[74] A. Murphy. If you thought the speed of writing code was your problem – you have bigger problems. Blog post, 17 March 2026. https://andrewmurphy.io/blog/if-you-thought-the-speed-of-writing-code-was-your-problem-you-have-bigger-problems.

[75] E. Murphy-Hill, J. Butler, and A. Savelieva. Adoption and impact of command-line AI coding agents: A study of Microsoft's early 2026 rollout of Claude Code and GitHub Copilot CLI. arXiv:2607.01418, 2026.

[76] P. Naur. Programming as theory building. *Microprocessing and Microprogramming*, 15(5):253–261, 1985. doi:10.1016/0165-6074(85)90032-8.

[77] R. Lopopolo. Harness engineering: Leveraging Codex in an agent-first world. OpenAI, 11 February 2026. https://openai.com/index/harness-engineering/.

[78] G. Orlanski, D. Roy, A. Yun, C. Shin, A. Gu, A. Ge, D. Adila, N. Roberts, F. Sala, and A. Albarghouthi. SlopCodeBench: Benchmarking how coding agents degrade over long-horizon iterative tasks. arXiv:2603.24755, 2026.

[79] K. Beck, interviewed by G. Orosz. TDD, AI agents and coding with Kent Beck. *The Pragmatic Engineer* podcast, 11 June 2025. https://www.youtube.com/watch?v=aSXaxOdVtAQ.

[80] A. Osmani. The 70% problem: Hard truths about AI-assisted coding. *Elevate* (newsletter), December 2024. https://addyo.substack.com/p/the-70-problem-hard-truths-about.

[81] S. Ouyang, J. M. Zhang, M. Harman, and M. Wang. An empirical study of the non-determinism of ChatGPT in code generation. *ACM Transactions on Software Engineering and Methodology*, 34(2):42, 2025. doi:10.1145/3697010.

[82] R. Pan, J. Zhang, L. Wu, Y. Zhang, H. Zhang, and L. Zhang. Do modifications made by coding agents make subsequent software maintenance harder? arXiv:2610.14768, 2026.

[83] D. L. Parnas. Software aging. In *Proceedings of the 16th International Conference on Software Engineering (ICSE '94)*, pages 279–287. IEEE, 1994. doi:10.1109/ICSE.1994.296790.

[84] A. Pavlenko, B. Crivat, B. Haynes, C. Curino, F. Psallidas, J. Slawinski, J. Freischuetz, L. Pereira Sanchez, M. Weimer, M. Demarne, M. Jasny, M. Gandhi, M. Bovykin, M. Milletari, P. Ghosh, Q. Bai, R. Ramakrishnan, R. Pandita, S. Matusevich, S. Venkataraman, S. Krishnan, M. T. Mahmood, T. Bang, V. Emani, X. Zhao, and Y. Zhu. Towards an AI software factory for data systems. arXiv:2609.36323v1, 28 September 2026. https://arxiv.org/abs/2609.36323v1.

[85] S. R. O. Peralta, F. Hoshi, H. Washizaki, N. Ubayashi, I. Kondo, Y. Higo, H. Mukai, N. Yoshida, K. Kusama, H. Tanaka, and Y. Fan. Why are agentic pull requests merged or rejected? An empirical study. arXiv:2605.22534, 2026.

[86] PhotoCraft contributors. PhotoCraft: Source, parity records and public tracker observations. GitHub, source commit `5bb8536`; retrieved 25 October 2026. https://github.com/storytold/photocraft/tree/5bb853654196eca807212ff8955ba2eb293071ea. Dated counts and claim locators in the ancillary repository-observation record.

[87] W. W. Royce. Managing the development of large software systems. In *Proceedings of IEEE WESCON*, pages 1–9, August 1970.

[88] P. Runeson and M. Höst. Guidelines for conducting and reporting case study research in software engineering. *Empirical Software Engineering*, 14(2):131–164, 2009. doi:10.1007/s10664-008-9102-8.

[89] C. Sadowski, E. Söderberg, L. Church, M. Sipko, and A. Bacchelli. Modern code review: A case study at Google. In *Proceedings of the 40th International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP)*, pages 181–190. ACM, 2018. doi:10.1145/3183519.3183525.

[90] A. Sarkar. AI should challenge, not obey. *Communications of the ACM*, 67(10):18–21, 2024. doi:10.1145/3649404.

[91] J. M. Servera Bondroit. Aithena: Source, Squad records and public tracker observations. GitHub, source commit `f27aa2e`; retrieved 25 October 2026. https://github.com/jmservera/aithena/tree/f27aa2e9f949ea76f2a437249e68b52670a22835. Dated counts and claim locators in the ancillary repository-observation record.

[92] J. M. Servera Bondroit. AMA Case Study 48: research and solution design for the Zava Forward retrofit programme. GitHub repository, commit 29c6b51, 24 October 2026. https://github.com/jmservera/ama.

[93] P. Ralph et al. Empirical standards for software engineering research. arXiv:2010.03525v2, 2021 (first posted 2020). ACM SIGSOFT Empirical Standards: https://www2.sigsoft.org/EmpiricalStandards/.

[94] A. Simkute, L. Tankelevitch, V. Kewenig, A. E. Scott, A. Sellen, and S. Rintel. Ironies of generative AI: Understanding and mitigating productivity loss in human-AI interaction. *International Journal of Human–Computer Interaction*, 41(5):2898–2919, 2025. doi:10.1080/10447318.2024.2405782.

[95] A. Sinha, A. Arun, S. Goel, S. Staab, and J. Geiping. The illusion of diminishing returns: Measuring long horizon execution in LLMs. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2509.09677.

[96] Squad contributors. Squad: Human-led AI agent teams. GitHub, `dev` commit `481c944`; retrieved 25 October 2026. https://github.com/bradygaster/squad/blob/481c944596abfa2053e2acd88d765639f994d795/README.md.

[97] M. Strathern. 'Improving ratings': Audit in the British university system. *European Review*, 5(3):305–321, 1997.

[98] L. Tankelevitch, V. Kewenig, A. Simkute, A. E. Scott, A. Sarkar, A. Sellen, and S. Rintel. The metacognitive demands and opportunities of generative AI. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, pages 1–24. ACM, 2024. doi:10.1145/3613904.3642902.

[99] Thoughtworks. Complacency with AI-generated code. Technology Radar (Techniques, Hold), 2024–2025. https://www.thoughtworks.com/radar/techniques/complacency-with-ai-generated-code.

[100] A. Tornhill and M. Borg. Code red: The business impact of code quality. A quantitative study of 39 proprietary production codebases. In *Proceedings of the International Conference on Technical Debt (TechDebt '22)*, pages 11–20. ACM, 2022. doi:10.1145/3524843.3528091.

[101] M. Waseem, A. Ahmad, K.-K. Kemell, J. Rasku, S. Lahti, K. Mäkelä, and P. Abrahamsson. Vibe coding in practice: Flow, technical debt, and guidelines for sustainable use. arXiv:2512.11922, 2025.

[102] S. Willison. Vibe engineering. Simon Willison's Weblog, 7 October 2025. https://simonwillison.net/2025/Oct/7/vibe-engineering/.

[103] C. Wohlin, P. Runeson, M. Höst, M. C. Ohlsson, B. Regnell, and A. Wesslén. *Experimentation in Software Engineering*. Springer, 2012. doi:10.1007/978-3-642-29044-2.

[104] W. Yan. Don't build multi-agents. Cognition blog, 12 June 2025. https://cognition.ai/blog/dont-build-multi-agents.

[105] C. Yang, H. He, T.-C. Cheng, J. Butler, E. Murphy-Hill, C. Badea, and C. Bird. (When) should a software factory be lights-off? Benchmarking code review agents on bug detection. arXiv preprint arXiv:2610.13668v1, 9 October 2026. https://arxiv.org/abs/2610.13668v1.

[106] H. Yu, L. Liu, X. Jiang, Y. Jia, S. Wang, P. Qian, and Y. Chen. Habituation at the gate: Rising approval and declining scrutiny in human review of AI agent code. KDD 2026 Workshop on Agentic Software Engineering, 2026. arXiv:2606.22721.

[107] Z. Zhong, A. Raghunathan, and N. Carlini. ImpossibleBench: Measuring LLMs' propensity of exploiting test cases. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2510.20270.

A Supplementary practitioner context

These sources document contemporary arguments and reported practices. They are not primary evidence that this case's candidate mechanisms caused its outcome or that the harness is effective.

A.1 Additional empirical context

Fowler's design stamina hypothesis frames attention to design as an investment in later change [36]. Code-quality and technical-debt studies report associations with defects, development time and lost productivity [18, 100]. Their settings and measures differ from this case; they do not identify its cause or estimate the benefit of the proposed harness.

Observational studies of AI-tool adoption and repository changes report increased complexity, warnings or duplication [41, 45]. DORA's 2024 and 2025 reports discuss adoption alongside delivery stability, documentation and existing organisational strengths and weaknesses [31–33, 44]. These sources have different sampling and commercial contexts, not a common controlled estimate of agent-caused decay. Heander et al. associate CodeHealth with review-token cost, while their batch fixes did not change median CodeHealth [46].

The METR authors' later account qualifies generalisation from their early-2025 productivity experiment to newer tools [71]. Industrial review guidance and Google's small-change practice describe conditions for manageable review, not a demonstrated universal size limit [26, 89]. These accounts motivate measuring actual outcomes and review effort rather than interpreting output volume as productivity.

A.2 Craft, constraints and reported practice

Karpathy's throwaway-project framing, Willison's accountable vibe engineering, Osmani's unfinished final stretch and Fowler's non-deterministic engineering analogy describe different practitioner positions, not experimental comparisons [37, 52, 80, 102]. Thoughtworks warns against complacency with generated code [99]; Sarkar proposes AI that challenges rather than only obeys [90].

Beck's augmented-coding account distinguishes caring about code, complexity, tests and coverage from accepting plausible output. He describes loops, unrequested functionality and disabled tests as warning signs [13, 79]. His Prodacity talk argues for learning through software and alternating feature work with consolidation; his mathematicians essay distinguishes visible output from understanding and abstraction [14–16]. These arguments motivate the hypothesis, not a measured treatment effect.

Martin's 2024 treatment of language models as tools and his later call for executable standards emphasise coverage, mutation testing, complexity limits and knowing the customer [68–70]. Gamma's discussion of stochastic simulation testing concerns evaluation containing a model, not a reason to treat all deterministic tests as unreliable [39]. Murphy applies the Theory of Constraints to review queues and work in progress, while also describing the loss of craft [42, 73, 74].

Lanzetta advises small chunks, tests first, bounded complexity and more attention to PR review [59]. His account of a two-week, roughly 60,000-line sprint describes repeated architectural reorientation, a done gate and retrospectives that block the next sprint until findings are resolved [60]. Lamanna reports spending agentic capacity on reliability, performance and security rather than more features, with improved support outcomes for one product [58]. These first-party accounts do not isolate consolidation from other changes, and their output measures are not comparable controlled estimates.

A.3 Informal field observations

In October 2026 I presented HVE Core to two partners and discussed agentic delivery with peers. I omit partner names and generalise identifying details. At one partner session, an engineer challenged orchestration overhead, token cost, rule enforcement, documentation bloat and committed tracking files, and asked about lighter alternatives such as Spec Kit. The other session raised trust and net benefit after costs. A fellow architect asked how one learns how the solution works with such a backlog. These are informal, retrospectively reported observations, not systematically collected data, independent corroboration or evidence of prevalence.

B Motivating experience and external repository observations

These examples were selected after my experience, not sampled as independent cases. My judgement that Aithena became difficult to maintain is retrospective, not a measured complexity trajectory or controlled comparison of frameworks.

Aithena and Squad. Aithena is my book-search project, with PDF ingestion, full-text and embedding-based search, and a browser interface. At the inspected `dev` revision `f27aa2e`, its Squad records describe specialist agents, shared decisions, a work monitor, pre-task design review and post-failure retrospectives [91]. Squad's current documentation describes persistent learning through repository files, but explicitly calls the framework human-led and retains human accountability for priorities, review and decisions [96]. These are designed feedback mechanisms, not evidence that every session used them effectively or that self-improvement was demonstrated.

Aithena issue #1828 reports misleading end-to-end coverage from skipped Phase 3 scenarios. The pinned test file contains active preflight assertions and unconditional `pytest.skip` calls in fixture-dependent scenarios: neither "all tests are skipped" nor "all intended behaviour is tested" follows. Issue #1804 reports ingestion acknowledgement after processing failures; the

pinned callback places `basic_ack` in its `finally` block. This supports examining the failure contract, not a claim that a document was lost in a reproduced run. Quality gates, releases and substantive search functionality also exist. Of 35 open PRs at retrieval, 34 carried a dependency label; the queue is not a measure of architectural decay [91].

PhotoCraft: a known target is not a complete oracle. PhotoCraft describes itself as an early-alpha, clean-room Rust reimplementation of Adobe Photoshop, not the whole Adobe suite [86]. Its controls include dependency-layer checks, regression tests, real-file corpora, visual inspection instructions and a common command interface for the UI, CLI and MCP. Its scorecard reports 631 of 631 menu items live. The inspected `parity.rs` recognises command, tool or UI handlers; it does not execute every reference workflow. The README explicitly warns that menu wiring is not behaviour.

The project's 10 October assessment estimated about 76% feature breadth and 45% readiness for real work. These are partly subjective historical project estimates, not a fresh independent assessment. Its gap register describes PSD exchange and performance limits, including no automated third-party-editor check of exports [86].

At the 25 October 2026, 22:52 UTC tracker snapshot, PhotoCraft had 2,060 open issues, including 212 labelled `bug`, and 1,091 open PRs, of which 49 were drafts; it also had 2,604 closed issues and 3,189 merged PRs. These are tracker counts, not confirmed unique defects or a defect rate. Selected unreproduced reports concern Windows printing through CUPS (#5328), repeated network-share save prompts despite successful saving (#9440), and a crash opening a large PSD (#9448). Duplicate labels occur; PR #9552 proposes helper consolidation. Both problems and corrective work are visible, while queue size can reflect contribution and review capacity [86].

Reference-based testing still needs inputs, oracles and tolerances for file exchange, platforms, document size and interacting tools. These observations motivate distinguishing issue-level correction from cumulative steering. They establish neither framework inferiority, inevitable deterioration nor a permanently human steering role. The ancillary observation record retains the source pins, sampling boundaries and locators.

C Proposed feedback-first practices

The seven practices in Table 11 are implications for practitioners to evaluate, not an empirically validated operating model. One-to-two-week horizons, three parallel sessions and five acceptance criteria are starting heuristics, not estimated optima or new rules for this repository. They do not override required engineering or human approval gates.

A checklist for Monday. Can a human complete an intended task in today's deployed increment? Does a merge preserve that journey? Is the horizon short and work in progress bounded? Are criteria small enough to review? Is there a demo checkpoint and a decision before the next wave? Can important lessons be executed or retrieved with their evidence? Is required context readable? Do gates test behaviour without weakening mandatory safeguards? Is cost attributable to accepted outcomes? Can the owner explain the core design without an agent? These questions expose missing evidence; they do not certify a delivery process.

Implications for framework builders. HVE Core already supplies human stops, critiques and file-based context. Possible additions are review paths that exercise the running increment, evidence requirements scaled to risk, and executable lessons with warnings when required context exceeds a budget. Such additions require evaluation; this case does not establish that they improve outcomes or that existing gates should be removed.

Table 11: Proposed practices, candidate mechanisms and suggested observations.

Practice	Proposed application and boundary	Observe
P1 Protect a running increment	Exercise a real user journey before replacing a working system; distinguishes usability from health checks.	First human use; age of last usable increment
P2 Bound batches and horizon	Start with one to two weeks, at most three sessions and five criteria per issue; revise to fit task risk. Addresses specification/gate inflation.	Work in progress; scope versus validated behaviour
P3 Hold human checkpoints	Demo every few merges or daily, decide what to keep, cut or tidy, and record the decision. Addresses feedback starvation [12, 16].	Product-use feedback and decisions, not attendance alone
P4 Make lessons usable	Convert suitable lessons into tests, lint rules or fitness functions; provide compact, provenance-linked context while retaining the original evidence. Addresses learning evaporation.	Executable lessons; effective read-path size
P5 Make gates proportional	Prefer behaviour-scoped checks and risk-based records, subject to mandatory full/publication and safety gates. Addresses process inflation and proxy capture.	Gate time and defects detected per accepted outcome
P6 Measure outcomes	Compare automated scores with real journeys; track behaviour-changing merges, review effort and attributable cost. Hedge density is only a prompt to inspect records.	Score–demo disagreement; cost per accepted outcome
P7 Preserve theory building	Pair on the first slice, own acceptance examples, read the domain code and invite challenge rather than compliance alone [35, 90].	What the owner can predict and explain without the agent

D Case rival-explanation register

The main interpretation is in Section 5.7. The register preserves recorded rivals separately from untested alternatives. A limit is not grounds for ruling an explanation out. Score/deployment correspondence remains unverified (Section 3.6).

Table 12: Rival explanations with direct case records.

Explanation	Case support	Counter-evidence or limits	Treatment
Migration decision	ADR 0006 (issue #196) froze feature work in the MVP and prioritised a new layout.	Health and restart checks passed, not usability.	Migration and coordination changed together; autonomy alone is not identified.
Capstone rubric	Research and documentation are rewarded; full completeness marks coexist with blocked sign-in.	A working demonstrator is required; release/scope linkage is pending.	Possible incentive, not a measured effect.
My overrides and priorities	Committed RPI records, full gates and delegated merging; PR #445 required an exception.	The MVP used agents successfully; HVE Core defaults retain human stops.	Owner choices are part of the case.
Model and tool changes	Versions changed during the study.	No matched rerun under fixed versions.	Actual session configuration remains partly unknown.
CI and cloud budgets	Issue #413 moved validation locally; costs prompted a higher ceiling and reduced resources.	Merges continued without established deployed usability.	More budget is not proven to resolve delivery.
Identity and sign-in setup	Missing registration/staff bindings; issue #349 distinguishes redirect from sign-in.	Those steps worked on 12 October.	Concrete configuration obstacle, not proof of code decay or lost knowledge.

Table 13: Additional plausible rivals and unperformed discriminating checks.

Explanation	Reason considered	Counter-evidence or limits	Evidence still needed
External services and deployment drift	Model/identity configuration differs from the MVP.	No provider outage is established; health checks were narrower.	Versioned deployment/configuration and dependency-health records for the journey.
Scope expansion	RAI and consumption criteria added to issues; further resident-preview obligations.	Expansion predates autonomy; some controls are justified.	Original/added scope, sequencing and time-to-outcome comparison.
Inadequate acceptance tests	Checks passed without completed real-user sign-in; scorer read artefacts.	Bounded, honest tests need not be poor tests.	Capability-to-task-oracle mapping and execution evidence.
Rate and context limits	Parallel sessions and a large read path.	No runtime rate-limit, truncation or attention dataset analysed.	Actual inputs and blocked/retried request events.
Specification ambiguity	Selective review of long, cross-referenced requirements.	Important domain/consent decisions survived; ambiguity not independently coded.	Independent interpretation and conflicting acceptance examples.
Ordinary prototype debt	Rapid MVP followed by restructuring and rebuilding.	MVP worked intermittently; no comparable human-led migration.	Failure analysis distinguishing inherited debt from introduced faults.

E Candidate-mechanism evidence audits

These are operational boundaries for this paper, not validated necessary and sufficient conditions for all agentic development. The indicators refer to Table 1 and the case chronology. Experimental implications state what evidence would discriminate an explanation; the tagged experiment does

not manipulate the five candidates separately.

E.1 Specification inflation

Element	Audit
Definition	Requirements and acceptance obligations expand faster than independently validated behaviour, without evidence that the added scope is needed for the next usable increment. Length alone is insufficient.
Case indicators	O3: BRD/PRD growth, 192 issues and cross-cutting additions; the smallest resident preview had thirteen criteria.
Counter-evidence	Growth began before autonomy and sometimes followed the owner's feedback; regulatory and consent controls can justify detail.
Rival explanations	Genuine scope expansion, specification ambiguity, capstone incentives and an ambitious migration rather than agent-driven inflation.
Experimental implication	Compare smaller requirements horizons at matched scope and resources. The current fixed-suite experiment cannot identify this mechanism, even if consolidation helps.

E.2 Proxy capture

Element	Audit
Definition	A completion proxy becomes a decision criterion and remains positive when an independent test of the intended outcome is negative. Proxy use alone does not establish capture.
Case indicators	O2–O3: a 5/5 score and blocked sign-in coexist in the chronology; release/scope linkage is pending. Mandatory artefact presence and the evidence record for PR #445 are separate indicators.
Counter-evidence	Agents explicitly reported unmet acceptance; neither fabricated approval nor deliberate deception is established.
Rival explanations	An inadequate scorer or acceptance oracle, different evaluation targets, and a deployment failure invisible to repository review.
Experimental implication	Disagreement between visible completion and hidden behavioural tests would expose proxy limits. It would not by itself establish intentional test gaming or explain why a gate was chosen.

E.3 Learning evaporation

Element	Audit
Definition	A recorded lesson relevant to a later decision is absent from, unusable on, or not applied through that decision's effective context path, and the associated problem recurs. A missing citation alone is insufficient.
Case indicators	O4: simplicity references cease; working sign-in setup is not preserved; state and intent documents reach about 139,000 words.
Counter-evidence	Important domain decisions survived; the lesson could have been known but deferred. Actual session attention was not measured.
Rival explanations	Deliberate migration sequencing, deployment-specific configuration, context limits, or conflicting requirements rather than lost knowledge.
Experimental implication	Trace actual inputs and repeated faults. B–C cannot isolate memory quality because DESIGN and REVIEW notes and acting permissions differ. A matched-context study would be needed.

E.4 Process-gate inflation

Element	Audit
Definition	Additional procedural obligations increase per-change burden without demonstrated proportional improvement in the targeted outcome. More gates alone are not evidence that their net benefit is negative.
Case indicators	O5: full RPI and validation on each correction/rebase; hosted-minute rationing; explicit exception for PR #445.
Counter-evidence	Checks caught bounded defects and enforced evidence integrity. Gate duration and human review effort were not measured per PR.
Rival explanations	Legitimate safety and privacy requirements, budget constraints, new deployment complexity and owner-selected risk tolerance.
Experimental implication	Measure gate time and accepted outcomes under matched risk. H5 measures the consolidation package's cost, not the effect of removing this repository's required gates.

E.5 Feedback starvation

Element	Audit
Definition	Independent outcome-level feedback is insufficient to correct delivery decisions despite abundant artefact-level validation. The defining gap is between the evaluated proxy and intended outcome, not test count alone.
Case indicators	O1–O2 and O5: working MVP frozen; replacement unusable; passing checks and continued approvals did not restore a completed user task.
Counter-evidence	Human oversight continued; agents surfaced blockers; engineering checks provided real, though narrower, feedback.
Rival explanations	Identity and service configuration, migration priority, incomplete acceptance coverage, prototype debt or insufficient resources.
Experimental implication	Hidden retention tests and CR1 supply behavioural feedback to the evaluator. The experiment does not test live deployment recovery, product selection or a human-use checkpoint cadence.

F Measures and lexicon

Log entries. The knowledge-base log (`docs/reference/log.md`) was split into entries at each second-level heading that begins with a date. An entry belongs to the date in its heading. Word counts use whitespace tokenisation of the entry, heading included.

Hedging phrases. Each entry was searched, case-insensitively and on word boundaries, for these patterns: *unmet*; *not accepted*; *not inferred*; *is inferred*; *remain(s) open*; *remain(s) unproved*; *remain(s) unverified*; *not claimed*; *not established*; and *no* followed, within forty letters, spaces, commas, slashes or hyphens, by *is* or *was* and then *claimed* or *inferred*. Density is matches per 1,000 words.

Reference tracing. An entry cites the simplicity requirements if it contains an identifier from SA-001 to SA-010 or the word *simplicity*. It cites the development profile if it contains *deploymentProfile*, *development profile* or *allowPublicNetworkAccess*.

Repository counts. Issue and pull-request counts come from the GitHub search API on 24 October 2026 (for example, `is:pr is:merged merged:>=2026-10-15`). Document sizes are whitespace word counts of the files at commit `29c6b51`.

Proposed measures. *Time to first human use*: elapsed time from the start of a delivery cycle to the first time a person uses the running increment for its purpose. *Age of the last usable increment*: time since a person last verified that the deployed system could be used for its main journey. *Behaviour-changing merge ratio*: the share of merged pull requests that change what a user can observe in the running increment. *Cost per accepted outcome*: total model, tool and cloud cost divided by the number of outcomes a human accepted in the same period.

G Consolidation step prompt

The prompt used for the consolidation step of arm B (Section 6). Braces mark parameters set by the experiment runner.

```
Do not add or change features. Your job is to leave the code better than
you found it without changing its behaviour.

1. Run ‘make check‘, then read reports/quality.md (functions above
   complexity 10, duplicated blocks, lint warnings, file sizes).
2. Review the last feature’s diff (‘git diff feature-start feature-end‘,
   tags the runner sets around each feature step) and the hotspots
   against this checklist: duplicated logic; long or complex functions;
   unclear names; dead code; responsibilities in the wrong place, or
   rules from one feature leaking into another; tests that check
   implementation details instead of behaviour.
3. Make small, behaviour-preserving changes. Apply every change through
   ‘./tcr "<message>"‘: it runs all tests and commits if they pass, or
   reverts if they fail.
4. Never modify or delete files in tests/examples/. You may add tests that
   pin current behaviour before you refactor.
5. Rewrite DESIGN.md in at most 300 words: the current structure, where
   each business rule lives, and known debts. Replace; do not append.
6. Stop when the quality budget is met (no function above complexity 10,
   duplicated lines below 3%, zero warnings in the configured lint rules)
   or when your time budget ({consolidation_budget}) is used.
7. Finish with a summary of at most five lines: what you changed and what
   debt remains.
```