

R-Tutorials Using Titanic Data

Josemari Feliciano

7/10/2017

There are three major parts to this tutorials:

1. How to read and extract data from RData file
2. How to create basic graphs
3. How to run basic descriptive statistics
4. How to run and read results of inferential statistics

Tutorial Notes:

The Beauty of R Studio is the ability to have notebooks for data analysis. It allows us to run R-code inline similar to IPython Notebooks.

Think of it as a fancy chemistry notebook where you can somehow run the experiments itself in the notebook – but for data analysis! For this notebook and R tutorial, I will use the titanic data for analysis. This assumes that you have R and RStudio loaded.

Note : mosaic package is required for this if you want to run data yourself and not to simply view them. If you do not have this, run this code in your r-console independently:

```
install.packages("ggplot2")
```

Part 1: Reading data

We probably want to load the titanic data first. We probably want to load the mosaic library out of the way.

Loading Data:

We can accomplish both data loading and library call with the following script:

```
load("Titanic.Rdata")
library("mosaic")
```

Note: Always rerun/replay the code above when entering this data. The pre-ran scripts will remain intact but rerunning them might display errors. So reran this. Or if you see an error, know that this code might be the culprit.

Which Variables Are In Data?

Now that the data has been loaded, we probably want to see which data variables we will deal with! Below, we will use `names()` to print the variable names in our data to have them handy.

```
names(Titanic)
```

```
## [1] "Gender" "Age" "Name" "Fare" "Class" "Survived"
```

The `names()` function we just ran displayed the 6 variables within the Titanic Data which include Gender, Age, Name, Fare, Class and Survived.

Of course, you could have looked at the actual CSV file or RData file directly. But functions like `names()` are very useful when wrangling data such as JSON and similar data types.

Exploring Data Types:

The `sapply()` function is very useful for this. The data types do make sense.

```
sapply(Titanic,class)
```

```
##   Gender      Age      Name      Fare      Class  Survived
## "factor" "numeric" "factor" "numeric" "factor" "factor"
```

The output above does make sense; data types seem to match what we would expect. Age is numeric. And Gender is a 'factor', commonly known as string in other computer languages.

Another function we could have used is `str()`, but the output can be messy and dense. `str()` does provide more information on the variables in our data.

```
str(Titanic)
```

```
## 'data.frame':   1045 obs. of  6 variables:
## $ Gender   : Factor w/ 2 levels "Female","Male": 1 2 1 2 1 2 1 2 1 2 ...
## $ Age      : num  29 1 2 30 25 48 63 39 53 71 ...
## $ Name     : Factor w/ 1307 levels "Abbing, Mr. Anthony",...: 22 24 25 26 27 31 46 47 51 55 ...
## $ Fare     : num  211 152 152 152 152 ...
## $ Class    : Factor w/ 3 levels "Lower","Middle",...: 3 3 3 3 3 3 3 3 3 ...
## $ Survived: Factor w/ 2 levels "No","Yes": 2 2 1 1 1 2 2 1 2 1 ...
## - attr(*, "na.action")=Class 'omit' Named int [1:264] 16 38 41 47 60 70 71 75 81 107 ...
## .. ..- attr(*, "names")= chr [1:264] "16" "38" "41" "47" ...
```

As we can see, more information are provided. For instance, the output shows that there are 2 levels for Gender, “Famale” and “Male”. But `str()` can look a bit messy.

Note: We could have used `View(Titanic)` to open the spreadsheet in a difference pane or tab in RStudio. But that will require sifting through the spreadsheet. It’s good to familiarize with both `str()` and `sapply()` functions so we don’t have leave our tab.

Basic Data Tallying

There are multiple ways of tallying variables.

Using count format of `tally()`:

```
tally(~Gender, format = "count", data = Titanic)
```

```
## Gender
## Female   Male
##    388    657
```

Using proportion format of `tally()`:

Comparing Genders: