

Quantum Error Correction

Using Quantum Computing

Under guidance of
Prof. Jaideep Mulherkar

202001267 – Meet Bhatt
202003039 – Mukund Ladani
202003040 – Kashyap Halavadia



Why do we need QEC?

- 1) Each gate is slightly wrong.
- 1) Qubits get perturbed by small external forces
- 1) Measurements sometimes lie.

Remember that Quantum Computers are generally meant to perform huge computations, involving circuits which have large no of gates and qubits.

Physical and Logical Qubits

- 1) Textbook quantum algorithms assume that they are operating on perfect qubits (logical qubits).
- 1) Running these algos on physical qubits results in output that has no meaning.
- 1) Measurements sometimes lie.

Remember that Quantum Computers are generally meant to perform huge computations, involving circuits which have large no of gates and qubits.

Physical and Logical Qubits

- 1) Each of the gates that we use made out of physical qubits has some failure rate.
- 1) Desirable failure rate of a single or 2 qubit gate is 10^{-15} , but we have currently reached to failure rate of $1e-2$ only.
- 1) The way out is to make a logical qubit by using many physical qubits, that's what we do in QEC.
- 1) With 10,000 qubits it may be possible to have a failure rate of the formed logical qubit as low as 10^{-15} .

Error Correction

- 1) **Input**:- Some information to protect.
- 1) **Encoding**:- Transform the information to make it easier to protect
- 1) **Errors**:- Random perturbations of the encoded message.
- 1) **Decoding**:- Trying to deduce the input from the perturbed message

Repetition Codes

- 1) Make redundant copies of the logical qubit value on many physical qubits, this state is called encoded state.
- 1) The receiver will decode the message through majority voting.
- 1) Misunderstanding can only happen when the majority of the copies are flipped , its possible but it is unlikely.


Repetition Codes

P (probability that misunderstanding occurs decreases exponentially as we increase the no of copies i.e. d).

$$P = \sum_{n=d/2}^{n=d} \binom{d}{n} \cdot p^n (1-p)^{d-n} \approx \left(\frac{p}{1-p} \right)^{d/2}$$


Error correction in Computation

- 1) For computation, errors are introduced whenever we perform an operation.
- 1) We need to keep on correcting errors as they are introduced.
- 1) Can be done by constantly decoding and re-encoding



Error correction in Computation

4) But when we consider here qubits, the decoding requires measurements and that will destroy superposition.



Syndrome Measurements

- A decoding technique which only extracts the information that is required to find out where would have errors occurred . It doesn't measure the qubit values.
- It's not a logical qubit measurement at all, its information about the noise that has happened.

Quantum Repetition Code


- We use an extra qubit (ancilla qubit) for each pair of code qubits.
- It's not a logical qubit measurement at all, its information about the noise that has happened.

Quantum Repetition Code

- Can be done with some extra qubits: one for each pair of code qubits.
- They are initialized in state $|0\rangle$, and are used as the target for two CX gates
- The net effect is to measure the observable $Z_j Z_{j+1}$: the Z basis parity of the two qubits
- In short: whether they are the same or different

Quantum Repetition Code


- $\text{cx } |00\rangle = |00\rangle$
- $\text{cx } |01\rangle = |00\rangle$
- $\text{cx } |10\rangle = |11\rangle$
- $\text{cx } |11\rangle = |10\rangle$



Decoding

- Start with an unrealistically simple case: errors between parity measurements only (not during)
- Focus on identifying errors for now (not correcting)
- Look for changes between rounds
- Errors create pairs of 'defects'. Majority voting can be used to find a minimal pairing.


Decoding



Decoding

- Next, a simple model of noise in the measurements: they randomly lie
- Again, look for changes between rounds
- Bit flips create defects with space-like separation, measurement errors with time-like
- Pairing is now a 2D problem, majority voting won't work

Decoding



THANKYOU

