

**084Z4196****Temperature sensor, MBT 3560**

Process Connections: G1/4 , ISO 228-1-A, Temperature range [°C]: -50 - 200,
 Insertion length [mm]: 100, Output signal [mA]: 4 - 20, Protection tube
 material: AISI 316 Ti, Electrical connection: M12 x 1, Electrical connection
 size: 4 pin

PRODUCT DETAILS

Gross weight	0.15 kg
Net weight	0.14 kg
EAN	5702428956826
Ambient temperature max. [°C]	85 °C
Ambient temperature max. [°F]	185 °F
Connection material	Stainless steel
Connection standard	ISO 228
Connection type	G
Electrical conn. Male/Female	Male
Electrical connection	M12 x 1
Electrical connection size	4 pin
Electrical connection standard	EN 60947-5-2
Enclosure rating IP	IP65
Insertion length [in]	3.94 in
Insertion length [mm]	100 mm
Insertion type	Fixed
Output signal [mA] [Max]	20 mA
Output signal [mA] [Min]	4 mA
Packing format	Multi pack
Process connection Male/Female	Male
Process connection material	Stainless steel
Process Connections	G1/4 , ISO 228-1-A
Product group	Sensors
Product name	Temperature sensor
Protection tube diameter [in]	0.31 in
Protection tube diameter [mm]	8 mm
Protection tube material	AISI 316 Ti
Quantity per packing format	13 pc
Sensor element tolerance	< ± 1% FS
Sensor Insert	Fixed
Supply voltage [V] DC [Max]	32 V
Supply voltage [V] DC [Min]	10 V
Temperature range [°C] [Max]	200 °C
Temperature range [°C] [Min]	-50 °C
Temperature range [°F] [Max]	392 °F
Temperature range [°F] [Min]	-58 °F
Transmitter setting range [°C] [Max]	150 °C
Transmitter setting range [°C] [Min]	-50 °C



PRODUCT DETAILS

Transmitter setting range [°F] [Max]	302 °F
Transmitter setting range [°F] [Min]	-58 °F
Transmitter type	Integrated
Type	MBT 3560
Type designation	MBT 3560-0000-0100-60-415

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)