### AMR NETWORK INFRASTRUCTURE REQUIREMENTS

# **AMR NETWORK INFRASTRUCTURE REQUIF**

Document ID: NF-TECH-2024-003

Version: 2.0

Effective Date: January 15, 2024

**Classification: Confidential - Technical Documentation** 

Owner: NaviFloor Robotics, Inc.

#### 1. PURPOSE AND SCOPE

1. This document specifies the mandatory network infrastructure requ

2. These requirements apply to all customer facilities implementing N  2. NETWORK ARCHITECTURE REQUIREMENTS  1. Primary Network Infrastructure  - Dedicated VLAN for AMR operations  - Minimum 1Gbps network backbone  - IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization  - IPv6 compatibility with dual-stack support
2. NETWORK ARCHITECTURE REQUIREMENTS  1. Primary Network Infrastructure  - Dedicated VLAN for AMR operations  - Minimum 1Gbps network backbone  - IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization
2. NETWORK ARCHITECTURE REQUIREMENTS  1. Primary Network Infrastructure  - Dedicated VLAN for AMR operations  - Minimum 1Gbps network backbone  - IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization
2. NETWORK ARCHITECTURE REQUIREMENTS  1. Primary Network Infrastructure  - Dedicated VLAN for AMR operations  - Minimum 1Gbps network backbone  - IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization
2. NETWORK ARCHITECTURE REQUIREMENTS  1. Primary Network Infrastructure  - Dedicated VLAN for AMR operations  - Minimum 1Gbps network backbone  - IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization
2. NETWORK ARCHITECTURE REQUIREMENTS  1. Primary Network Infrastructure  - Dedicated VLAN for AMR operations  - Minimum 1Gbps network backbone  - IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization
1. Primary Network Infrastructure  Dedicated VLAN for AMR operations  Minimum 1Gbps network backbone  IEEE 802.1Q VLAN tagging support  Quality of Service (QoS) capabilities for real-time traffic prioritization
1. Primary Network Infrastructure  Dedicated VLAN for AMR operations  Minimum 1Gbps network backbone  IEEE 802.1Q VLAN tagging support  Quality of Service (QoS) capabilities for real-time traffic prioritization
Dedicated VLAN for AMR operations  Minimum 1Gbps network backbone  IEEE 802.1Q VLAN tagging support  Quality of Service (QoS) capabilities for real-time traffic prioritization
- Minimum 1Gbps network backbone  - IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization -
- Minimum 1Gbps network backbone  - IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization -
Minimum 1Gbps network backbone  - IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization -
- IEEE 802.1Q VLAN tagging support  - Quality of Service (QoS) capabilities for real-time traffic prioritization -
- Quality of Service (QoS) capabilities for real-time traffic prioritization -
Quality of Service (QoS) capabilities for real-time traffic prioritization -
<del>-</del>
- IPv6 compatibility with dual-stack support
ii ve companomy min dual chack cuppen

2. Wireless Network Specifications
-
IEEE 802.11ac Wave 2 or newer
-
Minimum -65dBm RSSI throughout operational areas
-
Maximum 2% packet loss rate
- Channel width: 40MHz minimum
-
- Wireless controller redundancy with N+1 configuration
3. Coverage Requirements
-
Minimum 30% overlap between adjacent access points

3-
Maximum -67dBm signal strength at cell edges
-
Complete coverage of operational areas including charging stations
-
Seamless roaming with 802.11r Fast BSS Transition support
3. SECURITY REQUIREMENTS

1. Network Security

\_

WPA3-Enterprise authentication

-

802.1X authentication for all AMR devices

\_

Dedicated RADIUS server for AMR authentication
-
Network segmentation with strict access control lists
-
Regular security audits and penetration testing
2. Data Protection
-
End-to-end encryption for all AMR communications
-
TLS 1.3 or higher for management traffic
-
Secure key storage and rotation procedures
-
Regular backup of configuration data

- -5-

Encrypted storage of mapping and navigation data

#### 4. PERFORMANCE REQUIREMENTS

1. Network Performance

Maximum latency: 20ms within local network

Jitter: < 5ms

Minimum bandwidth per AMR: 2Mbps sustained

Network availability: 99.99% uptime

\_

Maximum failover time: 50ms

2. System Monitoring

SNMP v3 monitoring capabilities

Real-time performance metrics collection

Automated alerting system

Historical performance data retention

Network analytics dashboard access

### **5. HARDWARE SPECIFICATIONS**

1. Netwørk Equipment
-
Enterprise-grade switches with PoE+ capability
-
Redundant power supplies
-
Hot-swappable components
-
Industrial-grade access points (IP67 rated where applicable)
-
Temperature-hardened equipment for industrial environments
2. Server Infrastructure
-
Dedicated physical or virtual servers for NaviFleet(TM) platform

- -8-

Minimum 16-core processors

\_

64GB RAM minimum

\_

RAID 10 storage configuration

-

Redundant power and cooling systems

### **6. IMPLEMENTATION REQUIREMENTS**

1. Pre-deployment Assessment

-

Site survey with RF mapping

-

Networkscapacity planning
-
Infrastructure upgrade assessment
-
Security vulnerability assessment
-
Integration point identification
2. Installation Procedures
-
Professional installation by certified technicians
-
Compliance with local electrical codes
-
Documentation of all network configurations

- 10 -

Performance baseline establishment

\_

User acceptance testing

### 7. MAINTENANCE AND SUPPORT

1. Regular Maintenance

-

Quarterly network performance reviews

-

Monthly security patches and updates

-

Regular firmware updates

-

Prevenţiγe maintenance schedule
-
Configuration backup procedures
2. Support Requirements
-
24/7 technical support availability
-
Maximum 4-hour response time for critical issues
-
Remote monitoring and diagnostics
-
Regular system health checks
-
Incident response procedures

## 8. COMPLIANCE AND DOCUMENTATION

1. Required Documentation
Network topology diagrams
-
Configuration management database
-
Security compliance reports
-
Performance monitoring logs
-
Incident response documentation
2. Regulatory Compliance

- 13 -

NIST Cybersecurity Framework adherence

-

ISO 27001 compliance where applicable

\_

Industry-specific regulatory requirements

-

Data privacy compliance

-

Environmental safety standards

#### 9. DISCLAIMER

This document contains confidential and proprietary information of Na Robotics, Inc. Any unauthorized use, disclosure, or reproduction is str prohibited. NaviFloor Robotics reserves the right to modify these requasion as necessary to maintain optimal system performance and security.

#### **10. DOCUMENT CONTROL**

Last Updated: January 15, 2024

Approved By: Marcus Depth, CTO

Document Owner: Technical Operations Department

Review Cycle: Annual

Next Review Date: January 15, 2025

