AMR PERFORMANCE OPTIMIZATION GUIDE

AMR PERFORMANCE OPTIMIZATION GUIDE

NaviFloor Robotics, Inc.

Document Version: 2.4

Last Updated: January 11, 2024

Classification: Confidential - Internal Use Only

1. INTRODUCTION AND SCOPE

1. This AMR Performance Optimization Guide ("Guide") is a proprieta

2. This Guide applies to all NaviFloor Series X-2000 and X-3000 AMR

2. DEFINITIONS

1. "Performance Metrics" refers to the quantifiable measurements of A

a) Navigation accuracy (0.5cm)

b) Path optimization efficiency (>95%)

c) Battery utilization rates

d) Load handling precision

e) Surface adaptation response time

2. "Optimization Parameters" means the configurable settings within t

3. PERFORMANCE BASELINE REQUIREMENTS

1. Minimum Performance Standards:

- Navigation precision: 2cm deviation from programmed path
- Obstacle detection range: 5.0m at 360
- Load capacity utilization: 98% of rated capacity
- Battery cycle efficiency: 85%
- Surface transition time: 1.5 seconds

2. Environmental Parameters:

- Operating temperature: 0 C to 45 C

Humidity tolerance: 10% to 90% non-condensing

-

Floor condition variance: Grade 2 per ASTM F2678

4. OPTIMIZATION PROCEDURES

1. Initial Calibration Protocol:

a) Execute terrain mapping sequence using proprietary LiDAR calibra

b) Perform multi-surface adaptive testing across all designated operat

c) Configure depth-sensing parameters according to facility specificati

d) Validate navigation mesh accuracy against facility CAD drawings

2. Performance Tuning Sequence:

a) Adjust motion control parameters based on load characteristics

b) Optimize path planning algorithms for facility-specific requirements

c) Fine-tune surface transition protocols for maximum efficiency

d) Calibrate sensor fusion parameters for environmental conditions

5. MONITORING AND MAINTENANCE

1. Regular Performance Assessments:

-

Daily: Basic navigation and obstacle avoidance tests

-

Weekly: Comprehensive performance metric evaluation

-

Monthly: Full system optimization review

-

Quarterly: Firmware update compatibility verification

2. Documentation Requirements:

- Maintain detailed logs of all optimization activities
- Record performance metric variations
- Document all parameter adjustments
- Archive baseline comparison data

6. SAFETY AND COMPLIANCE

1. All optimization procedures must comply with:

- ANSI/RIA R15.06-2012 safety standards

ISO 10218-1:2011 robotics safety requirements

- Company safety protocols document REF-SAF-2024-001

2. Safety Override Parameters:

- Emergency stop response time: 100ms
- Safety zone monitoring: 360 continuous
- Human detection sensitivity: Level 4 minimum

7. PROPRIETARY INFORMATION

1. This Guide contains confidential and proprietary information of Nav

2. Distribution of this Guide is restricted to authorized personnel who h

8. DISCLAIMER

1. This Guide is provided "as is" without any warranties, express or im

2. Implementation of these procedures must be performed by certified

9. VERSION CONTROL

Document Version: 2.4

Release Date: January 11, 2024

Approved By: Dr. Elena Kovacs, Chief Research Officer

10. EXECUTION

APPROVED AND ADOPTED:

NaviFloor Robotics, Inc.

By: _

Name: Dr. Elena Kovacs

Title: Chief Research Officer

Date: January 11, 2024