

ARCTIC-GRADE ACTUATOR PERFORMANCE ANALYSIS 2023

ARCTIC-GRADE ACTUATOR PERFORMANCE

CONFIDENTIAL AND PROPRIETARY

Polar Dynamics Robotics, Inc.

Document No.: PDR-TECH-2023-114

1. EXECUTIVE SUMMARY

This technical analysis documents the performance specifications and key parameters of Polar Dynamics Robotics' proprietary arctic-grade actuators deployed in the BlueCore(TM) autonomous mobile robot (AMR) platform.

analysis covers testing conducted between January 2023 and December 2023 at the company's Cold Environment Testing Facility in Rochester, Minnesota.

2. SCOPE OF ANALYSIS

1. This analysis encompasses:

- (a) Performance metrics for Model AG-2300 Series actuators
- (b) Environmental testing results from -40 C to +25 C
- (c) Durability assessments under varying load conditions
- (d) Compliance verification with ISO 9001:2015 standards
- (e) Integration compatibility with BlueCore(TM) navigation systems

2. Testing Parameters:

-

Operational temperature range: -40 C to +25 C

- - 2 -

Humidity range: 15% to 95% RH

-

Load capacity: 0-750kg

-

Duty cycle: 24/7 continuous operation

-

Test duration: 5,000 operational hours per unit

3. TECHNICAL SPECIFICATIONS

1. Actuator Specifications:

-

Model: AG-2300-X

-

Power: 48V DC

-

Peak torque: 450 Nm

-

Continuous torque: 280 Nm

-

Position accuracy: 0.02

-

Protection class: IP67

-

Weight: 12.4 kg

2. Cold-Weather Adaptations:

-

Proprietary synthetic lubricant (Patent Pending #US2023/0145789)

- - 4 -

Reinforced carbon fiber composite housing

-

Double-sealed bearing system

-

Integrated thermal management system

-

Arctic-grade electrical insulation

4. PERFORMANCE RESULTS

1. Temperature Response:

-

Start-up time at -40 C: <3.5 seconds

-

Thermal equilibrium achieved: 15 minutes

-

Power consumption variation: 7% across temperature range

-

Position holding accuracy: 99.98% at all temperatures

2. Durability Metrics:

-

Mean Time Between Failures (MTBF): 50,000 hours

-

Wear rate at -40 C: <0.002mm/1000 hours

-

Impact resistance: Certified to IEC 60068-2-27

-

Vibration tolerance: Meets MIL-STD-810H

5. COMPLIANCE AND CERTIFICATION

1. Standards Compliance:

-

ISO 9001:2015

-

IEC 60529 (IP67)

-

CE Marking (European Union)

-

UL 1740 (Robotics Equipment)

-

CSA C22.2 No. 73

2. Testing Methodology:

- - 7 -

ASTM D2240 (Hardness)

-

ASTM B117 (Salt Spray)

-

IEC 60068-2-1 (Cold Testing)

-

IEC 60068-2-14 (Temperature Cycling)

6. INTEGRATION SPECIFICATIONS

1. BlueCore(TM) Compatibility:

-

Native protocol support

-

Real-time performance monitoring

-

Predictive maintenance integration

-

Autonomous fault detection

-

Remote diagnostics capability

2. Control Interface:

-

CAN bus communication

-

EtherCAT support

-

RS-485 redundancy

- - 9 -

Wireless monitoring capability

-

Emergency stop integration

7. LIMITATIONS AND DISCLAIMERS

1. This analysis is provided for internal evaluation purposes only and is not intended for external use.
2. Performance metrics are based on controlled testing environments and may vary in real-world applications.
3. All specifications and results are subject to Polar Dynamics Robotics Ltd. internal review and approval.

8. CERTIFICATION

The undersigned hereby certify that the testing and analysis described herein were conducted in accordance with the applicable standards and procedures.

were conducted in accordance with industry standards and Polar Dynamics Robotics' quality management system.

Approved by:

/s/ Dr. James Barrett

—

Dr. James Barrett

Chief Robotics Officer

Date: December 15, 2023

/s/ Marcus Chen

—

Marcus Chen

Chief Technology Officer

Date: December 15, 2023

9. CONFIDENTIALITY NOTICE

This document contains confidential and proprietary information belonging to Polar Dynamics Robotics, Inc. Any unauthorized copying, distribution, or use of this document is strictly prohibited and may result in legal action.

Document Control: PDR-TECH-2023-114

Version: 1.0

Last Updated: December 15, 2023

