ATH PLANNING OPTIMIZATION	FOR AUTONOMOUS FLOOR MAINTENANC
	PATH PLANNING OPTIMIZATION FOR AUT
	PROPRIETARY AND CONFIDENTIAL
	NaviFloor Robotics, Inc.
	Last Updated: January 11, 2024

1. OVERVIEW AND SCOPE

1. This document describes the proprietary path planning optimization algorithms also also be a second of the proprietary path planning optimization algorithms.

1-
2. The Path Planning System encompasses the complete technological frame
2. TECHNICAL SPECIFICATIONS
- 1. Core Components
- Dynamic Terrain Mapping Module (DTM-2000)
-
Adaptive Route Generation Algorithm (ARGA v4.2)
Multi-Surface Classification System (MSC-23)
Real-time Path Adjustment Protocol (RPAP)

- 2 -

- 2. Key Features
- (a) Multi-level surface detection and classification
- (b) Real-time obstacle avoidance with predictive modeling
- (c) Energy-optimized route planning
- (d) Fleet coordination and traffic management
- (e) Machine learning-based performance optimization

#### 3. INTELLECTUAL PROPERTY PROTECTION

-

1. Patent Protection

The Path Planning System is protected under the following:

\_

U.S. Patent No. 11,789,XXX ("Adaptive Navigation System for Autonomo
-
U.S. Patent Application No. 17/XXX,XXX ("Method for Multi-Surface Cl.
-
PCT Application No. PCT/US2023/XXXXX
-
2. Trade Secrets
The following components are maintained as trade secrets:
(a) Surface friction coefficient calculation methods
(b) Energy consumption optimization algorithms
(c) Fleet coordination protocols
(d) Machine learning training datasets

# 4. IMPLEMENTATION SPECIFICATIONS

1. System Requirements

Minimum processing power: 4.2 GHz quad-core processor

RAM: 16GB DDR4

Storage: 256GB SSD

Sensor array: NaviFloor LiDAR Model NF-L2024 or higher

Operating System: NaviFloor OS v3.5 or higher

- 5 -

2. Performance Metrics

\_

Path optimization completion time: <500ms

\_

Obstacle detection accuracy: 99.98%

-

Surface classification accuracy: 99.95%

-

Maximum supported fleet size: 50 units

-

Minimum turning radius: 0.75m

# **5. SECURITY PROTOCOLS**

- 6 1. Data Protection
(a) All path planning data is encrypted using AES-256 encryption
(b) Secure boot verification system
(c) Encrypted communication channels between units
(d) Regular security audits and penetration testing
2. Access Controls
Role-based access management
Multi-factor authentication for system modifications

Audit logging of all system access and changes

### 6. PRÓPRIETARY NOTICES

1. All components of the Path Planning System, including but not limited to
2. Any unauthorized use, reproduction, or distribution is strictly prohibited a

#### 7. MAINTENANCE AND UPDATES

1. Regular system updates are provided through the NaviFloor Update Serve

2. Critical security patches are automatically deployed

-

3. Performance optimization updates are released quarterly
-
4. System logs are retained for 90 days
8. COMPLIANCE AND CERTIFICATION
6. COMI LIANCE AND CERTIFICATION
-
1. The Path Planning System complies with:
_
ISO/TS 15066:2016 (Robots and robotic devices)
iso, is isomorphic (Robots and robotic devices)
-
IEC 61508 (Functional Safety)
-
CE Marking requirements
-

UL 3100 certification for automated guided vehicles

## 9. CONFIDENTIALITY

1. This document contains confidential and proprietary information of NaviF

2. Distribution of this document is restricted to authorized personnel only an

## **AUTHENTICATION**

Document ID: NF-PPO-2024-011

Version: 4.2

Classification: CONFIDENTIAL

#### Approved by:

\_

Dr. Elena Kovacs

Chief Research Officer

NaviFloor Robotics, Inc.

Date: January 11, 2024

-

Marcus Depth

Chief Technology Officer

NaviFloor Robotics, Inc.

Date: January 11, 2024

