

TEMPERATURE MAPPING STUDY PROTOCOL

TEMPERATURE MAPPING STUDY PROTOCOL

Polar Dynamics Robotics, Inc.

Protocol Number: TMP-2024-001

Effective Date: January 15, 2024

1. PURPOSE AND SCOPE

1 This Temperature Mapping Study Protocol ("Protocol") establishes the

2 This Protocol applies to all temperature mapping validation studies

2. DEFINITIONS

1 "Temperature Mapping" means the documented measurement of temperature

2 "Test Environment" refers to the controlled temperature facility where

3 "Critical Operating Parameters" means the essential performance m

4 "Validation Period" means the minimum 72-hour continuous monitor

3. RESPONSIBILITIES

1 Quality Assurance Department shall:

-

Oversee implementation of this Protocol

- - 2 -

Review and approve mapping study results

-

Maintain temperature mapping documentation

-

Issue final validation reports

2 Engineering Department shall:

-

Calibrate all temperature monitoring equipment

-

Position temperature sensors according to mapping grid

-

Monitor data collection systems

-

Analyze raw temperature data

4. EQUIPMENT AND MATERIALS

1 Required Equipment:

-

Calibrated temperature sensors (minimum accuracy 0.5 C)

-

Data logging system with minimum 1-minute recording intervals

-

BlueCore(TM) diagnostic interface system

-

Environmental chamber capable of maintaining -40 C

-

Backup power systems

2 Documentation Requirements:

-

Equipment calibration certificates

-

Sensor location diagrams

-

Raw data logs

-

Analysis worksheets

-

Deviation reports

5. PROCEDURE

1 Pre-Study Requirements

- a) Verify calibration status of all measurement equipment
- b) Document initial AMR configuration settings
- c) Create detailed sensor placement map
- d) Establish baseline environmental conditions

2 Study Execution

- a) Position minimum 15 temperature sensors at critical points
- b) Initialize data logging system
- c) Begin continuous 72-hour monitoring period
- d) Record all environmental events and deviations
- e) Monitor BlueCore(TM) performance metrics

3 Data Analysis

- a) Download complete temperature dataset

- b) Calculate mean kinetic temperature
- c) Identify temperature extremes and variations
- d) Evaluate temperature recovery times
- e) Compare results against acceptance criteria

6. ACCEPTANCE CRITERIA

1 Temperature Stability

-

Maximum deviation: 2.0 C from setpoint

-

Recovery time: 30 minutes after door opening

-

Temperature uniformity: 1.5 C across mapping points

2 BlueCore(TM) Performance

-

Navigation accuracy: 98% at -40 C

-

Power system efficiency: 85% of rated capacity

-

Sensor functionality: 100% operational

7. DOCUMENTATION AND REPORTING

1 Required Documentation

-

Completed temperature mapping protocol

-

Raw data files

- - 8 -

Calibration records

-

Deviation reports

-

Analysis worksheets

-

Final validation report

2 Report Contents

-

Executive summary

-

Study methodology

-

Results and data analysis

-

Conclusions and recommendations

-

Supporting documentation

8. DEVIATIONS AND CORRECTIVE ACTIONS

1 Any deviation from this Protocol must be documented and approved

2 Corrective actions must be implemented and documented for all dev

9. PROTOCOL APPROVAL

This Temperature Mapping Study Protocol has been reviewed and ap

Quality Assurance Director:

Date: _

Engineering Director: _

Date: _

Chief Technology Officer:

Date: _

10. REVISION HISTORY

Version | Date | Description | Approved By

---|---|---|---

0 | 2024-01-15 | Initial Release | M. Chen

1 | 2024-01-20 | Updated acceptance criteria | E. Frost

End of Document

