DYNAMIC OBSTACLE DETECTION SYSTEM DOCUMENTATION

DYNAMIC OBSTACLE DETECTION SYSTEM

NaviFloor Robotics, Inc.

Document Version: 3.2.1

Last Updated: January 11, 2024

Classification: CONFIDENTIAL

1. SYSTEM OVERVIEW

1. This Dynamic Obstacle Detection System Documentation ("Docum

2. The System utilizes advanced LiDAR sensors, depth-mapping algo-
2. TECHNICAL SPECIFICATIONS
1. Sensor Configuration
- Primary LiDAR Array: Dual NS-450X sensors
- Secondary Depth Sensors: Four (4) DM-8800 units
- Tertiary Motion Detection: Integrated IMU array
- Scanning Frequency: 40Hz nominal operation
2. Detection Parameters

- -2-

Minimum Obstacle Size: 2.5cm at 3m distance

-

Maximum Detection Range: 12m forward, 8m lateral

_

Angular Resolution: 0.13 horizontal, 0.18 vertical

-

Response Latency: <15ms from detection to actuation

3. PROPRIETARY ALGORITHMS

1. The System incorporates the following proprietary algorithms:

-

TerrainMap(TM) surface classification system

-

DynamigPath(TM) trajectory planning
-
ObstacleNet(TM) object recognition and classification
-
AdaptiveNav(TM) real-time route optimization
2. All algorithms listed in Section 3.1 are protected under U.S. Patent
-
US 11,234,567 B2
-
US 11,345,678 B2
-
US 11,456,789 B2

4. SAFETY FEATURES

1. Emergency Stop Protocol
The System maintains three-tier emergency stop capabilities:
-
Level 1: Soft stop (controlled deceleration)
-
Level 2: Hard stop (immediate motor cutoff)
-
Level 3: System-wide fleet shutdown
2. Redundancy Systems
-
Dual-redundant sensor arrays
-
Triple-redundant processing units
-

Backup power systems with 30-minute operation capability

5. COMPLIANCE AND CERTIFICATION

1. The System meets or exceeds the following standards:
-
ISO 13849-1:2015 (Performance Level D)
-
IEC 61508 (SIL 2)
-
ANSI/RIA R15.06-2012
-
CE Marking requirements for industrial machinery

2. Testing and Validation

All System components undergo:
-
Factory Acceptance Testing (FAT)
-
Site Integration Testing (SIT)
-
Periodic Performance Verification (PPV)
6. INTELLECTUAL PROPERTY PROTECTION

1. This Documentation and all technical information contained herein

2. No part of this Documentation may be reproduced, distributed, or to

7. WARRANTY AND LIMITATION OF LIABILITY

1. The Gampany warrants that the System will perform substantially in
2. THE COMPANY MAKES NO OTHER WARRANTIES, EXPRESS O
8. CONFIDENTIALITY
This Documentation contains confidential and proprietary information.
2. Recipients shall:
-
Maintain the confidentiality of this Documentation
-
Limit access to authorized personnel only
Return or destroy all copies upon request

8 - Report any unauthorized disclosure immediately
9. EXECUTION
IN WITNESS WHEREOF, the undersigned acknowledges receipt and Documentation and agrees to be bound by its terms.
NaviFloor Robotics, Inc.
By:
Name: Dr. Elena Kovacs
Title: Chief Research Officer
Date: _
Recipient:

By: -9-

Name: _

Title:

Date: _

