

# **OBSTACLE AVOIDANCE ALGORITHM FOR CONFINED SPACES**

## **OBSTACLE AVOIDANCE ALGORITHM FOR**

**PROPRIETARY AND CONFIDENTIAL**

NaviFloor Robotics, Inc.

Document ID: IP-ALG-2023-142

Version: 2.1

Last Updated: December 15, 2023

### **1. ALGORITHM OVERVIEW AND SCOPE**

-

1. This document describes the proprietary obstacle avoidance algorithm ("A

-

2. The Algorithm comprises a multi-layered decision matrix incorporating:

- (a) Real-time LiDAR sensor data processing
- (b) Depth-mapping neural network calculations
- (c) Predictive path planning optimization
- (d) Dynamic obstacle classification protocols
- (e) Emergency override parameters

**2. TECHNICAL SPECIFICATIONS**

-

1. Core Components:

-

Primary sensor array integration protocol

-

Multi-surface terrain analysis module

-

Velocity vector calculation engine

-

Proximity threshold management system

-

Emergency stop trigger mechanism

-

2. Performance Parameters:

-

Minimum detection range: 0.05 meters

-

Maximum detection range: 25 meters

-

Angular resolution: 0.25 degrees

-

Processing latency: <15 milliseconds

-

Accuracy rate: 99.97% in standard conditions

### **3. PROPRIETARY RIGHTS AND PROTECTION**

-

1. The Algorithm, including all component methodologies, source code, and

-

2. Access to this document and the information contained herein is strictly lin

## **4. IMPLEMENTATION REQUIREMENTS**

-

### **1. Hardware Requirements:**

-

Minimum processor: NaviFloor N-Series or equivalent

-

Required sensors: LiDAR Model NF-350 or higher

-

Memory allocation: 4GB dedicated RAM

-

Network latency: <5ms

-

### **2. Software Dependencies:**

- - 5 -

NaviFloor Core Framework v4.2 or higher

-

Terrain Mapping Module v2.1

-

Sensor Fusion Package v3.0

-

Safety Protocol Suite v2.5

## **5. SAFETY AND COMPLIANCE**

-

1. The Algorithm incorporates mandatory safety features including:

-

Redundant obstacle detection systems

- - 6 -

Fail-safe protocols for sensor malfunction

-

Emergency stop capabilities

-

Human presence detection prioritization

-

Dynamic speed adjustment protocols

-

2. Compliance with Standards:

-

ISO/TS 15066:2016

-

ANSI/RIA R15.06-2012

- - 7 -

EN ISO 13849-1:2015

-

IEC 61508-1:2010

## **6. VERSION CONTROL AND UPDATES**

-

1. This document reflects Version 2.1 of the Algorithm, released December 1

-

2. Previous versions:

-

v2.0: September 30, 2023

-



v1.5: June 15, 2023

-

v1.0: March 1, 2023

## **7. CONFIDENTIALITY AND DISTRIBUTION**

-

1. This document contains trade secrets and confidential information of Navi

-

2. Distribution limited to:

-

NaviFloor executive management

-

Authorized development team members

- - 9 -

Licensed implementation partners

-

Qualified potential acquirers under executed NDA

## **8. CERTIFICATION AND APPROVAL**

The undersigned hereby certify that this document accurately represents the current specification of NaviFloor Robotics' Obstacle Avoidance Algorithm Confined Spaces.

APPROVED BY:

—

Dr. Elena Kovacs

Chief Research Officer

Date: December 15, 2023

—

Marcus Depth

Chief Technology Officer

Date: December 15, 2023

—

Richard Torres

Chief Operating Officer

Date: December 15, 2023

## **9. DOCUMENT CONTROL**

Document Owner: Research & Development Department

Security Classification: Confidential - Level 1

Review Cycle: Quarterly

Next Review Date: March 15, 2024

Document Storage: NaviFloor Secure Repository - IP/ALGO/2023/142

