

# **MULTI-FLOOR NAVIGATION AND MAPPING SYSTEM**

## **MULTI-FLOOR NAVIGATION AND MAPPING**

### **TECHNICAL SPECIFICATION AND IP DOCUMENTATION**

*Document Reference: IP-NAV-2023-014*

*Last Updated: December 15, 2023*

#### **1. PROPRIETARY NOTICE**

This document contains confidential and proprietary information belonging exclusively to NaviFloor Robotics, Inc., a Delaware corporation ("Company"). This system specification describes the Company's protected intellectual

property relating to multi-floor autonomous navigation and mapping technology.

## **2. SYSTEM OVERVIEW**

1. The Multi-Floor Navigation and Mapping System ("System") comprises the following elements:
2. The System incorporates the following core technological components:
  - a) Advanced LiDAR-based simultaneous localization and mapping (SLAM) algorithms
  - b) Multi-sensor fusion architecture
  - c) Proprietary depth-sensing algorithms
  - d) Dynamic obstacle avoidance protocols
  - e) Real-time map updating and sharing capabilities

## **3. PROTECTED INTELLECTUAL PROPERTY**

## 1. Patents

-

US Patent No. 11,234,567: "Method for Real-Time Multi-Floor Robot I

-

US Patent No. 11,345,678: "System for Autonomous Floor Transition

-

PCT Application No. PCT/US2023/012345 (pending)

## 2. Trade Secrets

-

Proprietary sensor calibration methodologies

-

Custom SLAM optimization algorithms

-

Floor transition detection parameters

- - 3 -

Surface material classification database

-

Map merge protocols for multi-robot deployments

## **4. TECHNICAL SPECIFICATIONS**

### **1. Mapping Capabilities**

-

Resolution: 1cm spatial accuracy

-

Maximum mapped area: 100,000 sq ft per floor

-

Maximum number of floors: 12

-

Update frequency: 10Hz

-

Map storage format: Proprietary .NFM format

## 2. Navigation Parameters

-

Maximum navigation speed: 2.0 m/s

-

Minimum hallway width: 1.2m

-

Maximum slope handling: 15 degrees

-

Obstacle detection range: 25m

-

Position accuracy: 3cm

## 5. SYSTEM ARCHITECTURE

### 1. Hardware Components

- 

Custom-designed LiDAR array

- 

Inertial Measurement Unit (IMU)

- 

Depth cameras

- 

Floor transition sensors

- 

Edge computing unit

### 2. Software Components

- - 6 -

NaviCore(TM) navigation engine

-

MapFusion(TM) multi-floor mapping module

-

ObstacleNet(TM) detection system

-

FloorTransit(TM) elevation change handler

-

CloudSync(TM) map distribution system

## **6. IMPLEMENTATION REQUIREMENTS**

1. The System shall only be implemented on Company-approved hardware.

2. All System components must maintain specified security protocols:

-

AES-256 encryption for data transmission

-

Secure boot verification

-

Signed firmware updates

-

Access control authentication

## **7. CONFIDENTIALITY AND USAGE RESTRICTIONS**

1. This document and all technical information contained herein are s

2. No portion of the System may be reverse engineered, decompiled,



## **8. WARRANTY AND LIABILITY**

1. The Company makes no warranties regarding the System beyond the
2. The Company shall not be liable for any damages arising from una

## **9. CERTIFICATION**

The undersigned hereby certifies that this document accurately represents the technical specifications and intellectual property status of the Multi-Floor Navigation and Mapping System as of the date indicated below.

NAVIFLOOR ROBOTICS, INC.

**By:**

Dr. Elena Kovacs

Chief Research Officer

Date: December 15, 2023

## **10. DOCUMENT CONTROL**

Version: 3.2

Document ID: IP-NAV-2023-014

Classification: CONFIDENTIAL

Distribution: Authorized Personnel Only

Review Date: June 15, 2024

[END OF DOCUMENT]

