

# PROPRIETARY ALGORITHM FOR ICE DETECTION AND AVOIDANCE

## PROPRIETARY ALGORITHM FOR ICE DETECTION AND AVOIDANCE

CONFIDENTIAL AND PROPRIETARY

*Last Updated: January 11, 2024*

*Document ID: PDR-IP-2024-011*

### 1. OVERVIEW AND SCOPE

1. This document describes the proprietary algorithm ("Ice Detection Algorithm") used by the Company to detect and avoid ice.
2. The Algorithm is a core component of the Company's BlueCore(TM) system.

## 2. TECHNICAL SPECIFICATIONS

1. The Ice Detection Algorithm utilizes a multi-modal sensing approach:

- a) Infrared thermography
- b) LiDAR point cloud analysis
- c) Proprietary surface reflection modeling
- d) Machine learning-based pattern recognition

2. Core Algorithm Components:

-

Primary detection module (PDM-v4.2)

-

Environmental analysis engine (EAE-v2.1)

-

Real-time path optimization system (RPOS-v3.0)

-

Predictive maintenance calculator (PMC-v1.5)

### **3. INTELLECTUAL PROPERTY PROTECTION**

1. The Algorithm is protected through:

-

Patent protection (as referenced in Section 1.2)

-

Trade secret protection

-

Copyright registration (TX 9-247-385)

-

Contractual safeguards

## 2. Access Control Protocols:

-

Level 1: Source code access (CTO, Chief Robotics Officer only)

-

Level 2: Implementation documentation (Engineering team leads)

-

Level 3: Operational specifications (Technical staff)

## 4. IMPLEMENTATION REQUIREMENTS

### 1. Hardware Requirements:

-

BlueCore(TM) Processing Unit v2.0 or higher

-

Minimum 4 thermal sensors (Frost-Series TS400)

- - 4 -

Dedicated NVIDIA TX2i or equivalent processor

-

32GB RAM minimum configuration

## 2. Software Dependencies:

-

BlueCore(TM) Operating System v4.5+

-

Python 3.9 or higher

-

CUDA 11.4+

-

Proprietary sensor fusion framework v2.3

## 5. PERFORMANCE SPECIFICATIONS

### 1. Operating Parameters:

-

Temperature range: -40 C to +5 C

-

Humidity range: 15% to 95%

-

Detection accuracy: 98.7% (validated)

-

Response time: <50ms

### 2. Validation Metrics:

-

False positive rate: <0.3%

- - 6 -

False negative rate: <0.1%

-

System reliability: 99.99% uptime

## **6. CONFIDENTIALITY AND SECURITY**

1. This Algorithm is classified as Tier 1 Confidential Information under

2. Security Measures:

-

AES-256 encryption for all stored data

-

Secure boot verification

-

Runtime integrity checking

-

Automated audit logging

## **7. LICENSING AND USAGE**

1. The Algorithm may only be used in Company-manufactured devices

2. Prohibited Activities:

-

Reverse engineering

-

Unauthorized modification

-

Third-party implementation



- - 8 -

External distribution

## **8. MAINTENANCE AND UPDATES**

### 1. Update Schedule:

-

Major versions: Bi-annual

-

Security patches: Monthly

-

Emergency fixes: As needed

### 2. Version Control:

-

GitHub Enterprise repository

-

Mandatory code review process

-

Automated testing requirements

## **9. LEGAL NOTICES**

1. This document and the Algorithm described herein are protected by

2. CONFIDENTIALITY NOTICE: This document contains confidential

## **10. DOCUMENT CONTROL**

Document Owner: Marcus Chen, Chief Technology Officer

Technical Reviewer: Dr. James Barrett, Chief Robotics Officer

Legal Reviewer: Victoria Wells, CFO

Approved by:

Dr. Elena Frost, Ph.D.

CEO & Co-founder

Polar Dynamics Robotics, Inc.

Date: January 11, 2024

Marcus Chen

Chief Technology Officer

Polar Dynamics Robotics, Inc.

Date: January 11, 2024

