7 8

should be an Apollo 77C-140 Series -Ball valve

		Murphy-PFFS-					
Mark	QУ	Description	End 1	End 2	Lft	LDec	Size
4	1	Std Wt SA234 WPB CS BW RED TEE					4x3
3	+	T-134 Gate Valve					3/4
1	1	150lb RF Sch 40 Bore SA105 CS WN Flg					3
9	1	Std Wt SA234 WPB CS BW Cap					4
7	1	Std Wt SA234 WPB CS BW LR 90 Deg EII					4
6	1	3000∦ FS Thread-0-Let			1 1/16"	1.063	3/4x4
2	1	Sch 40 SA-53B CS Smls Pipe PE	BEV	BEV	5 7/8°	5.875	3
8	1	Sch 40 SA-53B CS Smls Pipe PE	BEV	BEV	5'-2 1/4"	62.235	4
5	1	Sch 80 A106B CS SMLS Pipe	MPT	MPT	3"	3.000	3/4

/4 3	314-997-6600 phone BIMCAD@murphy-stl.com								
4						APP			
/4 3 4 4 4x4 3 4 /4	ATION -		COMMENTS	MURPHY WPS#		DRN CHK			
4	IENTA IN TIGHT	NO	SO			DRN			
/4	TATIC TATIC TH'D	:ICATI			-				
	FLANGE WEIGHT/ORIENTATION FITTING ORIENTATION BOLTS/CPLG'S/TH'D TIGHT	SPOOL IDENTIFICATION	PWHT	¥					
	NGE V		EST		$\ $	z			
	FLA FIT	SPC	HYDRO 1	≨		DESCRIPTION			
	Ļ.	1	X-RAY HYDRO TEST PWHT	_		DESC			
	QA/QC ACCEPT		×	_					
	SAC		ASME	¥	-				
	A/Q($\frac{1}{1}$	DATE			
	Ø		SPEC.	¥	•	REV			
	ARCH BUILDING 3 CUP				REV O				
	OILE UILE	ر م			u.				
	Н В.	SFUULS	Z		or 1				
	ARCH 3 CUP	ر ا	2 VFNT		SHT/NO				
	ESEA NRB	, LO2	CH#2		돐				
	R K			'	Ę,				
	S/18/2021 WUSM RESE/	SERVICE NAMI		20					
	<u> </u>		<u></u>		XING NO. A-UPL2-120				
	3/2021					٦ آ [
	5/18	5			ACKING NO.) 			