Murphy-PFFS-SPOOL-BOM								
Mark	Qty	Description	End 1	End 2	Lft	LDec	Size	
3	1	Style 107N QuickVic EHP Pnt Rigid Cpl					6	
1	1	Std Wt SA234 WPB CS BW LR 90 Deg Ell					6	
2	1		Grooved End		6*	6.000	6	
4	1	Sch 40 SA-53B CS ERW Pipe PE	BEV	Grooved End	18'-0 13/16"	216.792	6	



CONSTRUCTORS CHARMERS MECHANICAL MIDUSTRIAL

1233 N. Price Rd.
St. Louis, MO 63132–2303
314–997–6600 phone
BIMCAD@murphy-stl.com

4/2021	WIICH DESERBEL BIII DING	O/VC	QA/QC ACCEPT	;EPT	FLANG	E WEIGHT	FLANGE WEIGHT/ORIENTATION
					FITTING	FITTING ORIENTATION	ATION
	NKB COF				BOLTS/	/CPLG'S/T	BOLTS/CPLG'S/TH'D TIGHT
	LVL02 SPOOLS				COGS	SPOOL INFINITION	NOITAC
	SERVE MANE				0 0	וווווו	
		SPEC.	ASME	X-RAY	SPEC. ASME X-RAY HYDRO TEST PWHT	PWHT	COMMENTS
		*	VIA.	VIV	**	AIA	TOWN AIRCHING THE TITLE THE TITLE THE TITLE THE

REV O

-04

Φ.	4

3	