

	Murphy-PFFS-SPOOL-BOM							
Mai	k Qty	Description	End 1	End 2	Lft	LDec	Size	CONSTRUCTORS •ENGINEERS
7	5	Std Wt SA234 WPB CS BW CONC RED					20x14	1233 N. Price St. Louis, MO
17	5	150lb FF Sch 40 Bore SA105 CS WN Flg					20	314-997-66
3	15	150lb RF Sch 40 Bore SA105 CS WN Flg					14	BIMCAD@mur
12	15	Style W77 Rigid Coupling					20	
15	5	150# CS Flange Bolt Set					20 (1-1/8x5-1/2)	
14	5	150# FF Garlock Gasket 1/16 Thick					20	WEIGHT/ORIENTATION ORIENTATION :PLG'S/TH'D TIGHT DENTIFICATION
5	10	150# RF Garlock Gasket 1/16 Thick					14	.AT∥ 11
2	10	150lb CS Flange Cap Screw Set					14 (1x2-3/4)	IENTA IN TIGHT
1	5	LD-1000 Butterfly Valve					14	AND TO
9	5	150 lb Brz 2pc FP Ball Valve Thd					2	T/C TH'I
8	5	Std Wt SA234 WPB CS BW LR 90 Deg Ell					20	SH: IS I
10	5	3000# FS Thread-0-Let			1 1/2"	1.500	2x20	E WEIGHT/ORIEN 3 ORIENTATION CPLG'S/TH'D TIG IDENTIFICATION
16	5	Std Wt SA-53B CS ERW Pipe PE	Grooved End	BEV	2'-7 3/8"	31.351	20	G C C C C C C C C C C C C C C C C C C C
13	10	Std Wt SA-53B CS ERW Pipe PE	Grooved End	Grooved End	10"	10.000	20	FLANGE WEIGHT/OF FITTING ORIENTATIC BOLTS/CPLG'S/TH'D SPOOL IDENTIFICAT
18	5	Std Wt SA-53B CS ERW Pipe PE	BEV	Grooved End	6*	6.000	20	FERS
11	5	Std SA-53B CS Smls Pipe NIP x 4	MPT	MPT	4"	4.000	2	1
6	5	Valve_Balancing_14 (350)_788					14	EPT
		•						

QTY 5

FLANGE WEIGHT/ORIENTATION
FITTING ORIENTATION
BOLTS/CPLG'S/TH'D TIGHT
SPOOL IDENTIFICATION QA/QC ACCEPT WUSM RESEARCH BUILDING NRB LVL03 CT SPOOLS TWS LVL03 Service name

1233 N. Price Rd. St. Louis, MO 63132-2303 314-997-6600 phone BIMCAD@murphy-stl.com

CT-1 THRU CT-5 OUTLET