	Murphy-PFFS-SPOOL-BOM							
ſ	Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
ſ	4	1	XH SA234 WPB CS BW LR 90 Deg Ell					4
Ī	2	1	XH SA234 WPB CS BW 45 Deg Ell					4
Ī	1	1	XH SA-53B CS SMLS Pipe	BEV	BEV	10'-4"	124.014	4
	3	1	XH SA-53B CS SMLS Pipe	BEV	BEV	1 11/16"	1.664	4



CONSTRUCTORS ENGINEERS MECHANICAL INDUSTRIAL

1233 N. Price Rd.
St. Louis, MO 63132-2303
314-997-6600 phone
BIMCAD@murphy-stl.com

21	MSIIM	פני	DESERBEL BILL DING	JNIC	QA	QA/QC ACCEPT)EPT	FLANG	E WEIGH	FLANGE WEIGHT/ORIENTATION	ATION	
		<u>i</u>	SEANCH DOLL		•			FITTIN	FITTING ORIENTATION	ATION		
			אא					BOLTS	/CPLG'S/T	BOLTS/CPLG'S/TH'D TIGHT	⊢	
								SPOO	SPOOL IDENTIFICATION	CATION		
Ī	TOWARD IN THE	إ)]
	SERVICE NAM		(Ľ	SPEC.	ASME	X-RAY	X-RAY HYDRO TEST PWHT	PWHT	Ö	COMMENTS	
) ב		¥	Ą	¥	Ą	Ą	ALIRPHY WPS#	7	
					:				:			
7	FIG.	. `	SHT/NO	° کی د								
_	.JE	_	l of l	O RE	REV DATE	TE T	DES	DESCRIPTION		DRN	DRN CHK APP	APP

2 H. 45 —10½6"— T.L.
H. 45
, , , , , , , , , , , , , , , , , , ,
' T.L. '
No refle
Φ