		Murphy-PFFS-	SP	00L-	-BON	1	
Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
5	1	Style 107 EHP Pnt QuickVic Rigid Coupling					4
2	1	Std Wt SA234 WPB CS BW LR 90 Deg EII					4
1	1	Sch 40 SA-53B CS ERW Pipe PE	BEV	Grooved End	6 3/4"	6.722	4
4	1	Sch 40 SA-53B CS ERW Pipe PE	BEV	Grooved End	4'-4 5/8"	52.634	4



CONSTRUCTORS CHARMERS MECHANICAL MIDUSTRIAL

1233 N. Price Rd.
St. Louis, MO 63132–2303
314–997–6600 phone
BIMCAD@murphy-stl.com

COMMENTS	8	WHT
	ENTIFICATION	ENTIFIC
⊨	LG'S/TH'D TIGHT	-G'S/TF
	VOIT	RIENTATION
'ATION	/EIGHT/ORIENTATION	EIGHT,

			こしつつてつびころ)) [
į						ŽI L L L	FITTING ORIENTATION	VOIT
C						BOLTS	BOLTS/CPLG'S/TH'D TIG	4'D TIG
Ŋ						SPOOL	SPOOL IDENTIFICATION	ATION
		SPEC.		ASME	X-RAY	X-RAY HYDRO TEST PWHT	THW	,
		AN	2		¥	¥N.	₹N	MURPHY
			•	•				
	실 (0						

ı		dS	Z	•	0
SM RESEARCH BUILDING NRB CUP LVL02 SPOOLS	E NAME	CHWP HPC		210	GIY. SHI/NO REV

1 or 1

WUS

PREF.DWG.
DRAWING NO./TRACKING NO.
210140-A-UPL2-26-10

<u></u> 1,-0%"	2		4	5
		 4'-	10 3 /4"	