

			Murphy-PFFS	S-SP	00L	-BOM	A	
Ī	Mark			End 1	End 2	Lft	LDec	Size
Ī	5	2	Style 107 EHP Pnt QuickVic Rigid Coupling					6
ſ	3	1	Sch 40 SA-53B CS Smls Pipe PE	BEV	BEV	21'-0"	252.000	10
	4	1	XH SA-53B CS SMLS Pipe	BEV	BEV		252.000	
ſ	1	1				20'-7 15/16"		
Ī	2	1	Sch 40 SA-53B CS ERW Pipe PE	Grooved End	Grooved End	20'-7 15/16"	247.925	6



CONSTRUCTORS •ENGINEERS MECHANICAL • INDUSTRIAL 0NSTRUCTORS **CHORECES MECHANICAL ** MRUDSIENNL.

1233 N. Price Rd.
St. Louis, MO 63132-2303
314-997-6600 phone

	BIM	CAD@	mur	phy-	-stl.c	om	
]							APP
		=		COMMENTS	WPS#		CHK
į	Z	TIGHT	ON	ၓ	HY W		DRN

DING		QA/QC ACCEPT	ACC	EPT:	FLANG	FLANGE WEIGHT/ORIENTATION	ORIENT	ATION
:)					FITIN	FITTING ORIENTATION	NOIL	
à					BOLTS	BOLTS/CPLG'S/TH'D TIGHT	'D TIGH	-
C.F.					SPOOL	SPOOL IDENTIFICATION	ATION	
	SPEC.	. ASME	ME	X-RAY	X-RAY HYDRO TEST	PWHT	00	COMMENTS
	¥	2	_	AN	¥	NA NA	MURPHY WPS#	#Sc
700		: 	1					
<u> </u>	0							
>	REV	DATE		DES	DESCRIPTION		DRN	DRN CHK

WUS!	A RES	-WUSM RESEARCH BUILDING - NRB	DING	G	QA/QC A(ĕ
<u> </u>	VEL	LEVEL 02 NRB RACK	×	l		
SERVICE NAME	NAME			SPEC.	H	ASME
				Ž	2	_≸
	QTY.	SHT/NO 7	REV	•		:
	_	Z of 3)	REV	REV DATE	L

46-

9			
	3		
5 2			

