

		Murphy-PFFS-	SP00	L	BO	М	
Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
4	2	Style 107 EHP Pnt QuickVic Rigid Coupling					4
1	1	Std Wt SA234 WPB CS BW LR 90 Deg Ell					4
3	1	Sch 40 SA-53B CS ERW Pipe PE	Grooved End	BEV	20'-0"	240.000	4
5	1	Sch 40 SA-53B CS ERW Pipe PE	Grooved End	BEV	5 7/8"	5.850	4

MURPHY

CONSTRUCTORS - ENGINEERS MECHANICAL - INDUSTRIAL

1233 N. Price Rd.
St. Louis, MO 63132–2303
314–997–6600 phone

MISI	IISM DESEA	CAPCE BILL DING		QA/QC ACCEPT	CEPT	FLANGE	E WEIGHT/C	FLANGE WEIGHT/ORIENTATION		
						FITTING	FITTING ORIENTATION	NOI		St. 31 BIM
	Ē	ARB COP				BOLTS/	BOLTS/CPLG'S/TH'D TIGHT	D TIGHT		Lou 4-9 ICAE
<u> </u>	LVL02	2 SPOOLS				SPOOL	SPOOL IDENTIFICATION	MOIL		is, M 97–0)@m
SEDVICE NAME	MAME))	i]	66
		Jah aw	SPEC.	ASME	X-RAY	X-RAY HYDRO TEST	PWHT	COMMENTS		63 00 phy-
	5		¥	¥	Ą	¥	NA NI	MURPHY WPS#		152 pho -stl
	֡֝֟֝֟֝֟֝֟֝֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟֟	9								-2 on .c
0	: \ :- :-	SHI/NO REV	0							:303 e om
6-07	_	lor I	REV	DATE	DES	DESCRIPTION		DRN CHK APP	APP	

REF.DWG.
DRAWING NO./TRACKING NO.
210140-A-UPL2-26-9