

Murphy-PFFS-SPOOL-BOM									MURPHY			
Mark	Qty	Description	End 1	End 2	Lft	LDec	Size	CONSTRUCTORS •ENGINEER	. '	SINI ANICAL •	CE 1907	
3	1	Std Wt SA234 WPB CS BW LR 22.50 Trimmed Ell	LIN I	LIU Z		шес	14	1233 N. Pr	ice Rd.			
15	1	No.647 TT Dielectric Transition Fitting	MPT	MPT	4"	4.000	2	St. Louis, N 314-997-	6600	phon	е	
12	1	150lb RF Sch 40 Bore SA105 CS WN Flg			·		14	BIMCAD@m	urphy	-stl.c	om	
2	1	Style W07 Rigid Coupling					14		ıl.		APP	
10	3	Style W77 Rigid Coupling					14			Ш	¥	
8	1	77C-140 Brz 2pc FP_SS-Vntd-B&S Ball Valve					3/4	<u>N</u>	SE SE		¥	
6	1	Thd Fig 1103 MI 90 Deg St Ell					7/4	E ⊢	COMMENTS	#S4M	불	
4	1	Std Wt SA234 WPB CS BW LR 90 Deg Ell					3/4		<u>.</u> 8		NAC NAC	
11	1	3000# FS Thread-0-Let			1 1/2"	1.500	2x14		2	MURPHY	2	
5	5	3000# FS Thread—0—Let				1.063		5 T T 5	Ĺ	3		
1	1	Std Wt SA-53B CS ERW Pipe PE	Grooved End	BEV	1 1/16" 6"	6.000	3/4x14 14	F I I I	: <u>.</u>	Ш		
9	1	Std Wt SA-53B CS ERW Pipe PE	BEV BEV	Grooved End	6"	6.000	14	NEI PER	PWH	≨		
13	2	Std Wt SA-53B CS ERW Pipe PE	Grooved End	Grooved End	8°	8.000	14	- 1 0 0 0 0 0 0 0 0 0 0	ׅׅׅׅׅׅׅׅׅ֓֟֟֝֟֝֟֝ ֡	$oxed{oxed}$		
14	1	Std Wt SA-53B CS ERW Pipe PE	BEV	Grooved End	4'-2 3/8"	50.404	14	FLANGE WEIGHT/ORIENTATION FITTING ORIENTATION BOLTS/CPLG'S/TH'D TIGHT	TEST		2	
7	1	Std SA-53B CS Smls Pipe NIP x 6	MPT	MPT	6"	6.000	3/4	FIT BOI	[2	≨	NCITOIGUSTON	
•		Sie di 300 oo onno i po ini x o		·	٧	3,000	<u> </u>	 `	F S S			
								QA/QC ACCEPT	X-RAY	¥	֓֞֜֜֞֜֜֜֜֓֓֓֓֓֓֓֓֓֜֜֜֓֓֓֓֓֓֡֓֓֡֓֡֓֓֓֓֡֓֜֜֡֓֡֓֡֓֡֓֡֓֡֓֡֓֡֓֡֓֡֓֡֓֡֓֡֓֡֓֡֡֡֓֜֡֓֡֡֡֓֡֓֡֡֡֓֜֡֓֡֡֓֜֡֓֡֡֓֜֡֓֜	
								VQC A	ASME	ž	DATE:	
								Q	SPEC.	¥	0	
								DRN JMM 5/12/2021			210140-A-UPL2-18-08 1 10F 1 0	