

		Murphy-PFFS-S	SPC	OOL	_ - B0	М	
Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
1	1	Std Wt SA234 WPB CS BW LR 90 Deg Ell					24
3	1	Std Wt SA-53B CS SMLS Pipe PE	BEV	BEV	17'-6 3/8"	210.401	24

MURPHY

constructors •engineers mechanical • industrial

1233 N. Price Rd.

233 N. Pric	e Rd.
l. Louis, MC	63132-2303
14-997-6	600 phone
IMCAD@mu	rphy-stl.com
	1 /

FITTING ORIENTATIC BOLTS/CPLG'S/TH'D SPOOL IDENTIFICAT SAME X-RAY HYDRO TEST PWHT NA NA NA NA NA NA NARA		3/22/2021	MICH		CEADCL		CN	Q	QA/QC ACCEPT	EPT	FLANG	E WEIGHT	FLANGE WEIGHT/ORIENTATION	NOIL		
THICK NAME LPS SPEC. ASME X-RAY HYDRO TEST PWHT SPEC. ASME X-RAY HYDRO TEST PWHT N NA			20 *	<u>.</u>		מסורר					FITTING	ORIENT	ATION			31 BIN
THE LPS SPEC. ASME X—RAY HYDRO TEST PWHT SPEC. ASME NA	\vdash				מ צ צ						BOLTS/	CPLG'S/T	H'D TIGHT			4-99 (CAD
PRINCE NAME LPS REC. ASME X-RAY HYDRO TEST PWHT NA NA NA NA MURE QTY. SHT/NO 1 10F 1 0 DEV, CATE	0	40									SPOOL	IDENTIFI	CATION			97–6 @mi
QTY. SHT/NO REV O PEY, CATE DESCRIPTION			SERMCE N	AME				SPEC		X-RAY	HYDRO TEST	PWHT	NO2	COMMENTS		irphy
QTY. SHT/NO REV O PEV CATE CESCEDITION	ĺ				\ \frac{1}{2}				7							р /-
any. SHI/NO REV O LATE DESCRIPTION					i			¥	≨	≨	≨	¥	MURPHY WPS#	-		stl
1 10F 1 0 0 DEV, CATE DESCRIPTION	Š	KING NO.		≘ .	SHT/NO		<u> </u>	}]				ŀ	\mid		ne .co
OF OF OF		-	_	•		•	•	0								m
DAIE DESCRIPTION	ì	A-UFLI-		_	<u>ਰ</u>	_	<u>ြီ</u>	REV D	ATE	DES	DESCRIPTION		DRN	DRN CHK APP	PP	