

		Murphy-PFFS-	SPOO	L-	BOM	1	
Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
4	1	150lb RF Sch 40 Bore SA105 CS WN Flg					14
2	1	Style W07 Rigid Coupling					14
1	1	Vic-300BFV GearOp ElastomerSeat					14
3	1	Std Wt SA-53B CS ERW Pipe PE	Grooved End	BEV	7 3/16"	7.178	14

/ / /	
	SINCE 1907

CONSTRUCTORS -ENGINEERS MECHANICA MOUSTBAL

1233 N. Price Rd.
St. Louis, MO 63132-2303
314-997-6600 phone
BIMCAD@murphy-stl.com

							4	1
RESEARCH RIIII DING		QA/QC ACCEPT	CCEPT	FLANG	E WEIGHT/0	FLANGE WEIGHT/ORIENTATION	_ z	
	<u> </u>			FITTING	FITTING ORIENTATION	NOIL		
NND COF				BOLTS/	BOLTS/CPLG'S/TH'D TIGHT	'D TIGHT		
VLUZ SPUULS	_			SPOOL	SPOOL IDENTIFICATION	ATION		
CH#1 TWR	<u>a</u> S	SPEC. ASME		X-RAY HYDRO TEST PWHT	PWHT	COMMENTS	s	_
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	2	¥	Ą	¥	AN N	MURPHY WPS#		_
SHT/NO	REV	i - -					L	_
1 or 1	<u>₽</u>	REV DATE	DES	DESCRIPTION		DRN CHK APP	APP	_

WNSW

REF.DWG.
DRAWING NO./TRACKING NO.
210140-A-UPL2-16-09