	Murphy-PFFS-SPOOL-BOM								
Mark			End 1	End 2	Lft	LDec	Siz		
3	1	Std Wt SA234 WPB CS BW LR 90 Deg Ell					4		
2	1	Sch 40 SA-53B CS ERW Pipe PE	Grooved End	BEV	1'-10 13/16"	22.788	4		
4	1	Sch 40 SA-53B CS ERW Pipe PE	BEV	Grooved End	3'-8 3/16"	44.214	4		



CONSTRUCTORS CHARMEERS MECHANICAL INDUSTRIAL

1233 N. Price Rd.
St. Louis, MO 63132–2303
314–997–6600 phone
BIMCAD@murphy-stl.com

WIISM RF	SFARCH BILLIDING		A/QC A	QA/QC ACCEPT	FLANG	E WEIGH <sup>-</sup>	FLANGE WEIGHT/ORIENTATION	_
		_			FITTIN	FITTING ORIENTATION	ATION	
- -	NKD COP				BOLTS	/CPLG'S/T	BOLTS/CPLG'S/TH'D TIGHT	
	OZ SPOOLS				SPOOL	SPOOL IDENTIFICATION	CATION	
SERVICE NAME			ŀ	ŀ	-			
1	VMIC	SPEC.	: ASME		X-RAY HYDRO LEST PWHT	PWHI	COMMENIS	•
	CHIC	¥	¥	¥	¥	¥	MURPHY WPS#	
740							#	
,	SHI/NO	0						
		REV	REV DATE	DES	DESCRIPTION		DRN CHK APP	APP

	-	4'-2 <sup>5</sup> ⁄ <sub>16</sub> "	-
<u> </u>	3	/	
		4	ILI
-2'-4 <sup>1</sup> 5 <sub>4</sub> 6"			
	2		