	Murphy-PFFS-SPOOL-BOM						
Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
4	1	Style W07 Rigid Coupling					14
2	1	Std Wt SA234 WPB CS BW LR 90 Deg Ell					14
1	1	Std Wt SA-53B CS ERW Pipe PE	Grooved End	BEV	6"	6.000	14
3	1	Std Wt SA-53B CS ERW Pipe PE	BEV	Grooved End	10'-1 1/8"	121.121	14



1233 N. Price St. Louis, MO 314-997-66 BIMCAD@mur	631 00 j	ohon	е	

	<u> </u>	' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' 	1 — — — ,	1 I	₹
			ATION	COMMENTS WPS#	똜
			ORIENT TION I'D TIGH ATION	COMME WURPHY WPS#	DRN
			VEIGHT/ DRIENTA PLG'S/TH	NA NA	
			FLANGE WEIGHT/ORIENTATION FITTING ORIENTATION BOLTS/CPLG'S/TH'D TIGHT SPOOL IDENTIFICATION	HYDRO TEST PWHT CON NA MURPHY WP	DESCRIPTION
			l . 1	X-RAY	
3			QA/QC ACCEPT	ASME	DATE
			Ö	SPEC.	
	A		BUILDING		REV 0
			RESEARCH NRB CUP LVL02 SPOC	ĭ≅	ату. sнт/No 1 10F 1
11'-101/4"			NSUW.	SERVICE IN	
			5/14/2021		DRAWING NO./TRACKING NO. 210140-A-UPL2-25-1
			DRN JMM CHK APP JOB NO.	REF.DWG.	DRAWI 21(