

			Murphy-PFFS-	SPOO	L	BOM	1	
N	Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
	4	1	150lb RF Sch 40 Bore SA105 CS WN Flg					14
	2	1	Style W07 Rigid Coupling					14
	1	1	Vic-300BFV GearOp ElastomerSeat					14
Γ	3	1	Std Wt SA-53B CS ERW Pipe PE	Grooved End	BEV	7 3/16"	7.178	14

1			BLV
	MU	K	SINCE 1907

constructors *Engineers Mechanical • INDUSTRIAL

1233 N. Price Rd.

St. Louis, MO 63132-2303

233 N. Price			
t. Louis, MO			
14-997-66	00 I	ohon	e
IMCAD@murj	ohy-	-stl.c	com

/12/2021	2021 WIISN DES		SEADCH BILL DING	JINIC	QA/Q	QA/QC ACCEPT	EPT	FLANG	E WEIGHT	FLANGE WEIGHT/ORIENTATION	TION	
	20	֧֧֡֝֞֝֝֝֝֝֝֝֝֝֝֝֝֝֝ ֡֝֡֡֡			,			FITTIN	FITTING ORIENTATION	ATION		
		Z ;	IKB CUP					BOLTS/	'CPLG'S/T	BOLTS/CPLG'S/TH'D TIGHT		
C	_		02 SPOOLS					SPOOL	SPOOL IDENTIFICATION	CATION		
	COTON ACT NIALIFE	ا							i			l
	SERVICE NAME	•		<i>s</i> ,	SPEC.	ASME	X-RAY	X-RAY HYDRO TEST PWHT	PWHT	MOD	COMMENTS	
		כ	1		1	1						Ī
						¥	≨	ž	¥	MURPHY WPS#	*	
16 NO.	<u>ਛ</u> ਹ	۲ نر	SHT/NO	چ کي د	L	_					_	
UFL2-19-09	60-6	_	l of l	O	REV DATE		DES	DESCRIPTION		DRN	DRN CHK APP	PP