



1/2"INSULATION


INSULATION





											4	3	ize 4 3 4 3	ize
DRN JMM	3/11/2021	3/11/2021 WIICM PECEAPCE	SEAPCH BIII DING	DING	QAVQ	QA/QC ACCEPT	EPT	FLANGE	FLANGE WEIGHT/ORIENTATION	ORIENT/	ATION			COP
CHK		A MCOM	_ [FITTING	FITTING ORIENTATION	NOIL			St. 31	ISTRUCTO
APP			NKB COP					BOLTS/	BOLTS/CPLG'S/TH'D TIGHT	I'D TIGHT	L		33 N. Loui 4–99 (CAD	
JOB NO. 210140	0140	T	PIPE RACKS					SPOOL	SPOOL IDENTIFICATION	ATION			s, M 97-6	IGINEERS
		SERVICE NAME	l		SPEC	ASME	X-RAY	X-RAY HYDRO TEST	PWHT	S	COMMENTS		ce Ro 0 6 8600 urphy	
REF.DWG.		- CUF	CUP LEVEL 02	<u>'L</u>	+		1		T	FOR ANGOLIN	3	T	3132 ph	CHANICAL
DRAWING NO./TRACKING NO.	ACKING NO.	QTY.	SHT/NO	<u>آ</u>	- - -	- [-	<u> </u>	<u> </u>	1		<u></u>	T	one	• INDU
210110	010110 A _ 11D1 0 _ 1 A		7	<u>و</u>										STRIA
401	-A-OFL2-	_ _ <u>{</u>		ر ا	REV DATE		DES	DESCRIPTION		DRN	DRN CHK APP	PP PP		AL.

		BOM-STEE	<u> L</u>		
Item No	Order	Description	Qty	Size	Steel L
H1	Fig137	Fig.137 U—Bolt (4)—Nut Black	2	6	
H2	Fig137	Fig.137 U-Bolt (4)—Nut Black	6	6	
S1	L4x4x3/8	ASTM A36 CS Equal Angle	2	L4x4x3/8	98"
S2	W4x13	ASTM A36 CS Wide Flange	2	W4x13	39"









/1.1/2		/ 			3	こしつつてつびてび	, -	ב ב ב]	CON
) : :		יוס פוס פיי					FITTING	FITTING ORIENTATION	ATION		123 St. 31 BIM
			NKB CUP					BOLTS/	CPLG'S/TI	BOLTS/CPLG'S/TH'D TIGHT		
NO. 210140		F	PIPE RACKS					SPOOL	SPOOL IDENTIFICATION	CATION		s, M 97-6
	CEDANCE MANE	MAME									1	0 66
	SERVICE			<u> </u>	SPEC.	ASME	X-RAY	X-RAY HYDRO TEST	PWHT	COMMENTS		Rd 6
		ב					:::::::::::::::::::::::::::::::::::::::	T				l. 31
DWG.		5	LL 1 0 2		¥	¥	¥	¥	¥	MURPHY WPS#		132 ohc
ING NO /TRACKING NO		ΔLO	CN/ IHS	<u>ب</u>		-				****		-2: one
	· ·	: `	(į (0							
0140-A-0FL2-1A	FL2-18		Z OF Z	-	REV	DATE	DES	DESCRIPTION		DRN CHK	APP	AL