

snap-it insul. block provided by insul. contractor will be used with strut clamps shown.

(1) \$00 x 1" insul.

1. SHUT OFF VALVE


FRONT ELEVATION
SCALE: 1/2" = 1'-0"

(1) 7/8 0 D × 1/2" MSW1, 3. THERMOSTATIC BALANCING STATION WITH THERMOMETER

(1) 7/800 x 1" insul.

KEYED NOTES:

| Mark | Qty | Size | Description | Length | Strut Width | Rod 1 Length | Rod 2 Length |
|------|-----|-----------|--|--------------|-------------|--------------|--------------|
| 1 | 1 | 1/2." | Cerro Type L Hard Copper Pipe | 19'-11 7/16" | | | |
| 2 | 1 | 3/4" | Cerro Type L Hard Copper Pipe | 19'-11 5/16" | | | |
| 3 | 1 | 3/4" | Swagelok SS316L 065 Wall Compression Seamless Tubing | 17'-5" | | | |
| 4 | 1 | 3/4" | Cerro Type L Hard Copper Pipe | 10'-2 11/16" | | | |
| 5 | 1 | 3/4" | Cerro Type L Hard Copper Pipe | 9'-7 1/4" | | | |
| 6 | 1 | 3/4* | Swagelok SS316 Compression Union 90 Elbow | | | | |
| 7 | 1 | 3/4"x1/2" | Nibco Wrot 611R CxCxC Reducing Tee | | | | |
| 8 | 2 | 3/4" | Nibou Wrot 607 90 Deg Ell CxC | | | | |
| 9 | 1 | 1/2" | Nibco Wrot 607 90 Deg Ell CxC | | | | |
| 10 | 6 | 2.5" | B-Line B2000 ZN Sch 40 Pipe Clamp | | | | |
| 11 | 3 | 1.5" | B-Line B2000 ZN Sch 40 Pipe Clamp | | | | |
| 12 | 3 | 0.5" | B-Line B2000 ZN Sch 40 Pipe Clamp | | | | |



TOP VIEW

SCALE: 1/2" = 1'-0"

WASH U NRB

PP-L00-034

1233 N Price Rd St Louis, Mo 631**32-2303** 314-997-6600 phone