UT TESTING IS REQUIRED FOR ALL **BUTT WELDS ON** THIS SPOOL. 4 EXPANSION JOINT IN PIT-**7** (II) should be an Apollo 83A-140 Series Ball valve

			Murphy-PFFS-	SP	00	L-B	MC	
I	Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
	1	1	Std Wt SA234 WPB CS BW RED TEE					16x12
f	11	+	→ 800# FS BB OS&Y Gate Valve SW					3/4
ſ	5	1	150lb RF Sch 40 Bore SA105 CS WN Flg					16
Ī	6	1	Std Wt SA234 WPB CS BW Cap					16
ſ	2	1	3M A105 FS SW 90 Deg Ell					3/4
ſ	7	1	3000# FS Soc−0-Let			1 5/16"	1.313	1x16
ſ	8	1	3000 <b>#</b> FS Soc−0-Let			1 1/16"	1.063	3/4x16
ſ	4	1	Std Wt SA-53B CS SMLS Pipe PE	BEV	BEV	9'-11 7/8"	119.864	16
ſ	9	1	Std Wt SA-53B CS SMLS Pipe PE	BEV	BEV	1'-1 1/4"	13.250	16
ſ	3	1	Sch 80 A106B CS SMLS Pipe	SW	SW	2*	2.000	3/4
Ī	10	1	Sch 80 A106B CS SMLS Pipe	SW	SW	1'-0"	12.000	3/4
-				•	-	•		

CONSTRUCTORS \*-DIGINEERS MECHANICAL \* INDUSTRIAL

1233 N. Price Rd. St. Louis, MO 63132-2303 314-997-6600 phone BIMCAD@murphy-stl.com

] [] [] [] []	COMMENTS COMMENTS RPHY WPS#	. HICA	N HYDRO TEST NA PROPERTION	ASME X-RAY HYDRO TEST PWHT NA NA NA NA NA TE DESCRIPTION	ASME	SPEC. A	REV O	HPS SHT/NO 1 OF 1	-	SERVICE NAM
	COMMENTS	PWHT	HYDRO TEST	X-RAY	ASME	SPEC.		NDN		SERVICE
	TION	IDENTIFICA	SPOOL							
	) TIGHT	BOLTS/CPLG'S/TH'D TIGHT	BOLTS/							
	NOI	FITTING ORIENTATION	FITTING				) :			; ) : -
	FLANGE WEIGHT/ORIENTATION	<b>E WEIGHT/O</b>	FLANGE	CEPT	QA/QC ACCEPT		DING	RESFARCH BUILDING		WOSM