

			Murphy-PFFS-	SPOO	L	BOM	1	
N	Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
	4	1	150lb RF Sch 40 Bore SA105 CS WN Flg					14
	2	1	Style W07 Rigid Coupling					14
	1	1	Vic-300BFV GearOp ElastomerSeat					14
Γ	3	1	Std Wt SA-53B CS ERW Pipe PE	Grooved End	BEV	7 3/16"	7.178	14

MU	RPHY
	SINCE 1907
	SINCE 1907

CONSTRUCTORS •ENGINEERS MECHANICAL • INDUSTRIAL

				ΡР
St. Louis 314-99	Price Rd. 6, MO 63 7—6600 9murphy	phone	е	

									-
ARCH RIII DING	CNIC	ð	QA/QC ACCEPT	CEPT	FLANG	FLANGE WEIGHT/ORIENTATION	ORIENT,	ATION	—
					FITTIN	FITTING ORIENTATION	TION		_
200.0					BOLTS	BOLTS/CPLG'S/TH'D TIGHT	I'D TIGH	–	_
SPOOLS					SPOOL	SPOOL IDENTIFICATION	ATION		_
		SPEC	ASME	H	X-RAY HYDRO TEST PWHT	PWHT	2	COMMENTS	ı
<u>ץ</u>		5							
		¥	¥	¥	¥	¥	MURPHY WPS#	#S	
	T A	ŀ	+					<u> </u>	ı
7	<u> </u>	0							
l of l	_ o	REV	DATE	DES	DESCRIPTION		DRN	DRN CHK AP	ΑP

WUSM RESEAR
NRB
LVL02 S
SERMCE NAME CH#5

/TRACKING NO. -A-UPL2-20-09