

		Murphy-PFFS-	SPOO	L	BOM	1	
Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
4	1	150lb RF Sch 40 Bore SA105 CS WN Flg					14
2	1	Style W07 Rigid Coupling					14
1	1	Vic-300BFV GearOp ElastomerSeat					14
3	1	Std Wt SA-53B CS ERW Pipe PE	Grooved End	BEV	7 3/16"	7.178	14

MU	RPHY
	SINCE 1907
	SINCE 1907

CONSTRUCTORS ENGINEERS MECHANICAL • INDUSTRIAL

bimcad@murphy=sn.com
314-997-6600 phone BIMCAD@murphy-stl.com
1233 N. Price Rd. St. Louis, MO 63132-2303

											_
MISI	A RES	WIISM RESEARCH BIIII DING	SNIC	QA	QA/QC ACCEPT	CEPT	FLANG	FLANGE WEIGHT/ORIENTATION	ORIENT	ATION	
5 - -	<u> </u>						FITTIN	FITTING ORIENTATION	NOIT		
1		IND COP					<b>BOLTS</b>	BOLTS/CPLG'S/TH'D TIGHT	'D TIGH	_	
	LVL	LVLUZ SPUOLS					SPOOL	SPOOL IDENTIFICATION	ATION		
SERVICE NAME		i i		SPEC	ACME	X-PAY	THWO ITSEL CHUNCH AND	DWHT	5	COMMENTS	
	ت	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		5		- N			3		
				¥	¥	¥	¥	NA MURPHY WPS#	URPHY WP	#S	
	<b>₽</b>	SHT/NO	REV	L							
0	7	T	_	_							
60-0	_	- - -	<u></u>	REV   DATE	ATE	DES	DESCRIPTION		DRN	DRN CHK APP	APP

CKING NO. 4-UPL2-18-09