



Murphy-PFFS-SPOOL-BOM								
y Description	End 1	End 2	Lft	LDec	Size			
Type K Hard Copper Pipe	Copper Ftg	Copper Ftg	20'-0"	240.000	2			
Sch 40 SA-53B CS ERW Pipe PE	Grooved End	Grooved End	20'-0"	240.000	3			
	Type K Hard Copper Pipe	Type K Hard Copper Pipe Copper Ftg	Type K Hard Copper Pipe Copper Ftg Copper Ftg	Type K Hard Copper Pipe Copper Ftg Copper Ftg 20'-0"	Type K Hard Copper Pipe Copper Ftg Copper Ftg 20'-0" 240.000			

Item No	Order	Description	Qty	Size	Steel L	O		
H1	Fig137	Fig.137 U—Bolt (4)—Nut Black	2	5		ATION	⊢	
H2	Fig137	Fig.137 U—Bolt (4)—Nut Black	2	5		Z	TIGHT ON	
Н3	929162	Klo-Shure Strut Clamp 1-1/2in Insul Cplg - Fiberglass_CTS	4	1-1/2		VORIENT	ALION H'D TIC CATIOI	I
S1	L3x3x3/8	ASTM A36 CS Equal Angle	1	L3x3x3/8	99"			ŀ
S2	L3x3x3/8	ASTM A36 CS Equal Angle	1	L3x3x3/8	36 3/4"	WEIGHT	ORIENI PLG'S/T DENTIFI	I
S2	L3x3x3/8	ASTM A36 CS Equal Angle	1	L3x3x3/8	99"	WE		
S2	L3x3x3/8	ASTM A36 CS Equal Angle	1	L3x3x3/8	36 3/4"	- \		
S3	B52 GRN	1FT GREEN 12GA CHANNEL	2	1-5/8x13/16	18"	ANGE	LTS/ OOL	1

Murphy-PFFS-Ship			Loose BOM				
Mark	Qty	Description	End 1	End 2	Lft	LDec	Size
10	2	101 Wrot Coupling without Stop					2
11	2	Style 107 EHP Pnt QuickVic Rigid Coupling					3





SINCE 1907
------------

1233 N. Price Rd. St. Louis, MO 63132-2303 314-997-6600 phone BIMCAD@murphy-stl.com

MURPHY WPS#	NA ML	AN A
COMMENTS	DRO TEST PWHT	SME X-RAY HYDRO TEST
TION	SPOOL IDENTIFICATION	
D TIGHT	BOLTS/CPLG'S/TH'D TIGHT	
NOI	FITTING ORIENTATION	
DRIENTATION	FLANGE WEIGHT/ORIENTATION	ACCEPT
L		

	_			_	_	+	
DING						REV	(
	֡֝֟֝֟֝֟֝֟֝֓֓֓֟֝֟֓֓֓֓֟֡֟֓֓֓֓֟֡֓֓֓֓֡֟֜֓֓֓֓֡֡֡֡֓֡֓֡֡֡֓֡֓֡֡֡֡֡֡֡֡	. !	S		05		•
		NKB CUP	PIPE RACKS		CUP LEVEL 02	SHT/NO	•
710	קיני	ם צו צו	PE		<b>ا</b>	胀	
	) <sup>4</sup> -		置	AME	S	g∏≺.	•
	<b>E</b> O			SERVICE NAME			_
_	<u> </u>			S	1	ł	•
19/2021 WIIGW DECEADED DIII DINC						S No.	