■ MODULE 02 OF 07 — DEEP-DIVE EDITION ■

QUBITS, SUPERPOSITION & ENTANGLEMENT

The three ideas that turn ordinary computers into quantum machines.

Quantum Computing for Ambitious Professionals

■ READ TIME	■ CHAPTERS	■ RESEARCH	■ LEVEL
~60 minutes	10 Deep Chapters	20,000+ Words	Beginner-Intermediate

DIARKA QUANTUM LIMITED

diarkaquantum.co.uk · nageshj@diarkaquantum.co.uk

© 2025 Diarka Quantum Limited · Registered in England & Wales

Confidential — Licensed to Purchaser Only — Do Not Redistribute

WHAT YOU WILL LEARN

01 From Bits to Qubits — A New Kind of Information

02 The Mathematics of a Qubit — Dirac Notation Made Simple

03 The Bloch Sphere — Visualising the Quantum State

04 Superposition — Being in Two States at Once

05 Measurement — Where Quantum Strangeness Becomes Real

06 The Double-Slit Experiment — The Evidence That Started It All

07 Entanglement — The Strangest Correlation in Nature

08 Bell's Theorem & the 2022 Nobel Prize

09 Qubits in Action — How Real Quantum Computers Use These Principles

10 Why This Matters — The Foundation of Everything That Comes Next

HOW TO READ THIS MODULE

This module builds in layers. Each chapter starts with intuition, then adds the maths, then the evidence. You do not need a physics degree. Read end-to-end on a first pass — do not get stuck on equations. The mental model matters more than the algebra. After the first read, return to the chapters that interested you and go deeper.

EXECUTIVE SUMMARY

The Three Ideas in 60 Seconds

If you read nothing else, read this. Module 2 covers three fundamental ideas of quantum computing. Each is settled science. Each is necessary to understand any of the rest.

Idea 1 — Superposition

A quantum bit, or qubit, is the fundamental unit of information in a quantum computer, but unlike a classical bit, it does not obey the familiar rules of classical computing. A traditional computer stores information using bits that exist strictly as either a 0 or a 1. Every calculation performed by a classical machine is ultimately built upon billions of these tiny binary switches flipping between two definite states.

A qubit operates according to the laws of quantum mechanics, where information behaves in a profoundly different way. Instead of existing only as a 0 or a 1, a qubit can exist in a quantum superposition, a state in which it simultaneously contains aspects of both 0 and 1 at the same time until it is measured. Importantly, this does not mean that we simply “do not yet know” whether the qubit is a 0 or a 1. In classical probability, something hidden still possesses a definite value underneath the uncertainty. Quantum systems are different. Before measurement, the qubit genuinely exists as a combination of both states simultaneously, described mathematically through complex probability amplitudes that determine the likelihood of each outcome when observed.

This idea is one of the most counterintuitive aspects of quantum physics because it challenges the deeply classical intuition humans have about reality. Yet experimentally, superposition has been repeatedly verified for decades and forms the foundation of modern quantum technologies.

The real computational power emerges when many qubits interact together. In a classical computer, adding more bits increases computational capacity linearly. But in a quantum system, multiple qubits can exist in a shared superposition across an exponentially expanding state space. A system of 2 qubits can simultaneously represent 4 possible states. 3 qubits represent 8 states. 10 qubits represent 1,024 states simultaneously. By the time a quantum processor reaches 50 qubits, the number of possible quantum states becomes so enormous that simulating the system accurately on classical supercomputers becomes extraordinarily difficult.

At around 300 qubits, the scale becomes almost incomprehensible. Such a system can mathematically represent 2^{300} possible quantum states simultaneously, a number vastly larger than the estimated number of atoms in the observable universe. This does not mean a quantum computer magically "tries every answer at once" in a simplistic science-fiction sense, but it does mean quantum systems can encode and manipulate extraordinarily complex probability spaces that classical machines struggle to represent efficiently.

When combined with another uniquely quantum phenomenon called entanglement, where qubits become deeply correlated regardless of physical distance, quantum computers gain the ability to process information in ways fundamentally impossible for classical architectures. Carefully designed quantum algorithms can exploit superposition and entanglement to solve specific categories of problems dramatically faster than traditional computers.

This is why quantum computing is attracting global attention from governments, research institutions, and major technology companies. The technology has the potential to transform fields such as cryptography, optimisation, materials science, pharmaceutical discovery, financial modelling, climate simulation, logistics, and artificial intelligence. Quantum computers may eventually solve problems that would take today's most powerful supercomputers millions of years to compute.

Although large-scale fault-tolerant quantum computing is still under development, the progress being made today marks the beginning of a major technological transition, one that many researchers compare to the early emergence of classical computing or the birth of the internet itself.

Idea 2 — Measurement

When a qubit is measured, its quantum superposition collapses into one definite outcome — either 0 or 1. Before measurement, however, the qubit can exist in a combination of both states simultaneously, described by mathematical quantities called **probability amplitudes**.

These amplitudes determine the likelihood of each outcome through the **Born rule** (1926):

*Probability=(Amplitude)2\text{Probability} = (\text{Amplitude})^2*Probability=(Amplitude)2

This means the amplitudes themselves are not probabilities directly — they must first be squared.

For example, imagine a qubit has the quantum state:

*0.8∣0⟩+0.6∣1⟩0.8|0\rangle + 0.6|1\rangle*0.8|0⟩+0.6|1⟩

Here:

- amplitude for measuring **0** = 0.8
- amplitude for measuring **1** = 0.6

To calculate the actual probabilities:

$0.8^2=0.64$ *and* $0.6^2=0.36$

So:

- there is a **64% probability** the qubit will collapse to 0
- there is a **36% probability** it will collapse to 1

Once the measurement happens, the superposition disappears completely. If the result is 0, the qubit is now fully in state 0. The previous quantum combination no longer exists.

This is why quantum algorithms must carefully manipulate amplitudes *before* measurement occurs.

A useful way to understand this is with a simple search example.

Imagine there are four possible answers to a problem:

$A, B, C, DA, | B, | C, | D$A, B, C, D

Initially, a quantum computer may place all answers into an equal superposition:

$0.5A+0.5B+0.5C+0.5D0.5A + 0.5B + 0.5C + 0.5D$0.5A+0.5B+0.5C+0.5D

Squaring the amplitudes gives:

$0.52=0.250.5^2 = 0.25$0.52=0.25

So every answer initially has:

- 25% probability of being measured.

At this stage, measurement would simply give a random answer.

The quantum algorithm then performs interference operations.

Suppose after several quantum operations:

- wrong answers partially cancel each other
- the correct answer becomes amplified

The state may evolve into something like:

$$0.1A + 0.1B + 0.2C + 0.96D$$

Now calculate probabilities:

$$0.1^2 = 0.01$$
$$0.2^2 = 0.04$$
$$0.96^2 \approx 0.92$$

Final probabilities:

- A → 1%
- B → 1%
- C → 4%
- D → 92%

Now, when the system is measured, the correct answer **D** is overwhelmingly likely to appear.

This is the real power of quantum computing.

Quantum computers do not simply “try every answer at once” and instantly reveal them. Instead, they use quantum interference to reshape probability amplitudes, suppressing incorrect possibilities while amplifying the correct one until measurement becomes highly likely to produce the desired result.

This principle sits at the heart of major quantum algorithms such as:

- Grover’s search algorithm
- Shor’s factoring algorithm
- Quantum machine learning models
- Variational quantum algorithms used in modern NISQ systems

In essence, quantum computation is the art of engineering probabilities before reality collapses into a single observable outcome.

Idea 3 — Entanglement

Two or more qubits can become connected through a phenomenon known as **quantum entanglement**, where their quantum states become deeply correlated in a way that classical physics cannot explain.

In a classical system, two objects can certainly be related. For example, if you place one red ball and one blue ball into separate boxes, then send the boxes to different cities, opening one box instantly tells you the colour of the other. But the colours were already decided from the beginning.

Quantum entanglement is fundamentally different.

With entangled qubits, the outcomes are not predetermined in the classical sense. Instead, the qubits share a single combined quantum state. When one qubit is measured, the state of the other becomes instantly correlated, even if the qubits are separated by enormous distances.

A simple example is an entangled pair written mathematically as:

$$\frac{1}{\sqrt{2}}(|00\rangle+|11\rangle)$$

This means the two qubits exist in a superposition of:

- both being 0
- and both being 1

simultaneously.

Before measurement:

- neither qubit individually has a definite value
- the system only defines their relationship

Now imagine:

- one qubit is kept in London
- the other is sent to Tokyo

When the London qubit is measured:

- if the result is 0, the Tokyo qubit will instantly also be 0
- if the result is 1, the Tokyo qubit will instantly also be 1

The outcomes are perfectly correlated.

Importantly, this does **not** mean information travels faster than light. Rather, the quantum system behaves as a single connected state, regardless of distance.

This strange behaviour troubled even Einstein, who famously called it:

“spooky action at a distance.”

For decades, many physicists believed hidden classical information might secretly determine the outcomes in advance. These ideas became known as **hidden variable theories**.

However, experiments based on **Bell’s Theorem** showed that nature does not behave according to any local hidden-variable explanation.

The evidence became so overwhelming that the **2022 Nobel Prize in Physics** was awarded to Alain Aspect, John Clauser, and Anton Zeilinger for experiments proving that entanglement is real and that the universe violates classical assumptions about locality and hidden variables.

Entanglement is not just a scientific curiosity, it is one of the core resources that gives quantum computing its power.

To understand why, consider a classical system with two ordinary bits:

- each bit can only store one value at a time
- correlations remain limited and classical

But with entangled qubits, operations performed on one qubit immediately affect the combined quantum state of the system. As the number of entangled qubits grows, the quantum computer can represent and manipulate enormously complex probability spaces that classical computers struggle to simulate.

For example:

- 2 classical bits can represent only one of 4 states at a time
- 2 entangled qubits can represent a superposition of all 4 states simultaneously
- 10 entangled qubits represent 1024 quantum states together
- 50 entangled qubits represent over one quadrillion possible states simultaneously

This exponential structure is what allows quantum algorithms to explore problem spaces in fundamentally new ways.

Modern quantum algorithms rely heavily on entanglement:

- Shor's algorithm uses entanglement for factoring large numbers
- Quantum teleportation depends entirely on entangled states
- Quantum error correction uses highly entangled logical qubits
- Quantum machine learning models exploit entangled feature spaces
- Quantum cryptography uses entanglement to detect eavesdropping

In many ways, entanglement is the "fuel" of quantum computing. Without it, quantum computers would lose much of the advantage that makes them fundamentally different from classical machines.

■ WHY THESE THREE MATTER

Every major quantum algorithm — from Shor's factoring algorithm to Grover's search and today's emerging quantum machine learning models — is built on the same foundational principles: superposition, interference, and entanglement. Understand these deeply, and quantum computing stops feeling like science fiction and starts becoming intelligible technology. Ignore them, and the field will always sound like abstract buzzwords. Spending just 60 minutes with this module may be one of the highest-leverage investments a business or technical leader can make to prepare for the next era of computing.

CHAPTER 01

From Bits to Qubits

A new kind of information — and why it changes what computers can do.

Module 1 ended with a question. Classical computers had hit a wall — quantum tunnelling, thermal density, mathematical intractability. Engineers cannot simply make transistors smaller forever. But the same physics that ended the old paradigm opened the door to a new one. To walk through that door, we need a new unit of information. We need the qubit.

Start with what you already know

A classical bit is the most fundamental object in modern computing. Everything built in the digital world, from smartphones and cloud platforms to artificial intelligence systems and global financial networks, ultimately reduces down to bits. A bit has only two possible states: 0 or 1. That is the entire alphabet of classical computation.

Physically, those states can be implemented in many ways. Inside a processor, a bit may be represented by a tiny electrical voltage - high voltage for 1, low voltage for 0. Inside computer memory, it may exist as a microscopic, stored charge, charge present for 1, absent for 0. On a hard disk, it may be encoded as a tiny magnetic region pointing in one direction or the other. In optical systems, it may correspond to the presence or absence of light. Different engineering implementations, identical logical behaviour: at any given moment, a classical bit is always definitively one value or the other.

There is never ambiguity inside the computational state itself. A classical bit cannot be partially 0 and partially 1. It cannot occupy multiple logical states simultaneously. It cannot exist in a probabilistic combination of values waiting to be resolved later. At the deepest level of classical computation, reality is assumed to be discrete, definite, and binary.

This is not simply a design choice engineers happened to make. It is the very foundation of classical computing as a mathematical and physical framework. Every classical algorithm ever written, every operating system, database, programming language, search engine, encryption protocol, and AI model, assumes that the underlying units of computation are definite two-valued objects that transition predictably from one state to another.

That assumption is so deeply embedded into modern computing that we rarely even notice it. It feels obvious because every digital system humanity has ever built has operated according to this logic.

Quantum computing changes that assumption completely.

A quantum computer is not merely a faster version of a classical machine. It is built on an entirely different model of reality. The quantum bit, or qubit, does not obey the same binary restrictions as a classical bit. Instead of existing strictly as either 0 or 1, a qubit can exist in a quantum superposition of both states simultaneously, described by probability amplitudes rather than definite classical values.

This seemingly simple difference changes everything.

It transforms how information can be represented, how computation evolves over time, and how problems can be solved. The leap from classical bits to qubits is not like upgrading from an older processor to a faster processor. It is closer to moving from classical physics to quantum physics itself, a shift in the underlying rules governing computation.

Now meet the qubit

A qubit "short for *quantum bit"* is the fundamental unit of quantum information. In the same way that all classical computing is ultimately built from bits, all quantum computing is built from qubits. Every quantum algorithm, quantum circuit, and quantum system begins here.

Like a classical bit, a qubit has two fundamental basis states. We denote them as:

$$|0\rangle \quad \text{and} \quad |1\rangle$$

pronounced "ket zero" and "ket one." This notation comes from the mathematical language of quantum mechanics known as **Dirac notation**, which we will explore properly in Chapter 2. For now, you can think of these simply as the quantum equivalents of classical 0 and 1.

At first glance, this appears identical to classical computing. A system with two possible states does not sound revolutionary.

The revolution begins with what quantum mechanics allows a qubit to do next.

Unlike a classical bit, which must always exist definitively as either 0 or 1, a qubit can also exist in a combination of both states simultaneously. A qubit may be partly ($|0\rangle$) and partly ($|1\rangle$) at the same time, with mathematically controllable proportions called probability amplitudes.

This idea is profoundly different from anything in classical computing.

A qubit is not rapidly switching back and forth between 0 and 1. It is not the case that the qubit secretly "already knows" which value it has and we simply lack the information to determine it. Quantum mechanics is making a far stranger claim: before measurement, the qubit genuinely exists in a superposed quantum state containing both possibilities simultaneously.

This phenomenon is called **superposition**, and it is the first major principle underlying quantum computing.

To understand why this matters, imagine a classical coin lying flat on a table. Before you look at it, the coin is still definitely either heads or tails, you simply do not yet know which. That is classical uncertainty.

A qubit is fundamentally different. A better analogy is a spinning coin suspended in motion. While spinning, it is not fully heads or fully tails. Instead, it occupies a dynamic state that contains aspects of both possibilities until the moment it is observed.

Of course, even this analogy eventually breaks down, because quantum superposition is not merely a visual trick or a temporary blur between states. It is a mathematically real quantum phenomenon repeatedly confirmed by experiment.

The implications are enormous.

A single classical bit can represent only one value at a time:

- 0 or 1

But a qubit in superposition can encode both possibilities simultaneously within its quantum state.

As additional qubits are added, the computational space grows exponentially:

- 2 qubits can represent 4 quantum states simultaneously
- 10 qubits represent 1024 states
- 50 qubits represent more than one quadrillion states
- 300 qubits represent more possible states than there are atoms in the observable universe

This exponential structure is one of the reasons quantum computing has the potential to solve certain classes of problems that become effectively impossible for classical computers.

Superposition is therefore not just a strange feature of quantum physics. It is one of the foundational resources that gives quantum computing its power. Understanding it deeply is the first step toward understanding the entire field.



Figure 1.1 — A classical bit lives in one of two boxes. A qubit lives anywhere on the surface of a sphere.

Why this matters, even before the maths

At this point, quantum superposition can still sound abstract. The mathematics may be unfamiliar, and the physics may feel counterintuitive. But even before understanding the equations, it is important to understand *why* these ideas matter computationally.

Imagine trying to solve a large maze.

A classical computer approaches the problem step by step. It begins at the entrance, chooses a path, follows it forward, discovers whether it succeeds or fails, then backtracks and tries another route.

One path at a time.

This approach is methodical, deterministic, and extremely reliable. Modern classical computers are astonishingly good at this kind of sequential logic. But as the maze becomes larger and more complex — perhaps containing millions or billions of possible paths — the search process can become enormously time-consuming.

The computational cost grows rapidly because the machine must continue evaluating possibilities individually.

Now imagine a very different kind of explorer.

At every junction in the maze, the explorer could split into multiple versions of themselves:

- one copy going left
- another going right
- another exploring forward
- another testing alternative routes

Each version continues splitting again and again at every new junction, exploring many possible paths simultaneously.

Eventually, dead ends are discarded while successful paths reinforce each other, and somehow the explorer reunites carrying information primarily about the correct route.

This is not literally what a quantum computer does, but it provides useful intuition for understanding the power of superposition and quantum interference.

A quantum computer does not simply “try every answer at once” in the simplistic science-fiction sense often claimed online. The reality is more subtle and far more interesting. Quantum algorithms manipulate probability amplitudes across many computational possibilities simultaneously, then use interference to suppress incorrect paths and amplify correct ones before measurement occurs.

For certain types of problems, this creates dramatic computational advantages.

The key phrase, however, is **certain types of problems**.

Quantum computing is not a universal replacement for classical computing. A quantum computer will not make every application exponentially faster. In fact, for many everyday tasks - web browsing, spreadsheets, databases, video streaming, operating systems — classical computers remain vastly more practical and efficient.

But there exists an important class of problems where the combinatorial explosion of possibilities overwhelms classical systems:

- Cryptographic factorisation
- Optimisation problems
- Molecular simulation
- Quantum chemistry
- Certain machine learning tasks
- Complex search spaces

These are the domains where quantum algorithms may eventually achieve transformative speed-ups.

For example, a classical computer attempting to search an unsorted database of one million entries may need, on average, hundreds of thousands of checks to find the correct answer. Grover’s quantum search algorithm can reduce this dramatically through amplitude amplification, requiring roughly the square root of the number of possibilities instead.

Likewise, Shor’s algorithm demonstrated that a sufficiently powerful quantum computer could factor large numbers exponentially faster than known classical methods, a discovery that fundamentally changed global thinking around cryptography and cybersecurity.

This is why superposition matters.

It changes the structure of computation itself.

Instead of evaluating possibilities strictly one after another, quantum systems can evolve across vast probability spaces simultaneously, allowing entirely new computational strategies that are impossible within purely classical frameworks.

■ IMPORTANT CAVEAT

Quantum computers are not faster classical computers. They will not make your laptop snappier. They are a fundamentally different kind of machine, suited to a small but important class of problems. Knowing which problems benefit from quantum and which do not is the core skill of quantum literacy. We will return to this distinction.

What a qubit is physically

A qubit is not merely a mathematical abstraction or a theoretical idea written on a whiteboard. It is a real physical object built from matter, energy, electromagnetic fields, or light — a system engineered carefully enough that it begins to obey the strange laws of quantum mechanics in a controllable way.

This is one of the first major conceptual shifts in quantum computing.

When most people imagine a computer, they imagine silicon chips packed with billions of microscopic transistors switching on and off. Quantum computers are fundamentally different. Their basic computational objects do not resemble classical transistors at all.

Instead, different quantum computing companies and research groups build qubits using entirely different physical systems, each attempting to solve the same core challenge:

- preserve fragile quantum states long enough to compute
- manipulate them precisely
- and measure them accurately before quantum effects disappear

Here are the four most important platforms used today:

SC	IO	NA	PH
Superconducting circuits	Trapped ions	Neutral atoms	Photons

Superconducting Qubits: SC are currently the most commercially mature and widely deployed approach to quantum computing.

These systems are built from microscopic metal circuits fabricated on chips similar in appearance to classical processors. However, unlike ordinary electronics, they operate at temperatures extremely close to absolute zero — typically around **15 millikelvin**, colder than outer space itself.

At these temperatures, electrical resistance disappears entirely, allowing current to flow without energy loss. Under these extreme conditions, the circuit begins behaving not like a classical electrical component, but as a controllable quantum system capable of existing in superposition.

Superconducting qubits are fast, highly programmable, and compatible with existing semiconductor manufacturing techniques, which is one reason they became an early industry leader.

Major organisations using this platform include:

- IBM Quantum
- Google Quantum AI
- Rigetti

Google's 2019 "quantum supremacy" experiment and IBM's large-scale quantum roadmap are both based on superconducting architectures.

Trapped Ion Qubits: Trapped ion quantum computers use individual electrically charged atoms suspended in space using electromagnetic fields.

The atoms themselves become the qubits.

Lasers are then used with extraordinary precision to manipulate the quantum energy states of those ions, allowing information to be encoded, processed, and measured.

Compared with superconducting systems, trapped ions typically operate more slowly, but they often achieve significantly higher fidelity — meaning fewer computational errors.

One of the remarkable features of trapped-ion systems is that every ion is naturally identical at the atomic level, giving them exceptional consistency and stability.

Major companies using trapped-ion architectures include:

- IonQ
- Quantinuum
- Oxford Ionics

Many researchers believe trapped ions may become one of the strongest candidates for fault-tolerant quantum computing.

Neutral Atom Qubits: Neutral atom quantum computers use individual atoms held in place by highly focused laser beams known as **optical tweezers**.

These laser traps can position atoms with astonishing precision, allowing researchers to create programmable arrays of hundreds — and potentially thousands — of controllable qubits.

Neutral atom systems have attracted enormous attention because of their scalability potential. Unlike some other architectures, atoms can be rearranged dynamically into different geometric configurations, making the systems highly flexible.

Companies such as:

- QuEra
- Pasqal
- Atom Computing

are leading development in this area.

A major milestone came in 2023, when researchers from Harvard and QuEra demonstrated **48 logical qubits encoded using 280 physical neutral atoms** — an important step toward practical quantum error correction and fault-tolerant quantum computation.

Many experts now consider neutral atoms one of the most promising long-term architectures in the industry.

Photonic Qubits: Photonic quantum computing uses photons — the fundamental particles of light — as qubits.

Instead of manipulating electrical circuits or trapped atoms, these systems encode quantum information directly into properties of light such as:

- polarisation
- phase
- or optical paths

One of the biggest advantages of photonic systems is that they can operate at or near room temperature, avoiding the enormous refrigeration requirements needed by superconducting platforms.

Photons also naturally travel well across long distances, making photonic systems especially attractive for:

- quantum networking
- quantum communication
- and future quantum internet infrastructure

Major photonic quantum companies include:

- PsiQuantum
- Xanadu
- QuiX Quantum

Photonic systems remain technically challenging, particularly in reliably generating and controlling large numbers of identical photons, but many researchers believe they may ultimately provide one of the most scalable routes to large-scale quantum computing.

The physics differs. The maths does not. Whatever physical system implements a qubit, the mathematical description is the same. That mathematics is what we turn to next.

CHAPTER 02

The Mathematics of a Qubit

Dirac notation made simple — what those funny brackets mean.

Quantum mechanics has its own mathematical language, and at first glance it can look intimidating. Expressions such as:

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

often appear mysterious to newcomers, as though quantum computing requires an entirely new kind of mathematics inaccessible to ordinary professionals or engineers.

It does not.

The notation is remarkably elegant once you understand the underlying rules. Most of the apparent complexity comes not from the mathematics itself, but from unfamiliar symbols and conventions developed by physicists to describe quantum systems compactly and precisely.

This notation is known as **Dirac notation** — or *bra-ket notation* — introduced by the physicist Paul Dirac, one of the founders of quantum mechanics. It became the universal language of quantum theory because it provides an extraordinarily efficient way to describe quantum states, transformations, measurements, and entanglement.

And importantly, modern quantum computing cannot really be understood without it.

Every serious quantum paper, textbook, quantum software framework, research article, and quantum algorithm eventually uses this notation. Whether reading about:

- superposition
- quantum gates
- entanglement
- Grover's algorithm
- Shor's algorithm
- or quantum machine learning

you will encounter expressions like these constantly.

The good news is that the notation is far less complicated than it initially appears.

In fact, most expressions follow a small set of consistent rules. Once those rules become familiar, the symbols stop looking abstract and instead become surprisingly intuitive — almost like learning the grammar of a new language.

This chapter is therefore an important turning point.

Up until now, we have discussed quantum ideas conceptually and intuitively. From this point forward, we begin connecting those ideas to the mathematical framework that powers the entire field.

You do not need an advanced physics background to follow what comes next.

You only need patience, curiosity, and the willingness to become comfortable with a new symbolic language.

Once this notation "clicks," a large part of modern quantum computing suddenly becomes readable in a way it was not before.

This chapter is the unlock.

The 'ket' — a quantum state in a box

One of the first things you notice in quantum mechanics is the unusual notation:

|0⟩, |1⟩, |ψ⟩ or can be written as |0\rangle,\ |1\rangle,\ |\psi\rangle

At first, these symbols can look strange or intimidating. They are simply labels for quantum states.

The structure:

|something⟩|

is called a **ket**.

You can think of a ket as a mathematical "container" that holds the description of a quantum state. Whatever appears inside the symbol is simply the label or name of that state.

So:

- *|0⟩ or |0\rangle*|0⟩ is read **"ket zero"**
- *|1⟩ or |1\rangle*|1⟩ is read **"ket one"**

These represent the two fundamental states of a qubit — analogous to the 0 and 1 of classical computing.

But quantum systems are not restricted to just those two fixed states. A qubit can also exist in combinations of them, which is why physicists use symbols like:

|ψ⟩ or |\psi\rangle|ψ⟩

pronounced **"ket psi."**

The Greek letter *ψ\psi*ψ ("psi") is simply a placeholder for a general quantum state, much like *xx*x is used in algebra to represent an unknown variable.

So whenever you see:

|ψ⟩ or |\psi\rangle|ψ⟩

you can mentally read it as:

"some quantum state."

For example, a qubit in superposition may be written as:

|ψ⟩=α|0⟩+β|1⟩ or |\psi\rangle = \alpha|0\rangle + \beta|1\rangle

This equation says the qubit exists partly in state *|0⟩|0\rangle*|0⟩ and partly in state *|1⟩|1\rangle*|1⟩, with proportions determined by the amplitudes *α\alpha*α and *β\beta*β.

The "Bra" — The Ket's Mathematical Partner

Quantum mechanics also defines a companion object called a **bra**.

A bra looks like this:

$\langle 0|$ or $\langle$

and is read:

"bra zero."

If a ket represents a quantum state, the bra is the mathematical object used to interact with that state mathematically — especially when calculating:

- probabilities
- amplitudes
- overlaps between states
- and measurement outcomes

When a bra and ket appear together, they form a **bracket**:

$\langle \text{bra}|\text{ket}\rangle$

This is where the term **"bra-ket notation"** comes from.

The physicist Paul Dirac introduced the notation in the 1930s as both a practical mathematical system and a clever joke:

- "bra"
- "ket"
- together forming "bracket."

The notation survived because it turned out to be one of the cleanest and most elegant ways to describe quantum systems.

Today, nearly all of quantum mechanics and quantum computing is written using this language.

Once you become comfortable reading symbols like $|\psi\rangle$, $\langle 0|$, and $\langle\phi|\psi\rangle$, quantum equations stop looking mysterious and start looking structured, compact, and surprisingly intuitive.

> ■ **THE NOTATION IS JUST A LABEL**
>
> Do not let the symbols intimidate you. $|0\rangle$ is a name, like 'apple'. The interesting stuff is what the names combine into. The kets are nouns. What we will do with them — adding them, scaling them, transforming them — is the verbs.

The general qubit state

Any qubit state can be written as:

$|\psi\rangle=\alpha|0\rangle+\beta|1\rangle$ or $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$

Here α (alpha) and β (beta) are numbers — specifically, **complex numbers** — called **amplitudes**. They describe how strongly the qubit is associated with the states $|0\rangle$ or $|0\rangle$ and $|1\rangle$ or $|1\rangle$.

You can think of amplitudes as the hidden mathematical quantities that determine what we are likely to observe when the qubit is measured.

If the magnitude of α is larger than β, the qubit is more likely to collapse to $|0\rangle$. If β is larger, the qubit is more likely to collapse to $|1\rangle$.

But amplitudes are not probabilities themselves.

Quantum mechanics uses a deeper rule:

$|\alpha|^2+|\beta|^2=1$

This is called the **normalisation condition**.

It states that the squared magnitudes of the amplitudes must always add up to 1.

Why?

Because:

- $|\alpha|^2$ is the probability of measuring the qubit as 0
- $|\beta|^2$ is the probability of measuring the qubit as 1

And probabilities of all possible outcomes must always sum to 100%.

For example, suppose:

$\alpha=0.8$ and $\beta=0.6$

Then:

$|0.8|^2=0.64$ and $|0.6|^2=0.36$

Adding them together gives:

$0.64+0.36=1$

So this is a valid quantum state.

What does it mean physically?

It means:

- there is a 64% probability the qubit will be measured as $|0\rangle$
- and a 36% probability it will be measured as $|1\rangle$

Before measurement, however, the qubit is not secretly one or the other.

It genuinely exists in the quantum state:

$|\psi\rangle=0.8|0\rangle+0.6|1\rangle$

Only when we measure it does the superposition collapse into one definite outcome.

This idea — that reality evolves through amplitudes, while observations emerge through squared probabilities — is one of the deepest conceptual shifts in quantum mechanics.

Three states you should remember

Three qubit states appear so often that they have shorthand names. They are worth memorising.

State	Written as	Meaning
$\|0\rangle$	$1\cdot\|0\rangle + 0\cdot\|1\rangle$	Definite zero
$\|1\rangle$	$0\cdot\|0\rangle + 1\cdot\|1\rangle$	Definite one
$\|+\rangle$	$(\|0\rangle + \|1\rangle) / \sqrt{2}$	Equal mix — 50/50 chance of 0 or 1
$\|-\rangle$	$(\|0\rangle - \|1\rangle) / \sqrt{2}$	Equal mix — but with a minus sign

Figure 2.1 — Four named qubit states. The $|+\rangle$ and $|-\rangle$ states are equal superpositions of $|0\rangle$ and $|1\rangle$.

The factor of $\frac{1}{\sqrt{2}}$ in the states $|+\rangle$ and $|-\rangle$ comes from the **normalisation condition** we discussed earlier.

The states are written as

$|+\rangle=\frac{1}{\sqrt{2}}(|0\rangle+|1\rangle)$

$|-\rangle=\frac{1}{\sqrt{2}}(|0\rangle-|1\rangle)$

Why use $\frac{1}{\sqrt{2}}$?

Because quantum states must satisfy the rule:

$|\alpha|^2+|\beta|^2=1$

In both $|+\rangle$ and $|-\rangle$, the amplitudes are:

$$\frac{1}{\sqrt{2}}$$

Squaring them gives:

$$\left(\frac{1}{\sqrt{2}}\right)^2=\frac{1}{2}$$

Since there are two components, the total probability becomes:

$$\frac{1}{2}+\frac{1}{2}=1$$

So the state is properly normalised.

The maths works perfectly.

At first glance, $|+\rangle$ and $|-\rangle$ seem almost identical.

Both produce:

- 50% probability of measuring $|0\rangle$
- 50% probability of measuring $|1\rangle$

So what is the difference?

The answer is the **minus sign**.

That tiny sign changes the **phase relationship** between the two amplitudes.

And phase is one of the deepest ideas in quantum computing.

A useful way to think about this is through waves.

Imagine two water waves meeting:

- if their peaks align, they reinforce each other (**constructive interference**)
- if a peak meets a trough, they cancel (**destructive interference**)

Quantum amplitudes behave similarly.

The plus sign in $|+\rangle$ means the amplitudes are "in phase." The minus sign in $|-\rangle$ means they are "out of phase."

Even though the measurement probabilities initially look identical, the states behave differently when combined with other quantum operations.

That difference is what allows quantum algorithms to:

- amplify correct answers
- cancel wrong answers
- and produce computational advantages impossible in classical systems.

This is why quantum computing is not simply "probabilistic computing."

A classical probabilistic system only stores probabilities.

A quantum system stores **amplitudes with phase information**, allowing interference effects that classical probability theory cannot reproduce.

That hidden phase structure is the secret sauce of quantum computing — and one of the reasons quantum mechanics is fundamentally different from classical physics.

Why complex numbers?

Complex numbers are one of the reasons quantum mechanics feels so different from everyday mathematics.

In ordinary arithmetic, every number sits somewhere on a number line:

- positive
- negative

- fractions
- decimals

These are called **real numbers**.

Complex numbers extend this system by introducing a new quantity:

$$i$$

defined by the property:

$$i^2=-1$$

At first, this seems impossible.

After all, no ordinary real number squared gives −1:

- $1^2=1$
- $(-1)^2=1$

So, mathematicians created a larger number system where this new object i exists.

A complex number therefore looks like:

$$a+bi$$

where:

- a is the real part
- b is the imaginary part
- and i is the square root of −1.

For example:

$$3+2i$$

is a complex number.

Why does quantum mechanics need them?

Because real numbers alone cannot describe:

- quantum phase
- interference
- oscillations of quantum states
- or the way quantum systems evolve through time.

Complex amplitudes are not just mathematical decoration.

They are a physical necessity.

Without complex numbers:

- interference would not work correctly
- quantum gates would not behave properly
- and the mathematics would fail to match experimental reality.

In other words, quantum mechanics genuinely requires a richer mathematical language than classical physics.

A helpful analogy is waves.

A classical probability only tells you *how likely* something is.

A quantum amplitude tells you:

- how likely something is
- **and**
- the phase relationship of the wave associated with it.

That extra phase information is encoded naturally using complex numbers.

This is what allows quantum amplitudes to:

- reinforce each other
- cancel each other
- and create interference patterns that classical probability theory cannot reproduce.

That interference is the engine behind quantum algorithms.

The good news is that you do not need deep complex-number mathematics immediately.

For most of this module, you can safely read:

$|\alpha|^2$

as simply:

"alpha squared"

and think of α as if it were an ordinary real number.

That approximation is enough to understand:

- superposition
- measurement
- probabilities
- and the conceptual foundations of qubits.

The full machinery of complex amplitudes becomes important later — especially when studying:

- quantum gates
- interference
- Bloch spheres
- and quantum algorithm design.

We introduce the idea now so that when complex numbers appear later, they feel like a natural extension of the story rather than an intimidating surprise.

A worked example

Consider the state $|\psi\rangle = (3/5)|0\rangle + (4/5)|1\rangle$. Is it a valid qubit state?

Check the normalisation: $|3/5|^2 + |4/5|^2 = 9/25 + 16/25 = 25/25 = 1$. Yes — it is valid. If you measured this qubit, you would get 0 with probability 9/25 (36%) and 1 with probability 16/25 (64%). The qubit leans slightly toward 1, but contains real probability of either outcome.

If you have followed this far, you have mastered the syntax of quantum computing. Most people stall here because the notation is unfamiliar, not because the ideas are hard. You now have the alphabet. Time to read.

CHAPTER 03

The Bloch Sphere

A way to see — actually see — what a single qubit is doing.

Equations are powerful. They let us describe quantum systems with extraordinary precision.

But sometimes a picture reveals an idea faster than pages of mathematics.

That is exactly why the **Bloch sphere** became one of the most important visual tools in quantum computing.

In the 1940s, the Swiss-American physicist Felix Bloch developed a geometric way to represent the state of a qubit. Bloch later received the 1952 Nobel Prize in Physics for his pioneering work on nuclear magnetic resonance (NMR), a discovery that eventually contributed to technologies like MRI scanners.

His visual model became known as the **Bloch sphere**.

And once you see it, quantum states stop feeling abstract.

A classical bit can only occupy one of two states:

- 0
- or 1

A qubit is different.

Because of superposition, a qubit can exist in infinitely many combinations of $|0\rangle$ and $|1\rangle$.

The Bloch sphere gives us a way to *see* all those possibilities geometrically.

Imagine a perfect sphere:

- the **north pole** represents $|0\rangle$
- the **south pole** represents $|1\rangle$

Every other point on the surface corresponds to a different quantum superposition.

So instead of thinking of a qubit as a switch with only two positions, you can think of it as an arrow pointing somewhere on a sphere.

That single visual idea is enormously powerful.

For example:

- points near the north pole are more likely to measure as 0
- points near the south pole are more likely to measure as 1
- points exactly around the equator correspond to equal probability superpositions like:

$$|+\rangle=\frac{1}{\sqrt{2}}(|0\rangle+|1\rangle)$$

and

$$|-\rangle=\frac{1}{\sqrt{2}}(|0\rangle-|1\rangle)$$

The crucial insight is that different locations on the sphere encode different **phases** as well as different probabilities.

That means the Bloch sphere is not merely a probability diagram.

It is a map of the full quantum state.

This picture becomes central to quantum computing because quantum gates can be visualised as rotations of the qubit around the sphere.

Instead of imagining mysterious equations acting on invisible states, you can imagine:

- rotating a vector
- around a sphere
- through precisely controlled quantum operations.

Once that intuition clicks, much of quantum computing starts feeling far more tangible and far less mystical.

The Bloch sphere is one of those rare scientific ideas that is simultaneously:

- mathematically rigorous
- visually elegant
- and conceptually transformative.

The picture

Imagine a sphere. Think of a globe of the Earth. The north pole of the sphere is the state |0⟩. The south pole is the state |1⟩. Every other possible state of a qubit corresponds to some point on the surface of this sphere. Not inside it. On its surface. Every point on the surface is a valid qubit state. Every valid qubit state corresponds to exactly one point.



Figure 3.1 — The Bloch sphere. North pole is |0⟩, south pole is |1⟩. The state |ψ⟩ is described by two angles: θ (polar) and ϕ (azimuthal).

How angles encode the state

Two angles describe any point on the surface of a sphere — the same way latitude and longitude describe any point on Earth. Quantum physicists call these angles θ (theta) and ϕ (phi).

Do not memorise the formula. The picture is what matters. θ is how far the state has rotated from the north pole. When θ = 0, you are at the north pole — pure |0⟩. When θ = π (180°), you are at the south pole — pure |1⟩. When θ = π/2 (90°), you are on the equator — equal superposition.

ϕ is the longitude — how far around the equator you have rotated. The longitude does not change the probability of measuring 0 or 1 (those come from θ alone). What ϕ encodes is phase. Two states at the same latitude but different longitudes have the same probabilities, but the phase difference matters when those states later interfere. This is why ϕ is real.

The equator is special

Anywhere on the equator, the qubit is in a 50/50 superposition. The state |+⟩ — the equal mix we met in the last chapter — sits at one point on the equator. The state |−⟩ sits at the opposite point on the equator. They look like equal superpositions if you only ask 'what is the probability of measuring 0?'. But geometrically they are 180° apart in ϕ. That is why the minus sign matters.

> **■ WHAT YOU CANNOT SEE ON THE BLOCH SPHERE**
>
> The Bloch sphere works for one qubit only. Two qubits cannot be drawn on a sphere. Their state lives in a 4-dimensional complex space. We have no good visual for it. This is one of the reasons quantum computing is hard — past one qubit, our brains have to rely on the maths because the geometry escapes ordinary intuition.

Why it works as a tool

The Bloch sphere is not just a teaching diagram or a simplified picture for beginners. It is a genuine working tool used throughout quantum computing research.

Every single-qubit operation, every quantum gate applied to one qubit, can be understood as a rotation of the qubit's state around the Bloch sphere.

For example:

- the **Pauli-X gate** (the quantum version of a NOT gate) acts like a 180° rotation around the X-axis
- phase shifts correspond to rotations around the Z-axis
- and the **Hadamard gate**, one of the most important gates in quantum computing, can also be visualised as a specific rotation that moves states between classical-looking and superposition states

This geometric interpretation is incredibly powerful because it turns abstract matrix algebra into something visual and intuitive.

Instead of imagining mysterious equations acting on invisible states, physicists can think in terms of:

- rotating vectors
- changing directions
- and moving qubits smoothly around the surface of the sphere

In practice, many researchers first design or analyse single-qubit operations using Bloch sphere geometry, verify the desired rotation behaviour visually, and only then translate the operation into matrix mathematics for implementation.

The picture is not merely educational.

It is genuinely part of how some of the world's leading quantum scientists think about quantum systems.

A common misconception, addressed

It is very tempting to think the Bloch sphere *is* the qubit.

It is not.

The Bloch sphere is a representation of the qubit's **state** — a mathematical and geometric picture that helps us visualise how a qubit behaves. It is accurate and enormously useful, but it is still a map rather than the territory.

The actual qubit is a physical object.

Depending on the hardware platform, it may be:

- a tiny superconducting electrical circuit cooled to millikelvin temperatures
- an electrically charged ion suspended in a vacuum chamber
- a neutral atom trapped by laser tweezers
- or even a photon moving through an optical system

Those are real physical systems obeying the laws of quantum mechanics.

The Bloch sphere describes the *state* of those systems.

It is important to keep both ideas in your head simultaneously:

1. the **physical qubit**
2. the **abstract state space** represented by the Bloch sphere

Quantum computing constantly moves between these two layers.

When physicists or engineers say:
"rotate the qubit,"
they do not mean physically spinning a tiny object like a planet.
They mean applying a precisely controlled physical interaction that changes the qubit's quantum state.
For example:

- in a superconducting qubit, this may involve a carefully timed microwave pulse
- in trapped-ion systems, it may involve lasers tuned to extremely specific frequencies
- in photonic systems, it may involve optical phase shifters or beam splitters

These physical operations manipulate the quantum system in controlled ways.
Mathematically, however, the effect can be described elegantly as a rotation of the state vector on the Bloch sphere.
So:

- the microwave pulse is real
- the laser is real
- the electromagnetic interaction is real
- but the "rotation" is a mathematical description of how the state evolves

The astonishing thing about quantum mechanics is how perfectly these two descriptions map onto one another.
A carefully engineered physical signal produces an exactly predictable geometric transformation in abstract quantum state space.
That connection between physical engineering and abstract mathematics is at the heart of quantum computing.
Quantum hardware engineers design the pulses.
Quantum theorists describe the rotations.
And quantum computation emerges from the exact correspondence between the two.

CHAPTER 04

Superposition

The first of the three big ideas — being in two states at once.

Superposition is the principle that a quantum system can exist in multiple states simultaneously until it is measured.
It is the first truly non-classical idea in quantum mechanics — the moment where quantum computing stops behaving like an advanced version of ordinary computing and starts operating according to fundamentally different rules.
We have already hinted at superposition several times:

- when discussing qubits
- when introducing amplitudes
- and when exploring the Bloch sphere

Now we examine it directly:

- what it actually means

- what it definitely does *not* mean
- and why it is one of the foundations of quantum computation.

In classical computing, a bit is always in one definite state:

- 0
- or 1

Even if you do not know which one it is, the bit itself still has a definite value.

A qubit is different.

A qubit can exist in a combination of both states at once:

$|\psi\rangle=\alpha|0\rangle+\beta|1\rangle$

This is not:

- the qubit secretly being 0 or 1 while we lack information
- a rapid oscillation between the two
- or a probabilistic coin flip

The qubit genuinely exists in a superposed quantum state until measurement occurs.

Only when the system is measured does the superposition collapse into one definite outcome.

That collapse produces probabilities determined by the amplitudes:

- $|\alpha|^2$
- and $|\beta|^2$

Why does this matter?

Because superposition allows quantum systems to explore many computational possibilities simultaneously.

With one qubit, you can represent combinations of two states. With two qubits, four states. With three qubits, eight.

In general:

$2n$

states for nn qubits.

That exponential growth is one of the reasons quantum computing is so powerful.

But superposition alone is not enough.

The real power emerges when superposition combines with:

- interference
- entanglement
- and carefully designed quantum algorithms

to amplify correct answers and suppress wrong ones.

Understanding superposition is therefore not just a physics lesson.

It is the conceptual gateway into how quantum computation becomes possible at all.

The metaphor — and its limits

Imagine flipping a coin high into the air.

While it is spinning, you cannot yet say it is heads. You cannot yet say it is tails.
Many introductory explanations use this as a metaphor for quantum superposition: the coin is “both” heads and tails while spinning, then becomes one definite result when it lands.
As a first intuition, the metaphor is helpful.
But it is also deeply incomplete.

A spinning classical coin still has a definite physical state at every moment.
If we filmed, it with a high-speed camera and knew:

- its initial force
- air resistance
- spin rate
- and angle of motion

we could, in principle, predict exactly how it would land.
The uncertainty is only in *our knowledge*.
The coin itself is never genuinely both heads and tails.
It always has a definite reality, even if we do not know it.

Quantum superposition is fundamentally different.
A qubit in the state:
$|\psi\rangle=\alpha|0\rangle+\beta|1\rangle$
is not secretly $|0\rangle$ or $|1\rangle$ while hiding that fact from us. Nor is it secretly $|1\rangle$.
The superposition itself *is* the physical state.
The qubit genuinely exists in a combination of both possibilities simultaneously, in proportions determined by the amplitudes α and β.
That distinction is crucial.
Quantum mechanics is not merely a theory of incomplete information.
It is a theory in which reality itself can exist in states that have no classical equivalent.

This idea was so disturbing that even Albert Einstein resisted it for much of his life.
Einstein believed there must be hidden underlying variables determining the “real” state of a quantum system.
But decades of experiments — culminating in the Bell inequality tests that led to the 2022 Nobel Prize in Physics — strongly supported the quantum view: there is no hidden classical value waiting to be revealed.
The superposition is not ignorance.
The superposition is the state itself.

How we know it is real and not just ignorance

How do we know superposition is real and not merely a reflection of our ignorance?
This is not just a philosophical debate.

It is an experimental question — and physics has tested it repeatedly for decades.
Throughout the 20th century, physicists designed increasingly sophisticated experiments to distinguish between two fundamentally different possibilities.

Possibility A: Hidden Variables

Quantum systems always possess definite properties, but we simply do not know them yet.
In this view, a qubit really *is* either $|0\rangle$ or $|1\rangle$, and superposition merely reflects incomplete information — like not knowing the outcome of a spinning coin before it lands.
This idea is called a **hidden variables theory**.
Many early physicists, including Albert Einstein, hoped this explanation would ultimately prove correct.
Einstein famously expressed his discomfort with quantum uncertainty by saying:
"God does not play dice with the universe."

Possibility B: Genuine Superposition

Quantum systems do not possess definite classical values before measurement.
Instead, they genuinely exist in superposed states until observation occurs.
The state:
$|\psi\rangle=\alpha|0\rangle+\beta|1\rangle$
is not hiding a secret classical answer underneath.
The superposition itself is physically real.

In 1964, John Bell proved mathematically that these two possibilities make different experimental predictions in carefully designed setups involving entangled particles.
These predictions became known as **Bell inequalities**.
Since then, physicists have performed thousands of increasingly precise experiments across laboratories worldwide.
The result has consistently been the same:
Quantum mechanics wins.
The experimental evidence overwhelmingly supports genuine superposition and rejects large classes of hidden-variable explanations.

But the evidence goes even deeper.
Quantum systems produce observable effects that are only possible if superposition is physically real.
The clearest example is **interference**.
In the famous double-slit experiment, single electrons are fired one at a time toward a screen containing two slits.
Classically, each electron should pass through:

- the left slit
- or the right slit

If that were true, the final pattern on the screen would simply be the sum of two particle streams.
But that is not what experiments show.
Instead, an interference pattern gradually appears — the same kind of pattern produced by overlapping waves.

That pattern only emerges if each electron behaves as though it passes through *both slits simultaneously* in a superposed state.
If the electron had secretly chosen one slit all along, the interference disappears mathematically.
The observed results cannot be reproduced by ordinary hidden classical probabilities.
The amplitudes themselves interfere:

- some paths reinforce each other
- others cancel each other

And that interference directly changes measurable outcomes.

Modern quantum computing depends entirely on this reality.
Quantum algorithms work because superposed amplitudes can interfere constructively and destructively during computation.
If superposition were merely ignorance:

- quantum interference would not occur
- quantum algorithms would fail
- and quantum computers would lose their unique advantages

Yet interference is observed constantly in laboratories around the world.
So physicists do not believe in superposition because it sounds philosophically attractive.
They believe in it because experiments repeatedly produce results that only genuine superposition can explain.
Time.

> **■ THE 2022 NOBEL PRIZE**
>
> The 2022 Nobel Prize in Physics was awarded to Alain Aspect, John Clauser, and Anton Zeilinger for experiments that closed every remaining loophole in Bell tests. The Royal Swedish Academy of Sciences' official statement: their work demonstrated that 'quantum mechanics cannot be replaced by a theory that uses hidden variables.' Superposition is not philosophical speculation. It is settled physics.

How much superposition? Amplitudes are the answer

A qubit is not simply “in superposition” or “not in superposition.”
Superposition is not a binary switch. It is a continuous spectrum, and the amplitudes α alpha α and β beta β determine *how much* the qubit leans toward each possible outcome.
The quantum state
$|\psi\rangle=\alpha|0\rangle+\beta|1\rangle$
can represent anything from a completely definite classical state to a perfectly balanced quantum superposition.
Three examples make this concrete.

Example 1 — No Superposition

$|\psi\rangle=|0\rangle$
Here:

- $\alpha=1$

- $\beta=0$

The qubit is entirely in the state $|0\rangle$.

The probabilities are:

- $P(0)=|1|^2=1$
- $P(1)=|0|^2=0$

If you measure this qubit a million times, you will obtain 0 every single time.

This is effectively behaving like a classical bit fixed at 0.

Example 2 — Maximum Superposition

$|\psi\rangle=\frac{1}{\sqrt{2}}(|0\rangle+|1\rangle)$

- Here:
- $\alpha=\beta=\frac{1}{\sqrt{2}}$
- Squaring the amplitudes gives:
- $P(0)=(\frac{1}{\sqrt{2}})2=\frac{1}{2}$
- $P(1)=\frac{1}{2}$

Now the qubit has equal probability of collapsing to either outcome.

This is often called a **maximally superposed state** because neither basis state dominates.

On the Bloch sphere, this state lies exactly halfway between the north and south poles.

Example 3 — Partial Superposition

$|\psi\rangle=\frac{\sqrt{3}}{2}|0\rangle+\frac{1}{2}|1\rangle$

Now the amplitudes are unequal.

The probabilities become:

- $P(0)=(\frac{\sqrt{3}}{2})^2=\frac{3}{4}$
- $P(1)=(\frac{1}{2})^2=\frac{1}{4}$

So if you measured many identical copies of this qubit:

- roughly 75% of the results would be 0
- roughly 25% would be 1

The qubit still exists in superposition, but it “leans” more heavily toward $|0\rangle$.

This is one of the deepest differences between classical and quantum information.

A classical bit only has two possibilities:

- 0
- or 1

A qubit has infinitely many possible states because the amplitudes can vary continuously.

That is why the Bloch sphere is so powerful.

It transforms superposition from an abstract equation into continuous geometry: every point on the sphere corresponds to a different balance of amplitudes, a different quantum state, and therefore a different probabilistic behaviour under measurement.

Why superposition is computationally powerful

If you have one qubit in superposition, it is 'partly 0 and partly 1' in the sense we have described. But here is where it gets genuinely strange. If you have two qubits, each in superposition, the system as a whole is in a superposition of all four basis states at once:
|00⟩, |01⟩, |10⟩, |11⟩.

Figure 4.2 — Each additional qubit doubles the number of basis states. With 300 qubits, the number exceeds atoms in the observable universe.

Three qubits in superposition — eight states at once. Ten qubits — 1,024 states. Fifty qubits — over a quadrillion states. Three hundred qubits — more states represented simultaneously than there are atoms in the observable universe. This exponential scaling is the source of quantum computing's potential power.

Crucially: this is not because the quantum computer is 'really' running 2 to the 300 separate computations. Rather, the quantum state mathematically spans all those basis states at once, and quantum gates can act on the whole superposition in a single

operation. The computational advantage emerges only when we cleverly arrange the operations so that the right answer emerges from the interference of all those amplitudes
— a topic we will treat in detail in Module 4.

What superposition is not

Superposition is powerful, but it is also one of the most misunderstood ideas in technology. To understand quantum computing properly, it is important to separate the science from the hype.

It is *not* infinite parallelism

People often hear that a 300-qubit quantum computer can represent more states than there are atoms in the observable universe and conclude that it must therefore “try every answer at once.”
That is not how quantum computing works.
A quantum computer cannot simply compute every possible answer in parallel and then magically read out the correct one. The moment you measure the quantum state, the superposition collapses to a single outcome, with probabilities determined by the amplitudes.

The real challenge of quantum algorithm design is therefore not creating superposition — that part is comparatively easy. The challenge is engineering the system so that the amplitudes corresponding to *correct* answers become large, while the amplitudes corresponding to wrong answers cancel out through interference.
This is the central trick behind famous algorithms like:

- Shor's factoring algorithm
- Grover's search algorithm
- modern quantum machine learning approaches

Quantum advantage comes not from "trying everything simultaneously," but from manipulating probability amplitudes in mathematically structured ways.

It is *not* magic

Quantum computers are not universally superior computers.
They are not replacements for laptops, cloud servers, or classical AI systems.
Most computational problems do **not** possess the mathematical structure required for quantum interference to produce an advantage. For many tasks, classical computers remain vastly more practical, cheaper, and faster.
Quantum computing matters because a small but extremely important class of problems *does* appear to benefit dramatically:

- cryptography
- optimisation
- molecular simulation
- quantum chemistry
- certain machine learning methods

Quantum literacy therefore means understanding both sides:

- where quantum helps
- and where it does not

That distinction is far more valuable than believing exaggerated claims about "quantum supremacy everywhere."

It is *fragile*

Superposition exists only while a quantum system remains isolated from unwanted interaction with its environment.
A stray photon.
A tiny thermal vibration.
Electromagnetic noise.
Even microscopic imperfections in materials.
Any of these can disturb the quantum state and destroy the superposition. This process is called **decoherence**, and it is the single greatest engineering challenge in building practical quantum computers.
That is why many quantum systems operate:

- near absolute zero
- inside ultra-high vacuum chambers
- with extraordinary shielding and error correction systems

Modern quantum hardware is essentially an attempt to preserve delicate quantum behaviour long enough to complete a computation before the environment destroys it.

We will return to decoherence, noise, and quantum error correction in Module 4, because understanding these limitations is essential to understanding where the industry truly stands today.

CHAPTER 05

Measurement

Where quantum strangeness becomes real — and where superposition ends.

Superposition is invisible.

It exists in the mathematical state of the qubit, not as something we can directly observe with our eyes or instruments in the ordinary sense. We cannot "look at" a qubit in superposition the way we can watch a spinning coin or see a wave moving across water.

In fact, the central difficulty of quantum mechanics is that the very act of observing a quantum system changes it.

A qubit can remain in a superposed state such as

$|\psi\rangle=\alpha|0\rangle+\beta|1\rangle$

while it evolves quietly according to the laws of quantum mechanics. But we never directly witness that superposition itself. What we observe are the outcomes produced when we perform measurements on many identically prepared qubits.

And measurement is not passive.

In classical physics, measuring something merely reveals a property that already existed. A thermometer reads a temperature that was already there. A voltmeter reveals a voltage already present in a circuit.

Quantum measurement is fundamentally different.

The moment we measure a qubit, the superposition collapses. The qubit stops behaving like a spread-out quantum state and becomes one definite outcome:

- either $|0\rangle$
- or $|1\rangle$

The probabilities of those outcomes are determined by the amplitudes:

- $|\alpha|^2$
- $|\beta|^2$

After measurement, the original superposition is gone.

This is one of the strangest and most important ideas in quantum computing: measurement does not simply reveal reality — it actively participates in creating the outcome we observe.

What measurement does

When you measure a qubit in the state

$\alpha|0\rangle+\beta|1\rangle$

two things happen simultaneously.

→ The qubit produces a definite answer

The measurement gives a single classical outcome:

- either 0
- or 1

Not "partly 0."
Not "both at once."
Not "uncertain."

A specific bit value emerges — exactly the kind of definite binary information that ordinary computers, sensors, and electronic systems can read.

The probabilities of obtaining each outcome are determined by the amplitudes:

- probability of measuring 0 is $|\alpha|^2$
- probability of measuring 1 is $|\beta|^2$

For example, if the qubit is in the state

$$\frac{\sqrt{3}}{2}|0\rangle+\frac{1}{2}|1\rangle$$

then:

- there is a 75% chance of measuring 0
- and a 25% chance of measuring 1

Before measurement, the qubit exists in superposition. After measurement, only one outcome remains.

→ The quantum state collapses

Measurement does not merely *reveal* the state. It changes it.

If the measurement returns:

- 0, the qubit collapses into the state $|0\rangle$
- 1, the qubit collapses into the state $|1\rangle$

The original superposition is destroyed.

This collapse is irreversible. Once the measurement has happened, the delicate combination of amplitudes that defined the superposition no longer exists.

That is why measurement is such a profound event in quantum mechanics: it converts a probabilistic quantum state into a definite classical reality.

And something even stranger follows.

If you immediately measure the qubit again, you will obtain the same answer with complete certainty.

For example:

- first measurement → 0
- second measurement → 0 again
- third measurement → still 0

Why?

Because after the first measurement, the qubit is no longer in superposition. It has already collapsed into a definite state.

The uncertainty existed only before the act of measurement.

Probability — and why amplitudes get squared

Which answer does the qubit actually produce when measured?

Quantum mechanics says the outcome is genuinely random, with probabilities determined by the amplitudes of the quantum state.

For a qubit in the state

$|\psi\rangle=\alpha|0\rangle+\beta|1\rangle$

the probabilities are:

$P(0)=|\alpha|^2$

and

$P(1)=|\beta|^2$

This means the amplitudes themselves are not probabilities. The *squared magnitudes* of the amplitudes are.

That distinction matters enormously.

For example, suppose:

$|\psi\rangle=\frac{\sqrt{3}}{2}|0\rangle+\frac{1}{2}|1\rangle$

The amplitudes are:

- $\frac{\sqrt{3}}{2}\approx 0.866$
- $\frac{1}{2}=0.5$

But the probabilities are obtained by squaring them:

- $P(0)=(\frac{\sqrt{3}}{2})2=\frac{3}{4}=75\%$
- $P(1)=(\frac{1}{2})2=\frac{1}{4}=25\%$

So the qubit is three times more likely to collapse to 0 than to 1.

This squaring rule is not an arbitrary mathematical trick.

It is one of the foundational laws of quantum mechanics, known as the **Born rule**, proposed by the German physicist Max Born in 1926.

The Born rule connects the abstract mathematics of quantum states to experimentally observable reality. Without it, the equations of quantum mechanics would not tell us what outcomes we should actually expect to see in experiments.

And remarkably, every experiment performed over the last century has confirmed it with extraordinary precision.

Max Born received the 1954 Nobel Prize in Physics in part for this insight.

One of the deepest lessons of quantum mechanics is therefore this:

Nature does not directly give us amplitudes.

Nature gives us probabilities derived from the squares of amplitudes.

And from that simple rule emerges interference, quantum algorithms, and ultimately the computational power of quantum computing itself.

■ RANDOM — BUT NOT ARBITRARY

The randomness in quantum measurement is not 'we don't know'. It is fundamental. Even with complete knowledge of the qubit's state, the next measurement outcome is not predictable. This is one of the deepest claims in physics. Einstein hated it. Bohr defended it. Decades of experiment have proven Bohr right. Quantum measurement outcomes are intrinsically random.

Why this kills superposition

Suppose a qubit is in the state (|0⟩ + |1⟩)/√2. You measure it and get 0. Now what?

The qubit is in state $|0\rangle$. Not state $(|0\rangle + |1\rangle)/\sqrt{2}$. The amplitudes have changed. The superposition is gone. If you immediately measure again, you will get 0 with certainty — no 50/50 randomness this time. Measurement does not just reveal information; it changes the state.

This is sometimes phrased as 'the wave function collapses on measurement'. The terminology is dramatic. The mechanism is real. And it is one of the most counter-intuitive aspects of quantum physics: the act of looking at a quantum system irreversibly changes it.

The measurement problem

What exactly counts as a 'measurement'? A human looking at a detector? A photon hitting a screen? An electron interacting with a wire? The mathematical formalism of quantum mechanics treats measurement as a special operation, but does not specify what physical processes count as measurements. This is called the measurement problem, and it is genuinely unsolved.

Different interpretations of quantum mechanics handle this differently. The Copenhagen interpretation (the most widely taught) says measurement is a primitive concept that we accept. The Many-Worlds interpretation says there is no collapse — every possible outcome happens in a separate branch of reality. Decoherence theory says measurement is what happens when a quantum system becomes irreversibly entangled with its macroscopic environment.

For the purposes of building quantum computers, the interpretation does not matter. The mathematical rules — superposition, evolution by quantum gates, collapse on measurement — are the same regardless of what philosophy you bring to them. Engineers and algorithm designers use the rules. Philosophers debate what the rules mean.

How measurement is used in algorithms

If measurement destroys superposition, why is it useful? Because the whole point of a quantum algorithm is to first set up a useful superposition, then use quantum gates to concentrate the amplitudes on the right answer, then measure to read it out.

A useful quantum algorithm is structured like this:

Step 1. Initialise qubits in a known starting state, usually $|000...0\rangle$.

Step 2. Apply Hadamard or similar gates to create superposition over many basis states.

Step 3. Apply a sequence of quantum gates that encode the problem. These gates manipulate the amplitudes — boosting some, cancelling others — through quantum interference.

Step 4. Measure. With high probability, the answer that emerges is the one you want.

Steps 1-3 happen in superposition, where quantum advantage exists. Step 4 destroys superposition — but by then the work is done. The output is a classical bit string. Quantum advantage lives between the input and the output, not in either endpoint.

CHAPTER 06

The Double-Slit Experiment

The single experiment that contains every strange feature of quantum mechanics.

Richard Feynman — widely regarded as one of the greatest physicists and science communicators of the 20th century — once said of the double-slit experiment:

"It has in it the heart of quantum mechanics. In reality, it contains the only mystery."

That is not an exaggeration.

The double-slit experiment compresses nearly every strange feature of quantum mechanics into one deceptively simple setup:

- superposition
- probability amplitudes
- interference
- wave-particle duality
- the role of observation
- and the strange effect of measurement itself

Everything we have discussed so far appears inside this single experiment.

If you truly understand the double-slit experiment, you understand the *spirit* of quantum mechanics — not just the equations, but the conceptual revolution beneath them.

The experiment forces us to abandon deeply classical intuitions about how reality should behave. Tiny quantum objects do not act purely like particles. They do not act purely like waves. And the act of measuring them fundamentally changes what happens.

That is why generations of physicists keep returning to this experiment. It is not merely a historical curiosity. It is the conceptual foundation beneath modern quantum computing, quantum cryptography, quantum communication, and quantum information science itself.

In many ways, the entire quantum revolution begins with two tiny slits in a screen.

Setting up the experiment

The setup is beautifully simple.

You begin with a source that emits tiny quantum objects one at a time. Historically, the experiment was performed with electrons, but the same basic idea works with photons, atoms, and even small molecules.

These particles travel toward a barrier containing two narrow openings: the famous **two slits**. Behind the barrier is a detector screen that records where each particle eventually lands.

At first glance, this sounds like an ordinary experiment in motion.

A source emits objects. The objects pass through openings. A screen records their arrival.

But the result is anything but ordinary.

If the particles behaved like tiny classical objects — like miniature billiard balls — the expectation would be straightforward.
Each particle should go through either the left slit or the right slit.
Not both.
One or the other.
Over time, as many particles pass through the apparatus, the detector screen should build up two bright regions: one behind the left slit and one behind the right slit.
It would look like throwing tennis balls through two doorways. Most of the balls would land in two clusters behind the openings. That is exactly what classical particle behaviour predicts.
Two slits should produce two impact bands.
Simple.

But waves behave differently.
Imagine water waves moving toward a wall with two gaps in it. When the wave reaches the barrier, part of the wave passes through each gap. Each slit then becomes a new source of spreading waves.
These two waves overlap.
Where their peaks meet, they reinforce each other. This is called **constructive interference**.
Where the peak of one wave meets the trough of another, they cancel each other out. This is called **destructive interference**.
The result is not two simple bands.
Instead, the detector would show a striped pattern:

- bright bands where the waves reinforce
- dark bands where the waves cancel

That striped pattern is the unmistakable signature of wave behaviour.

So classical intuition gives us two possibilities.
If electrons behave like particles, we should see two bands.
If they behave like waves, we should see an interference pattern.
The shocking discovery is that quantum objects produce the wave-like interference pattern — even when they are sent through the apparatus one at a time.
That is where the mystery begins.

What actually happens

When the experiment is performed, the result is astonishing.
If you fire many particles through the two slits — electrons, photons, atoms, or even certain molecules — the detector screen does **not** show two simple clusters behind the slits.
Instead, it gradually builds up an **interference pattern**: alternating bright and dark bands, exactly the kind of pattern we expect from waves.
That alone would already be strange.
But the truly remarkable part comes when the particles are sent through the apparatus **one at a time**.

The experiment can be arranged so that each particle enters the setup alone, with enough delay that there is no possibility of one particle interacting with another.

One electron enters. It hits the screen. Then another electron enters. It hits the screen. Then another.

Each individual particle appears on the detector as a single dot, like a tiny particle impact.

But after thousands or millions of these individual dots accumulate, they form a wave-like interference pattern.

This means each particle is somehow interfering with itself.

That is the mystery.

There is no second electron present. No crowd of particles. No classical wave of many objects moving together.

And yet the final pattern is unmistakably an interference pattern.

The only way quantum mechanics explains this is that the particle's state travels through the apparatus as a **superposition** of possibilities.

In this case, the particle is not simply going through the left slit or the right slit in the classical sense.

Its quantum state is a combination of:

*went through the left slit**text{went through the left slit}*went through the left slit

and

*went through the right slit**text{went through the right slit}*went through the right slit

at the same time.

Those two parts of the quantum state then spread out, overlap, and interfere with each other before the particle is finally detected on the screen.

Where the amplitudes reinforce each other, particles are more likely to land. Where the amplitudes cancel each other, particles are unlikely to land.

That is why bright and dark bands appear.

This is superposition made visible.

The interference pattern is not just a mathematical prediction or a philosophical interpretation. It is an experimental result. It shows that the superposed quantum state has real physical consequences.

If the particle had secretly chosen one slit all along, like a tiny classical object, the interference pattern would disappear.

But the pattern appears.

Again and again.

That is why the double-slit experiment remains one of the clearest demonstrations that superposition is not merely ignorance, confusion, or incomplete information.

It is a real feature of quantum systems.

> ■ **KEY HISTORICAL FACT**
>
> Thomas Young first performed the double-slit experiment with light in 1801, demonstrating that light is a wave. One hundred years later, in 1909, G. I. Taylor showed the same interference pattern emerges even when

only one photon is in the apparatus at a time — proving that each photon interferes with itself. The result has since been replicated with electrons (1961), atoms (1991), and large molecules (2019). The mystery deepens with every replication.

The which-path puzzle

Now the double-slit experiment becomes even stranger.

Suppose we place a tiny detector near the slits to find out which path each particle takes. The goal is simple: we want to check whether the particle "really" went through the left slit or the right slit.

In classical physics, this should not be a problem. Observing the path of a tennis ball does not change the fact that it passed through a doorway. Measurement simply reveals what already happened.

But quantum mechanics behaves differently.

The moment we gain which-path information, the interference pattern disappears.

Instead of bright and dark wave-like bands, the detector screen now shows two ordinary clusters — one behind each slit — exactly like classical particles passing through two openings.

This is profound.

Before measurement, the particle's quantum state behaves as a superposition of both possibilities:

$left\ path + right\ path|text\{left\ path\} + |text\{right\ path\}$left path+right path

Both paths contribute amplitudes to the final outcome, and those amplitudes interfere. Some reinforce each other, creating bright bands. Others cancel each other, creating dark bands.

But when we measure which slit the particle went through, the superposition is destroyed. The particle is forced into one definite path: left or right.

Once that happens, there are no longer two parts of the quantum state available to interfere with each other.

So the interference disappears.

This is the same collapse-on-measurement principle we saw earlier, now displayed physically on a screen. As long as the particle remains unmeasured, both possible paths participate in the result. The instant we ask, "Which path did it take?" the quantum state collapses into one answer — and the wave-like behaviour vanishes.

The lesson is simple but extraordinary:

Quantum systems can preserve multiple possibilities only while those possibilities remain unmeasured.

Measurement does not merely reveal the path.

It changes the experiment.

Why this matters for quantum computing

The double-slit experiment is not just a famous physics demonstration.

It is a miniature version of the logic behind quantum computing.

In one simple setup, it reveals the three principles that every quantum computer depends on: **superposition, interference, and measurement**.

✓ Superposition is real

In the double-slit experiment, a quantum object behaves as though it takes multiple paths at once.

It is not simply that we do not know which path it took. The interference pattern shows that both possible paths contribute to the result.

Quantum algorithms use the same principle.

Instead of placing a particle into a superposition of “left slit” and “right slit,” a quantum computer places qubits into superpositions of many possible computational states.

Those states may represent:

- possible solutions
- possible paths
- possible configurations
- possible values in a search space

This is what gives quantum computers access to enormous state spaces.

✓ Interference is the resource

The real power is not superposition alone.

The real power is **interference**.

In the double-slit experiment:

- bright bands appear where amplitudes reinforce each other
- dark bands appear where amplitudes cancel each other

Quantum algorithms are built around the same idea.

They are designed so that amplitudes associated with useful or correct answers increase through constructive interference, while amplitudes associated with wrong answers shrink through destructive interference.

This is why quantum computing is not simply “trying every answer at once.”

If all possible answers were merely placed into superposition and then measured immediately, the result would usually be random.

The algorithm must first shape the amplitudes.

That shaping process is the computation.

✓ Measurement collapses the advantage

The double-slit experiment also shows why measurement is dangerous.

If you measure which slit the particle goes through, the interference disappears.

The same idea applies to quantum computing.

A quantum computer only gains advantage while its qubits remain coherent and unmeasured. If the environment accidentally extracts information from the qubits — through heat, vibration, electromagnetic noise, or stray interactions — the quantum state collapses or decoheres.

This is called **decoherence**, and it is one of the central engineering challenges in building real quantum computers.

In practical terms, quantum hardware must protect qubits long enough for the algorithm to complete its interference pattern before measurement happens.

Every major quantum algorithm — Shor’s algorithm, Grover’s search, QAOA, and modern variational methods — is, at its deepest level, a more sophisticated version of the double-slit experiment.

The setup is more elaborate.

The mathematics is more advanced.

The number of possible paths is vastly larger.

But the core principles are the same:

create superposition, use interference, then measure only after the amplitudes have been shaped toward the answer you want.

CHAPTER 07

Entanglement

The strangest correlation in nature — and the second pillar of quantum computing.

Superposition is about one quantum system holding multiple possibilities at once.

Entanglement is different.

Entanglement is what happens when two or more quantum systems become linked so deeply that they can no longer be fully described independently. The state of one qubit is no longer just "its own" state. Instead, the qubits share a single combined quantum state.

That distinction matters.

A single qubit can be in a superposition of $|0\rangle$ and $|1\rangle$. But when multiple qubits become entangled, the information is no longer stored separately in each qubit. It is stored in the relationship between them.

This is the second of our three quantum pillars:

- superposition
- entanglement
- interference

And entanglement is one of the main reasons quantum computing becomes radically different from classical computing.

Einstein found this idea deeply unsettling. In his view, physics should describe a universe where objects have definite properties and no influence can travel faster than light. Entanglement seemed to challenge that intuition, because measuring one particle could instantly determine the correlated state of another, even if the two were separated by a vast distance.

He famously dismissed this as:

"spooky action at a distance."

Einstein meant the phrase as criticism.

But history did something interesting with it.

The universe took the insult and turned it into a label.

Today, "spooky action at a distance" is one of the most famous phrases in physics — not because Einstein's discomfort was foolish, but because he had identified exactly what makes entanglement so strange, so powerful, and so central to the quantum world.

The simplest example

Imagine two qubits prepared in this special joint state:

$$|\Phi^+\rangle = (|00\rangle + |11\rangle) / \sqrt{2}$$

Read this state carefully, because it captures the essence of entanglement.

We have a system made of **two qubits**. Their joint quantum state is not four independent possibilities. It is a superposition of only two:

|00⟩

and

|11⟩

That means the system is in a quantum combination of:

- both qubits being 0
- both qubits being 1

It is **not** in a superposition of:

|01⟩

or

|10⟩

So the qubits are perfectly correlated.

If one is measured as 0, the other will also be 0. If one is measured as 1, the other will also be 1.

They always agree.

This kind of state is one of the famous **Bell states** — a family of special two-qubit states that are maximally entangled. In a Bell state, the information is not stored in either qubit individually. It is stored in the relationship between them.

That is the key idea.

Now imagine separating the two qubits.

Give one qubit to Alice in London. Send the other to Bob on a spaceship halfway to Mars.

The distance does not break the joint quantum state. The two qubits are still described together. They remain part of one shared entangled system.

Before measurement:

- Alice's qubit does not have a definite value
- Bob's qubit does not have a definite value
- neither is secretly already 0 or 1
- the combined system is still in superposition

But the relationship between them is definite:

They will match.

If Alice measures her qubit and gets 0, Bob will get 0 when he measures his. If Alice gets 1, Bob will get 1.

This is what makes entanglement so strange. The individual outcomes are random, but the correlation is perfectly structured.

Alice cannot control whether she gets 0 or 1. Bob cannot use this to receive a faster-than-light message.

But once both compare their results later, they will discover that the measurements were correlated in a way no ordinary classical explanation can fully reproduce.

That is the power of entanglement: the quantum state belongs to the pair, not to the individual qubits separately.

Now Alice measures her qubit

Alice now measures her qubit.

At that moment, the shared entangled state collapses.

Her result is genuinely random:

- 50% chance she measures 0
- 50% chance she measures 1

From Alice's local perspective, this looks exactly like measuring a single qubit in an equal superposition. She cannot choose the result. She cannot force it to be 0 or 1.

Suppose Alice measures and gets:

$00$0

Then the joint entangled state collapses into the matching outcome:

$|00\rangle$

Alice's qubit is now in state:

$|0\rangle$

And Bob's qubit is also now in state:

$|0\rangle$

Even if Bob is many light-minutes away.

That is the strange power of entanglement.

Bob's qubit did not receive an ordinary signal from Alice's qubit. No message travelled across space telling it what to become. There was no classical communication, no physical wire, and no interaction moving between them at the speed of light.

Instead, the two qubits were never truly independent objects in the first place.

They were parts of one shared quantum state.

So when Alice measured her half of the system, the joint state was forced into one consistent outcome.

If Alice had measured:

$11$1

then the shared state would have collapsed into:

$|11\rangle$

and Bob's qubit would now be in state:

$|1\rangle$

Whatever Alice gets, Bob's result will match.

The individual outcome is random.

But the relationship is perfectly structured.

Alice cannot use this to send a message to Bob faster than light, because she cannot control whether her result is 0 or 1. But when Alice and Bob later compare their measurement records through ordinary communication, they will find that their outcomes were perfectly correlated.

That is what makes entanglement so extraordinary:

the randomness is local, but the correlation is global.

The two qubits can be separated by a room, a city, or a cosmic distance — yet the shared quantum state links their outcomes in a way classical physics cannot explain.

> ■ **WHAT IT DOES NOT DO**
>
> It is essential to understand: this cannot be used to send messages faster than light. Alice's measurement gives her a random outcome. Bob's measurement also gives him a random outcome. Each individually sees pure random noise. The correlation only becomes visible when Alice and Bob later compare notes — and their comparison must travel at light speed or slower. Special relativity remains intact. Entanglement creates correlation, not communication.

The 'spooky' part

Einstein was deeply disturbed by entanglement for two main reasons.

The first reason was **non-locality**.

In an entangled pair, Bob's qubit appears to become correlated with Alice's measurement instantly, even if Bob is far away — across a city, across a planet, or even many light-minutes into space.

From Einstein's point of view, this was profoundly uncomfortable.

His theory of relativity had established that no usable signal or physical influence should travel faster than the speed of light. Yet entanglement seemed to suggest that measuring Alice's qubit immediately affected the state assigned to Bob's qubit, with no obvious mechanism connecting them through space.

This does **not** allow faster-than-light communication, because Alice cannot control whether she gets 0 or 1. But it still challenged Einstein's intuition that physical effects should be local — that what happens "here" should not instantly determine what is observed "there."

That is why he famously described entanglement as:

"spooky action at a distance."

The second reason was even deeper: the correlations are **too strong for any classical explanation**.

You might try to rescue classical intuition by saying:

"Maybe the qubits already had definite hidden values from the start. Alice and Bob are simply discovering what was already there."

This is called a **hidden variables** explanation.

It sounds reasonable at first. But in 1964, the physicist John Bell proved something extraordinary: if hidden local values really existed, then the correlations between Alice's and Bob's measurements would have to obey certain mathematical limits, now called **Bell inequalities**.

Quantum mechanics predicts correlations that violate those limits.

And experiments have repeatedly confirmed that quantum mechanics is right.

The work of Alain Aspect, John Clauser, and Anton Zeilinger demonstrated these violations with increasing experimental sophistication, eventually earning them the 2022 Nobel Prize in Physics.

So, Einstein was not disturbed because entanglement was merely strange.

He was disturbed because it appeared to expose something fundamentally non-classical about reality itself:

- measurement outcomes are not simply pre-written hidden values
- distant quantum systems can share correlations stronger than classical physics allows
- and nature does not obey the local, intuitive picture Einstein hoped would survive

Entanglement does not break relativity by sending messages faster than light.
But it does break the classical idea that separated objects must always have independent, pre-existing properties.

Entanglement as a computing resource

Entanglement matters because it gives quantum computers and quantum communication systems capabilities that have no true classical equivalent.
Superposition allows a quantum system to hold multiple possibilities at once. Interference allows amplitudes to reinforce or cancel. But entanglement allows multiple qubits to behave as one connected quantum system, even when separated. That shared state is one of the key resources that makes quantum information fundamentally different from classical information.
Here are three concrete examples.

1. Quantum teleportation

Quantum teleportation does not mean teleporting a physical object like in science fiction.
It means transferring the **exact quantum state** of one qubit from Alice to Bob, using:

- a pre-shared entangled pair
- one additional qubit whose state Alice wants to send
- and two ordinary classical bits of information

The remarkable part is that Alice does not need to physically send the original qubit itself. By performing a special measurement on her side and sending Bob two classical bits, Bob can reconstruct the original quantum state at his location.
The quantum state effectively arrives at Bob's side intact.
This matters because quantum states cannot be copied directly — a rule known as the **no-cloning theorem**. Teleportation provides a way to move quantum information without copying it.
This is one of the foundations of future quantum networks, quantum communication systems, and eventually a quantum internet.

2. Superdense coding

Superdense coding shows the reverse kind of power.
If Alice and Bob already share an entangled pair, Alice can send Bob **two classical bits of information** by transmitting only **one qubit**.
Classically, one bit carries one bit of information.
But with entanglement already shared between Alice and Bob, one transmitted qubit can carry more classical information than would otherwise be possible.
This does not violate physics or allow magical communication. The entanglement has to be established beforehand. But once it exists, it becomes a communication resource that can be used in highly efficient quantum protocols.
Superdense coding is one of the clearest examples of entanglement acting as a practical information-processing tool.

3. Quantum algorithms

Entanglement also plays a central role inside quantum computation itself.

Many important quantum algorithms require qubits to become entangled during the computation. The algorithm creates correlations between qubits so that the quantum computer is no longer processing each qubit independently. Instead, it is manipulating a shared multi-qubit state.

This matters for algorithms such as:

- Shor's algorithm for factoring
- Grover's search algorithm
- QAOA for optimisation
- variational quantum algorithms used on today's NISQ hardware
- quantum machine learning models

In these systems, entanglement helps create the rich quantum state space on which interference can operate.

Without entanglement, many quantum systems can often be efficiently simulated by classical computers. In that case, the machine may look quantum physically, but it does not deliver a meaningful computational advantage.

This is why entanglement is often described as a core resource of quantum computing.

It is not just a strange philosophical feature of quantum mechanics. It is something quantum technologies actively use.

Entanglement allows quantum information to be distributed, compressed, transferred, and processed in ways that classical systems cannot fully reproduce. Without it, quantum computing would lose much of what makes it genuinely powerful.

A real-world example — Quantum Key Distribution

One of the most mature real-world applications of quantum information today is **Quantum Key Distribution**, usually shortened to **QKD**.

QKD is not a general-purpose encryption system by itself. Instead, it solves one extremely important problem: how two parties can securely exchange encryption keys.

One especially important version is the **E91 protocol**, proposed by Artur Ekert in 1991. Unlike earlier QKD approaches, E91 is based directly on **entanglement** and the violation of Bell inequalities. In other words, the same strange quantum correlations that disturbed Einstein become a practical security tool.

Here is the core idea.

Alice and Bob share pairs of entangled particles. Each receives one particle from every pair. When they measure their particles, the results are strongly correlated in a way that classical physics cannot reproduce.

If no one interferes with the system, Alice and Bob observe the quantum correlations they expect.

But if an eavesdropper — traditionally called Eve — tries to intercept or measure the particles in transit, she cannot do so invisibly. Her measurement disturbs the quantum state and weakens or destroys the entanglement.

Alice and Bob can detect this by comparing a sample of their measurement results and performing a Bell-type test. If the correlations fall below the quantum-mechanical threshold, they know the channel has been compromised.

That is the key promise of QKD: the security is not based only on computational difficulty, but on the laws of physics. Toshiba and ID Quantique are among companies offering QKD systems, and KETS Quantum Security in Bristol has been active in the UK quantum-secure communications ecosystem. Toshiba lists QKD products for long-

distance and multiplexed network use, while ID Quantique describes QKD as a method for securing symmetric key distribution using quantum physics.

QKD has also moved beyond laboratory theory. In 2007, Geneva, Switzerland used quantum cryptography technology from ID Quantique to help protect election data transmission, an early real-world deployment that received international attention.

For quantum computing, the lesson is important: entanglement is not just a philosophical curiosity. It is already being used as an engineering resource for secure communication, quantum networking, and the early foundations of a future quantum internet.

■ QKD IS NOT THE SAME AS POST-QUANTUM CRYPTOGRAPHY

QKD uses quantum physics to protect the key exchange itself. Post-quantum cryptography (PQC) uses new mathematical problems that even quantum computers cannot break easily. They solve different parts of the problem. QKD requires specialised hardware and works only over short distances today. PQC is software-only and can be deployed everywhere now. Most organisations will use PQC; some high-security government and financial users will combine both. Module 6 covers both in depth.

CHAPTER 08

Bell's Theorem & the 2022 Nobel Prize

Proving entanglement is real — settling Einstein's last objection.

Einstein never fully accepted entanglement.

To him, the idea that two particles could remain mysteriously linked across distance was deeply unsatisfying. Physics, in Einstein's view, should describe a reality made of definite properties, governed by local causes. What happens in one place should not instantly determine what happens somewhere far away.

In 1935, Einstein, together with Boris Podolsky and Nathan Rosen, published one of the most famous papers in the history of quantum mechanics. It became known simply as the **EPR paper**, after the initials of its three authors.

Their argument was not that quantum mechanics was useless. By then, quantum theory was already extraordinarily successful at predicting experimental results. Their argument was more subtle and more serious: **quantum mechanics must be incomplete.**

According to Einstein, Podolsky, and Rosen, particles must possess hidden properties that quantum theory was failing to describe. These hidden properties — later called **hidden variables** — would determine the results of measurements in advance.

In this view, quantum randomness was not truly fundamental.

It only looked random because we lacked access to the deeper information underneath.

A simple analogy would be a shuffled deck of cards. If you draw a card without looking, the result seems random to you. But the card already had a definite identity before you observed it. Your ignorance does not make the card physically undecided.

Einstein believed quantum systems might work the same way.

When Alice and Bob measured their entangled particles, perhaps the results were not being created at the moment of measurement. Perhaps the particles had carried hidden instructions from the beginning — instructions telling them exactly how to respond later.

For nearly thirty years, this remained one of the deepest philosophical disputes in physics.

On one side was Einstein's view: quantum systems have definite hidden properties, and randomness reflects our ignorance.

On the other side was the standard quantum view: measurement outcomes are genuinely probabilistic, and entangled particles do not possess pre-written classical values before measurement.

For decades, there seemed to be no way to decide between them experimentally.

Both views could explain many of the same observations.

Then, in 1964, an Irish physicist named **John Bell** changed everything.

Bell showed that this was not merely a philosophical disagreement. It was a testable scientific question. Hidden-variable theories and standard quantum mechanics make different predictions under carefully designed experimental conditions.

That result transformed the foundations of quantum mechanics.

After Bell, the question was no longer:

"Which interpretation feels more reasonable?"

It became:
“Which prediction does nature actually follow?”
And nature, as later experiments showed, sided with quantum mechanics.

Bell's insight

Bell asked a beautifully sharp question:
Could any theory based on **hidden variables** and **locality** reproduce all the predictions of quantum mechanics?
In other words, could Einstein still be right if particles carried hidden instructions from the beginning, and no influence travelled faster than light?
Bell’s answer was extraordinary.
He proved that any theory built on both assumptions — hidden variables plus locality — must obey a specific mathematical limit. That limit is now known as **Bell’s inequality**.
The idea is simple in spirit, even if the mathematics is subtle.
If Alice and Bob measure two separated particles, and those particles merely carried pre-written hidden values from the start, then their results can only be correlated up to a certain strength. Classical hidden-variable theories cannot exceed that limit.
Quantum mechanics predicts something different.
For entangled particles, quantum mechanics predicts correlations that are stronger than any local hidden-variable theory allows. In certain carefully designed experiments, those correlations violate Bell’s inequality.
That changed everything.
Before Bell, the argument between Einstein and the standard quantum view looked philosophical. It seemed to be a matter of interpretation: is quantum randomness real, or are we simply ignorant of deeper hidden properties?
After Bell, the dispute became empirical.
The two views made different predictions.
That meant nature could be asked directly.
Build the experiment.
Measure the correlations.
Check whether Bell’s inequality is obeyed or violated.
If the inequality holds, Einstein’s local hidden-variable picture survives.
If the inequality is violated, the quantum view wins.
This was one of the most important moments in modern physics: Bell turned a debate about the meaning of reality into a laboratory test.

■ **WHAT BELL'S THEOREM REALLY SAYS**

> Bell's theorem is often summarised as 'no hidden variables theory can reproduce quantum mechanics'. More precisely: no local hidden variables theory can. If experiments violate Bell's inequality, we are forced to conclude that at least one of two ideas must be wrong: (a) the world has definite properties before measurement, or (b) effects cannot propagate faster than light. Both ideas were dear to Einstein. Quantum mechanics requires giving up at least one.

The experiments

It took years to design experiments good enough to test Bell's inequality. The first decisive test was performed by John Clauser at Berkeley in 1972, using entangled photons. He found, as quantum mechanics predicted, that the correlations violated Bell's inequality.

But Clauser's experiment had loopholes. Over the next 50 years, increasingly ingenious experiments closed each loophole one by one:

1982	1998	2015	2022
Aspect, Paris	Zeilinger, Innsbruck	Hensen, Delft	Nobel Prize
locality loophole	detection loophole	all loopholes	Finally settled

Alain Aspect closed the 'locality loophole' in 1982 by ensuring that measurement choices were made too fast for any light-speed signal. Anton Zeilinger closed the 'detection loophole' through more efficient detectors. Ronald Hansen in Delft, in 2015, closed all loopholes simultaneously. By 2018, multiple research groups had reproduced this result.

The 2022 Nobel Prize

On **October 4, 2022**, the Royal Swedish Academy of Sciences awarded the **Nobel Prize in Physics** to **Alain Aspect, John Clauser, and Anton Zeilinger**:

“for experiments with entangled photons, establishing the violation of Bell inequalities and pioneering quantum information science.”

This was not simply a prize for an elegant theory.

It was recognition of one of the deepest experimental achievements in modern physics: the question raised by Einstein, Podolsky, and Rosen in 1935 had finally been tested — and nature had answered.

Einstein had hoped that quantum mechanics was incomplete. Perhaps, he argued, particles carried hidden information that determined their measurement outcomes in advance. Perhaps the randomness of quantum mechanics was only an illusion caused by our ignorance.

Bell showed that this idea could be tested.

Aspect, Clauser, Zeilinger, and many others performed the experiments.

The result was clear: entangled particles violate Bell inequalities exactly as quantum mechanics predicts.

That means no theory based on **local hidden variables** — hidden pre-existing values plus no faster-than-light influence — can explain the observed correlations.

This is why entanglement is not just a strange mathematical feature.

It is real.

The universe does not behave like a classical machine with hidden instructions running underneath. At the quantum level, nature permits correlations stronger than any local classical theory can produce.

Quantum mechanics, with all its discomfort and strangeness, has survived one of the most profound experimental tests in science.

What this means for Diarka Quantum's clients

When Diarka Quantum briefs executives, board members, founders, or investors, this point matters enormously: Quantum computing is not built on speculation.

The field rests on physical phenomena — **superposition, entanglement, and interference** — that have been tested with extraordinary precision for decades. These are not marketing concepts or theoretical fantasies. They are experimentally verified features of nature.

The 2022 Nobel Prize in Physics was an important signal to the wider world: the strange foundations of quantum mechanics are not just mathematically elegant; they are real. Entanglement, in particular, has been tested, challenged, and confirmed. The universe behaves in the quantum way, not the classical way Einstein hoped might still be hidden underneath.

For business leaders, this distinction is crucial.

The question is no longer:

“Is quantum mechanics real enough to build technology on?”

That question has already been answered.

The real question is:

“When will the engineering become mature enough to create practical, economic value?”

That is where the industry race now sits.

The remaining challenges are not foundational physics problems. They are engineering problems:

- keeping qubits coherent long enough to compute
- reducing error rates
- scaling from noisy devices to fault-tolerant machines
- improving control systems, cooling, fabrication, and error correction
- identifying business problems where quantum advantage will matter

These challenges are extremely difficult. But they are not reasons to dismiss the field.

They are the same kind of engineering challenges every transformative technology faces between scientific discovery and commercial adoption.

The science is real.

The race is now to turn that science into reliable machines, useful applications, and measurable business value.

CHAPTER 09

Qubits in Action

How real quantum computers use these principles — gates, circuits, and the simplest entanglement.

We have built the conceptual foundation.

Now it is time to watch quantum computing actually *do* something.

So far, we have discussed the ideas that make quantum systems different from classical systems: superposition, measurement, interference, and entanglement. These ideas can feel abstract when described only in words. But inside a quantum computer, they are not abstract at all. They are implemented through specific operations called **quantum gates**.

A quantum gate is the quantum equivalent of a logic gate in classical computing. Classical gates manipulate bits: turning 0 into 1, comparing values, or combining signals. Quantum gates manipulate qubits. They rotate quantum states, create superpositions, change phases, and link qubits together through entanglement.

In this chapter, we move from concept to operation.

We will see how a quantum computer takes an ordinary qubit in the state:

$$|0\rangle$$

and applies a gate that transforms it into a superposition:

$$(|00\rangle + |11\rangle) / \sqrt{2}$$

Then we will see how two ordinary qubits, initially independent, can be transformed into an entangled pair — a state where the qubits are no longer separately describable, but instead share one joint quantum state.

This is the moment quantum computing becomes concrete.

Superposition is no longer just an idea. Entanglement is no longer just a mystery. They become operations — things a quantum computer can deliberately create, control, and use.

By the end of this chapter, you will understand the basic moves quantum computers perform: how gates act on qubits, how circuits are built from those gates, and how simple operations produce the foundations of quantum advantage.

Gates — what a quantum computer can do

A classical computer performs computation by applying **logic gates** to bits.

These gates include familiar operations such as:

- AND
- OR
- NOT
- XOR

Each gate takes one or more input bits and produces output bits according to fixed rules. This is the foundation of classical digital computation.

A quantum computer works in a similar spirit, but with a very different kind of object.

Instead of applying classical logic gates to bits, a quantum computer applies **quantum gates** to qubits.

A quantum gate is an operation that changes the state of a qubit. On the Bloch sphere, many single-qubit gates can be visualised as rotations. In algebra, they are represented by matrices. Physically, they are implemented through carefully controlled pulses, lasers, microwave signals, or optical components depending on the hardware platform.

But quantum gates must obey two important rules.

First, they must preserve total probability. If a qubit has some probability of being measured as 0 and some probability of being measured as 1, those probabilities must still add up to 1 after the gate is applied.

Second, quantum gates must be reversible. In principle, if you know the output state and the gate that was applied, you can work backward to recover the input state. This reversibility is one of the deep differences between quantum computation and many ordinary classical logic operations.

For single-qubit operations, three gates appear constantly:

$$X, H, Z$$

These are among the most important building blocks in quantum computing.

The **X gate** is the quantum version of NOT. It flips $|0\rangle$ to $|1\rangle$, and $|1\rangle$ to $|0\rangle$.

The **H gate**, or Hadamard gate, creates superposition. It can turn a definite $|0\rangle$ state into an equal combination of $|0\rangle$ and $|1\rangle$.

The **Z gate** changes phase. It leaves $|0\rangle$ unchanged but adds a minus sign to $|1\rangle$, which becomes crucial when we later discuss interference.

Together, these gates show how quantum computers manipulate information: not by simply switching bits on and off, but by rotating, combining, and phase-shifting quantum states.

The Pauli-X gate — the quantum NOT

The **X gate** is the quantum version of the classical **NOT gate**.

In classical computing, a NOT gate flips a bit:

$$0 \to 1 \text{ and } 1 \to 0$$

The X gate does the same thing to the two basis states of a qubit.

It transforms:

$$|0\rangle \to |1\rangle$$

and

$$|1\rangle \to |0\rangle$$

So if a qubit starts in the state $|0\rangle$, applying the X gate turns it into $|1\rangle$. If it starts in $|1\rangle$, the X gate turns it into $|0\rangle$.

That is why the X gate is often called the **quantum NOT gate**.

But quantum gates become more interesting when the qubit is in superposition.

Suppose the qubit is in the state:

$$\alpha|0\rangle + \beta|1\rangle$$

Here, α |alpha α is the amplitude attached to $|0\rangle$, and β is the amplitude attached to $|1\rangle$.

When the X gate is applied, it swaps the amplitudes:

$$\alpha|0\rangle + \beta|1\rangle \to \beta|0\rangle + \alpha|1\rangle$$

So whatever weight the qubit previously had on $|0\rangle$ moves to $|1\rangle$, and whatever weight it had on $|1\rangle$ moves to $|0\rangle$.

On the Bloch sphere, this operation appears as a **180° rotation around the x-axis**.

That geometric picture is useful: the X gate flips the qubit to the opposite side of the sphere along the x-axis. The north pole $|0\rangle$ becomes the south pole $|1\rangle$, and the south pole becomes the north pole.

In simple terms:

The X gate flips the computational basis states and swaps the amplitudes of a superposition.

The Hadamard gate — creator of superposition

The **Hadamard gate**, usually written as **H**, is one of the most important gates in quantum computing.

Unlike the X gate, which behaves like a quantum version of the classical NOT gate, the Hadamard gate has no true classical counterpart. Its special role is that it can take a definite qubit state and turn it into a balanced superposition.

If the qubit starts in state $|0\rangle$, the Hadamard gate produces:

$$H|0\rangle = (|0\rangle + |1\rangle) / \sqrt{2} = |+\rangle$$

This means the qubit now has:

- 50% probability of measuring 0
- 50% probability of measuring 1

If the qubit starts in state $|1\rangle$, the Hadamard gate produces:

$$H|1\rangle = (|0\rangle - |1\rangle) / \sqrt{2} = |-\rangle$$

This is also a 50/50 superposition, but with a crucial difference: the $|1\rangle$ component carries a minus sign. That minus sign represents **phase**, which becomes essential for quantum interference.

The Hadamard gate is remarkable because applying it twice brings you back to where you started.

For example:

$$H(H|0\rangle)=|0\rangle$$

and

$$H(H|1\rangle)=|1\rangle$$

This means the Hadamard gate is its own inverse. It creates superposition, but it can also undo the superposition it created.

This property is central to quantum algorithms. A typical quantum algorithm often begins by applying Hadamard gates to many qubits at once. If you apply H to n qubits initially set to $|0\rangle$, the system becomes a uniform superposition over all 2^n basis states.

For example:

- 1 qubit → 2 states
- 2 qubits → 4 states
- 3 qubits → 8 states
- nn qubits → 2^n states

This is how quantum computers open a large computational space at the beginning of many algorithms. The rest of the algorithm then uses phase, interference, and entanglement to shape that superposition so that useful answers become more likely when measured.

The Pauli-Z gate — silent but useful

The **Z gate** is one of the simplest quantum gates to write down, but one of the most important for understanding interference.

It acts like this:

$$Z|0\rangle=|0\rangle$$

$$Z|1\rangle=-|1\rangle$$

So the Z gate leaves $|0\rangle$ unchanged, but flips the sign of $|1\rangle$.

This is called a **phase flip**.

At first, this can seem strange. If the only thing that changes is a minus sign, does anything physically meaningful actually happen?

The answer is yes — but not always immediately.

Suppose the qubit is in the state:

$$\alpha|0\rangle+\beta|1\rangle$$

After applying the Z gate, the state becomes:

$\alpha|0\rangle-\beta|1\rangle$

The probability of measuring 0 is still:

$$|\alpha|^2$$

and the probability of measuring 1 is still:

$$|\beta|^2$$

So, if you measure immediately after applying Z, the measurement probabilities are unchanged.

That is the subtlety.

The Z gate does not change *how much* probability sits on $|0\rangle$ or $|1\rangle$. It changes the **phase relationship** between them.

And phase is what allows quantum states to interfere.

When the Z gate is combined with other gates — especially the Hadamard gate — that hidden sign change can become visible as a different measurement outcome.

This is why Z is so important in quantum algorithms.

In algorithms like **Grover's search**, phase flips are used to mark the correct answer. The algorithm then uses interference to amplify that marked answer and suppress the wrong ones.

So, the Z gate may look quiet when viewed alone.

But inside a full quantum circuit, it becomes one of the essential tools for controlling interference.

In simple terms:

The X gate flips values.
The H gate creates superposition.
The Z gate flips phase.

And phase is where much of quantum computing's power lives.

The CNOT gate — the entangler

So far, every gate we have discussed acts on a **single qubit**.

The X gate flips a qubit.

The H gate creates superposition.

The Z gate changes phase.

But single-qubit gates alone cannot create entanglement.

To entangle qubits, we need an operation that acts on **two qubits at once**.

The most important two-qubit gate is the **CNOT gate**, short for **Controlled-NOT**.

Its rule is simple:

If the control qubit is $|1\rangle$, flip the target qubit.

If the control qubit is $|0\rangle$, do nothing.

So the CNOT gate has two roles:

- the first qubit is the **control**
- the second qubit is the **target**

If the control is 0, the target remains unchanged.

If the control is 1, the target is flipped:

$$|0\rangle \to |1\rangle$$
$$|1\rangle \to |0\rangle$$

For ordinary basis states, CNOT behaves predictably:

$$|00\rangle \to |00\rangle$$
$$|01\rangle \to |01\rangle$$
$$|10\rangle \to |11\rangle$$
$$|11\rangle \to |10\rangle$$

The first qubit controls whether the second qubit flips.

But the real power appears when the control qubit is in superposition.

Suppose the first qubit is in a balanced superposition and the second qubit starts as $|0\rangle|0\rangle$ rangle|0⟩:

$$(|0\rangle + |1\rangle) / \sqrt{2} \otimes |0\rangle$$

This can be written as:

$$(|00\rangle + |11\rangle) / \sqrt{2}$$

Now apply CNOT.

The $|00\rangle$ part remains unchanged because the control qubit is 0.

The $|10\rangle$ part becomes $|11\rangle$ because the control qubit is 1, so the target flips.

The result is:

$$(|00\rangle + |11\rangle) / \sqrt{2}$$

This is an entangled state.

The two qubits are no longer independent. If you measure the first qubit and get 0, the second will also be 0. If you measure the first and get 1, the second will also be 1.

This is why the CNOT gate is so important.

It turns superposition into entanglement.

In many quantum circuits, the basic recipe is:

1. Use Hadamard to create superposition
2. Use CNOT to spread that superposition across another qubit
3. The result is entanglement

That simple pattern is one of the most important building blocks in all of quantum computing.

Putting it together — making a Bell state

Here is the simplest non-trivial quantum circuit. Start with two qubits, both in state |0⟩. Apply Hadamard to the first qubit. Then apply CNOT with the first qubit as control and the second as target. Done. Two gates, two qubits, and you have created an entangled pair — a Bell state.



Figure 9.1 — A two-gate circuit that creates an entangled Bell state.

Let us trace through the maths. The starting state is |00⟩ — both qubits 0. After Hadamard on qubit 0: the combined state is (|00⟩ + |10⟩)/√2. After CNOT: |00⟩ stays as |00⟩, but |10⟩ becomes |11⟩. The combined state is now (|00⟩ + |11⟩)/√2 — the Bell state.

In Qiskit code

```
from qiskit import QuantumCircuit

qc = QuantumCircuit(2)
qc.h(0)          # Hadamard on qubit 0
qc.cx(0, 1)      # CNOT, control=0, target=1
qc.measure_all()
```

Figure 9.2 — The Bell state circuit in Qiskit (Python). Anyone with a free IBM Quantum account can run this on real hardware today.

When this Bell-state circuit runs ideally, it prepares the state:

$$|\psi\rangle = |00\rangle + |11\rangle \frac{1}{\sqrt{2}}$$

This means the amplitudes are:

$$\alpha_{00} = \frac{1}{\sqrt{2}}$$
$$\alpha_{11} = \frac{1}{\sqrt{2}}$$
$$\alpha_{01} = 0$$
$$\alpha_{10} = 0$$

Using the Born rule:

$$P(outcome) = |amplitude|^2$$

we get:

$$P(00)=|\frac{1}{\sqrt{2}}|^2=\frac{1}{2}=50\%$$
$$P(11)=|\frac{1}{\sqrt{2}}|^2=\frac{1}{2}=50\%$$
$$P(01)=|0|^2=0$$
$$P(10)=|0|^2=0$$

So, the ideal result is:

$$P(00)=50\%, P(11)=50\%, P(01)=0\%, P(10)=0\%$$

This is the mathematical signature of the Bell state:

$$|\psi\rangle=|00\rangle+|11\rangle\frac{1}{\sqrt{2}}$$

The two qubits are perfectly correlated. They always agree.

On a real noisy quantum computer, the measured distribution may look more like:

$P(00)\approx 47\%$

$$P(11)\approx 47\%$$
$$P(01)\approx 3\%$$
$$P(10)\approx 3\%$$

So instead of the ideal distribution:

$$(50\%, 0\%, 0\%, 50\%)$$

for:

$$(|00\rangle, |01\rangle, |10\rangle, |11\rangle)$$

we might observe:

$$(47\%, 3\%, 3\%, 47\%)$$

The error probability is therefore approximately:

$$P(error)=P(01)+P(10)$$
$$P(error)=3\%+3\%=6\%$$

The correct correlated outcomes are:

$$P(correct)=P(00)+P(11)$$
$$P(correct)=47\%+47\%=94\%$$

So the real device still mostly produces the Bell-state behaviour, but with a small error rate:

$$|\psi_{ideal}\rangle=|00\rangle+|11\rangle\frac{1}{\sqrt{2}}$$

while the measured hardware output looks approximately like:

$$P_{real}=\{P(00)\approx 0.47\ P(01)\approx 0.03 P(10)\approx 0.03 P(11)\approx 0.47$$

The gap between:

$$P_{ideal}(01)=P_{ideal}(10)=0$$

and:

$$Preal(01) \approx P_{real}(10) \approx 0.03$$

is caused by hardware noise, imperfect gates, readout errors, and decoherence.

■ YOU HAVE REACHED THE THRESHOLD OF QUANTUM PROGRAMMING

If you understand this circuit, you have crossed a real line. Most quantum algorithms are built on the same principles — Hadamards to create superposition, controlled gates to entangle, more single-qubit gates to manipulate amplitudes through interference, and finally measurement to read out the result. Shor's algorithm, Grover's search, and the variational quantum algorithms used today are all elaborations of this basic structure.

Module 4 will take you into those algorithms in detail.

CHAPTER 10

Why This Matters

The foundation of everything that comes next — and what it means for business and society.

We have now spent nine chapters building around three core ideas: **superposition, measurement, and entanglement**.

In one sense, they are simple.

Superposition allows a qubit to exist in multiple possible states before measurement. Measurement forces that quantum state into one definite classical outcome. Entanglement links multiple qubits so deeply that their shared state cannot be understood by looking at each qubit alone.

Three ideas.

Elegant mathematics.

But in another sense, these ideas are revolutionary.

They break the assumptions that classical computing has relied on for more than half a century. A classical computer processes definite bits. A quantum computer manipulates amplitudes, phases, correlations, and probabilities before producing a final measurable answer.

That shift changes what computation can be.

Every major promise of quantum computing — faster search, new cryptographic threats, molecular simulation, optimisation, quantum machine learning, and future quantum networks — depends on these three principles working together.

Superposition creates the space of possibilities. Entanglement links those possibilities across many qubits. Measurement extracts one final answer.

And interference, which we will continue building toward, is the mechanism that makes useful answers more likely than useless ones.

If you understand these foundations, quantum computing stops sounding like magic. It becomes a new model of information processing — strange, powerful, limited, and deeply real.

What we now have the language to discuss

Two months ago, the word **"qubit"** may have sounded like an empty buzzword — impressive, technical, and vague. Now it has meaning.

You know that a qubit is not just an abstract symbol, but a real physical object: a superconducting circuit, an ion, an atom, or a photon engineered to behave quantum mechanically. You know that its state can be represented as a point on the Bloch sphere. You know that superposition means a qubit can exist in a genuine combination of $|0\rangle$ and $|1\rangle$, not because we are ignorant of its value, but because the state itself contains both possibilities.

You also know that measurement changes everything. It collapses the superposition into one definite classical result. And you know that entanglement links multiple qubits in a way classical physics cannot reproduce — correlations so deep that their reality was recognised by the 2022 Nobel Prize in Physics.

That is genuine quantum literacy.

It is more than knowing vocabulary. It is understanding the conceptual machinery underneath the vocabulary.

And it is more than many managers, executives, investors, policy writers, and even many technology journalists ever develop when discussing quantum computing.

This foundation matters because every later topic depends on it:

- quantum hardware
- quantum algorithms
- quantum-AI integration
- post-quantum cryptography
- quantum strategy

Without this foundation, those topics sound like hype.

With it, they become intelligible.

This is the point of the module: not to turn you into a physicist, but to give you enough real understanding to think clearly about one of the most important technologies of the coming decades.

What quantum computers can do — realistically

Quantum computers will not make your laptop faster. They will not replace classical computers for the vast majority of tasks. What they will do falls into a small number of well-defined categories:

Optimisation	Simulation	Cryptography
Logistics, finance, resource allocation	Chemistry, materials, drug discovery	Breaking RSA; quantum-safe security

- **Optimisation** is one major opportunity. Problems like logistics routing, portfolio optimisation, supply-chain planning, grid balancing, and resource allocation can involve massive solution spaces. Quantum algorithms may help by using interference to amplify better answers and suppress weaker ones. McKinsey's 2025 Quantum Technology Monitor estimates quantum computing could reach **$28B–$72B in market size by 2035**.
- **Quantum simulation** may be the most natural advantage. Chemistry, materials science, drug discovery, batteries, catalysts, and molecular modelling are quantum systems by nature. Classical computers struggle to simulate them exactly at scale, while quantum computers may eventually model them more efficiently.
- **Cryptography** is where the disruption is more urgent. Shor's algorithm could break RSA and other widely used public-key encryption once fault-tolerant quantum computers exist. That is why NIST published its first post-quantum cryptography standards in **August 2024: FIPS 203, FIPS 204, and FIPS 205**.

For Diarka Quantum, this makes **quantum-safe security advisory** a key service line.

The message for clients is clear: quantum advantage will not arrive everywhere at once, but in optimisation, simulation, and cryptography, the strategic signals are already strong enough to prepare now.

Why this matters for Diarka Quantum's mission

Diarka Quantum exists to be the bridge between quantum technology and business decision makers.

But that bridge only has credibility if it is built on genuine understanding — not recycled buzzwords, vague hype, or surface-level explanations.

That is why this module matters.

Before advising organisations on quantum readiness, post-quantum security, AI-quantum integration, or long-term technology strategy, we first need a serious foundation in what quantum computing actually is. Not enough to become theoretical physicists, but enough to think clearly, ask better questions, and separate real capability from exaggerated claims.

This module provides that foundation.

The technology itself will continue to evolve. Hardware will become more stable. Error rates will improve. Algorithms will mature. New platforms will emerge. Commercial use cases will become clearer over time.

But the foundational physics will not change.

Superposition, measurement, and entanglement are not speculative ideas. They are settled scientific principles, validated through decades of experiment and recognised at the highest levels of physics, including Nobel Prize-winning work.

They will remain the foundation of quantum computing in 2030, 2040, and 2050.

For Diarka Quantum, understanding these principles is not academic decoration.

It is the technical ground beneath the advisory work.

■ THE FIVE-MINUTE TEST

If you can explain to a curious non-technical colleague — in five minutes, using your own words — what a qubit is, what superposition means, why measurement matters, and why entanglement was so controversial that it took the 2022 Nobel Prize to settle the debate, you have achieved working quantum literacy. That is more than 95% of business leaders and IT executives have today. It will be one of your most valuable professional assets over the coming decade.

What is next

Module 3 takes us into the physical world: The Quantum Hardware Landscape Today. We will see — in detail — the four major quantum hardware platforms (superconducting, trapped ion, neutral atom, photonic), how each works, what each is best at, who builds them, and how a business leader chooses between them.

Module 4 then shifts to Quantum Algorithms — Where Advantage Is Real. Modules 5, 6, and 7 close the course on the highest-leverage frontier topics: AI-Quantum Convergence, Post-Quantum Cryptography & NIST Standards, and Quantum Strategy for Organisations.

We are at the very beginning. Everything that comes next — the hardware, the algorithms, the applications, the strategy — sits on the three pillars you have just learned. Master them, and the rest will follow.

End of Module 02.

CONTINUE TO MODULE 03 — THE QUANTUM HARDWARE LANDSCAPE

ABOUT THIS COURSE

Quantum Computing for Ambitious Professionals is a 7-module course taking anyone from zero quantum knowledge to genuine, practical understanding of the technology reshaping computing, AI, and cryptography. No physics degree required.

Module	Title	Access
01	Why Classical Computers Hit a Fundamental Wall	FREE PREVIEW
02	Qubits, Superposition & Entanglement Explained	£19
03	Quantum Hardware Landscape Today	£19
04	Quantum Algorithms & Where Advantage Is Real	£19
05	AI-Quantum Convergence & Quantum Machine Learning	£19
06	Post-Quantum Cryptography & NIST Standards	£19
07	Quantum Strategy for Organisations	£19

Access Modules 2-7 at: diarkaquantum.co.uk/education

nageshj@diarkaquantum.co.uk