

CS 334 Fall 2020: Problem Set 2.

Problem 1. (15 points)

- Construct an FSA with 6 states to recognize $L_4 = \{1111\}$. Can you reduce the number of states below 6? (Hint: recall a basic property of directed graphs from CS 135!)
- Use your argument to prove that, for all $k \geq 3$ there is a language that can be accepted by a k -state FSA that cannot be recognized by any FSA with fewer states.

Problem 2. (15 points) For any string $w = w_1w_2 \cdots w_n$, the *reverse* of w , written w^R , is the string w in reverse order, $w_n \cdots w_2w_1$. For any language A , let $A^R = \{w^R | w \in A\}$. Show that if A is regular, so is A^R .

Problem 3. (20 points) In this problem you will design an FSA that checks if the sum of two numbers equals a third number. Each number is an arbitrarily long string of bits. At each step, the input to the FSA is a symbol that encodes 3 bits, one from each number. In other words, the alphabet of the FSA is:

$$\Sigma = \left\{ \begin{bmatrix} 0 \\ 0 \\ 0 \end{bmatrix}, \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix}, \begin{bmatrix} 0 \\ 1 \\ 0 \end{bmatrix}, \begin{bmatrix} 0 \\ 1 \\ 1 \end{bmatrix}, \begin{bmatrix} 1 \\ 0 \\ 0 \end{bmatrix}, \begin{bmatrix} 1 \\ 0 \\ 1 \end{bmatrix}, \begin{bmatrix} 1 \\ 1 \\ 0 \end{bmatrix}, \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix} \right\}$$

In the input string $\begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \\ 1 \end{bmatrix}$ the bits in the top row represent the number 01, the bits in the middle row represent 00 and the third row represents 11. In this case, since $01+00 \neq 11$, the FSA must reject the input. On the other hand, the input string $\begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix} \begin{bmatrix} 0 \\ 1 \\ 0 \end{bmatrix} \begin{bmatrix} 1 \\ 1 \\ 0 \end{bmatrix}$ will be accepted by the FSA since $001 + 011 = 100$.

Formally, let $B = \{w \in \Sigma^* : \text{the bottom row of } w \text{ equals the sum of the top two rows}\}$, where Σ^* represents all finite strings over the alphabet Σ . Your goal is to design an FSA for the language B .

To get started, first design a 2-state FSA that recognizes B^R – this should be straightforward because the input arrives least significant bits first and most significant bits at the end. Next, use the technique of Problem 2 to design the final FSA for B .

Optional Problem. (20 points) For any string σ , over alphabet Σ , we define the string $SHIFT(\sigma)$ as follows: if $\sigma = a w, a \in \Sigma, w \in \Sigma^*$ then $SHIFT(\sigma) = w a$. For example, $SHIFT(0111) = 1110$, and $SHIFT(10110) = 01101$. Prove that if L is regular, then so is $SHIFT(L) = \{SHIFT(\sigma) : \sigma \in L\}$.