

Hayakawa Electronics (Phils.) Corp.

CEZ Drive, Cavite Economic Zone Rosario, Cavite, Philippines 4106 Tel (046)437-1401 - Fax (046) 437-1413

PRODUCT APPROVAL WORKSHEET

CUSTOMER	: FUJITSU DIE TECH
PART NAME	: CABLE PURCHASE SPECIFICATION
PART NUMBER	: L0KD04467-D970 (REV.05)
HEPC SPECIFICATION NUMBER	: F-FDPH-0451-2
CUSTOMER'S JUDGMENT:	
FULL APPROVAL	
CONDITIONALLY APPROVED REJECTED	
-	ì
Telliaks.	
į —	
QVITTO)	ATTING STOLLTENED
CUSTON	MER'S SIGNATURE: Signature Over Printed Name
ATTACHMENT/S UPON SUBMISSION:	
Design Change Request (DCR- Product Specification	Harness Sample/s (pc./s) Others (pls specify:)
Signature: MR. M	MANUEL GARCIA ACTORY MANAGER
FOR DESIGN INTERNAL USE ONLY:	Rev. No02
ATTACHMENTS: Material Details Form Product S	SPECIAL INSTRUCTIONS: Specification
☐ Sub-Assembly Sheet ☐ Revision I	History Record
	ing Change Notice
☐ Job Order for Moulding Sheet ☐ Customer	r Sample 22-Ja
☐ Job Order for Shielded Wire Sheet ☐ Approved☐ Shipping Inspection Report ☐ Oth	A Sample Rosafte Adrias thers (pls specify) Signature Over Printed Name
Shipping inspection kepon Unit	iers (pis specify) Signature Over Printed Name


Q10FC-0057 DOC.: 07 SEPT. '15

PRODUCT SPECIFICATION

RoHS/ELV COMPLIANT

Page No.: 4 / 5

Rev. No. : 01



P10FC-0003



PRODUCT SPECIFICATION

RoHS/ELV COMPLIANT

Rev. No.: 01

Date: Approved by PROVING Issued by 1.22.19 ISSUANCE ARIES SPECS NUMBER: PART NUMBER: CUSTOMER: LOKD04467-D970 (REV.05) F-FDPH-0451-2 FUJITSU DIE TECH ₽ No. $\triangleright \triangleright$ Date 01.10.19 01.16.18 ABAP1801000013 CHANGED PN/IK/ADD MATERIAL ABAP1812000006 CHANGED PN/IK/QTY. REVISION SOURO Prepared SORRO Checked Approved Prepared **JASON** JASON 07.19.17 SORRO Page No. : 5 JASON 07.19.17 Checked ARIES 07.19.17 Approved

1. THE SPECIFICATION OF THE WIRE MUST CONFORM WITH THE UL/ R/C(AVV2)/ CS4 STANDARDS.

2. PUT STICKER LABEL ON PIN NO. 1 OF ALL HOUSING.

3. SOLDERING AND SHRINK TUBE DETAIL:

ਨ ਜ

HOUSING	LABEL	<u>9~15</u>	STICKER LABEL DETAIL:	(Q) (P) (P)	S CN1	\ \ \
L	_					

5. WITHSTAND VOLTAGE: IT SHOULD NOT BE DAMAGED BETWEEN SIGNALS/SIGNALS AND GROUND WHILE AC 350V VOLTAGE IS APPLIED ON FOR 0.5 SEC.

4.2~6.3

6. INSULATION RESISTANCE: KEEP 50MQ OR MORE AFTER DC500V IS APPLIED BETWEEN SIGNALS/SIGNALS GROUND.
7. FOR TAPING PROCESS, DIVIDE IT BY EIGHT WIRES.

Z	~	×	₹	<	c	-	S	æ	۵	v	0	z	Z	_	~	ے	-	Ξ	ဝ	Ŧ	m	ō	ဂ	В	>	Ņ.	
STICKER LABEL	STICKER LABEL	STICKER LABEL	STICKER LABEL	STICKER LABEL	STICKER LABEL	STICKER LABEL	STICKER LABEL	FLUX	SOLDER BAR	SHRINK TUBE	ACETATE CLOTH TAPE	SPIRAL TUBE	SPIRAL TUBE	BINDER	HOUSING	HOUSING	HOUSING	HOUSING	HOUSING	TERMINAL	TERMINAL	TERMINAL	TERMINAL	TERMINAL	WIRE	ITEM	
"HFCN" (HTLW25) WHITE	"SMS-R" (HTLW25) WHITE	"MLS" (HTLW25) WHITE	"TBS" (HTLW25) WHITE	"MRS1" (HTLW25) WHITE	"IOS-F" (HTLW25) WHITE	"PSES" (HTLW25) WHITE	"THSN2" (HTLW25) WHITE	T-1	ECO M705	GSHS-1625G ID2.5 BLACK	No.5 W10mm BLACK	TS-4A NATURAL	TS-6A NATURAL	T18R CLEAR	DF11-26DEP-2C BLACK	SMR-03V-B BLACK	ZHR-3 WHITE	DF3-3S-2C BLACK	SHDR-40V-S-B WHITE	DF11-EP2428PCF	SYM-001GW-0.6A	SZH-002T-P0.5	DF3-2428SCF	SSH-003GA-P0.2	UL 1061 awg28 (7/0.127) LF	PART NUMBER	MATERIALS
_	1	_	_	1	_	_	1	~	ı	6	∆6	1	_	<u></u> ≱7	1	1	4	2	1	20	3	12	6	32	47	QTY.	
TSUCHIYA	TSUCHIYA	TSUCHIYA	TSUCHIYA	TSUCHIYA	TSUCHIYA	TSUCHIYA	TSUCHIYA	SENJU	SENJU	LS	NITTO	TYTON	NOTYT	TYTON	HIROSE	JST	JST	HIROSE	JST	HIROSE	JST	JST	HIROSE	JST	HCV	MAKER	
<	<	<	<	<	<	<	<	<	<	<u> </u>	<	<	<	<	~	<u> </u>	<	<	~	<u> </u>	<	<	<	~	<	Checked Checker	
<	<	<	<	<	<	<	<	<	<	<	<	<	<	<	<	<	<u> </u>	<	<	<	<	<	<	<	<	Checked	

DCR No.: EDCR-17-0471 APPROVED

COLOR CODES: BK - BLACK; R - RED; O - ORANGE; BL - BLUE; V - VIOLET; SB - SKYBLUE; Y - YELLOW; G - GREEN; GY - GRAY; W - WHITE; P - PINK; LG - LIGHT GREEN; BK/BL - BASE/STRIPE; BK-BL - FLATWIRE