Assignment #4: T-primes + 贪心

Updated 0337 GMT+8 Oct 15, 2024

2024 fall, Complied by 金俊毅 物理学院

1. 题目

34B. Sale

greedy, sorting, 900, https://codeforces.com/problemset/problem/34/B

代码

```
m,n=map(int,input().split())
value=list(map(int,input().split()))
value.sort()
earn=0
for i in range(n):
    if value[i] <=0:
        earn+=value[i]
print(-earn)</pre>
```

代码运行截图 (至少包含有"Accepted")



160A. Twins

greedy, sortings, 900, https://codeforces.com/problemset/problem/160/A

```
n=int(input())
money=list(map(int,input().split()))
money.sort(reverse=True)
sum=0
self=0
number=0
for i in money:
    sum+=i
for i in money:
    self+=i
    number+=1
```

```
if self*2>sum:
    break
print(number)
```


代码运行截图 == (至少包含有"Accepted") ==



1879B. Chips on the Board

constructive algorithms, greedy, 900, https://codeforces.com/problemset/problem/1879/B


```
N=int(input())
ans=[]
for i in range(N):
    answer1=0
    answer2=0
    n=int(input())
    a=list(map(int,input().split()))
    b=list(map(int,input().split()))
    a.sort()
    b.sort()
    for j in range(n):
        answer1+=a[0]+b[j]
        answer2+=b[0]+a[j]
    answer=min(answer1,answer2)
    ans.append(answer)
for i in range(N):
    print(ans[i])
```



158B. Taxi

*special problem, greedy, implementation, 1100, https://codeforces.com/problemset/problem/15 8/B

```
n = int(input())
a = 0
b = 0
c = 0
d = 0
childs = input().split()
for s in childs:
    if s == "1":
        a += 1
    elif s == "2":
        b += 1
    elif s == "3":
        c += 1
    else:
        d += 1
ans = d + c + b // 2
a -= c
if b % 2 != 0:
    ans += 1
    a = 2
if a > 0:
    ans += a // 4
    if a % 4 != 0:
        ans += 1
print(ans)
```



*230B. T-primes (选做)

binary search, implementation, math, number theory, 1300, http://codeforces.com/problemset/problemset/problem/230/B

```
arbit = [False,True,True] + [False,True]*500000
i = 3
while i**2 <= 1000000:
    if arbit[i-1] == True:
        for j in range(i*2, 1000001, i):
            arbit[j-1] = False
    i += 1
import math
n = int(input())
number = list(map(int, input().split()))
for i in number:
    p = int(math.sqrt(i)) - 1
   while p**2 <= i:
    if (p-1)**2 == i and i != 1 and arbit[p-2]:
        print("YES")
    else:
        print("NO")
```

By jnullm, contest: Codeforces Round 142 (Div. 2), problem: (B) T-primes, Accepted, #, Copy

```
arbit = [False, True, True] + [False, True]*500000
i = 3
while i**2 <= 1000000:
    if arbit[i-1] == True:
        for j in range(i*2, 1000001, i):
            arbit[j-1] = False
    i += 1

import math
n = int(input())
number = list(map(int, input().split()))
for i in number:
    p = int(math.sqrt(i)) - 1
    while p**2 <= i:
        p += 1
    if (p-1)**2 == i and i != 1 and arbit[p-2]:
        print("YES")
    else:
        print("NO")</pre>
```

→Judgement Protocol

```
Test: #1, time: 530 ms., memory: 14764 KB, exit code: 0, checker exit code: 0, verdict: OK
Input

3
4 5 6
Output

YES
NO
NO
Answer

YES
NO
OLO
Checker Log

Checker Log
```

*12559: 最大最小整数 (选做)

greedy, strings, sortings, http://cs101.openjudge.cn/practice/12559

代码

ok 3 lines

```
n = int(input())
num = sorted(input().split(), reverse=True)
for i in range(1, n):
    j = i
    while num[j] == num[j-1][:len(num[j])]:
        if num[j] + num[j-1] > num[j-1] + num[j]:
            num[j-1], num[j] = num[j], num[j-1]
            j -= 1
    else:
        break
    if j == 0:
        break
print("".join(num) + " " + "".join(num[::-1]))
```

代码运行截图 (至少包含有"Accepted")

状态: Accepted

```
基本信息
源代码
                                                                                                #: 46614601
                                                                                              题目: 12559
 n = int(input())
                                                                                            提交人: 24n2400011454
 num = sorted(input().split(), reverse=True)
                                                                                              内存: 3644kB
 for i in range(1, n):
                                                                                              时间: 23ms
     j = i
      \label{eq:while} \textbf{while} \ \texttt{num[j]} \ == \ \texttt{num[j-1][:len(num[j])]:}
                                                                                              语言: Python3
          if num[j] + num[j-1] > num[j-1] + num[j]:
    num[j-1], num[j] = num[j], num[j-1]
                                                                                          提交时间: 2024-10-20 15:11:17
               j -= 1
           else:
              break
           if j == 0:
 print("".join(num) + " " + "".join(num[::-1]))
©2002-2022 POJ 京ICP备20010980号-1
                                                                                                                 English 帮助 关于
```

2. 学习总结和收获

本周是继续看《算法基础与在线实践》,把上面每一章都看了一遍,各个章节都做了一些题目,于是就回来从之前因为看书断开的进度,开始回头赶每日选做了。看算法书前觉得很难的题目,现在会比较容易地想到思路,仍然是有进步的。

这周学的时间比较诡异,周一到周四课余时间一直在写其他课程的论文,从周五下午开始才开始写计概作业。因为前几天都没写,于是周五晚上和周六日整天都在学,合计也应该有20小时。