

Below are the algorithms that make up the AI for our agent. We chose to use a model-based agent, as a purely reflex based agent would not take advantage of the possibilities of logical inference in the world, and the lack of information about the proximity of the gold would have made a goal-based agent useless.

The agent only moves to tiles that it knows are safe, and that it has not visited previously. If the agent ever finds itself in a position in which it cannot move to a safe, unexplored tile, it will return to the origin and start over. This eliminates the risk of our agent trapping itself in a region of the map and exiting prematurely. However, this also means that our agent refuses to accept the possibility that there is no way of reaching the gold (if any exists). In other words, our AI will *never give up*.

We ensure that we only move to tiles we have some knowledge about by making cross-moves before diagonal ones. As we also shuffle the order in which we do diagonal moves, our choice of the next base (which is the tile reached via the last executed safe move) has a degree of randomness. This should reduce the risk of our agent boxing itself into a region (and even if it does, as explained above, we will still start over).

## List of Algorithms

1	Search Function - <b>explore()</b> . . . . .	2
2	Inference Function - <b>infer()</b> . . . . .	3
3	Safety Evaluation Function - <b>isSafe()</b> . . . . .	4
4	Escaping Function - <b>escape()</b> . . . . .	4

---

**Algorithm 1** Search Function - **explore()**

---

**Require:** CROSS MOVES  $\leftarrow [(1,0),(-1,0),(0,1),(0,-1)]$ **Require:** DIAGONAL MOVES  $\leftarrow [(1,1),(-1,-1),(1,-1),(-1,1)]$ 

```
1: KnowledgeBase  $\leftarrow \emptyset$ 
2: explored  $\leftarrow \emptyset$ 
3:
4: origin  $\leftarrow (0,0)$ 
5: origin state  $\leftarrow$  perceive
6: KnowledgeBase.put(origin state)
7: infer(origin)
8: explored(origin.X,origin.Y)  $\leftarrow true$ 
9: base  $\leftarrow$  origin
10:
11: loop
12:   MOVES  $\leftarrow$  CROSS MOVES  $\cup$  shuffle(DIAGONAL MOVES)
13:   for all Move m in MOVES do
14:     newX  $\leftarrow$  base.x + m.x
15:     newY  $\leftarrow$  base.y + m.y
16:     movesMade  $\leftarrow$  0
17:     if isSafe(newX,newY)  $\wedge \neg$  explored(newX,newY) then
18:       moveTo(newX,newY)
19:       movesMade  $\leftarrow$  movesMade + 1
20:       state  $\leftarrow$  perceive
21:       KnowledgeBase.put(state)
22:       infer(state)
23:       explored(newX,newY)  $\leftarrow true$ 
24:       if isGlittery(state) then
25:         pickUpGold
26:         foundTheGold  $\leftarrow true$ 
27:         escape(newX,newY)
28:       end if
29:       if  $\neg$ isBlack(state) then
30:         nextBase  $\leftarrow$  (newX,newY)
31:       end if
32:       moveTo(base.x,base.y)
33:     end if
34:   end for
35:   if movesMade = 0 then
36:     escape(base.x,base.y)
37:   end if
38:   base  $\leftarrow$  nextBase
39:   moveTo(base.x,base.y)
40: end loop
```

---

---

**Algorithm 2** Inference Function - **infer()**

---

**Require:** a state to infer knowledge about

**Require:** CROSS MOVES  $\leftarrow [(1,0),(-1,0),(0,1),(0,-1)]$

**Require:** a KnowledgeBase to update

```
1: for all Move m in CROSS MOVES do
2:   adjacentX  $\leftarrow$  state.x + m.x
3:   adjacentY  $\leftarrow$  state.y + m.y
4:   if KnowledgeBase.contains(adjacentX,adjacentY) then
5:     adjState  $\leftarrow$  KnowledgeBase.get(adjacentX,adjacentY)
6:   else
7:     adjState  $\leftarrow$  new State
8:   end if
9:
10:  if isEmpty(state) then
11:    adjState.isEmpty  $\leftarrow$  true
12:  else
13:    if isBreezy(state) then
14:      adjState.pitPossibility  $\leftarrow$  adjState.pitPossibility + 1
15:    end if
16:    if isSmelly(state) then
17:      adjState.wumpusPossibility  $\leftarrow$  adjState.wumpusPossibility + 1
18:    end if
19:  end if
20:  KnowledgeBase.update(adjState)
21: end for
```

---

---

**Algorithm 3** Safety Evaluation Function - **isSafe()**

---

**Require:** a position (x,y) to evaluate

**Require:** a KnowledgeBase

```
1: state  $\leftarrow$  KnowledgeBase.get(x,y)
2: if isBlack(state) then
3:   return false
4: end if
5: if isEmpty(state)  $\vee$  (state.pitPossibility = 0  $\wedge$  state.wumpusPossibility = 0) then
6:   return true
7: else
8:   return false
9: end if
```

---

---

**Algorithm 4** Escaping Function - **escape()**

---

**Require:** a KnowledgeBase

**Require:** a startingPosition

**Require:** whether we foundTheGold

```
1: currentPosition  $\leftarrow$  startingPosition
2: repeat
3:   nextPosition  $\leftarrow$  a safe neighbour of currentPosition that minimises
     the straight line distance to (0,0)
4:   moveTo(nextPosition)
5:   currentPosition  $\leftarrow$  nextPosition
6: until currentPosition = (0,0)
7: if  $\neg$ foundTheGold then
8:   explore
9: end if
```

---