Algorithm 1 Search Function

Require: CROSS MOVES ← [(1,0),(-1,0),(0,1),(0,-1)]
Require: DIAGONAL MOVES ← [(1,1),(-1,-1),(1,-1),(-1,1)]
Require: a KnowledgeBase

origin ← (0,0)
base ← origin
loop
  infer(base)
  MOVES ← CROSS MOVES ∪ **shuffle**(DIAGONAL MOVES)
  for all Move m in MOVES **do**
    newX ← base.x + m.x
    newY ← base.y + m.y
    if isSafe(newX,newY) ∧ ¬ **explored**(newX,newY) **then**
      moveTo(newX,newY)
      state ← **perceive**
      KnowledgeBase.**put**(state)
      infer(state)
      explored(newX,newY) ← *true*
      if isGlittery(state) **then**
        pickUpGold
        escape(newX,newY)
      end if
      if m is the last Move in MOVES ∧ ¬**isBlack**(state) **then**
        base ← (newX,newY)
      else
        moveTo(base.x,base.y)
      end if
    end if
  end for
end loop

Algorithm 2 Inference Function

Require: a state to infer knowledge about
Require: CROSS MOVES ← [(1,0),(-1,0),(0,1),(0,-1)]
Require: a KnowledgeBase to update

```
1:  for all Move m in CROSS MOVES do
2:      adjacentX ← state.x + m.x
3:      adjacentY ← state.y + m.y
4:      if KnowledgeBase.contains(adjacentX,adjacentY) then
5:          adjState ← KnowledgeBase.get(adjacentX,adjacentY)
6:      else
7:          adjState ← new State
8:      end if
9:
10:     if isEmpty(state) then
11:         adjState.isEmpty ← true
12:     else
13:         if isBreezy(state) then
14:             adjState.pitPossibility ← adjState.pitPossibility + 1
15:         end if
16:         if isSmelly(state) then
17:             adjState.wumpusPossibility ← adjState.wumpusPossibility + 1
18:         end if
19:     end if
20:     KnowledgeBase.update(adjState)
21: end for
```

Algorithm 3 Safety Evaluation Function

Require: a position (x,y) to evaluate
Require: a KnowledgeBase
1: state ← KnowledgeBase.**get**(x,y)
2: **if isEmpty**(state) ∨ (state.pitPossibility = 0 ∧ state.wumpusPossibility = 0) **then**
3: **return** *true*
4: **else**
5: **return** *false*
6: **end if**

Algorithm 4 Escaping Function

Require: a KnowledgeBase
Require: a startingPosition
1: currentPosition ← startingPosition
2: **repeat**
3: nextPosition ← a safe neighbour of currentPosition that minimises the straight line distance to (0,0)
4: **moveTo**(nextPosition)
5: currentPosition ← nextPosition
6: **until** currentPosition = (0,0)