```
Algorithm 1 Search Function
Require: CROSS MOVES \leftarrow [(1,0),(-1,0),(0,1),(0,-1)]
Require: DIAGONAL MOVES \leftarrow [(1,1),(-1,-1),(1,-1),(-1,1)]
Require: a KnowledgeBase
 1: origin \leftarrow (0,0)
 2: base \leftarrow origin
 3: loop
      base state \leftarrow perceive
 4:
 5:
      KnowledgeBase.put(base state)
 6:
      infer(base)
 7:
      explored(base.X,base.Y) \leftarrow true
 8:
      MOVES \leftarrow CROSS MOVES \cup shuffle(DIAGONAL MOVES)
 9:
      for all Move m in MOVES do
10:
        newX \leftarrow base.x + m.x
11:
12:
        newY \leftarrow base.y + m.y
13:
         if isSafe(newX,newY) \land \neg explored(newX,newY) then
           moveTo(newX, newY)
14:
           state \leftarrow perceive
15:
           KnowledgeBase.put(state)
16:
           infer(state)
17:
           explored(newX, newY) \leftarrow true
18:
           if isGlittery(state) then
19:
20:
             pickUpGold
21:
             escape(newX,newY)
           end if
22:
           if m is the last Move in MOVES \land \neg isBlack(state) then
23:
             base \leftarrow (newX, newY)
24:
25:
26:
             moveTo(base.x,base.y)
           end if
27:
         end if
28:
      end for
29:
30: end loop
```

## Algorithm 2 Inference Function

```
Require: a state to infer knowledge about
Require: CROSS MOVES \leftarrow [(1,0),(-1,0),(0,1),(0,-1)]
Require: a KnowledgeBase to update
 1: for all Move m in CROSS MOVES do
 2:
      adjacentX \leftarrow state.x + m.x
      adjacentY \leftarrow state.y + m.y
 3:
 4:
      if KnowledgeBase.contains(adjacentX,adjacentY) then
 5:
         adjState \leftarrow KnowledgeBase.get(adjacentX,adjacentY)
 6:
      else
 7:
         adjState \leftarrow new State
      end if
 8:
 9:
10:
      if isEmpty(state) then
         adjState.isEmpty \leftarrow true
11:
      else
12:
        if isBreezy(state) then
13:
           adjState.pitPossibility \leftarrow adjState.pitPossibility + 1
14:
         end if
15:
         if isSmelly(state) then
16:
           adjState.wumpusPossibility \leftarrow adjState.wumpusPossibility + 1
17:
18:
         end if
      end if
19:
      KnowledgeBase.update(adjState)
20:
21: end for
```

## Algorithm 3 Safety Evaluation Function

```
Require: a position (x,y) to evaluate

Require: a KnowledgeBase

1: state ← KnowledgeBase.get(x,y)

2: if isEmpty(state) ∨ (state.pitPossibility = 0 ∧ state.wumpusPossibility = 0) then

3: return true

4: else

5: return false

6: end if
```

## Algorithm 4 Escaping Function

Require: a KnowledgeBase Require: a startingPosition

- 1: currentPosition  $\leftarrow$  startingPosition
- 2: repeat
- 3: nextPosition  $\leftarrow$  a safe neighbour of currentPosition that minimises the straight line distance to (0,0)
- 4: **moveTo**(nextPosition)
- 5:  $currentPosition \leftarrow nextPosition$
- 6: **until** currentPosition = (0,0)