UNIVERSITY OF AARHUS

Faculty of Science

Department of Engineering

Indlejret Software Udvikling
Eksamens Dispositioner

Bjørn Nørgaard
IKT
201370248
bjornnorgaard@post.au.dk

Joachim Andersen
IKT
20137032
joachimdam@post.au.dk

Sidste ændring: December 14, 2015
LaTeX-koden kan findes her[1]

---

[1] https://github.com/BjornNorgaard/I3ISU/tree/master/Eksamen

Todo list

Indholdsfortegnelse

List of Figures

1 Programs in relation to the OS and the kernel

1.1 Sub topics

- Processes and threads.

- Threading model.

- Process anatomy.

- Virtual memory.

- Threads being executed on CPU, the associated scheduler and cache.

1.2 Curriculum

- Slides "Intro to OS's".

- Slides "Parallel programs, processes and threads".

- OLA: "Anatomy of a program in memory", Gustavo Duarte.

- OLA: "The free lunch is over".

- OLA: "Virtual memory", pages 131-141.

- OLA: " Introduction to operating systems".

- OLA: "Multithreading".

- Kerrisk: Ch. 3-3.4 - System programming concepts.

- Kerrisk: Ch. 29 - Threads: Introduction.

1.3 Exercises

- Posix Threads.

1.4   Processes and threads

- En **process** er en instans af et program, som eksekveres.

- En **thread** er en del af eksekveringen, alle processer har mindst én thread.

Processes

- Har hver sit memory space.

- Process A kan ikke skrive i Process B's hukommelse.

- Kan kun kommunikere gennem IPC[1]

- Kan skabe andre processer som kan eksekvere det samme eller andre programmer.

Threads

- Alle tråde i en process deler hukommelse på heap'en.

- Alle tråde har hver sin stack og program counter.

- Kan fucke med hinanden

  – Skal passe på at man ikke sletter de øvrige trådes data.

hvad vil program counter sige?

Tråde er forskellige fra processer selvom de deler flere egenskaber og kendetegn. En tråd eksekveres i en process

1.5   Threading model

Der findes tre forskellige modeller:

- User level threading.

- Kernel level threading.

- Hybrid level threading.

User level threading

- Simpel implementering, ingen kernel support for threads.

- Ekstremt hurtig thread kontekst skift (ikke brug for kernel handling).   woot?

- Ikke muligt at håndtere flere kerner.   hvorfor?

Kernel level threading

- Brug for thead bevisthed i kernel.

- Mapper direkte til threads som *scheduleren* kan kontrollere.

- Effektiv brug af flere kerner.

Hybrid level threading

- Komplex implementering. ⟶ `why?`

- Kræver god koordination mellem userspace og kernelspace scheduleren - ellers ikke optimal brug af resources.

1.6   Process anatomy

- Når et program startes, starter en ny process.

- En process kører i sin egen memory sandbox, som et *virtual address space* (4GB på 32-bit platform).

- Hver process har sin egen **pagetable/virtual address space**.

- Den virtuelle memory mapper til fysisk memory addresser vha. pagetables.

- Alle processer har **virtual address space**, hvor en del er bestemt til kernel space.

- Kernel space er ens for alle processor og mapper til samme fysiske hukommelse.

- Kernel space er flagged i pagetable med privileged code, så kun kernel space programmer kan ⟶ `uddybning` tilgå det memory. Page fault hvis user-space process forsøger at tilgå.

Alle processors mapning ad virtual space er den samme. Af sikkerhedshensyn er der indført random-størrelse offsets mellem de forskellige enheder (stack, heap, etc.). ⟶ `bedre forklaring`

Resten, udover kernel space processens egen.

Her findes: Stack, heap, memory mapping, BSS, data og text/code segment.
Alle processor har deres eget virtual address space, som bliver skiftet ved context switches, se figur **??**.

BSS   Indeholder **ikke** initialiserede statiske variabler. Dette område er anonymt. ⟶ `mere om dette?`

Data segment   Indeholder statisk initialiserede variabler, dette område er **ikke** anonymt, det er ⟶ `udbyd!` dog privat. Dette på kortlægger de initialiserede statiske værdier givet i source koden, fordi det er ⟶ `vil sige?` privat bliver ændringer ikke gemt i dette område.

For eksempel, indholdet af en pointer er i data segmentet men selve det den peger på ligger i ⟶ `igen, privat?` **text segmentet**, som er *read-only* og indeholder alt din kode . Text segmentet kortlægger ens ⟶ `data og text segment??` binære filer i hukommelsen.

1.7   Virtual memory

1.8   Threads being executed on CPU, associated scheduler and cache ⟶ `min hvordan`

---

[1]Inter-Process Communication, mekanismer kontrolleret af OS.

2 Synchronization and protection

2.1 Sub topics

- Data integrity - Concurrency challenge.

- Mutex and Semaphore.

- Mutex and Conditionals.

- Producer / Consumer problem.

- Dining philosophers.

- Dead locks.

2.2 Curriculum

- Slides: "Thread Synchronization I and II".

- Kerrisk: Chapter 30: Thread Synchronization.

- Kerrisk: Chapter 31: Thread Safety and Per-Thread Storage (Speed read)".

- Kerrisk: Chapter 32: Thread Safety and Per-Thread Storage (Speed read)".

- Kerrisk: Chapter 53: Posix Semaphores (Named not in focus for this exercise)".

- OLA: "pthread-Tutorial" - chapters 4-6.

- OLA: "Producer/Consumer problem".

- OLA: "Dining Philosophers problem".

2.3 Exercises

- Posix Threads

- Thread Synchronization I & II

3   Thread communication

3.1   Sub topic

- The challenges performing intra-process communication.

- Message queue.

  - The premises for designing it.
  - Various design solutions - Which one chosen and why.
  - Its design and implementation.

- Impact on design/implementation between before and after the Message Queue.

- Event Driven Programming.

  - Basic idea.
  - Reactiveness.
  - Design - e.g. from sequence diagrams to code (or vice versa).

3.2   Curriculum

- Slides: "Inter-Thread Communication".

- OLA: "Event Driven Programming: Introduction, Tutorial, History - Pages 1-19 & 30-51".

- OLA: "Programming with Threads - chapters 4 & 6".

3.3   Exercises

- Thread Communication

4   OS API

4.1   Sub topics

- The design philosophy - Why OO and OS Api?

- Elaborate on the challenge of building it and its currenct design:

  - The PIMPL / Cheshire Cat idiom - The how and why.
  - CPU / OS Architecture.

- Effect on design/implementation:

  - MQs (Message queues) used with pthreads contra MQ used in OO OS Api.
  - RAII in use.
  - Using Threads before and now.

- UML Diagrams to implementation (class and sequence) - How?

4.2   Curriculum

- Slides: OS Api".

- OLA: OSAL SERNA SAC10".

- OLA: Speciffcation of an OS Api".

- Kerrisk: Chapter 35: Process Priorities and Schedul-ing".

4.3   Exercises

- OS API.

5   Message Distribution System (MDS)

5.1   Sub topics

- Messaging distribution system - Why & how?

- The PostOffice design - Why and how?

- Decoupling achieved.

- Design considerations & implementation.

- Patterns per design and in relation to the MDS and PostOffice design:

  - GoF Singleton Pattern
  - GoF Observer Pattern
  - GoF Mediator Pattern

5.2   Curriculum

- Slides: "A message system".

- OLA: "GoF Singleton pattern".

- OLA: "GoF Observer pattern".

- OLA: "GoF Mediator pattern".

5.3   Exercises

- The Message Distribution System

6 Resource handling

6.1 Sub topics

- RAII - What and why?

- Copy construction and the assignment operator.

- What is the concept begind a Counted SmartPointer?

- What is $boost :: shared\_ptr <>$ and how do you use it?

6.2 Curriculum

- Slides: "Resource Handling".

- OLA: "RAII - Resource Acquisition Is Initialiation".

- OLA: "SmartPointer".

- OLA: "Counted Body".

- OLA: "$boost :: shared\_ptr$".

- OLA: "Rule of 3".

6.3 Exercises

- Resource Handling.