

Diffusion models made EZ

Joachim Vandekerckhove

Winter 2025

Goals of cognitive models

Cognitive model virtues

Goals of cognitive models

Cognitive model virtues

- Good cognitive models describe the process by which the data come about
 - Ideally, describing a parameterized process whose parameters have psychological meaning

Goals of cognitive models

Cognitive model virtues

- Good cognitive models describe the process by which the data come about
 - Ideally, describing a parameterized process whose parameters have psychological meaning
- Can be used as a **lens on the data**
 - Focusing on the interesting aspects
 - Filtering out the uninteresting aspects

Goals of cognitive models

Cognitive model virtues

- Good cognitive models describe the process by which the data come about
 - Ideally, describing a parameterized process whose parameters have psychological meaning
- Can be used as a **lens on the data**
 - Focusing on the interesting aspects
 - Filtering out the uninteresting aspects
- Transform the data (with a complex distribution) into one or more **interpretable quantities**


Dual spaces interpretation of cognitive modeling

Dual spaces interpretation of cognitive modeling

When we collect data, we are sampling from some data space.


Dual spaces interpretation of cognitive modeling

When we collect data, we are sampling from some data space.





Dual spaces interpretation of cognitive modeling

Often, we do our familiar analyses in this data space.





Dual spaces interpretation of cognitive modeling

But instead, we can map the data into a space of **interpretable parameters**.



Dual spaces interpretation of cognitive modeling

... and do our familiar analyses in that space for added clarity.



A useful cognitive model

The drift diffusion model (DDM) can be used as such a lensing function

A useful cognitive model

The drift diffusion model (DDM) can be used as such a lensing function

Input: Speeded choice response times

A useful cognitive model

The drift diffusion model (DDM) can be used as such a lensing function

Input: Speeded choice response times

Output: Speed of evidence accumulation (drift rate ν)

A useful cognitive model

The drift diffusion model (DDM) can be used as such a lensing function

Input: Speeded choice response times

Output: Speed of evidence accumulation (drift rate ν)

Conservativeness (boundary separation α)

A useful cognitive model

The drift diffusion model (DDM) can be used as such a lensing function


Input: Speeded choice response times

Output: Speed of evidence accumulation (drift rate ν)

Conservativeness (boundary separation α)

Time for encoding and motor response (nondecision time τ)

A useful cognitive model



A useful cognitive model

The drift diffusion model (DDM) can be used as such a lensing function

Input: Speeded choice response times

Output: Speed of evidence accumulation (drift rate ν)

Conservativeness (boundary separation α)

Time for encoding and motor response (nondecision time τ)

This type of model allows us to transform complex multidimensional data into interpretable low-dimensional parameter sets.

Drift diffusion – example

Consider these data from a study by Ratcliff and Rouder where participants had to judge the brightness of pixel arrays as “high” or “low”:

- 33 stimulus configuration levels controlling the proportion of black vs. white pixels.
- 2 instruction conditions: Speed vs. accuracy.

Drift diffusion – example

Consider these data from a study by Ratcliff and Rouder where participants had to judge the brightness of pixel arrays as “high” or “low”:

- 33 stimulus configuration levels controlling the proportion of black vs. white pixels.
- 2 instruction conditions: Speed vs. accuracy.

The instruction condition is known to have an effect on the boundary parameter α .

Drift diffusion – example

Consider these data from a study by Ratcliff and Rouder where participants had to judge the brightness of pixel arrays as “high” or “low”:

- 33 stimulus configuration levels controlling the proportion of black vs. white pixels.
- 2 instruction conditions: Speed vs. accuracy.

The instruction condition is known to have an effect on the boundary parameter α .

How do brightness and instruction affect the easiness of the task (drift rate ν)?

Drift diffusion – example

Consider these data from a study by Ratcliff and Rouder where participants had to judge the brightness of pixel arrays as “high” or “low”:

- 33 stimulus configuration levels controlling the proportion of black vs. white pixels.
- 2 instruction conditions: Speed vs. accuracy.

The instruction condition is known to have an effect on the boundary parameter α .


How do brightness and instruction affect the easiness of the task (drift rate ν)?

Use a nonlinear regression with effects of instruction X_i and brightness Z_s on $\nu_{i,s}$.

$$\nu_{i,s}^{\text{pred}} = \mu_\nu + \beta_0 \Phi(\beta_1 + \beta_2 |Z_s| + \beta_3 X_i |Z_s|) + \beta_4 X_i$$

Drift diffusion – example

$$\nu_{i,s}^{\text{pred}} = \mu_{\nu} + \beta_0 \Phi(\beta_1 + \beta_2 |Z_s| + \beta_3 X_i |Z_s|) + \beta_4 X_i$$



- The **Simple DDM** is a three-parameter model that accounts for choice and RT data using a Wiener likelihood function.

- The **Simple DDM** is a three-parameter model that accounts for choice and RT data using a Wiener likelihood function.
- The likelihood of the DDM is quite complicated so maximum likelihood estimation can be slow.

- The **Simple DDM** is a three-parameter model that accounts for choice and RT data using a Wiener likelihood function.
- The likelihood of the DDM is quite complicated so maximum likelihood estimation can be slow.
- People have written entire PhD dissertations on how to fit the DDM.

- The **Simple DDM** is a three-parameter model that accounts for choice and RT data using a Wiener likelihood function.
- The likelihood of the DDM is quite complicated so maximum likelihood estimation can be slow.
- People have written entire PhD dissertations on how to fit the DDM.
- Sampling from the DDM is not so difficult but a little time consuming.

EZ diffusion

- The **EZ diffusion model** is a simplified method that allows us to compute estimated parameters directly from observed summary statistics.

EZ diffusion

- The **EZ diffusion model** is a simplified method that allows us to compute estimated parameters directly from observed summary statistics.
- A lot like signal detection theory, but with response times).

EZ diffusion

- The **EZ diffusion model** is a simplified method that allows us to compute estimated parameters directly from observed summary statistics.
- A lot like signal detection theory, but with response times).

Summary statistics	
Accuracy rate	R^{obs}
Mean RT	M^{obs}
Variance RT	V^{obs}

EZ diffusion

- The **EZ diffusion model** is a simplified method that allows us to compute estimated parameters directly from observed summary statistics.
- A lot like signal detection theory, but with response times).

Summary statistics			Parameters	
Accuracy rate	R^{obs}	\leftrightarrow	Drift rate	ν^{est}
Mean RT	M^{obs}		Boundary separation	α^{est}
Variance RT	V^{obs}		Nondecision time	τ^{est}

EZ diffusion

- The **EZ diffusion model** is a simplified method that allows us to compute estimated parameters directly from observed summary statistics.
- A lot like signal detection theory, but with response times).

Summary statistics			Parameters	
Accuracy rate	R^{obs}	\leftrightarrow	Drift rate	ν^{est}
Mean RT	M^{obs}		Boundary separation	α^{est}
Variance RT	V^{obs}		Nondecision time	τ^{est}

- EZ diffusion involves two sets of equations, the **forward** equations give the summary statistics in terms of parameters, and the **inverse** equations give the parameters in terms of summary statistics.

Forward EZ equations:

$$R^{\text{pred}} = \frac{1}{y + 1} \quad (1)$$

$$M^{\text{pred}} = \tau + \left(\frac{\alpha}{2\nu}\right) \left(\frac{1 - y}{1 + y}\right), \quad (2)$$

$$V^{\text{pred}} = \left(\frac{\alpha}{2\nu^3}\right) \left\{ \frac{1 - 2\alpha\nu y - y^2}{(y + 1)^2} \right\} \quad (3)$$

with $y = \exp(-\alpha\nu)$.

Inverse EZ equations:

$$\nu^{\text{est}} = \text{sgn}\left(R^{\text{obs}} - \frac{1}{2}\right) \sqrt[4]{\frac{L\left(R^{\text{obs}^2}L - R^{\text{obs}}L + R^{\text{obs}} - \frac{1}{2}\right)}{V^{\text{obs}}}} \quad (4)$$

$$\alpha^{\text{est}} = \frac{L}{\nu^{\text{est}}} \quad (5)$$

$$\tau^{\text{est}} = M^{\text{obs}} - \left(\frac{\alpha^{\text{est}}}{2\nu^{\text{est}}}\right) \left[\frac{1 - \exp(-\nu^{\text{est}}\alpha^{\text{est}})}{1 + \exp(-\nu^{\text{est}}\alpha^{\text{est}})}\right]. \quad (6)$$

with $L = \log\left(\frac{R^{\text{obs}}}{1-R^{\text{obs}}}\right)$.

This is extremely useful, because now we can calculate these interesting parameters without having to use complicated numerical algorithms.

This is extremely useful, because now we can calculate these interesting parameters without having to use complicated numerical algorithms.

But how good is this?

This is extremely useful, because now we can calculate these interesting parameters without having to use complicated numerical algorithms.

But how good is this?

What we want is an algorithm that can give us (ν, α, τ) if given some data that was in fact generated by (ν, α, τ) .

This is extremely useful, because now we can calculate these interesting parameters without having to use complicated numerical algorithms.

But how good is this?

What we want is an algorithm that can give us (ν, α, τ) if given some data that was in fact generated by (ν, α, τ) .

But data is noisy! Even if a person's true accuracy rate is 80%, sometimes they score 90% by chance. How do we **test** EZ diffusion while accounting for this randomness?

This is extremely useful, because now we can calculate these interesting parameters without having to use complicated numerical algorithms.

But how good is this?

What we want is an algorithm that can give us (ν, α, τ) if given some data that was in fact generated by (ν, α, τ) .

But data is noisy! Even if a person's true accuracy rate is 80%, sometimes they score 90% by chance. How do we **test** EZ diffusion while accounting for this randomness?

We actually know how to generate “noisy,” “observed” accuracy rates from “true” accuracy rates, and we know this for means and variances as well.

EZ diffusion – sampling distributions

If N observations are drawn from a diffusion model whose accuracy rate is R^{pred} , then the sampling distribution of the observed number of correct trials $T^{\text{obs}} = N \times R^{\text{obs}}$ is:

$$T^{\text{obs}} \sim \text{Binomial} \left(R^{\text{pred}}, N \right). \quad (7)$$

EZ diffusion – sampling distributions

If N observations are drawn from a diffusion model whose accuracy rate is R^{pred} , then the sampling distribution of the observed number of correct trials $T^{\text{obs}} = N \times R^{\text{obs}}$ is:

$$T^{\text{obs}} \sim \text{Binomial} \left(R^{\text{pred}}, N \right). \quad (7)$$

If N observations are drawn from a sample whose mean and variance of the RTs are M^{pred} and V^{pred} , then the sampling distribution of the observed mean RT M^{obs} is:

$$M^{\text{obs}} \sim \text{Normal} \left(M^{\text{pred}}, \frac{V^{\text{pred}}}{N} \right). \quad (8)$$

EZ diffusion – sampling distributions

If N observations are drawn from a diffusion model whose accuracy rate is R^{pred} , then the sampling distribution of the observed number of correct trials $T^{\text{obs}} = N \times R^{\text{obs}}$ is:

$$T^{\text{obs}} \sim \text{Binomial} \left(R^{\text{pred}}, N \right). \quad (7)$$

If N observations are drawn from a sample whose mean and variance of the RTs are M^{pred} and V^{pred} , then the sampling distribution of the observed mean RT M^{obs} is:

$$M^{\text{obs}} \sim \text{Normal} \left(M^{\text{pred}}, \frac{V^{\text{pred}}}{N} \right). \quad (8)$$

And the sampling distribution of the variance of the RTs follows this probability law:

$$V^{\text{obs}} \sim \text{Gamma} \left(\frac{N-1}{2}, \frac{2V^{\text{pred}}}{N-1} \right). \quad (9)$$

EZ diffusion – simulate and recover

We could now test how good EZ diffusion is at recovering its own parameters!

EZ diffusion – simulate and recover

We could now test how good EZ diffusion is at recovering its own parameters!

1. Select some ‘true’ parameters (ν, α, τ) and a sample size N

EZ diffusion – simulate and recover

We could now test how good EZ diffusion is at recovering its own parameters!

1. Select some 'true' parameters (ν, α, τ) and a sample size N
2. Use Equations 1, 2, and 3 to generate 'predicted' summary statistics $(R^{\text{pred}}, M^{\text{pred}}, V^{\text{pred}})$

EZ diffusion – simulate and recover

We could now test how good EZ diffusion is at recovering its own parameters!

1. Select some 'true' parameters (ν, α, τ) and a sample size N
2. Use Equations 1, 2, and 3 to generate 'predicted' summary statistics $(R^{\text{pred}}, M^{\text{pred}}, V^{\text{pred}})$
3. Use Equations 7, 8, and 9 to simulate 'observed' summary statistics $(R^{\text{obs}}, M^{\text{obs}}, V^{\text{obs}})$

EZ diffusion – simulate and recover

We could now test how good EZ diffusion is at recovering its own parameters!

1. Select some ‘true’ parameters (ν, α, τ) and a sample size N
2. Use Equations 1, 2, and 3 to generate ‘predicted’ summary statistics $(R^{\text{pred}}, M^{\text{pred}}, V^{\text{pred}})$
3. Use Equations 7, 8, and 9 to simulate ‘observed’ summary statistics $(R^{\text{obs}}, M^{\text{obs}}, V^{\text{obs}})$
4. Use Equations 4, 5, and 6 to compute ‘estimated’ parameters $(\nu^{\text{est}}, \alpha^{\text{est}}, \tau^{\text{est}})$

EZ diffusion – simulate and recover

We could now test how good EZ diffusion is at recovering its own parameters!

1. Select some ‘true’ parameters (ν, α, τ) and a sample size N
2. Use Equations 1, 2, and 3 to generate ‘predicted’ summary statistics $(R^{\text{pred}}, M^{\text{pred}}, V^{\text{pred}})$
3. Use Equations 7, 8, and 9 to simulate ‘observed’ summary statistics $(R^{\text{obs}}, M^{\text{obs}}, V^{\text{obs}})$
4. Use Equations 4, 5, and 6 to compute ‘estimated’ parameters $(\nu^{\text{est}}, \alpha^{\text{est}}, \tau^{\text{est}})$
5. Compute the estimation bias $b = (\nu, \alpha, \tau) - (\nu^{\text{est}}, \alpha^{\text{est}}, \tau^{\text{est}})$ and squared error b^2

EZ diffusion – simulate and recover

We could now test how good EZ diffusion is at recovering its own parameters!

1. Select some ‘true’ parameters (ν, α, τ) and a sample size N
2. Use Equations 1, 2, and 3 to generate ‘predicted’ summary statistics $(R^{\text{pred}}, M^{\text{pred}}, V^{\text{pred}})$
3. Use Equations 7, 8, and 9 to simulate ‘observed’ summary statistics $(R^{\text{obs}}, M^{\text{obs}}, V^{\text{obs}})$
4. Use Equations 4, 5, and 6 to compute ‘estimated’ parameters $(\nu^{\text{est}}, \alpha^{\text{est}}, \tau^{\text{est}})$
5. Compute the estimation bias $b = (\nu, \alpha, \tau) - (\nu^{\text{est}}, \alpha^{\text{est}}, \tau^{\text{est}})$ and squared error b^2

Ideally, b is close to 0 on average, and b^2 should decrease when we increase N .

EZ diffusion – simulate and recover

We could now test how good EZ diffusion is at recovering its own parameters!

1. Select some ‘true’ parameters (ν, α, τ) and a sample size N
2. Use Equations 1, 2, and 3 to generate ‘predicted’ summary statistics $(R^{\text{pred}}, M^{\text{pred}}, V^{\text{pred}})$
3. Use Equations 7, 8, and 9 to simulate ‘observed’ summary statistics $(R^{\text{obs}}, M^{\text{obs}}, V^{\text{obs}})$
4. Use Equations 4, 5, and 6 to compute ‘estimated’ parameters $(\nu^{\text{est}}, \alpha^{\text{est}}, \tau^{\text{est}})$
5. Compute the estimation bias $b = (\nu, \alpha, \tau) - (\nu^{\text{est}}, \alpha^{\text{est}}, \tau^{\text{est}})$ and squared error b^2

Ideally, b is close to 0 on average, and b^2 should decrease when we increase N .

Certainly, b should be 0 when we set $(R^{\text{obs}}, M^{\text{obs}}, V^{\text{obs}}) = (R^{\text{pred}}, M^{\text{pred}}, V^{\text{pred}})$.

This **simulate and recover** exercise lets us make a simple but necessary claim:

This **simulate and recover** exercise lets us make a simple but necessary claim:

IF data are truly generated by an EZ diffusion model THEN the estimation procedure can recover them accurately.

EZ diffusion – simulate and recover

This **simulate and recover** exercise lets us make a simple but necessary claim:

IF data are truly generated by an EZ diffusion model THEN the estimation procedure can recover them accurately.

This is a **pretty low bar**, but not all models clear it!

EZ diffusion – assignment

For your final project, you will program a simulate-and-recover study for EZ diffusion.

- Use the equations in these slides to implement the forward equations, inverse equations, and sampling
- Use all the best practices covered in class, including:
 - Unit testing, including the expected value of b if there is no noise (slide 16)
 - A folder structure like the one recommended in class, and meaningful names for classes, methods, variables, etc.
 - Readable, maintainable code that works in the class container
 - Appropriate acknowledgment of outside sources

Diffusion models made EZ

Joachim Vandekerckhove

Winter 2025