

Organizing Python files for unittest

- `unittest` collects tests from `./tests/`.

- `unittest` collects tests from `./tests/`.
- Each test file is a normal module: names resolve only via `sys.path`.

Organizing files for `unittest`

- `unittest` collects tests from `./tests/`.
- Each test file is a normal module: names resolve only via `sys.path`.
- **`ModuleNotFoundError`** → fix layout + where you run `unittest`.

Goal: `tests/` imports a module sitting next to it at the `repo root`.

Goal: `tests/` imports a module sitting next to it at the `repo root`.

```
myproject/  
  counter.py          # implementation  
  tests/  
    test_counter.py  # tests
```

`counter.py` defines `increment`. In `tests/test_counter.py`:

counter.py defines increment. In tests/test_counter.py:

```
import unittest
```

```
import counter
```

```
class TestCounter(unittest.TestCase):
```

```
    def test_increment(self):
```

```
        self.assertEqual(counter.increment(0), 1)
```



```
import counter
```

- Run **unittest** from **myproject/** (the folder that contains both **counter.py** and **tests/**).

```
import counter
```

- Run **unittest** from **myproject/** (the folder that contains both **counter.py** and **tests/**).
- With **python -m unittest**, the current working directory is on **sys.path**, so **counter** maps to **./counter.py**.

```
import counter
```

- Run **unittest** from **myproject/** (the folder that contains both **counter.py** and **tests/**).
- With **python -m unittest**, the current working directory is on **sys.path**, so **counter** maps to **./counter.py**.

```
import counter
```

- Run **unittest** from **myproject/** (the folder that contains both **counter.py** and **tests/**).
- With **python -m unittest**, the current working directory is on **sys.path**, so **counter** maps to **./counter.py**.

Discover all tests

```
import counter
```

- Run **unittest** from **myproject/** (the folder that contains both **counter.py** and **tests/**).
- With **python -m unittest**, the current working directory is on **sys.path**, so **counter** maps to **./counter.py**.

Discover all tests

From **myproject/**:

```
import counter
```

- Run **unittest** from **myproject/** (the folder that contains both **counter.py** and **tests/**).
- With **python -m unittest**, the current working directory is on **sys.path**, so **counter** maps to **./counter.py**.

Discover all tests

From **myproject/**:

```
python -m unittest discover -s tests -p 'test_*.py'
```

```
import counter
```

- Run **unittest** from **myproject/** (the folder that contains both **counter.py** and **tests/**).
- With **python -m unittest**, the current working directory is on **sys.path**, so **counter** maps to **./counter.py**.

Discover all tests

From **myproject/**:

```
python -m unittest discover -s tests -p 'test_*.py'
```

Single file:

```
import counter
```

- Run **unittest** from **myproject/** (the folder that contains both **counter.py** and **tests/**).
- With **python -m unittest**, the current working directory is on **sys.path**, so **counter** maps to **./counter.py**.

Discover all tests

From **myproject/**:

```
python -m unittest discover -s tests -p 'test_*.py'
```

Single file:

```
python -m unittest tests.test_counter
```