

Tarea Big Data - SQL

Grupo DataLab: Joaquin Gelves, Augusto Diaz de Valdes, Simon Godino, Benjamin Alonso, Justo Valente y Simon Lawson

Complejidad Inicial

1)

```
SELECT customername, country
FROM client_data
where country = 'France'
```

2)

```
SELECT productcode, msrp
FROM product_data
Order by msrp ASC
```

3)

```
SELECT *
FROM transaction_data
where quantityordered > 50
```

4)

```
SELECT COUNT(status)
FROM order_data
where status = 'Cancelled'
```

5)

```
SELECT customername, city
FROM client_data
WHERE city Like '%San%'
```

Complejidad intermedia

1)

```
SELECT productline, sum(sales)
FROM product_data inner join transaction_data
ON product_data.PRODUCTCODE = transaction_data.PRODUCTCODE
group by productline
```

2)

```
SELECT CUSTOMERNAME, STATUS
FROM client_data c
JOIN transaction_data t ON c.customer_id = t.CLIENT_ID
JOIN order_data o ON t.ORDERNUMBER = o.ORDERNUMBER
WHERE o.STATUS = 'Disputed'
```

3)

```
SELECT COUNT(DISTINCT t.ORDERNUMBER) AS cantidad_pedidos
FROM transaction_data t
JOIN order_data o
ON t.ORDERNUMBER = o.ORDERNUMBER
WHERE o.STATUS = 'Shipped'
AND t.YEAR_ID = 2003
```

4)

```
SELECT country, sum(sales)
FROM transaction_data inner JOIN client_data ON transaction_data.CLIENT_ID =
client_data.customer_id
```

GROUP BY country

5)

```
SELECT productline, avg(priceeach)
FROM transaction_data INNER join product_data
on transaction_data.PRODUCTCODE=product_data.PRODUCTCODE
group by productline
```

6)

```
SELECT customername, sum(sales)
FROM transaction_data
JOIN client_data ON transaction_data.CLIENT_ID = client_data.customer_id
GROUP BY customername
ORDER BY sum(sales) DESC
LIMIT 5
```

7)

```
SELECT PRODUCTCODE, SUM(QUANTITYORDERED)
FROM transaction_data
GROUP BY PRODUCTCODE
ORDER BY SUM(QUANTITYORDERED) DESC
LIMIT 3;
```

8)

```
SELECT QTR_ID , SUM(SALES)
FROM TRANSACTION_DATA
WHERE YEAR_ID = 2003
GROUP BY QTR_ID
ORDER BY QTR_ID ASC;
```

9)

```
SELECT COUNT(DISTINCT customer_id)
FROM CLIENT_DATA
WHERE TERRITORY = 'EMEA';
```

10)

```
SELECT t.ORDERNUMBER, c.CUSTOMERNAME
FROM transaction_data t
JOIN order_data o ON t.ORDERNUMBER = o.ORDERNUMBER
JOIN client_data c ON t.CLIENT_ID = c.customer_id
WHERE o.STATUS = 'Cancelled'
GROUP BY t.ORDERNUMBER, c.CUSTOMERNAME;
```

Complejidad avanzada

1)

```
SELECT
SUM(t.SALES) AS TOTAL_VENTAS
FROM transaction_data t
JOIN client_data c ON t.CLIENT_ID = c.customer_id
WHERE c.COUNTRY = 'USA'
AND t.QTR_ID = 1;
```

2)

```
SELECT DISTINCT c.CUSTOMERNAME
FROM transaction_data t
```

```
JOIN product_data p ON t.PRODUCTCODE = p.PRODUCTCODE  
JOIN client_data c ON t.CLIENT_ID = c.customer_id  
WHERE p.PRODUCTLINE = 'Classic Cars'  
ORDER BY c.CUSTOMERNAME;
```