₁ Contents

2	1	Sum	nmary	3			
3	2	2 Core team					
4	3	App	plication questions	5			
5		3.1	BBSRC schemes	5			
6		3.2	BBSRC remit classification	7			
7		3.3	Vision	8			
8			3.3.1 Context	8			
9			3.3.2 Specific aims	11			
10		3.4	Approach	15			
11			3.4.1 Offline Analysis Methods	16			
12			3.4.1.1 Initial List of Methods to Include in the Library	16			
13			3.4.1.2 Non-stationarity	18			
14			3.4.1.3 Computational efficiency	21			
15			3.4.1.4 Deliverables	22			
16			3.4.2 Real-Time Machine Learning Methods	22			
17			3.4.2.1 Real-Time Machine Learning in Neuroscience	22			
18			3.4.2.2 Bonsai and Bonsai.ML	24			
19			3.4.2.3 Deliverables	24			
20			3.4.3 Visual Exploration	25			
21			3.4.3.1 Continuous Visualizations	25			
22			3.4.3.2 Epoched and Interactive Visual Analytics	26			
23			3.4.3.3 Software Stack for Interactive Visualizations .	27			
24			3.4.3.4 Deliverables	29			
25			3.4.4 Offline spike Sorting	29			
26			3.4.4.1 Outputs	29			
27			3.4.5 Online spike Sorting	29			
28			3.4.5.1 Outputs	29			
29		3.5	Applicant and team capability to deliver	30			
30		3.6	Project partners	32			
31		3.7	Project partners: statement of support				
32		3.8	Trusted Research and Innovation (TR&I)				
33		3.9	Resources and cost justification				
34		3.10	Data management and sharing				

35	3.11	Facilities	37
36	3.12	Ethics and responsible research and innovation (RRI)	38
37	3.13	Genetic and biological risk	39
38	3.14	Research involving the use of animals	40
39	3.15	Conducting research with animals overseas	41
40	3.16	Research involving human participation	43
41	3.17	Research involving human tissues or biological samples	44

2 1 Summary

- Word limit: 550
- In plain English, provide a summary we can use to identify the most suitable experts to assess your application.
- We usually make this summary publicly available on external-facing websites, therefore do not include any confidential or sensitive information. Make it suitable for a variety of readers, for example:
- opinion-formers
- policymakers
- the public
- the wider research community
- Guidance for writing a summary Clearly describe your proposed work in terms of:
- context
- the challenge the project addresses
- aims and objectives
- potential applications and benefits
- its relevance to the BBSRC long-term research and innovation priorities and, if applicable Responsive Mode Spotlight areas

2 Core team

- 62 List the key members of your team and assign them roles from the following:
- project lead (PL)
- project co-lead (UK) (PcL)
- specialist
- professional enabling staff
- research and innovation associate
- technician
- researcher co-lead (RcL)
- Only list one individual as project lead.
- UKRI has introduced a new addition to the 'specialist' role type. Public contributors such as people with lived experience can now be added to an application.
- Find out more about UKRI's core team roles in funding applications and our eligibility guidance.

₆ 3 Application questions

3.1 BBSRC schemes

- 78 Word limit: 1
 - Indicate the scheme through which you are applying.
- In the text box, copy the number corresponding to the scheme you are applying through. These are:
- 1. standard (no scheme)
- 2. Industrial Partnership Award (IPA)
- 84 3. LINK
- 4. Brazil (FAPESP)
- 5. Luxembourg (FNR)
- 6. NSF-Bio
- 88 Additional guidance
- This is for administrative purposes to help the initial application processing.
- Please follow the scheme specific guidance below and upload the additional documents listed as a single PDF no larger than 8MB:
- IPA or LINK:
- a letter from your institution's technology transfer office outlining the management of outputs from the proposed research
- FAPESP:
- FAPESP proposal form
- FAPESP consolidated budget form
- FAPESP letter of eligibility
- FNR:

- CVs of international collaborators
- FNR 'INTER' budget form
- FNR 'INTER' cost justification
- NSF-Bio:
- US biosketches
- US budget forms

3.2 BBSRC remit classification

.08 Word limit: 1

107

Your application will be considered by one of our four research committees made up of independent experts. Indicate which you feel would be best placed to assess your application.

In the text box, write only the letter (in uppercase) corresponding to the committee you feel would be best placed to assess your application. These are:

- A animal disease, health and welfare
- 16 B plants, microbes, food and sustainability
- C genes, development, and science, technology, engineering and maths (STEM) approaches to biology
- 19 D molecules, cells and industrial biotechnology
- 120 Additional guidance:
 - This is for administrative purposes to help the initial application processing. We will check your choice and make a final decision as to which committee will assess your application.

3.3 Vision

Word limit: 550

126

127

128

131

132

133

134

135

144

145

146

148

149

150

What are you hoping to achieve with your proposed work?

What the assessors are looking for in your response

Explain how your proposed work:

- 1. is of excellent quality and importance within or beyond the field(s) or area(s)
 - 2. has the potential to advance current understanding, or generate new knowledge, thinking or discovery within or beyond the field or area
 - 3. is timely given current trends, context, and needs
 - 4. impacts world-leading research, society, the economy, or the environment

You may demonstrate elements of your responses in visual form if relevant. Further details are provided in the Funding Service. References may be included within this section.

3.3.1 Context

Conventional systems neuroscience experiments are typically short in duration and often place significant constraints on subjects behaviours to simplify data analysis. However, these restrictions may limit our ability to observe critical aspects of brain function and behaviour that only manifest in more naturalistic and extended conditions.

At the Sainsbury Wellcome Centre (SWC) and Gatsby Computational Neuroscience Unit (GCNU) we are pioneering **Naturalistic**, **Long-Duration**, and **Continual (NaLoDuCo) experiments** in mice that span weeks to months. During these experiments, we collect high-resolution behavioural and neural recordings in naturalistic settings (Figure 1).

To support this endeavor, we are developing the **AEON platform**, an innovative set of hardware and software tools for NaLoDuCo experimental control, data store and access. We are using this platform to investigate the neural basis of foraging behavior in mice over prolonged periods of time (Campagner et al., 2024).




Figure 1: **a**: Example of natural behaviours in rodents that take place over different timescale, spatial extensions and involving different numbers of individuals.

b-d: Close-up views of one possible configuration of the Aeon environment in which naïve mice and mice chronically implanted with Neuropixels probe can live while expressing a variety of natural behaviours including exploring, drinking, escaping, foraging, nesting, sleeping, eating and interacting socially.

Our US partner, the Allen Institute for Neural Dynamics (AIND) is also performing NaLoDuCo experimentation, using the AEON platform, studying naturalistic olfactory learning over weeks to month outside conventional task structures (Fink et al., 2024).

NeuroGEARS Ltd, our industrial partner, is a UK-based company supporting academic institutions implementing innovative technology for scientific investigation. It is the main developer of the Bonsai software ecosystem for experimental control (Lopes et al., 2015), used by thousands of scientists around the world, and powering the AEON platform. NeuroGEARS has played a central role in the development of the AEON platform, and provides services to both the SWC and the AIND.

NaLoDuCo experimentation will enable researchers to explore neural mechanisms underlying ethological behaviours in naturalistic environments over months, for the first time. The experiments will shed new light on a wide range of poorly understood neural mechanisms, including how the brain structures complex behavioural sequences as a function of the animal needs, learning, adaptation, sleep-dependent memory consolidation and social dynamics. The data generated from NaLoDuCo experiments represent an entirely new resource in neuroscience, with the potential to drive breakthroughs and discoveries that are beyond the reach of traditional experiments.

While naturalistic, long-duration, or continuous neuroscience experiments have been conducted in the past (Nagy et al., 2023; Ho et al., 2023; Ray et al., 2025; Weissbrod et al., 2013; Dhawale et al., 2017; Newman et al., 2024), to the best of our knowledge, we are the first ones to integrate all three of these features in a single experimental paradigm.

This emerging paradigm of long-duration experimentation is poised to become mainstream in the coming years. However, experiments spanning weeks to months generate massive datasets—often reaching hundreds of terabytes—posing significant challenges in data acquisition, management, distribution, visualization, and analysis. To address these challenges, we (GCNU, SWC, AIND, and NeuroGEARS Ltd) will collaboratively extend the AEON platform with functionality to visualise and statistically analyze previously collected NaLoDuCo experimental data on the cloud, and to perform real-time machine to enable the intelligent control of NaLoDuCo experiments.

3.3.2 Specific aims

Data generated by NaLoDuCo experiments will be of general interest to the neuroscience community. We want to share our NaLoDuCo foraging and odor learning recordings and allow other groups collecting this type of data to share their own. However, this dissemination is not trivial, as datasets are of the order of hundreds of terabytes, and it will take users several days to download them over standard Internet connections.

Instead of bringing data to users, we will bring users to data, by storing datasets in the cloud (or in institutional clusters), and providing cloud software to allow users to visually explore and statistically analyse behavioural and neural NaLoDuCo datasets where they live (1 and 2 in Figure 2).

Our statistical analysis of neural time series will require knowledge of the spiking activity of single units; i.e., spike sorting. In long-duration experiments with freely moving animals spike sorting is a challenging problem, because movements of recording probes change the shape of spike waveforms over time and complicate the assignment of spikes to units based on their waveforms. We will address this problem by developing **spike sorting methods for long-duration**, **continual and high-channel-count recordings** (3 in Figure 2).

Funded by a BBSRC award we are adding machine learning functionality to Bonsai in order to enable a new type of experimentation controlled by advanced machine learning inference on behavioral and neural recordings (Bonsai.ML, Guilbeault et al., 2025). We have developed this functionality for conventional short duration experiments. We will add to Bonsai.ML real-time machine learning functionality for processing nonstationary data, such as that generated in NaLoDuCo experiments.

Most of the online neural data analysis methods that we will add to AEON require sorted spikes. We will adapt the previous offline **spike sorting methods for long-duration experiment to operate in real-time** (5 in Figure 2).

2 References

Campagner, D., Bhagat, J., Lopes, G., Calcaterra, L., Ahn, J., Almeida, A., Carvalho, F. J., Cruz, B., Erskine, A., Lo, C., Nguyen, T. T.,




Figure 2: Specific aims

- Pouget, A., Rapela, J., Ryan, T., Reggiani, J., and Group, S. S.
- F. B. W. (2024). Aeon: an open-source platform to study the
- neural basis of ethological behaviours over naturalistic timescales.
- https://www.sfn.org/-/media/SfN/Documents/NEW-SfN/Meetings/
- Neuroscience-2024/Abstracts-and-Sessions/Abstract-PDFs/
- 230 SFN24_Abstracts-PDF-Posters_SAT_PM.pdf.
- Dhawale, A. K., Poddar, R., Wolff, S. B., Normand, V. A., Kopelowitz, E., and Ölveczky, B. P. (2017). Automated long-term recording and analysis of neural activity in behaving animals. *Elife*, 6:e27702.
- Fink, A. J., Hogan, M., and Schoonover, C. E. (2024). Olfactory investigation in the home cage. *Neurobiology of Learning and Memory*, 213:107951.
- Guilbeault, N., Lopes, G., and Rapela, J. (2025). Bonsai.ml: machine learning for intelligent experimental control. https://bonsai-rx.org/machinelearning/.
- Ho, H., Kejzar, N., Sasaguri, H., Saito, T., Saido, T. C., De Strooper, B., Bauza, M., and Krupic, J. (2023). A fully automated home cage for long-term continuous phenotyping of mouse cognition and behavior. *Cell Reports Methods*, 3(7).
- Lopes, G., Bonacchi, N., Frazão, J., Neto, J. P., Atallah, B. V., Soares, S.,
 Moreira, L., Matias, S., Itskov, P. M., Correia, P. A., et al. (2015). Bonsai:
 an event-based framework for processing and controlling data streams.
 Frontiers in neuroinformatics, 9:7.
- Nagy, M., Naik, H., Kano, F., Carlson, N. V., Koblitz, J. C., Wikelski, M., and Couzin, I. D. (2023). Smart-barn: Scalable multimodal arena for real-time tracking behavior of animals in large numbers. *Science Advances*, 9(35):eadf8068.
- Newman, J. P., Zhang, J., Cuevas-López, A., Miller, N. J., Honda, T., van der Goes, M.-S. H., Leighton, A. H., Carvalho, F., Lopes, G., Lakunina, A., et al. (2024). Onix: a unified open-source platform for multimodal neural recording and perturbation during naturalistic behavior. *Nature Methods*, pages 1–6.
- Ray, S., Yona, I., Elami, N., Palgi, S., Latimer, K. W., Jacobsen, B., Witter, M. P., Las, L., and Ulanovsky, N. (2025). Hippocampal coding of identity,

- sex, hierarchy, and affiliation in a social group of wild fruit bats. Science, 387(6733):eadk9385.
- Weissbrod, A., Shapiro, A., Vasserman, G., Edry, L., Dayan, M., Yitzhaky,
 A., Hertzberg, L., Feinerman, O., and Kimchi, T. (2013). Automated
 long-term tracking and social behavioural phenotyping of animal colonies
 within a semi-natural environment. Nature communications, 4(1):2018.

3.4 Approach

265 Word limit: 3,300

266

267

268

269

271

275

277

278

279

280

282

283

284

286

288

289

290

How are you going to deliver your proposed work?

What the assessors are looking for in your response

Explain how you have designed your approach so that it:

- 1. is effective and appropriate to achieve your objectives
- 2. is feasible, and comprehensively identifies any risks to delivery and how they will be managed
- 3. uses a clearly written and transparent methodology (if applicable)
- 4. summarises the previous work and describes how this will be built upon and progressed (if applicable)
 - 5. will maximise translation of outputs into outcomes and impacts
 - 6. describes how your, and if applicable your team's, research environment (in terms of the place and relevance to the project) will contribute to the success of the work

You may demonstrate elements of your responses in visual form if relevant.

Please make sure to check sizing and readability of the image using 'read view' prior to submission. Further details are provided in the Funding Service.

References may be included within this section.

Within the 'Approach' section we also expect you to:

 provide a detailed and comprehensive project plan including milestones and timelines in the form of an embedded Gantt chart or similar (please make sure to check sizing and readability of the image using 'read view' prior to submission)

BBSRC's action plan for EDI outlines our commitment to removing barriers to participation in our programmes, ensuring investments do not inadvertently prevent access or usage by individuals from minority groups, for example disabled researchers.

To this end, applications should identify how accessibility and inclusiveness in the widest sense have been incorporated into the design of the project. For example, you may wish to reference relevant institutional strategies and policies which support equality, diversity, and inclusion as they relate to access to equipment and facilities and indicate how the proposed project has been designed and will be delivered with broad access in mind.

We have collected unprecedented NaLoDuCo datasets at the SWC and AIND, comprising continuous, multimodal recordings over weeks to months. However, the scientific value of these massive datasets cannot be fully realized without robust tools for visual exploration and analysis. To address this need, we will develop and disseminate an open-source library of methods for the visualization and analysis of NaLoDuCo experimental data.

This library will include tools for both offline and online analysis (Sections 3.4.1 and ??), visual exploration (Section 3.4.3), and scalable offline and real-time spike sorting (Sections 3.4.4 and 3.4.5). Together, these methods will make NaLoDuCo data more accessible, interpretable, and actionable for the neuroscience community.

3.4.1 Offline Analysis Methods

294

296

299

300

301

302

303

304

305

306

307

300

315

317

319

Modern neuroscience lacks robust methods to characterize longduration and continual time series, especially in settings where the statistical properties of the data evolve over time. This limitation present a methodological gap that must be addressed in order to unlock the scientific potential of NaLoDuCo experiments.

To bridge this gap, we will develop and disseminate a software library containing new implementations of machine learning methods specifically tailored to: (1) operate effectively under **non-stationary** conditions, and (2) scale to **very long time series**.

3.4.1.1 Initial List of Methods to Include in the Library

We will initially populate this library with new implementations of methods already in use at the GCNU, SWC, and AIND to analyze neural and behavioral time series from NaLoDuCo foraging and olfactory learning experiments in mice. These methods span multiple domains—kinematics, neural dynamics, behavioral state segmentation, forecasting, and joint modeling—and are

designed to work together within an integrated analysis pipeline. We described these methods below and summarise them in Table 1.

Behavioral Analysis: The first step in behavioral analysis involves multibody-part tracking. For this, we will use **deep learning-based pose estimation** methods such as SLEAP, which enable accurate and efficient tracking of multiple unmarked mice across long recording sessions.

From the tracked poses, we will infer continuous kinematic variables using linear dynamical systems (LDS), including particle filter-based variants to handle uncertainty and measurement noise. These kinematic features will be used to infer discrete behavioral states with Hidden Markov Models (HMMs), as implemented in tools such as MoSeq.

We will relate these inferred states and kinematic variables to foraging-related outcomes—such as patch-leaving decisions—using both **generalized linear models (GLMs)** and **deep neural networks**. These models will allow us to capture both interpretable and high-capacity representations of behavioral decision-making processes.

To recover the latent strategies guiding animal behavior, we will apply inverse reinforcement learning methods such as HIQL, which estimate the underlying reward functions and policies based on observed actions.

NaLoDuCo recordings uniquely support behavioral forecasting over extended horizons—ranging from hours to days—far beyond what is feasible in conventional short-duration experiments. To capitalize on this, we will apply long-horizon forecasting models using **recurrent neural networks** (RNNs) and **transformer architectures**, which are well-suited to modeling long-range temporal dependencies.

Neural Data Analysis: Analysis of high-density electrophysiology will begin with latent variable modeling to reduce the dimensionality of population neural recordings. We will use both linear and nonlinear latent dynamics models, including svGPFA, which uses Gaussian processes, and LFADS, a deep generative model based on recurrent neural networks.

The resulting low-dimensional trajectories will be used to infer discrete neural states via **HMMs**, using methods such as **SSM**. For neural activity forecasting across long durations, we will again employ **RNNs** and **transformers**, which can model complex temporal structure in spiking activity.

We will also decode the animal's position from hippocampal spike trains using **point-process decoders**, enabling the analysis of spatial coding and

replay phenomena during naturalistic foraging behavior. We will build on existing implementations such as replay_trajectory_classification.

Joint Neural-Behavioral Modeling: To understand the interactions between neural dynamics and behavior, we will use models that extract shared latent representations from both domains. These models will help reveal how cognitive and behavioral states are jointly encoded in neural activity.

We will adapt Recognition-Parametrized Models (RPM), a Bayesian approach developed at the GCNU, which infers latent variables that explain multiple observation streams through highly nonlinear relationships. We will also use CEBRA, a state-of-the-art contrastive learning framework designed for multimodal representation learning, to discover temporally and semantically aligned neural-behavioral structure.

3.4.1.2 Non-stationarity

Many conventional methods for analyzing neural and behavioral time series assume that the underlying data-generating processes are stationary—that is, their statistical properties remain constant over time. While this assumption may be acceptable in short-duration experiments, it breaks down in long-duration and continual recordings. In such settings, animals learn and adapt, their internal states and motivations fluctuate, and their behavior and physiology are influenced by biological rhythms such as circadian, ultradian, and infradian cycles. These changes induce non-stationarity in the data, making models that assume stationarity progressively less reliable or even obsolete.

To address this challenge, we will adapt and develop methods that are explicitly designed to operate in non-stationary environments. Our approach draws on techniques from multiple domains, including adaptive signal processing, machine learning, and Bayesian inference.

Adaptive Signal Processing. The field of adaptive signal processing has produced robust methods for modeling linear systems with time-varying dynamics (Haykin, 2002). The recursive least-squares (RLS) algorithm, for example, is a well-known adaptation of the ordinary least squares algorithm that continuously updates model parameters to perform linear regression under non-stationary conditions. We will use RLS to study time-varying relations between behavioral states, as inferred by hidden Markov models, and

Table 1: Initial data analysis methods to disseminate $\,$

Domain	Functionality	Method	Model Type
behaviour	multi-body-part	SLEAP	deep neural network
	tracking		
behaviour	kinematics infer-	LDS	linear dynamical system
	ence		
behaviour	kinematics infer-	LDS	particle filter
	ence		
behaviour	state inference	SSM	hidden Markov model
behaviour	regression		generalized linear model
behaviour	regression		deep neural network
behaviour	policy inference	L(M)V-IQL	reinforcement learning
behaviour	long-duration		RNN
	forecasting		
behaviour	long-duration		transformers
	forecasting		
brain	latents inference	svGPFA	Gaussian processes
brain	latents inference	LFADS	RNN
brain	state inference	SSM	hidden Markov model
brain	long-duration		RNN
	forecasting		
brain	long-duration		transformers
	forecasting		
brain	decoding	NA	point-process decoder
brain &	latents inference	RPM	Bayesian inference +
behaviour			deep neural network
brain &	latents inference	CEBRA	contrastive learning
behaviour			

foraging visit durations.

Continual Learning. The field of continual learning develops adaptive methods for artificial neural networks. In classic continual learning, a model learns a sequence of discrete, well-defined tasks. But in NaLoDuCo experimentation, as in many real-world settings there are not specific task boundaries. So methods that do not require task boundaries are needed. They are studied by the subfield of task-free continual learning and include online regularization (which constrain the update of relevant weights), experience replay (which maintain a small, representative buffer of past samples) and ensemble methods (which combine the predictions of multiple individual models with, for example, different learning rates). We will use these techniques, for example, to train pose tracking models on month-long continuous recordings.

Adaptive State-Space Models. In state-space modeling, the Kalman filter provides a principled way to handle non-stationary Gaussian processes with drifting mean and covariance. More flexible approaches are needed when data exhibit abrupt regime shifts or complex latent dynamics. Switching state-space models, such as Switching Linear Dynamical Systems (SLDS) and Switching Hidden Markov Models (sHMMs), model discrete changes in underlying system dynamics. For nonlinear, non-Gaussian signals, particle filters approximate the posterior distribution through sequential sampling. Bayesian online learning techniques offer a general framework for continually updating model parameters as new data arrive. Using these techniques we will build models that robustly infer kinematics over months.

Concept Drift in Machine Learning. In the machine learning literature, non-stationarity is often framed under the concept of *concept drift*, which refers to changes in the joint distribution of inputs and outputs over time. Such drift can take various forms—sudden, gradual, or cyclical (e.g., reemergence of behavioral patterns linked to circadian or ultradian rhythms).

Techniques for handling concept drift generally fall into three categories: (1) detection methods, which monitor for significant changes in data distribution; (2) adaptation methods, which incrementally update models using strategies such as sliding windows, online learning, or ensemble-based approaches; and (3) forgetting mechanisms, which allow models to discard outdated information while retaining relevant past knowledge.

We will apply techniques from the concept drift literature to models that fall outside the previous categories of focus (e.g., linear models, artificial neural networks, and state-space models). In particular, we will explore their use in building Recognition-Parametrized Models (RPMs) to estimate joint behavioral and neural latent variables over timescales of weeks to months.

In summary, robust analysis of NaLoDuCo datasets requires models that continuously adapt to evolving data distributions. Our offline analysis framework will integrate both established adaptive algorithms and cutting-edge methods from continual learning and concept drift to meet this challenge.

3.4.1.3 Computational efficiency

Neural and behavioral data analysis is most effective when computations are performed quickly, ideally in real time. Slow computations discourage data exploration and hinder scientific discovery. The large dataset sizes generated by NaLoDuCo experimentation pose a significant challenge for fast data analysis.

To overcome this limitation, we will combine distributed and GPU computing. Distributed computing is a paradigm in which tasks and data are divided across multiple computers. Instead of relying on a single powerful machine, distributed computing accelerates processing by executing multiple parts of a computation in parallel. GPU computing is a parallel computing approach that uses Graphics Processing Units (GPUs) to accelerate computational tasks. Unlike traditional Central Processing Units (CPUs), which execute a few complex operations sequentially, GPUs consist of thousands of smaller cores optimized for executing many operations simultaneously. Distributed computing allows to split workload across multiple machines, overcoming memory and computational limitations. It is particularly useful for scaling to massive datasets.

For distributed computing to deliver substantial speed improvements, computations must be decomposable into independent parallel tasks. Due to their serial dependencies, time series models are difficult to decomposed in this manner. Still, time series models can benefit from distributed computing infrastructures, as many parts of time series pipelines are parallelizable, like preprocessing steps (e.g., filtering, feature extraction, normalization) or parallel model evaluation across hyperparameter sweeps. In addition, when datasets are too large to fit in memory, distributed computing (e.g., with Ray, Dask, or Spark) can Distribute I/O and preprocessing, train models in

parallel on different subsets (e.g., one model per animal or time window) and run hyperparameter sweeps or model variants in parallel. Furthermore, even with serial dependencies GPU acceleration significantly speeds up the processing of each item in the time series, specially when large matrix operation are involved.

We will develop accelerated implementations of all methods in the library. These implementations will use JAX for model learning, inference, and numerical computation, Apache Spark or Dask to distribute pre-processing and feature extraction, and Ray to distribute machine learning and deep learning functionality.

Related to this item is the library Thunder, which accelerate the analysis of large scale neural data. It was pioneering by introducing the use of distributed computing in neural data analysis. Our library is different from Thunder in that, besides analyzing large scale neural data, it processes continual recordings, and needs to overcome non-stationarity problems. In addition, Thunder implements simpler methods assuming independent and identically distributed data, while our library contains more sophisticated time series ones.

3.4.1.4 Deliverables

469

470

471

472

474

476

477

478

480

482

486

487

488

490

491

492

493

- 1. repository containing implementations of machine learning algorithms for offline processing NaLoDuCo experimental data, adapted to operate in non-stationary environments, and optimized to perform at scale when running on public clouds or institutional high-performance-computing clusters.
- 2. SWC NaLoDuCo foraging dataset storred in DANDI.
- 3. deployment of the methods in 1 in Amazon EC2 instances, to allow users to analyze on the cloud the datasets in 2.

94 3.4.2 Real-Time Machine Learning Methods

3.4.2.1 Real-Time Machine Learning in Neuroscience

Real-time machine learning (RTML) is widely used across sectors such as finance, logistics, and environmental monitoring. For instance, in climate science, RTML enables real-time wildfire and flood detection from satellite

data, as well as the forecasting of extreme weather events using streaming radar and sensor signals. In food delivery systems, RTML is used to estimate delivery times based on traffic, kitchen queue lengths, and historical performance, and to dynamically optimize dispatching routes.

Surprisingly, RTML is still underutilized in neuroscience. This represents a missed opportunity—particularly in the context of naturalistic, long-duration, and continual (NaLoDuCo) experimentation—where adaptive, low-latency computation could significantly enhance both experimental control and analysis.

Real-Time Experimental Design Verification. In traditional neuroscience workflows, analysis is done offline, often days or weeks after data collection. Errors or design flaws are only discovered post hoc, sometimes necessitating a costly repetition of experiments. This problem is exacerbated in NaLoDuCo settings, where experiments may last weeks or months. RTML can address this by providing online assessments of experiment progress and data quality, allowing early detection of issues and in-situ protocol adjustments.

Intelligent Neuromodulation. Neuromodulation can be performed optically, chemically, or electrically. Typically, stimulation is delivered at predefined times or based on simple thresholds in neural or behavioral signals. With RTML, these interventions can be driven by more sophisticated models that infer high-level internal states from ongoing data.

For example, a scientist may hypothesize that a peak in a latent neural variable—estimated in real time from a prefrontal cortex population—signals the onset of a foraging decision. To test this, she uses an online latent variable model to forecast the peak's occurrence and triggers optogenetic inactivation just before the predicted moment. If the intervention disrupts foraging onset, this provides causal support for the hypothesis.

Intelligent Data Storage. As the richness and duration of NaLoDuCo experiments increase, storing all raw data becomes infeasible. We will need RTML algorithms to make real-time decisions about what data to retain and what to discard.

For example, consider a setup with ten high-resolution cameras monitoring a mouse in a large arena. Storing all video streams continuously is inefficient. Instead, a tracking model can estimate the animal's location in real time. When the confidence of the tracker is high, only the streams from relevant cameras are saved. When uncertainty is high, more data can be preserved for later inspection.

3.4.2.2 Bonsai and Bonsai.ML

530

541

542

545

547

548

549

550

551

552

553

554

558

550

560

561

562

Bonsai is a widely adopted open-source software ecosystem for experimental control in neuroscience (Lopes et al., 2015). With support from the BBSRC, we are developing software infrastructure to enable intelligent experimentation through the Bonsai.ML package.

We have already integrated several real-time ML models into Bonsai.ML, including linear regression, linear dynamical systems, hidden Markov models, and Bayesian point-process decoders. In collaboration with researchers at SWC and UCL, we have applied these tools to real-time inference of visual receptive fields, foraging kinematics, behavioral state classification, and spatial decoding from hippocampal spiking activity.

However, existing Bonsai.ML methods assume stationarity, which—as discussed in Section 3.4.1—is inappropriate for NaLoDuCo data. We will adapt these methods to operate under non-stationary conditions using techniques outlined in Section 3.4.1.2.

All new RTML methods for non-stationary experimental control will be released as open-source extensions to the Bonsai.ML library.

At SWC and AIND, where Bonsai is used for experimental control, we will collaborate with domain experts to apply these advanced RTML methods to cutting-edge NaLoDuCo experiments in real-world settings.

3.4.2.3 Deliverables

- 1. A repository of real-time ML methods for neuroscience experimental control, adapted to handle non-stationary data streams.
- 2. Publications co-authored with scientists at SWC and AIND, reporting experimental findings made possible by non-stationary Bonsai.ML methods.

3.4.3 Visual Exploration

568

580

582

583

584

585

586

588

589

590

591

Visualizations are essential for extracting insight from any dataset. Given the scale of NaLoDuCo datasets, downloading them locally is impractical. Therefore, visualization methods must operate where the data resides—either

in the cloud or on institutional compute clusters.

We will develop visualization functionality for both continuous datasets (Section 3.4.3.1) and epoched datasets, where epochs are anchored around events identified by advanced machine learning methods (Section ??).

1 3.4.3.1 Continuous Visualizations

Continuous visualizations will enable users to seamlessly explore large-scale behavioral and neural datasets spanning weeks to months. Users should be able to fluidly zoom out to gain a high-level overview (e.g., across an entire month) and zoom in to inspect millisecond-level detail. Our goal is to provide an interactive experience analogous to Google Maps—where one can zoom from a global perspective down to individual buildings—with time series data.

To achieve this, we will employ a combination of tiling, hierarchical storage, and streaming techniques:

Multi-Resolution Tiling.

- Large volumetric and time series datasets will be preprocessed into tiles at multiple spatial and temporal resolutions.
- When the user zooms into a specific time or spatial window, only the relevant tiles at the appropriate resolution will be rendered, minimizing latency and resource use.

Hierarchical Storage.

- Data will be organized using hierarchical file formats (e.g., Zarr, HDF5) that support chunked access and multi-resolution storage.
- These formats allow efficient random access to specific subsets of data and integration with modern data infrastructure.

On-Demand Streaming.

- Visualizations will stream data dynamically based on the user's current view, leveraging cloud infrastructure to deliver data at the required resolution and scale.
- We will develop custom APIs for real-time access and transformation of neural and behavioral data streams.

3.4.3.2 Epoched and Interactive Visual Analytics

A key strength of our platform is its support for **epoched visualization**and interactive, closed-loop visual analytics, which together enable the
discovery and refinement of neural and behavioral patterns in long-duration
datasets.

Epoched visualizations are essential for analyzing data around events of interest—such as decision points, sensory cues, or machine learning-inferred transitions. These visualizations will support:

- Grouping trials or epochs by event type, time of day, or machine learning-inferred state
- Overlaying neural, behavioral, and environmental variables aligned to key event markers
- Flexible sorting and filtering of epochs to uncover context-dependent patterns

We will implement interactive interfaces that allow researchers to define, explore, and compare arbitrary epoch-based segments. These will support exploratory data analysis as well as hypothesis-driven comparisons across conditions, individuals, and time periods.

Machine Learning-Defined Events. A core feature of our system will be the ability to align epochs not just to experimenter-defined events, but also to latent state transitions inferred via unsupervised methods (e.g., hidden Markov models, behavioral clustering, inverse reinforcement learning). This will support deeper investigation into emergent patterns in long-duration, naturalistic behavior.

Closed-Loop Analytics. There will be a *closed-loop interaction* between visualizations and machine learning algorithms: algorithmic outputs will generate new visualizations, and visual insights will guide further machine learning analysis, forming an iterative discovery cycle. This process allows the visualization platform to function not just as a display tool, but as a central component in data-driven scientific inquiry.

In this loop:

624

627

628

630

631

632

633

634

635

636

637

638

646

647

648

649

650

651

652

- Machine learning algorithms extract latent states, classify behaviors, infer structure, or forecast dynamics from NaLoDuCo data.
- These outputs feed into the visualization engine to generate novel views (e.g., state-aligned rasters, dynamic embeddings, attention maps).
- Users explore these visualizations interactively, discovering unexpected, task-agnostic, or contextual patterns.
- New queries and insights drive further rounds of machine learning analysis—closing the loop.

This design enables researchers to co-develop computational models and scientific hypotheses iteratively, with human insight and machine inference deeply intertwined.

3.4.3.3 Software Stack for Interactive Visualizations

To support scalable, cloud-based, and interactive visualization of NaLoDuCo datasets, we will develop our system using a modern and modular software stack optimized for high performance, extensibility, and ease of integration with existing neuroscience infrastructure.

$_{5}$ Frontend (User Interface).

- **React.js** will serve as the primary framework for building a dynamic, modular, and responsive web-based interface.
- Visualization components will leverage libraries such as **D3.js**, **Plotly**, and **Deck.gl** to render interactive time series, raster plots, and behavioral trajectories at scale.
- For GPU-accelerated rendering of large datasets, we will use WebGL and related technologies such as regl or Three.js.

Backend (Computation and Data Services).

- The backend will be written in **Python**, using **FastAPI** or **Flask** to serve data and model outputs to the frontend.
- Time series pre-processing, tiling, and downsampling will be handled via NumPy, Xarray, and Dask to enable scalable, distributed processing.
- For storage, we will use chunked, cloud-native formats such as **Zarr** and **HDF5**, which allow efficient retrieval and hierarchical access to long-duration recordings.
- Machine learning integration will rely on PyTorch, scikit-learn, and
 model serving frameworks such as TorchServe or ONNX Runtime.

664 Cloud Infrastructure.

654

655

656

657

658

659

660

661

665

666

667

668

669

670

671

672

674

675

676

677

678

- The system will be deployable on commercial or academic cloud platforms (e.g., AWS, GCP, or institutional clusters).
- For orchestration of services, we will use **Kubernetes**, enabling autoscaling and distributed deployment of visualization and ML services.
 - **Docker** containers will ensure reproducibility and portability across environments.
 - The visualization system will integrate directly with the **DANDI Archive** for cloud-native access to neurophysiology data.

73 Data Interoperability.

- All tools will be compatible with **Neurodata Without Borders** (**NWB**) and follow FAIR data principles.
- The system will expose APIs for programmatic access to raw and derived data, enabling integration with existing tools like **Bonsai**, **CaImAn**, or **napari**.

This software stack ensures that our visualization tools will be performant, scalable, and usable across a wide range of environments, from local lab systems to cloud-based scientific platforms.

3.4.3.4 Deliverables

- 1. visualisations for continuous behavioural and neural recording
- 2. visualisations for epoched behavioural and neural recording
- 3. visualisations for model outputs
- 4. indexing system to support intelligent visualisations
- 5. deployment of the above items to allow users to visualise NaLoDuCo
 DANDI datasets on the cloud

689 3.4.4 Offline spike Sorting

$_{690}$ 3.4.4.1 Outputs

691

692

1. Repository with implementations and benchmarking of offline spike sorting algorithms for long-duration recordings

693 3.4.5 Online spike Sorting

694 **3.4.5.1** Outputs

1. Repository with implementations and benchmarking of online spike sorting algorithms

References

- Haykin, S. S. (2002). Adaptive filter theory. Pearson Education India.
- 699 Lopes, G., Bonacchi, N., Frazão, J., Neto, J. P., Atallah, B. V., Soares, S.,
- Moreira, L., Matias, S., Itskov, P. M., Correia, P. A., et al. (2015). Bonsai:
- an event-based framework for processing and controlling data streams.
- Frontiers in neuroinformatics, 9:7.

3.5 Applicant and team capability to deliver

Word limit: 1,650

703

705

707

708

709

711

712

713

714

715

717

718

719

720

721

722

723

726

732

Why are you the right individual or team to successfully deliver the proposed work?

What the assessors are looking for in your response

Please ensure the current job titles of the core team members are included here to ensure eligibility can be established for the core team roles assigned. Find out more about UKRI's core team roles in funding applications and our eligibility guidance.

Evidence of how you, and if relevant your team, have:

- the relevant experience (appropriate to career stage) to deliver the proposed work
- the right balance of skills and expertise to cover the proposed work
- the appropriate leadership and management skills to deliver the work and your approach to develop others
- contributed to developing a positive research environment and wider community

You may demonstrate elements of your responses in visual form if relevant.

Further details are provided in the Funding Service.

The word limit for this section is 1,650 words: 1,150 words to be used for R4RI modules (including references) and, if necessary, a further 500 words for Additions.

Use the Résumé for Research and Innovation (R4RI) format to showcase the range of relevant skills you and, if relevant, your team (project and project co-leads, researchers, technicians, specialists, partners and so on) have and how this will help deliver the proposed work. You can include individuals' specific achievements but only choose past contributions that best evidence their ability to deliver this work.

Complete this section using the R4RI module headings listed. Use each heading once and include a response for the whole team, see the UKRI guidance on R4RI. You should consider how to balance your answer, and emphasise where appropriate the key skills each team member brings:

- contributions to the generation of new ideas, tools, methodologies, or knowledge
 - the development of others and maintenance of effective working relationships
 - contributions to the wider research and innovation community
 - contributions to broader research or innovation users and audiences and towards wider societal benefit

Additions

736

737

738

739

740

742

743

749

750

Provide any further details relevant to your application. This section is optional and can be up to 500 words. You should not use it to describe additional skills, experiences, or outputs, but you can use it to describe any factors that provide context for the rest of your R4RI (for example, details of career breaks if you wish to disclose them).

Complete this as a narrative. Do not format it like a CV.

References may be included within this section.

The roles in funding applications policy has descriptions of the different project roles.

3.6 Project partners

753

755

759

761

763

765

766

768

769

770

771

Add details about any project partners' contributions. If there are no project partners, you can indicate this on the Funding Service.

A project partner is a collaborating organisation who will have an integral role in the proposed research. This may include direct (cash) or indirect (inkind) contributions such as expertise, staff time or use of facilities. Project partners may be in industry, academia, third sector or government organisations in the UK or overseas, including partners based in the EU.

If you are applying via the IPA or LINK scheme, please include details of industry partners here.

If applying under the BBSRC-NSF lead agency scheme, please include details of your US partner here.

Add the following project partner details:

- the organisation name and address (searchable via a drop-down list or enter the organisation's details manually, as applicable)
- the project partner contact name and email address
- the type of contribution (direct or in-direct) and its monetary value

If a detail is entered incorrectly and you have saved the entry, remove the specific project partner record and re-add it with the correct information.

For audit purposes, UKRI requires formal collaboration agreements to be put in place if an award is made.

3.7 Project partners: statement of support

Word limit: 3,000

774

776

779

780

781

782

785

787

789

790

792

794

795

796

797

Only complete a statement of support if you have named project partners in the project partner section above. A statement is required to be provided from each partner you named in the 'Project partners' section.

If you are applying via the IPA or LINK scheme, please include details of industry partner support here.

What the assessors are looking for in your response

A project partner is a collaborating organisation who will have an integral role in the proposed research. This may include direct (cash) or indirect (in-kind) contributions such as expertise, staff time or use of facilities.

Each statement should:

- confirm the partner's commitment to the project
- clearly explain the value, relevance, and possible benefits of the work to them
- describe any additional value that they bring to the project

Ensure you have prior agreement from project partners so that, if you are offered funding, they will support your project as indicated in the 'Project partners' section.

For audit purposes, UKRI requires formal collaboration agreements to be put in place if an award is made.

Do not provide a statement of support from host and project co-leads' research organisations.

Do not provide a statement of support from collaborators. Contributions from collaborators not listed as project partners can be outlined in 'Applicant and team capability to deliver'.

3.8 Trusted Research and Innovation (TR&I)

Mord limit: 100

മവ

802

804

807

808

809

811

812

814

816

Does the proposed work involve international collaboration in a sensitive research or technology area?

What the assessors are looking for in your response

Demonstrate how your proposed international collaboration relates to TR&I, including:

- list the countries your international project co-leads, project partners and visiting researchers, or other collaborators are based in
- if international collaboration is involved, explain whether this project is relevant to one or more of the 17 areas of the UK National Security and Investment (NSI) Act
- if one or more of the 17 areas of the UK National Security and Investment (NSI) Act are involved list the areas

If your proposed work does not involve international collaboration, you will be able to indicate this in the Funding Service. If your proposed work does not involve international collaboration, please indicate this by stating 'N/A'. We may contact you following submission of your application to provide additional information about how your proposed project will comply with our approach and expectation towards TR&I, identifying potential risks and the relevant controls you will put in place to help manage these risks.

3.9 Resources and cost justification

 $_{2}$ Word limit: 1,000

821

823

825

826

827

829

834

836

837

839

840

845

846

What will you need to deliver your proposed work and how much will it cost?

What the assessors are looking for in your response

The FEC of your project can be up to a maximum of £2 million. We will fund 80million, we will fund £1.6 million and your research organisation will be expected to fund £400,000.

Please note, equipment over £10,000 is funded by BBSRC at 50%. The Funding Service does not currently have the ability to record this. For this round we ask that you include equipment over £10,000 in 'Exceptions' at 100% of cost. We will cut this to 50% at award. You must ensure you have prior agreement from your research organisation to fund the remaining 50%.

Justify the application's more costly resources, in particular:

- project staffsignificant travel for field work or collaboration (but not regular travel between collaborating organisations or to conferences)
- any equipment that will cost more than £10,000
- any consumables beyond typical requirements, or that are required in exceptional quantities
 - all facilities and infrastructure costs
- all resources that have been costed as 'Exceptions'

Assessors are not looking for detailed costs or a line-by-line breakdown of all project resources. Overall, they want you to demonstrate how the resources you anticipate needing for your proposed work:

- are comprehensive, appropriate, and justified
- represent the optimal use of resources to achieve the intended outcomes
- maximise potential outcomes and impacts

3.10 Data management and sharing

49 Word limit: 500

850

852

How will you manage and share data collected or acquired through the proposed research?

What the assessors are looking for in your response Provide a data management plan that clearly details how you will comply with UKRI's published data sharing policy, which includes detailed guidance notes.

3.11 Facilities

859

861

862

863

864

866

867

Word limit: 250 Does your proposed research require the support and use of a facility?

What the assessors are looking for in your response

If you will need to use a facility, follow your proposed facility's normal access request procedures. Ensure you have prior agreement so that if you are offered funding, they will support the use of their facility on your project.

For each requested facility you will need to provide the:

- name of facility, copied and pasted from the facility information list (DOCX, 42KB)
- proposed usage or costs, or costs per unit where indicated on the facility information list
- confirmation you have their agreement where required

Facilities should only be named if they are on the facility information list above. If you will not need to use a facility, you will be able to indicate this in the Funding Service.

3.12 Ethics and responsible research and innovation (RRI)

873 Word limit: 500

872

877

879

881

882

884

886

887

What are the ethical or RRI implications and issues relating to the proposed work? If you do not think that the proposed work raises any ethical or RRI issues, explain why.

What the assessors are looking for in your response

Demonstrate that you have identified and evaluated:

- the relevant ethical or responsible research and innovation considerations
- how you will manage these considerations

If you are collecting or using data you should identify:

- any legal and ethical considerations of collecting, releasing or storing the data (including consent, confidentiality, anonymisation, security and other ethical considerations and, in particular, strategies to not preclude further reuse of data)
- formal information standards that your proposed work will comply with

You may demonstrate elements of your responses in visual form if relevant. Further details are provided in the Funding Service.

3.13 Genetic and biological risk

Word limit: 700

892

893

894

895

896

897

898

899

900

902

904

908

910

Does your proposed research involve any genetic or biological risk?

What the assessors are looking for in your response

In respect of animals, plants or microbes, are you proposing to:

- use genetic modification as an experimental tool, like studying gene function in a genetically modified organism
- release genetically modified organisms
- ultimately develop commercial and industrial genetically modified outcomes

If yes, provide the name of any required approving body and state if approval is already in place. If it is not, provide an indicative timeframe for obtaining the required approval. Identify the organism or organisms as a plant, animal or microbe and specify the species and which of the three categories the research relates to.

Identify the genetic and biological risks resulting from the proposed research, their implications, and any mitigation you plan on taking. Assessors will want to know you have considered the risks and their implications to justify that any identified risks do not outweigh any benefits of the proposed research.

If this does not apply to your proposed work, you will be able to indicate this in the Funding Service.

3.14 Research involving the use of animals

Does your proposed research involve the use of vertebrate animals or other organisms covered by the Animals Scientific Procedures Act?

What the assessors are looking for in your response

If you are proposing research that requires using animals, download and complete the Animals Scientific Procedures Act template (DOCX, 74KB), which contains all the questions relating to research using vertebrate animals or other Animals (Scientific Procedures) Act 1986 regulated organisms.

Save it as a PDF, ensuring it is no larger than 8MB. The Funding Service will provide document upload details when you apply. If this does not apply to your proposed work, you will be able to indicate this in the Funding Service.

3.15 Conducting research with animals overseas

Word limit: 700

926

927

928

930

932

937

939

940

941

942

943

944

945

947

951

952

954

Will any of the proposed animal research be conducted overseas?

What the assessors are looking for in your response

If you are proposing to conduct overseas research, it must be conducted in accordance with welfare standards consistent with those in the UK, as in Responsibility in the use of animals in bioscience research. Ensure all named applicants in the UK and overseas are aware of this requirement. Ensure all named applicants in the UK and overseas are aware of this requirement.

If your application proposes animal research to be conducted overseas, you must provide a statement in the text box. Depending on the species involved, you may also need to upload a completed template for each species listed.

Statement

Provide a statement to confirm that:

- all named applicants are aware of the requirements and have agreed to abide by them
- this overseas research will be conducted in accordance with welfare standards consistent with the principles of UK legislation
- the expectation set out in Responsibility in the use of animals in bioscience research will be applied and maintained
- appropriate national and institutional approvals are in place

Templates

Overseas studies proposing to use non-human primates, cats, dogs, equines or pigs will be assessed during NC3Rs review of research applications. Provide the required information by completing the template from the question 'Research involving the use of animals'.

For studies involving other species, such as:

- rodents
- rabbits
- sheep

- 955 goats
- 956 pigs
- cattle

960

961

962

- xenopus laevis and xenopus tropicalis
- zebrafish

Select, download, and complete the relevant Word checklist or checklists by exploring NC3Rs checklist for the use of animals overseas.

Save your completed template as a PDF and upload to the Funding Service. If you use more than one checklist template, save it as a single PDF. The Funding Service will provide document upload details when you apply.

If conducting research with animals overseas does not apply to your proposed work, you will be able to indicate this in the Funding Service.

3.16 Research involving human participation

8 Word limit: 700

969

971

973

975

976

Will the project involve the use of human subjects or their personal information? What the assessors are looking for in your response

If you are proposing research that requires the involvement of human subjects, provide the name of any required approving body and whether approval is already in place. Justify the number and the diversity of the participants involved, as well as any procedures.

Provide details of any areas of substantial or moderate severity of impact.

If this does not apply to your proposed work, you will be able to indicate this in the Funding Service.

3.17 Research involving human tissues or biological samples

Word limit: 700

979

983

984

985

987

988

Does your proposed research involve the use of human tissues, or biological samples?

What the assessors are looking for in your response

If you are proposing work that involves human tissues or biological samples, provide the name of any required approving body and whether approval is already in place.

Justify the use of human tissue or biological samples specifying the nature and quantity of the material to be used and its source.

If this does not apply to your proposed work, you will be able to indicate this in the Funding Service.