Spectral analysis

Joaquín Rapela

Gatsby Computational Neuroscience Unit
University College London

January 18, 2024

Motivation

- We are monitoring **continuous** signal.
- We are saving **discrete** samples of this signal in our computer.
- Under what conditions, and how, can we recover the continuous signal $x(t)$ from the saved samples?



The Fourier Transform

The Fourier transform allows to represent a continuous signal as a linear combination of sinusoids.



The Fourier Transform

$$x(t) = \frac{1}{2\pi}\int_{-\infty}^{\infty} X(j\Omega)e^{j\Omega t}\ d\Omega = \frac{1}{2\pi}\int_{-\infty}^{\infty} X(j\Omega)(\cos(\Omega t) + j\sin(\Omega t))\ d\Omega$$
$$= \frac{1}{2\pi}\int_{-\infty}^{\infty} X(j\Omega)\cos(\Omega t)d\Omega + j\frac{1}{2\pi}\int_{-\infty}^{\infty} X(j\Omega)\sin(\Omega t)\ d\Omega$$

where

$$x(j\Omega) = \int_{-\infty}^{\infty} x(t)e^{-j\Omega t}\ dt$$

Sampled signal

We sample values of a continuous function $x(t)$ at regular times nT, where T is called the **sampling interval** and its inverse $1/T$ is called the **sampling frequency**.



Figure 3.1 The sampling operation: (a) the continuous-time signal $x(t)$; (b) the point-sampled sequence $x[n]$; (c) the impulse-sampled signal $x_p(t)$.

Continuous representation of a sampled signal

- Dirac delta function ($\delta(t)$):

$$\delta(t - t_0) = 0 \quad t \neq t_0$$

$$\int_{t_1}^{t_2} f(t)\delta(t - t_0)\, dt = f(t_0) \quad t_1 < t_0 < t_2$$

- Thus, a sampled signal (with sample interval T) can be represented with the function:

$$x_c(t) = \sum_{n=-\infty}^{\infty} x(t)\, \delta(t - nT)$$

  - $x_c(t) = 0 \quad t \neq nT$
  - $\int_{nT-\Delta}^{nT+\Delta} x_c(t)\, dt = x(nT)$

Sampling theorem

Theorem (Sampling theorem (Shannon, 1948))

Let $x_s(t)$ be a sampled signal, with sampling period T, of a continuous signal $x(t)$.
Let $X(j\Omega)$ be the Fourier transform of $x(t)$.
Then the Fourier transform of $x_s(t)$ is $X_s(j\Omega) = \frac{1}{T}\sum_{k=-\infty}^{\infty} X\left(j\left(\Omega - \frac{2\pi k}{T}\right)\right)$.

Sampling theorem



Figure 6.4 Illustrations of the Sampling Theorem

$$\omega_s = \frac{2\pi}{T_s}$$

Poularikas and Seely, 1994

Reconstruction procedure

1. Fourier transform the sampled signal $x_s(t)$, yielding $X_s(j\Omega)$.



2. low-pass filter $X_s(j\Omega)$ between frequencies $\Omega = -\frac{\pi}{T}$ and $\Omega = \frac{\pi}{T}$, yielding $X_s^{LP}(j\Omega)$.



3. the desired continuous signal is the inverse Fourier transform of $X_s^{LP}(j\Omega)$ (i.e., $x(t) = \mathcal{IFT}\{X_s^{LP}(j\Omega)\}$).



Reconstruction requirements

- we want



- we do NOT want



- we want $\frac{\omega_s}{2} > \omega_N$, or $\frac{2\pi}{T}\frac{1}{2} = \frac{\omega_s}{2} > \omega_N = 2\pi f_N$, or $\frac{1}{T}\frac{1}{2} > f_N$, or $f_s = \frac{1}{T} > 2f_N$, or $f_s > 2f_N$.

Reconstruction requirements

- we want



- we do NOT want



- we want $\frac{\omega_s}{2} > \omega_N$, or $\frac{2\pi}{T}\frac{1}{2} = \frac{\omega_s}{2} > \omega_N = 2\pi f_N$, or $\frac{1}{T}\frac{1}{2} > f_N$, or $f_s = \frac{1}{T} > 2f_N$, or $f_s > 2f_N$.
  To reconstruct without error a continuous signal from its samples we need to sample it at a frequency larger than twice its maximal frequency.

Reconstruction example

- continuous signal in time domain

$$x(t) = (sinc(f_0 t))^2$$

$$sinc(t) = \begin{cases} \frac{sin(\pi t)}{\pi t} & t \neq 0 \\ 1 & t = 0 \end{cases}$$

- continuous signal in frequency domain

$$x(j\Omega) = \begin{cases} \frac{1}{f_0}\left(1 - \frac{|\Omega|}{2\pi f_0}\right) & \Omega \leq 2\pi f_0 \\ 0 & \Omega > \pi f_0 \end{cases}$$

$\omega_N = 2\pi f_0$, $f_N = f_0$ and by the sampling theorem $f_s > 2f_0$.

Reconstruction example: sampling below the Nyquist rate



Figure 3.4 Sampling of a band-limited signal below the Nyquist rate: (a) Fourier transform of the continuous-time signal; (b) Fourier transform of the sampled signal.

Reconstruction example: sampling below the Nyquist rate



Reconstruction example: sampling at the Nyquist rate



Resources

Mark Kramer's neural data analysis lectures.

Summary

Bibliography

Shannon, C. E. (1948). A mathematical theory of communication. *The Bell system technical journal*, 27(3):379–423.