

# (Fast) Introduction to R

Jump into a notebook

Joana Cima

13 outubro 2023

## My beamer

BlaBlaBla

## Outline

1. Motivation
2. Data
3. Conceptual discussion

## 3. Import data (from an excel file)

Load your data using point and click




Figure 1: Point and click

which corresponds to the following code

```
nlswork <- as.data.frame(read_excel("nlswork.xlsx"))  
# nlswork <- read_dta("nlswork.dta") # in case you have a Stata data source
```

## 4. Data manipulation – check the pipe operator, %>%

### 4.1. Select a subset of variables

```
nlswork_s <- nlswork %>%  
  select(idcode, ln_wage)
```

## 4.2. Rename variables

```
nlswork_r <- nlswork %>%  
  rename(cae = ind_code)
```

## 4.3. Filter a subset of observations

```
nlswork_f <- nlswork %>%  
  filter(age > 40)
```

## 4.4. Mutate: create variables


```
nlswork_m <- nlswork %>%  
  mutate(ln_asd=log(age))
```

## 4.5. Manipulate the data in a single sequence


```
nlswork1 <- nlswork %>%  
  rename(cae = ind_code) %>%  
  select(idcode, ln_wage, age) %>%  
  filter(age > 40) %>%  
  mutate(age2=age^2)
```

## 5. Visualize missing information:


```
vis_miss(nlswork)
```




```
gg_miss_var(nlswork) + labs(y = "Total missing values for each variable")
```



```
gg_miss_upset(nlswork)
```




```
gg_miss_fct(x = nlswork, fct = year)
```



## Alternative

```
vis_dat(nlswork)
```



## 6. Handling Missing Data

Handling missing data is a crucial step in the exploratory data analysis. Depending on the nature and mechanism of the missingness, we might decide to impute missing values or to exclude the observations with missing data.

### 6.1 Filling Missing Data

In some situations, we may opt to fill in the missing data. For instance, one common method involves replacing missing values with the mean of the variable.

```
library(tidyverse)
# Filling Missing Data

## (with the average - this is an example - it does not make sense in this case)
nlswork_filled <- nlswork %>%
  mutate(across(c("union"), ~ ifelse(is.na(.), mean(., na.rm = TRUE), .)))

## (with the mode)
### Create a function to compute mode
calc_mode <- function(x) {
  tbl <- table(x, useNA = "no") # ignore NAs
  max_freq <- max(tbl)
  mode_val <- as.numeric(names(tbl)[tbl == max_freq])
  if(length(mode_val) > 1) {
    warning("Existem múltiplas modas. Selecionando a menor.")
  }
}
```

```

    mode_val <- min(mode_val)
  }
  return(mode_val)
}

### compute the mode
mode_union <- calc_mode(nlswork$union)

### Replace NA by mode in column union
nlswork_filled <- nlswork %>%
  mutate(union = if_else(is.na(union), mode_union, union))

```

## 6.2 Excluding rows with missing data

```

# Or excluding rows with missing data

nlswork_no_na <- na.omit(nlswork)

```

## 7. Descriptive statistics

```
summary(nlswork_no_na)
```

```

##      idcode      year      birth_yr      age
## Min.   : 1      Min.   :70.00      Min.   :41.00      Min.   :16.0
## 1st Qu.:1280    1st Qu.:73.00      1st Qu.:46.00      1st Qu.:25.0
## Median :2594    Median :78.00      Median :48.00      Median :30.0
## Mean   :2589    Mean   :79.12      Mean   :48.11      Mean   :30.2
## 3rd Qu.:3859    3rd Qu.:83.00      3rd Qu.:51.00      3rd Qu.:35.0
## Max.   :5159    Max.   :88.00      Max.   :54.00      Max.   :46.0
##      race      msp      nev_mar      grade
## Length:13452      Min.   :0.0000      Min.   :0.0000      Min.   : 0.00
## Class :character    1st Qu.:0.0000      1st Qu.:0.0000      1st Qu.:12.00
## Mode  :character    Median :1.0000      Median :0.0000      Median :12.00
##                               Mean   :0.6257      Mean   :0.2081      Mean   :12.68
##                               3rd Qu.:1.0000      3rd Qu.:0.0000      3rd Qu.:14.00
##                               Max.   :1.0000      Max.   :1.0000      Max.   :18.00
##      collgrad      not_smsa      c_city      south
## Min.   :0.0000      Min.   :0.000      Min.   :0.0000      Min.   :0.0000
## 1st Qu.:0.0000      1st Qu.:0.000      1st Qu.:0.0000      1st Qu.:0.0000
## Median :0.0000      Median :0.000      Median :0.0000      Median :0.0000
## Mean   :0.1887      Mean   :0.284      Mean   :0.3417      Mean   :0.4081
## 3rd Qu.:0.0000      3rd Qu.:1.000      3rd Qu.:1.0000      3rd Qu.:1.0000
## Max.   :1.0000      Max.   :1.000      Max.   :1.0000      Max.   :1.0000
##      ind_code      occ_code      union      wks_ue
## Min.   : 1.000      Min.   : 1.000      Min.   :0.0000      Min.   : 0.000
## 1st Qu.: 5.000      1st Qu.: 3.000      1st Qu.:0.0000      1st Qu.: 0.000
## Median : 7.000      Median : 3.000      Median :0.0000      Median : 0.000
## Mean   : 7.842      Mean   : 4.839      Mean   :0.2286      Mean   : 2.112
## 3rd Qu.:11.000      3rd Qu.: 6.000      3rd Qu.:0.0000      3rd Qu.: 0.000
## Max.   :12.000      Max.   :13.000      Max.   :1.0000      Max.   :75.000
##      ttl_exp      tenure      hours      wks_work
## Min.   : 0.000      Min.   : 0.0000      Min.   : 1.0      Min.   : 0.00

```



```
## 1st Qu.: 3.417    1st Qu.: 0.8333    1st Qu.: 35.0    1st Qu.: 43.00
## Median : 5.635    Median : 2.0833    Median : 40.0    Median : 52.00
## Mean   : 6.773    Mean   : 3.4475    Mean   : 36.2    Mean   : 50.73
## 3rd Qu.: 9.263    3rd Qu.: 4.5000    3rd Qu.: 40.0    3rd Qu.: 58.00
## Max.   :28.885    Max.   :25.9167    Max.   :168.0    Max.   :103.00
##      ln_wage
## Min.    :0.000
## 1st Qu.:1.397
## Median :1.690
## Mean    :1.714
## 3rd Qu.:2.001
## Max.    :5.264
```

```
summary(nlswork_no_na[,c("grade", "union", "ln_wage")])
```

```
##      grade      union      ln_wage
## Min.   : 0.00    Min.   :0.0000    Min.   :0.000
## 1st Qu.:12.00    1st Qu.:0.0000    1st Qu.:1.397
## Median :12.00    Median :0.0000    Median :1.690
## Mean    :12.68    Mean    :0.2286    Mean    :1.714
## 3rd Qu.:14.00    3rd Qu.:0.0000    3rd Qu.:2.001
## Max.    :18.00    Max.    :1.0000    Max.    :5.264
```

```
str(nlswork_no_na)
```

```
## 'data.frame':    13452 obs. of  21 variables:
## $ idcode   : num  1 1 1 1 1 1 2 2 2 2 ...
## $ year     : num  72 77 80 85 87 88 71 77 78 83 ...
## $ birth_yr : num  51 51 51 51 51 51 51 51 51 51 ...
## $ age      : num  20 25 28 33 35 37 19 25 26 31 ...
## $ race     : chr  "black" "black" "black" "black" ...
## $ msp      : num  1 0 0 0 0 0 1 1 1 1 ...
## $ nev_mar  : num  0 0 0 0 0 0 0 0 0 0 ...
## $ grade    : num  12 12 12 12 12 12 12 12 12 12 ...
## $ collgrad : num  0 0 0 0 0 0 0 0 0 0 ...
## $ not_smsa : num  0 0 0 0 0 0 0 0 0 0 ...
## $ c_city   : num  1 1 1 1 0 0 1 1 1 1 ...
## $ south    : num  0 0 0 0 0 0 0 0 0 0 ...
## $ ind_code : num  4 12 5 5 5 5 4 4 4 4 ...
## $ occ_code : num  6 8 6 6 6 6 3 6 6 6 ...
## $ union    : num  1 0 1 1 1 1 0 1 1 1 ...
## $ wks_ue   : num  0 0 0 0 0 0 19 0 0 12 ...
## $ ttl_exp  : num  2.26 3.78 5.29 7.16 8.99 ...
## $ tenure   : num  0.917 1.5 1.833 1.917 3.917 ...
## $ hours    : num  40 32 45 42 45 48 40 40 40 38 ...
## $ wks_work : num  51 52 75 97 95 70 13 52 52 37 ...
## $ ln_wage  : num  1.59 1.78 2.55 2.61 2.54 ...
## - attr(*, "na.action")= 'omit' Named int [1:15082] 1 2 4 5 7 9 14 15 16 19 ...
## ..- attr(*, "names")= chr [1:15082] "1" "2" "4" "5" ...
```

## 7.1. Export descriptive statistics table to html, with 2 digits

### Shorter statistics

Statistic N Mean St. Dev. Min Max

```
age 13,452 30.20 6.41 16 46
collgrad 13,452 0.19 0.39 0 1
ttl_exp 13,452 6.77 4.41 0.00 28.88 union 13,452 0.23 0.42 0 1
hours 13,452 36.20 10.03 1 168
```

---

## 7.2. Export descriptive statistics table to txt, with 3 digits

### Shorter statistics

Statistic N Mean St. Dev. Min Max

```
age 13,452 30.203 6.414 16 46
collgrad 13,452 0.189 0.391 0 1
ttl_exp 13,452 6.773 4.409 0.000 28.885 union 13,452 0.229 0.420 0 1
hours 13,452 36.199 10.034 1 168
```

---

## 7.3. Transposing the descriptive statistics table

### Shorter statistics

Statistic age collgrad ttl\_exp union hours

```
N 13,452 13,452 13,452 13,452 13,452 Mean 30.203 0.189 6.773 0.229 36.199 St. Dev. 6.414 0.391 4.409 0.420
10.034 Min 16 0 0.000 0 1
Max 46 1 28.885 1 168
```

---

## 7.4. Export to pdf

% Table created by stargazer v.5.2.3 by Marek Hlavac, Social Policy Institute. E-mail: marek.hlavac at gmail.com % Date and time: sex, out 13, 2023 - 11:00:24

Table 1: Shorter statistics


| Statistic | age    | collgrad | ttl_exp | union  | hours  |
|-----------|--------|----------|---------|--------|--------|
| N         | 13,452 | 13,452   | 13,452  | 13,452 | 13,452 |
| Mean      | 30.203 | 0.189    | 6.773   | 0.229  | 36.199 |
| St. Dev.  | 6.414  | 0.391    | 4.409   | 0.420  | 10.034 |
| Min       | 16     | 0        | 0.000   | 0      | 1      |
| Max       | 46     | 1        | 28.885  | 1      | 168    |

## 8. Visualisation to explore your data

### 8.1. Relationships Between Continuous Variables


```
## `geom_smooth()` using formula = 'y ~ x'
```

Ln Wage vs. Experience



## 8.2. Categorical variable


```
ggplot(data = nlswork_no_na) +  
  geom_bar(mapping=aes(x=as.factor(collgrad))) +  
  xlab("College graduate (1=Yes)")
```



### 8.3. Continuous Variable Distributions


### 8.4 Categorical and continuous variables

```
nlswork_no_na %>% ggplot(aes(x=as.factor(collgrad), y=ln_wage)) +  
  geom_boxplot(fill="slateblue", alpha=0.2) +  
  xlab("College graduate (1=Yes)")
```



```
nlswork_no_na %>% ggplot(mapping = aes(x = ln_wage, y = ..density..)) +
  xlab("ln(wage)") +
  ylab("Density") +
  geom_freqpoly(mapping = aes(colour = factor(collgrad, labels=c("No", "Yes")))) +
  labs(color = "College degree")
```


```
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```



## 9. Correlation

```
ggpairs(nlswork_no_na[, c("age","ttl_exp","hours")], title="Correlogram with ggpairs()")
```

### Correlogram with ggpairs()



## 10. Assessment

### Problem 1: Data Importing

Import the “card” dataset.

```
#BEGIN SOLUTION
```

```
#END SOLUTION
```

### Problem 2: Visualizing Missing Data

Graphically show which variables have the most missing values.

```
#BEGIN SOLUTION
```

```
#END SOLUTION
```

### Problem 3: Handling Missing Data

Adopt a strategy to handle the missing values. How many observations were lost?

```
#BEGIN SOLUTION
```

```
#END SOLUTION
```

### Problem 4: Descriptive Statistics after Missing Data Handling

Present statistics of the dataset that has been treated for missing values.

```
#BEGIN SOLUTION
```

```
#END SOLUTION
```

### Problem 5: Relationship Visualization

Graphically show the relationship between age and salary. Does the relationship between the variables make sense?

```
#BEGIN SOLUTION
```

```
#END SOLUTION
```

### Problem 6: Age Distribution

Display the distribution of age.

```
#BEGIN SOLUTION
```

```
#END SOLUTION
```

### Problem 7: Correlation

What is the correlation value between age and salary?

```
#BEGIN SOLUTION
```

```
#END SOLUTION
```

### Problem 8:

In the `nlswork_no_na` dataset, can you identify any patterns or trends in the data related to unionized workers and their salaries?

```
#BEGIN SOLUTION
```

```
#END SOLUTION
```